

| | |
|---|--|
| | |
| Positioning | RESIDENTIAL-HIGH END |
| Product Description | 3100PSI (Vertical, Brass Head Pump) |
| Model Number | PWG3100VE |
| | |
| Brand | PULSAR |
| Image |  |
| | |
| PERFORMANCE | |
| RATED MAX. PRESSURE - PSI | 3100PSI |
| RATED MAX. FLOW - GPM | 2.5GPM |
| ENGINE | |
| Manufacturer / Model | DUCAR DV196 |
| Fuel Tank | Standard |
| Displacement (cc) / Net HP | 196cc(3600rpm) |
| Low Oil Sensor | NA |
| OVERALL DESIGN | |
| Frame Style | Hand Truck (1 1/0" Tubing) POWDER COATED Quick-Release Handle |
| Wheel Type | 12 " x 2" NEVER FLAT Treadcap / Plastic Rim |
| Axle | Short / Hitch-Pin |
| On-Board Detergent Container / Bottle Holder | (3L)Detergent Tank |
| PUMP | |
| Type | 3-Piston Axial Cam, Brass Head |
| Life Expectancy | 120h min. |
| a. Thermal Relief Valve | Yes -140°F |
| b. Chemical Injector | Low Pressure Venturi (HP Side) |
| c. EZ-Start Pump Valve | Built-In |
| d. Pressure / Flow Control Knob | NA |
| e. Pressure Relief Valve (Resettable) | NA |
| ACCESSORIES | |
| HP Hose | 5/16" ID x 30', Black PVC Outer Skin, Double nylon weave, M22 Couplers |
| Trigger Gun | 3600PSI Gun Front Entry , M22-M Inlet, Chrome-Plated Steel Tubing |
| Spray Wand | 20" Stainless Steel, M22 Connection, 1/4" QC Coupler |
| Nozzles | 5 QC Nozzles (0°, 15°,25° 40°, Soap Nozzle) |
| Engine Oil | NA |

| Other | PP 30%GF Accessory Panel |
|-----------------------------|--------------------------|
| CERTIFICATIONS | |
| UL 1776 | NA |
| CE | NA |
| EPA3 | YES |
| European Emissions Standard | NA |