

Tile Lab Gloss Sealer and Finish

Section 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Tile Lab Gloss Sealer and Finis	sh
Product Number:	F3529	
Product Use:	Sealant.	
Manufacturer/Supplier:	Custom Building Products 13001 Seal Beach Blvd Seal Beach, CA 90740	
Phone Number:	(562) 598-8808	
Emergency Phone:	INFOTRAC 1-800-535-5053 (L INTERNATIONAL + 1-352-323	,
Date of Preparation:	December 23, 2008	Revision Date: October 19, 2011
	Section 2: HAZARDS IDENTIF	ICATION

EMERGENCY OVERVIEW

CAUTION

MAY CAUSE EYE IRRITATION. MAY CAUSE SKIN IRRITATION.

Potential Health Effects: See Section 11 for more information.

Likely Routes of Exposure: Skin contact, eye contact, inhalation, and ingestion.

- **Eye:** May cause eye irritation.
- Skin: May cause skin irritation.

Ingestion: May be harmful if swallowed. May cause stomach distress, nausea or vomiting.

Inhalation: May cause respiratory tract irritation.

Chronic Effects: Prolonged or repeated contact may dry skin and cause irritation.

Signs and Symptoms: Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Symptoms may include redness, edema, drying, defatting and cracking of the skin.

Medical Conditions Aggravated By Exposure: Asthma. Allergies.

Target Organs: Skin, eyes, gastrointestinal tract, respiratory system.

Potential Environmental Effects: May cause long-term adverse effects in the aquatic environment. See Section 12 for more information.

	Section 3: COMPOSITION / INFORMATION ON INGREDIENTS			
Ingredient		CAS #	Wt. %	
Ethylene glyco	I monobutyl ether	111-76-2	1 - 5	
Section 4: FIRST AID MEASURES				
Eye Contact:	In case of contact, immediately flush eyes wit remove contact lenses, if worn.	th plenty of water. If eas	sy to do,	
Skin Contact:	In case of contact, immediately flush skin with contaminated clothing and shoes. Wash cloth if irritation develops and persists.			



Tile Lab Gloss Sealer and Finish

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.

Ingestion: If swallowed, do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.

General Advice: In case of accident or if you feel unwell, seek medical advice immediately (show the label or MSDS where possible).

Note to Physicians: Symptoms may not appear immediately.

Section 5: FIRE FIGHTING MEASURES

Flammability: Not flammable by WHMIS/OSHA criteria.

Means of Extinction:

Suitable Extinguishing Media: Powder, water spray, foam, carbon dioxide.

Unsuitable Extinguishing Media: Not available.

Products of Combustion: May include, and are not limited to: oxides of carbon.

Explosion Data:

Sensitivity to Mechanical Impact: Not available.

Sensitivity to Static Discharge: Not available.

Protection of Firefighters: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

Section 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental Precautions: Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.

Methods for Containment: Contain and/or absorb spill with inert material (e.g. sand, vermiculite), then place in a suitable container. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for Clean-Up: Soak into absorbent material. Spills of this material are a slipping hazard. Thoroughly wash the area with water after a spill or leak. Allow gas to dissipate harmlessly into the atmosphere.

Other Information: Not available.

Section 7: HANDLING AND STORAGE

Handling:

Avoid contact with skin and eyes. Do not swallow. Do not breathe gas/fumes/vapor/spray. Handle and open container with care. When using do not eat or drink. Wash hands before eating, drinking, or smoking.

Storage:

Keep out of the reach of children. Keep container tightly closed.



Tile Lab Gloss Sealer and Finish

Section 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

	Exposure	e Limits
Ingredient	OSHA-PEL	ACGIH-TLV
Ethylene glycol monobutyl ether	50 ppm	20 ppm

Engineering Controls: Use ventilation adequate to keep exposures (airborne levels of dust, fume, vapor, etc.) below recommended exposure limits.

Personal Protective Equipment:

Eye/Face Protection: Wear eye/face protection.

Hand Protection: Wear suitable gloves.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations: Handle according to established industrial hygiene and safety practices.

Section 9: PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Clear.
Color:	White.
Odour:	Characteristic.
Odour Threshold:	Not available.
Physical State:	Liquid.
pH:	8-9
Viscosity:	Water thin.
Freezing Point:	Not available.
Boiling Point:	~ 100 °C (~ 212 °F)
Flash Point:	Not available.
Evaporation Rate:	Not available.
Lower Flammability Limit:	Not available.
Upper Flammability Limit:	Not available.
Vapor Pressure:	Not available.
Vapor Density:	Not available.
Specific Gravity:	1.1
Solubility in Water:	Partial.
Coefficient of Water/Oil Distribution:	Not available.
Auto-ignition Temperature:	Not available.
Percent Volatile, wt. %:	75%
VOC content, wt. g/L:	140 g/L



Tile Lab Gloss Sealer and Finish

Section 10: STABILITY AND REACTIVITY

Stability: Stable under normal storage conditions.

Conditions of Reactivity: Heat. Incompatible materials.

Incompatible Materials: Oxidizers.

Hazardous Decomposition Products: May include, and are not limited to: oxides of carbon.

Possibility of Hazardous Reactions: No dangerous reaction known under conditions of normal use.

Section 11: TOXICOLOGY INFORMATION

EFFECTS OF ACUTE EXPOSURE

Component Analysis

••••••			
Ingredient		LD ₅₀ (oral)	LC ₅₀
Ethylene glyco	l monobutyl ether	470 mg/kg, rat	450 ppm 4hr, rat; 2.21 mg/L 4hr, rat
Eye:			ude discomfort or pain, excess blinking d swelling of the conjunctiva.
Skin:	May cause skin irritation defatting and cracking o		clude redness, edema, drying,
Ingestion:	May be harmful if swalld	wed. May cause st	omach distress, nausea or vomiting.
Inhalation:	May cause respiratory to	act irritation.	
EFFECTS OF C	HRONIC EXPOSURE		
Target Organ	s: Not available.		
Chronic Effec	ts: Not hazardous by W	HMIS/OSHA criteria	a.
Carcinogenic	ity: Not hazardous by W	HMIS/OSHA criteri	a.
Ingredient		С	hemical Listed as Carcinogen or Potential Carcinogen *
•	monobutyl ether	С	hemical Listed as Carcinogen or Potential Carcinogen * I-3
Ethylene glycol	monobutyl ether 5 for more information.	С	Potential Carcinogen *
Ethylene glycol * See Section 1	,		Potential Carcinogen *
Ethylene glycol * See Section 1 Mutagenicity:	5 for more information.	IIS/OSHA criteria.	Potential Carcinogen * I-3
Ethylene glycol * See Section 1 Mutagenicity:	5 for more information. Not hazardous by WHM Effects: Not hazardous	IIS/OSHA criteria.	Potential Carcinogen * I-3
Ethylene glycol * See Section 1 Mutagenicity: Reproductive Development	5 for more information. Not hazardous by WHM Effects: Not hazardous	IIS/OSHA criteria. by WHMIS/OSHA	Potential Carcinogen * I-3 criteria.
Ethylene glycol * See Section 1 Mutagenicity: Reproductive Development Terato	5 for more information. Not hazardous by WHM Effects: Not hazardous al Effects:	IIS/OSHA criteria. by WHMIS/OSHA by WHMIS/OSHA	Potential Carcinogen * I-3 criteria. criteria.
Ethylene glycol * See Section 1 Mutagenicity: Reproductive Development Terato Embry	5 for more information. Not hazardous by WHM Effects: Not hazardous al Effects: genicity: Not hazardous	IIS/OSHA criteria. by WHMIS/OSHA by WHMIS/OSHA s by WHMIS/OSHA	Potential Carcinogen * I-3 criteria. criteria.
Ethylene glycol * See Section 1 Mutagenicity: Reproductive Development Terato Embry Respiratory S	5 for more information. Not hazardous by WHM Effects: Not hazardous al Effects: genicity: Not hazardous otoxicity: Not hazardous	IIS/OSHA criteria. by WHMIS/OSHA by WHMIS/OSHA s by WHMIS/OSHA dous by WHMIS/OS	Potential Carcinogen * I-3 criteria. criteria. criteria. SHA criteria.

Section 12: ECOLOGICAL INFORMATION

Ecotoxicity: May cause long-term adverse effects in the aquatic environment.

Persistence / Degradability: Not available.

Bioaccumulation / Accumulation: Not available.



Tile Lab Gloss Sealer and Finish

Mobility in Environment: Not available.

Section 13: DISPOSAL CONSIDERATIONS

Disposal Instructions:

This material must be disposed of in accordance with all local, state, provincial, and federal regulations.

Section 14: TRANSPORTATION INFORMATION

DOT Ground Classification

Not regulated

TDG Ground Classification Not regulated

IATA Classification Not regulated

IMDG Classification

Not regulated

Section 15: REGULATORY INFORMATION

Federal Regulations

Canadian: This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

US: MSDS prepared pursuant to the Hazard Communication Standard (CFR29 1910.1200).

SARA Title III

Ingredient	Section 302	Section 304	CERCLA	Section
	(EHS) TPQ (Ibs.)	EHS RQ (Ibs.)	RQ (lbs.)	313
Ethylene glycol monobutyl ether	Not listed.	Not listed.	Not listed.	Yes.

State Regulations

New Jersey Right-To-Know: 2-Butoxyethanol. **Pennsylvania Right-To-Know:** Ethanol, 2butoxy-. **Massachusetts Right-To-Know:** 2-Butoxyethanol.

California Proposition 65:

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

Global Inventories

Ingredient	Canada DSL/NDSL	USA TSCA
Ethylene glycol monobutyl ether	DSL	Yes.

All ingredients are on DSL/NDSL and TSCA inventories or are exempt from listing.

HMIS - Hazardous Materials Identification System

Health - 1 Flammability - 0 Pl	ysical Hazard - 0 PPE – B
--------------------------------	---------------------------

NFPA - National Fire Protection Association:

Health - 1 Fire - 0 Reactivity - 0

Hazard Rating: 0 = minimal, 1 = slight, 2 = moderate, 3 = severe, 4 = extreme



Tile Lab Gloss Sealer and Finish

WHMIS Classification(s):

Class D2B - Skin/Eye Irritant

WHMIS Hazard Symbols:



- **OSHA (O)** Occupational Safety and Health Administration.
- ACGIH (G) American Conference of Governmental Industrial Hygienists.
 - A1 Confirmed human carcinogen.
 - A2 Suspected human carcinogen.
 - A3 Animal carcinogen.
 - A4 Not classifiable as a human carcinogen.
 - A5 Not suspected as a human carcinogen.

IARC (I) International Agency for Research on Cancer.

1 - The agent (mixture) is carcinogenic to humans.

2A - The agent (mixture) is probably carcinogenic to humans; there is limited evidence of carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals.

2B - The agent (mixture) is possibly carcinogenic to humans; there is limited evidence of carcinogenicity in humans in the absence of sufficient evidence of carcinogenicity in experimental animals.

- 3 The agent (mixture, exposure circumstance) is not classifiable as to its carcinogenicity to humans.
- 4 The agent (mixture, exposure circumstance) is probably not carcinogenic to humans.

NTP (N) National Toxicology Program.

- 1 Known to be carcinogens.
 - 2 Reasonably anticipated to be carcinogens.

Section 16: OTHER INFORMATION

Disclaimer:

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.

Expiry Date: December 23, 2014

Version #: 2.2

Prepared by: Nexreg Compliance Inc. Phone: (519) 488-5126 www.nexreg.com