



# 15" Color preference® Flushmount

1450lms | 120VAC | Model 54451511 | Part FM-15-22-802-SV-D-J

- > Energy Saving 22 Watt Integrated LED
- > Uses 78% Less Energy than Equivalent 100 Watt Incandescent Bulb
- > Soft White 3000k CCT  
Cool White 4000k CCT  
Daylight 5000k CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

<b>Model</b>	54451511
<b>Part</b>	FM-15-22-802-SV-D-J
<b>Description</b>	15" Color preference® Flushmount
<b>Input Voltage (VAC)</b>	120
<b>Wattage</b>	22
<b>Dimmability</b>	Triac
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	1450
<b>CCT<sup>3</sup></b>	3000k/4000k/5000k
<b>Location Rating</b>	UL Damp
<b>CRI<sup>4</sup></b>	80
<b>Beam Angle</b>	120
<b>Operating Temperature</b>	Min -4°F (-20° C), Max 95°F (35° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	15
<b>DUV</b>	-0.0009
<b>CBCP</b>	339
<b>Operating Frequency (Hz)</b>	60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

ETI

**LED lighting facts**  
A Program of the U.S. DOE

---

**Light Output (Lumens)** 1450  
**Watts** 22  
**Lumens per Watt (Efficacy)** 65.91

---

**Color Accuracy**  
Color Rendering Index (CRI) 80

---

**Light Color**  
Correlated Color Temperature (CCT) 3000 (Bright White)

2700K 3000K 4500K 6500K

---

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

---

Registration Number: YN84-XBWR4 (6/23/2017)  
 Model Number: 544512#(##=11-30)  
 Type: Luminaire - Other

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 15" Color preference® Flushmount

1450lms | 120VAC | Model 54451511 | Part FM-15-22-802-SV-D-J



## SHIPPING INFORMATION

Model	54451511
Part	FM-15-22-802-SV-D-J
UPC	849489001500
Product Dimensions (L x W x H in.)	14.84 x 14.84 x 3.66
Product Dimensions (L x W x H cm.)	37.7 x 37.7 x 9.30
Product Weight (lbs.)	1.34
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489001505
Master Carton Dimensions (L x W x H in.)	17.24 x 16.93 x 17.4
Master Carton Dimensions (L x W x H cm.)	43.8 x 43.0 x 44.2
Master Carton Weight (lbs)	13.6
Pallet Quantity	48

## COMPATIBILITY

### Dimmers:

Lutron	Leviton	Cooper
DVCL-153PR-WH	IPL06	DLC03P-LA
SCL-153RR-WH	6672	9573
SCL-153P		9530SG-K
TGCL-153PH-WH		
LG-600H-WH		
TG-603PGH-WH		

## AVAILABLE ACCESSORIES

Model	Description
95445151101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

ETi Solid State Lighting, Inc.  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256