



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** 6-56® Multi-Purpose Lubricant

**Other means of identification**

**Product code** 06005, 06006, 06007

**Recommended use** Multi-purpose lubricant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols Gases under pressure	Category 1 Compressed gas
<b>Health hazards</b>	Skin corrosion/irritation Specific target organ toxicity, single exposure Aspiration hazard	Category 2 Category 3 narcotic effects Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, acute hazard	Category 2
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash hands thoroughly after handling. Avoid breathing gas, mist or vapor. Wear protective gloves.

**Response** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

**Storage** Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.

<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.
<b>Supplemental information</b>	Not applicable.

### 3. Composition/information on ingredients

#### Mixtures

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), hydrotreated light		64742-47-8	60 - 70
Distillates (petroleum), solvent-refined heavy paraffinic		64741-88-4	10 - 20
n-Butyl stearate		123-95-5	3 - 5
Carbon dioxide		124-38-9	1 - 3
Fatty Acids, C18-unsatd., Dimers		61788-89-4	1 - 3
Petrolatum		8009-03-8	1 - 3
d-Limonene		5989-27-5	< 0.2
Terpinolene		586-62-9	< 0.2

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing. Wash off with soap and plenty of water. If skin irritation occurs: Get medical advice/attention.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms/effects, acute and delayed</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. May cause drowsiness or dizziness. Irritant effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Alcohol resistant foam. Water. Water spray. Dry powder. Carbon dioxide (CO2).
<b>Unsuitable extinguishing media</b>	None known.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may rupture when exposed to heat or flame.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
<b>Fire-fighting equipment/instructions</b>	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
<b>General fire hazards</b>	Extremely flammable aerosol.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate personal protective equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained.

### Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Following product recovery, flush area with water.

### Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

### Precautions for safe handling

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Avoid breathing mist or vapor. Avoid breathing gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, please see the product label.

### Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Keep away from heat, sparks and open flame. This material can accumulate static charge which may cause spark and become an ignition source.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### U.S. - OSHA

#### Components

Fatty Acids, C18-unsatd.,  
Dimers (CAS 61788-89-4)

#### Type

TWA

#### Value

5 mg/m<sup>3</sup>

#### Form

Respirable

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

#### Components

Carbon dioxide (CAS  
124-38-9)

Distillates (petroleum),  
solvent-refined heavy  
paraffinic (CAS 64741-88-4)

#### Type

PEL

#### Value

9000 mg/m<sup>3</sup>

#### Form

5000 ppm

5 mg/m<sup>3</sup>

Mist.

2000 mg/m<sup>3</sup>

500 ppm

5 mg/m<sup>3</sup>

Mist.

Petrolatum (CAS  
8009-03-8)

#### ACGIH

#### Components

Fatty Acids, C18-unsatd.,  
Dimers (CAS 61788-89-4)

#### Type

STEL

#### Value

10 mg/m<sup>3</sup>

#### Form

Respirable

TWA

5 mg/m<sup>3</sup>

Respirable

#### US. ACGIH Threshold Limit Values

#### Components

Carbon dioxide (CAS  
124-38-9)

Distillates (petroleum),  
solvent-refined heavy  
paraffinic (CAS 64741-88-4)

#### Type

STEL

TWA

TWA

30000 ppm

5000 ppm

5 mg/m<sup>3</sup>

Inhalable fraction.

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
n-Butyl stearate (CAS 123-95-5)	TWA	10 mg/m3	
Petrolatum (CAS 8009-03-8)	TWA	5 mg/m3	Inhalable fraction.

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
Carbon dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
	TWA	30000 ppm 9000 mg/m3	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	5000 ppm 100 mg/m3	
Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Petrolatum (CAS 8009-03-8)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
d-Limonene (CAS 5989-27-5)	TWA	165.5 mg/m3 30 ppm

**Biological limit values**

No biological exposure limits noted for the ingredient(s).

**Appropriate engineering controls**

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment****Eye/face protection**

Wear eye/face protection. Wear safety glasses with side shields (or goggles).

**Skin protection****Hand protection**

Wear protective gloves such as: Neoprene. Nitrile.

**Other**

Wear appropriate chemical resistant clothing.

**Respiratory protection**

If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards**

Wear appropriate thermal protective clothing, when necessary.

**General hygiene considerations**

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**9. Physical and chemical properties****Appearance****Physical state**

Liquid.

**Form**

Aerosol.

**Color**

Blue green.

**Odor**

Pleasant.

**Odor threshold**

Not available.

**pH**

Not available.

**Melting point/freezing point**

-72.4 °F (-58 °C) estimated

<b>Initial boiling point and boiling range</b>	380 °F (193.3 °C) estimated
<b>Flash point</b>	192 °F (88.9 °C) Tag Closed Cup
<b>Evaporation rate</b>	Slow.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	0.6 % estimated
<b>Flammability limit - upper (%)</b>	5.5 % estimated
<b>Vapor pressure</b>	1431 hPa estimated
<b>Vapor density</b>	> 1 (air = 1)
<b>Relative density</b>	0.84 estimated
<b>Solubility (water)</b>	Negligible.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	456.8 °F (236 °C) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity (kinematic)</b>	Not available.
<b>Percent volatile</b>	88.6 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Heat, flames and sparks. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents.
<b>Hazardous decomposition products</b>	Carbon oxides. Sulfur oxides. Hydrocarbons.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Inhalation</b>	Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. Prolonged inhalation may be harmful.
<b>Skin contact</b>	Causes skin irritation.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	May be fatal if swallowed and enters airways.

**Symptoms related to the physical, chemical and toxicological characteristics** Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Irritant effects.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. Narcotic effects.

Product	Species	Test Results
6-56® Multi-Purpose Lubricant		
<b>Acute</b>		
<b>Dermal</b>		
LD50	Rabbit	2133 mg/kg estimated
<b>Inhalation</b>		
LC50	Rat	6.3 mg/l, 4 hours estimated
<b>Oral</b>		
LD50	Rat	5317 mg/kg estimated

<b>Skin corrosion/irritation</b>	Causes skin irritation.
<b>Serious eye damage/eye irritation</b>	Direct contact with eyes may cause temporary irritation.
<b>Respiratory sensitization</b>	Not a respiratory sensitizer.
<b>Skin sensitization</b>	This product is not expected to cause skin sensitization.
<b>Germ cell mutagenicity</b>	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

**IARC Monographs. Overall Evaluation of Carcinogenicity**

d-Limonene (CAS 5989-27-5) 3 Not classifiable as to carcinogenicity to humans.

**US. National Toxicology Program (NTP) Report on Carcinogens**

Not available.

<b>Reproductive toxicity</b>	This product is not expected to cause reproductive or developmental effects.
<b>Specific target organ toxicity - single exposure</b>	Narcotic effects.
<b>Specific target organ toxicity - repeated exposure</b>	Not classified.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged exposure may cause chronic effects.

**12. Ecological information**

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
6-56® Multi-Purpose Lubricant		
<b>Aquatic</b>		
Crustacea	EC50	Daphnia
		5064.5264 mg/l, 48 hours estimated
<i>Acute</i>		
Fish	LC50	Fish
		4916.4028 ppm, 96 hours estimated
<b>Components</b>		
<b>Species</b>		
<b>Test Results</b>		

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

<b>Aquatic</b>		
<i>Acute</i>		
Fish	LC50	Bluegill (Lepomis macrochirus)
		2.2 mg/l, 96 hours
d-Limonene (CAS 5989-27-5)		
<b>Aquatic</b>		
Crustacea	EC50	Water flea (Daphnia pulex)
		69.6 mg/l, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)
		0.619 - 0.796 mg/l, 96 hours

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

d-Limonene	4.232
Fatty Acids, C18-unsatd., Dimers	1 - 2.5, logKow
Terpinolene	4.23

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

**13. Disposal considerations**

**Disposal of waste from residues / unused products** The dispensed liquid product is not a RCRA hazardous waste (See 40 CFR Part 261.20 - 261.33). Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Hazardous waste code** Not regulated.

Contaminated packaging Do not re-use empty containers.

## 14. Transport information

---

### DOT

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, limited quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Label(s)** 2.1  
**Packing group** Not applicable.  
**Special precautions for user** Not available.  
**Special provisions** Not available.  
**Packaging exceptions** 306  
**Packaging non bulk** None  
**Packaging bulk** None

### IATA

**UN number** UN1950  
**UN proper shipping name** Aerosols, flammable, limited quantity  
**Transport hazard class(es)**  
**Class** 2.1  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards** No.  
**ERG Code** 2L  
**Special precautions for user** Not available.  
**Other information**  
**Passenger and cargo aircraft** Allowed.  
**Cargo aircraft only** Allowed.

### IMDG

**UN number** UN1950  
**UN proper shipping name** AEROSOLS, LIMITED QUANTITY  
**Transport hazard class(es)**  
**Class** 2  
**Subsidiary risk** -  
**Packing group** Not applicable.  
**Environmental hazards**  
**Marine pollutant** No.  
**EmS** F-D, S-U  
**Special precautions for user** Not available.

## 15. Regulatory information

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

### **US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)**

Not listed.

### **SARA 304 Emergency release notification**

Not regulated.

### **US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance**

Not listed.

### **CERCLA Hazardous Substance List (40 CFR 302.4)**

Not listed.

### **CERCLA Hazardous Substances: Reportable quantity**

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.



**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.**Food and Drug Administration (FDA)** Not regulated.**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

<b>Section 311/312</b>	Immediate Hazard - Yes
<b>Hazard categories</b>	Delayed Hazard - No
	Fire Hazard - Yes
	Pressure Hazard - Yes
	Reactivity Hazard - No

<b>SARA 302 Extremely hazardous substance</b>	No
---	----

**US state regulations****US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)  
 Distillates (petroleum), solvent-refined heavy paraffinic (CAS 64741-88-4)  
 Petrolatum (CAS 8009-03-8)

**US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100)**

Not listed.

**US. New Jersey Worker and Community Right-to-Know Act**

Carbon dioxide (CAS 124-38-9)  
 Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

**US. Massachusetts RTK - Substance List**

Carbon dioxide (CAS 124-38-9)

**US. Pennsylvania Worker and Community Right-to-Know Law**

Carbon dioxide (CAS 124-38-9)  
 Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

**US. Rhode Island RTK**

None.

**US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

**Volatile organic compounds (VOC) regulations****EPA**

<b>VOC content (40 CFR 51.100(s))</b>	97.5 %
---------------------------------------	--------

<b>Consumer products (40 CFR 59, Subpt. C)</b>	Not regulated
--	---------------

**State**

<b>Consumer products</b>	This product is regulated as a Multi-Purpose Lubricant. This product is compliant for use in all 50 states.
--------------------------	---

<b>VOC content (CA)</b>	0 %
-------------------------	-----

<b>VOC content (OTC)</b>	0 %
--------------------------	-----

**International Inventories**

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No



Country(s) or region	Inventory name	On inventory (yes/no)*
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)  
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

---

<b>Issue date</b>	11-11-2013
<b>Revision date</b>	07-07-2015
<b>Prepared by</b>	Allison Cho
<b>Version #</b>	02
<b>Further information</b>	CRC # 510F
<b>HMIS® ratings</b>	Health: 1 Flammability: 3 Physical hazard: 0 Personal protection: B
<b>NFPA ratings</b>	Health: 1 Flammability: 3 Instability: 0

### NFPA ratings



### Disclaimer

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.