Date Printed: 11/9/2017 Page 1 / 5

# Safety Data Sheet



**Revision Date:** 

Supercedes Date:

### 1. Identification

RO 1-GL 2PK EGGSHELL LAKEFRONT **Product Name:** 

BLUE

**Product Identifier:** 332144

**Product Use/Class:** Top Coat

**Rust-Oleum Corporation** Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:** 

www.rustoleum.com

11/9/2017

**New SDS** 

**Rust-Oleum Corporation** Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

### 2. Hazard Identification

#### Classification

Symbol(s) of Product



#### Signal Word

Danger

### Possible Hazards

6% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

H350 Carcinogenicity, category 1A May cause cancer.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P201 Obtain special instructions before use.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations. Date Printed: 11/9/2017 Page 2 / 5

# 3. Composition / Information On Ingredients

#### **HAZARDOUS SUBSTANCES**

| Chemical Name   | CAS-No.    | Wt.%<br>Range | GHS Symbols           | GHS Statements       |
|---|------------|---------------|-----------------------|----------------------|
| Titanium Dioxide  | 13463-67-7 | 10-25         | Not Available         | Not Available        |
| Kaolin Clay   | 1332-58-7  | 2.5-10        | Not Available         | Not Available        |
| Aliphatic Petroleum Distillates                           | 64741-88-4 | 0.1-1.0       | GHS08                 | H350                 |
| 2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol                     | 126-86-3   | 0.1-1.0       | GHS05-GHS07           | H302-312-317-318     |
| 2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate               | 25265-77-4 | 0.1-1.0       | GHS06                 | H331                 |
| Oxirane, 2-Methyl-, Polymer with Oxirane, Monobutyl Ether | 9038-95-3  | 0.1-1.0       | GHS06                 | H330                 |
| Sodium Nitrite  | 7632-00-0  | 0.1-1.0       | GHS03-GHS06-<br>GHS08 | H272-301-319-331-350 |
| Titanium Dioxide  | 1317-70-0  | 0.1-1.0       | Not Available         | Not Available        |

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

#### Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Date Printed: 11/9/2017 Page 3 / 5

# 8. Exposure Controls / Personal Protection

| Chemical Name   | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|---|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Titanium Dioxide  | 13463-67-7 | 15.0                  | 10 mg/m3          | N.E.               | 15 mg/m3     | N.E.                 |
| Kaolin Clay   | 1332-58-7  | 10.0                  | 2 mg/m3           | N.E.               | 15 mg/m3     | N.E.                 |
| Aliphatic Petroleum Distillates                           | 64741-88-4 | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| 2,4,7,9-Tetramethyl-5-<br>Decyne-4,7-Diol                 | 126-86-3   | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| 2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate               | 25265-77-4 | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Oxirane, 2-Methyl-, Polymer with Oxirane, Monobutyl Ether | 9038-95-3  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Sodium Nitrite  | 7632-00-0  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Titanium Dioxide  | 1317-70-0  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |

#### PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

# 9. Physical and Chemical Properties

Appearance: **Physical State:** Liquid Liquid Odor: **Odor Threshold:** Solvent Like N.E. Relative Density: pH: 1.269

Not Determined

Freeze Point, °C: Viscosity: N.D. N.D. Partition Coefficient, n-octanol/ Solubility in Water: Slight N.D. Decompostion Temp., °C: N.D.

Boiling Range, °C: -18 - 537 **Explosive Limits, vol%:** N.A. - N.A.

Flammability: Flash Point. °C: 93 Does not Support Combustion **Evaporation Rate:** Auto-ignition Temp., °C: Slower than Ether N.D. Vapor Density: Heavier than Air Vapor Pressure: N.D.

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID:** No Information

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

### 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

Date Printed: 11/9/2017 Page 4 / 5

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)Contains Petroleum Distillates-Heavy Paraffinic, which is listed as an IARC Group 1 Carcinogen.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name   | Oral LD50        | Dermal LD50        | Vapor LC50     |
|------------|---|------------------|--------------------|----------------|
| 13463-67-7 | Titanium Dioxide  | >10000 mg/kg Rat | 2500 mg/kg         | N.E.           |
| 1332-58-7  | Kaolin Clay   | 5500 mg/kg       | N.E.               | 25             |
| 64741-88-4 | Aliphatic Petroleum Distillates                           | >5000 mg/kg Rat  | >2000 mg/kg Rabbit | N.E.           |
| 126-86-3   | 2,4,7,9-Tetramethyl-5-Decyne-4,7-Diol                     | >500 mg/kg Rat   | >1000 mg/kg Rabbit | N.E.           |
| 25265-77-4 | 2,2,4-Trimethyl-1,3-Pentanediol Isobutyrate               | 3200 mg/kg Rat   | >15200 mg/kg Rat   | >3.55 mg/L Rat |
| 9038-95-3  | Oxirane, 2-Methyl-, Polymer with Oxirane, Monobutyl Ether | 5000 mg/kg Rat   | 14904 mg/kg Rabbit | .1 mg/L Rat    |
| 7632-00-0  | Sodium Nitrite  | 85 mg/kg Rat     | N.E.               | 5.5 mg/L Rat   |

N.E. - Not Established

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** No Information

# 14. Transport Information

|                       | Domestic (USDOT) | International (IMDG) | Air (IATA)    | TDG (Canada)  |
|-----------------------|------------------|----------------------|---------------|---------------|
| UN Number:            | N.A.             | N.A.                 | N.A.          | N.A.          |
|                       |                  |                      |               |               |
| Proper Shipping Name: | Not Regulated    | Not Regulated        | Not Regulated | Not Regulated |
|                       |                  |                      |               |               |
| Hazard Class:         | N.A.             | N.A.                 | N.A.          | N.A.          |
| Packing Group:        | N.A.             | N.A.                 | N.A.          | N.A.          |
| Limited Quantity:     | No               | No                   | No            | No            |
|                       |                  |                      |               |               |

# 15. Regulatory Information

### **U.S. Federal Regulations:**

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

No Information

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Sodium Nitrite7632-00-0

Date Printed: 11/9/2017 Page 5 / 5

### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

Chemical NameCAS-No.Sodium Nitrite7632-00-0

No TSCA 12(b) components exist in this product.

### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 1 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 47

SDS REVISION DATE: 11/9/2017

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.