



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

## SECTION 1: Identification

### 1.1. Identification

Product form : Mixture  
Product name : Waterproof Patch & Seal Spray -- White

### 1.2. Recommended use and restrictions on use

Use of the substance/mixture : Flexible aerosol coating

### 1.3. Supplier

The Gorilla Glue Company  
2101 E. Kemper Road  
Sharonville, OH 45241  
513-271-3300  
www.gorillatough.com

### 1.4. Emergency telephone number

Emergency number : 1-800-420-7186

## SECTION 2: Hazard(s) identification

### 2.1. Classification of the substance or mixture

#### GHS-US classification

Flammable aerosol Category 1	H222	Extremely flammable aerosol
Gases under pressure Compressed gas	H280	Contains gas under pressure; may explode if heated
Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2	H319	Causes serious eye irritation
Carcinogenicity Category 2	H351	Suspected of causing cancer
Reproductive toxicity Category 2	H361	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	H336	May cause drowsiness or dizziness
Specific target organ toxicity (single exposure) Category 1	H370	Causes damage to organs
Specific target organ toxicity (repeated exposure) Category 2	H373	May cause damage to organs through prolonged or repeated exposure

Full text of H statements : see section 16

### 2.2. GHS Label elements, including precautionary statements

#### GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) : Danger

Hazard statements (GHS-US) :

- H222 - Extremely flammable aerosol
- H224 - Extremely flammable liquid and vapor
- H280 - Contains gas under pressure; may explode if heated
- H302 - Harmful if swallowed
- H315 - Causes skin irritation
- H319 - Causes serious eye irritation
- H336 - May cause drowsiness or dizziness
- H351 - Suspected of causing cancer
- H361 - Suspected of damaging fertility or the unborn child
- H370 - Causes damage to organs
- H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements (GHS-US) :

- P201 - Obtain special instructions before use
- P202 - Do not handle until all safety precautions have been read and understood
- P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- P211 - Do not spray on an open flame or other ignition source
- P233 - Keep container tightly closed
- P240 - Ground/Bond container and receiving equipment



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

- P241 - Use explosion-proof electrical/ventilating/lighting equipment
- P242 - Use only non-sparking tools
- P243 - Take precautionary measures against static discharge
- P251 - Pressurized container: Do not pierce or burn, even after use
- P260 - Do not breathe fume/gas/mist/vapors/spray
- P264 - Wash hands thoroughly after handling
- P270 - Do not eat, drink or smoke when using this product
- P271 - Use only outdoors or in a well-ventilated area
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P301+P312 - If swallowed: Call a poison center/doctor if you feel unwell
- P302+P352 - If on skin: Wash with plenty of water Take off immediately all contaminated clothing
- P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
- P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
- P307+P311 - If exposed: Call a poison control
- P308+P313 - If exposed or concerned: Get medical advice/attention
- P312 - Call a poison center/doctor if you feel unwell
- P314 - Get medical advice/attention if you feel unwell
- P332+P313 - If skin irritation occurs: Get medical advice/attention
- P337+P313 - If eye irritation persists: Get medical advice/attention
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P370+P378 - In case of fire: Use appropriate extinguishing media to extinguish
- P403+P233 - Store in a well-ventilated place. Keep container tightly closed
- P403+P235 - Store in a well-ventilated place. Keep cool
- P405 - Store locked up
- P410+P403 - Protect from sunlight. Store in a well-ventilated place
- P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
- P501 - Dispose of contents/container in accordance with local, state and federal regulations.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS-US classification
Toluene	(CAS No) 108-88-3	10 - 30*	Flam. Liq. 2, H225 Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Repr. 2, H361 STOT SE 3, H336 STOT RE 2, H373 Asp. Tox. 1, H304
n-Heptane	(CAS No) 142-82-5	5 - 10*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400
Acetone	(CAS No) 67-64-1	5 - 10*	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Titanium dioxide	(CAS No) 13463-67-7	1 - 5*	Carc. 2, H351
Hexane	(CAS No) 110-54-3	1 - 5*	Flam. Liq. 2, H225 Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Asp. Tox. 1, H304



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Name	Product identifier	%	GHS-US classification
Methyl alcohol	(CAS No) 67-56-1	1 – 5*	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301 Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370
Xylenes (o-, m-, p- isomers)	(CAS No) 1330-20-7	1 – 5*	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements: see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. Suspected of causing cancer. IF exposed or concerned: Get medical advice/attention. Call a POISON CENTER or doctor/physician.
- First-aid measures after inhalation : Cough. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.
- First-aid measures after eye contact : Rinse immediately with water for several minutes. Obtain medical attention if pain, blinking or redness persist.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects (acute and delayed)

- Potential Adverse human health effects and symptoms : Harmful if swallowed
- Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.
- Symptoms/injuries after inhalation : Shortness of breath. May cause drowsiness or dizziness.
- Symptoms/injuries after skin contact : Causes skin irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

No additional information available

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
- Unsuitable extinguishing media : Do not use a heavy water stream.

### 5.2. Specific hazards arising from the chemical

- Fire hazard : Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
- Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

### 5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. DO NOT fight fire when fire reaches explosives. Evacuate area.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : No smoking. Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust/fume/gas/mist/vapors/spray.

Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Hazardous waste due to potential risk of explosion. Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. Do not spray on an open flame or other ignition source. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapors/spray. Use only outdoors or in a well-ventilated area.

Hygiene measures : Wash hands thoroughly after handling.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Do not expose to temperatures exceeding 50 °C/ 122 °F. Keep in fireproof place. Keep container tightly closed.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage area : Store in a well-ventilated place.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Toluene (108-88-3)		
ACGIH	ACGIH TWA (ppm)	20 ppm
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
OSHA	OSHA PEL (Ceiling) (ppm)	300 ppm
IDLH	US IDLH (ppm)	500 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	375 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	560 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	150 ppm
Acetone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	500 ppm



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

<b>Acetone (67-64-1)</b>		
ACGIH	ACGIH STEL (ppm)	750 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2400 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
IDLH	US IDLH (ppm)	2500 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	250 ppm
<b>n-Heptane (142-82-5)</b>		
ACGIH	ACGIH TWA (ppm)	400 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2000 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
IDLH	US IDLH (ppm)	750 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	350 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	85 ppm
NIOSH	NIOSH REL (ceiling) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
NIOSH	NIOSH REL (ceiling) (ppm)	440 ppm
<b>Hexane (110-54-3)</b>		
ACGIH	ACGIH TWA (ppm)	50 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1800 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
IDLH	US IDLH (ppm)	1100 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	180 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	50 ppm
<b>Titanium dioxide (13463-67-7)</b>		
ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup> (total dust)
IDLH	US IDLH (mg/m <sup>3</sup> )	5000 mg/m <sup>3</sup>
<b>Methyl alcohol (67-56-1)</b>		
ACGIH	ACGIH TWA (ppm)	200 ppm
ACGIH	ACGIH STEL (ppm)	250 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	200 ppm
IDLH	US IDLH (ppm)	6000 ppm
NIOSH	NIOSH REL (TWA) (mg/m <sup>3</sup> )	260 mg/m <sup>3</sup>
NIOSH	NIOSH REL (TWA) (ppm)	200 ppm
NIOSH	NIOSH REL (STEL) (mg/m <sup>3</sup> )	325 mg/m <sup>3</sup>
NIOSH	NIOSH REL (STEL) (ppm)	250 ppm
NIOSH	US-NIOSH chemical category	Potential for dermal absorption
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>		
ACGIH	ACGIH TWA (ppm)	100 ppm



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Xylenes (o-, m-, p- isomers) (1330-20-7)		
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	435 mg/m <sup>3</sup>
OSHA	OSHA PEL (TWA) (ppm)	100 ppm

## 8.2. Appropriate engineering controls

No additional information available

## 8.3. Individual protection measures/Personal protective equipment

### Personal protective equipment:

Avoid all unnecessary exposure.

### Hand protection:

Wear protective gloves

### Eye protection:

Chemical goggles or safety glasses

### Skin and body protection:

Wear suitable protective clothing

### Respiratory protection:

Not required under normal conditions. If concentrations exceed exposure limits, use NIOSH approved respirator.

### Other information:

Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid, aerosol
Color	: White
Odor	: Characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available





# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Oxidizing properties : No data available

## 9.2. Other information

Gas group : Compressed gas

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No additional information available

### 10.2. Chemical stability

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Extreme risk of explosion by shock, friction, fire or other sources of ignition.

### 10.3. Possibility of hazardous reactions

Not established.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Heat. Sparks. Open flame. Overheating.

### 10.5. Incompatible materials

Strong acids. Strong bases.

### 10.6. Hazardous decomposition products

Carbon monoxide. Carbon dioxide.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed

<b>Toluene (108-88-3)</b>	
LD50 oral rat	636 mg/kg
LD50 dermal rabbit	8390 mg/kg
LC50 inhalation rat (mg/l)	12.5 mg/l/4h
ATE US (oral)	636 mg/kg body weight
ATE US (dermal)	8390 mg/kg body weight
ATE US (vapors)	12.5 mg/l/4h
ATE US (dust, mist)	12.5 mg/l/4h
<b>Acetone (67-64-1)</b>	
LD50 oral rat	5800 mg/kg
LC50 inhalation rat (mg/l)	50100 mg/m <sup>3</sup> (Exposure time: 8 h)
LC50 inhalation rat (ppm)	30000 ppm/4h
ATE US (oral)	5800 mg/kg body weight
ATE US (gases)	21090.651 ppmV/4h
<b>n-Heptane (142-82-5)</b>	
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (mg/l)	103 g/m <sup>3</sup> (Exposure time: 4 h)
ATE US (dermal)	3000 mg/kg body weight
ATE US (vapors)	103 mg/l/4h
ATE US (dust, mist)	103 mg/l/4h
<b>Hexane (110-54-3)</b>	
LD50 oral rat	25 g/kg
LD50 dermal rabbit	3000 mg/kg
LC50 inhalation rat (ppm)	48000 ppm/4h
ATE US (oral)	25000 mg/kg body weight
ATE US (dermal)	3000 mg/kg body weight
ATE US (gases)	48000 ppmV/4h



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

<b>Titanium dioxide (13463-67-7)</b>	
LD50 oral rat	> 10000 mg/kg

<b>Methyl alcohol (67-56-1)</b>	
LD50 oral rat	6200 mg/kg
LC50 inhalation rat (ppm)	22500 ppm (Exposure time: 8 h)
ATE US (oral)	100 mg/kg body weight
ATE US (dermal)	300 mg/kg body weight
ATE US (gases)	700 ppmV/4h
ATE US (vapors)	3 mg/l/4h
ATE US (dust, mist)	0.5 mg/l/4h

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LD50 oral rat	4300 mg/kg
LC50 inhalation rat (mg/l)	47635 mg/l/4h
ATE US (oral)	4300 mg/kg body weight
ATE US (dermal)	1100 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Causes skin irritation.  
 Serious eye damage/irritation : Causes serious eye irritation.  
 Respiratory or skin sensitization : Not classified  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Suspected of causing cancer.

<b>Toluene (108-88-3)</b>	
IARC group	3 - Not classifiable

<b>Titanium dioxide (13463-67-7)</b>	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
IARC group	3 - Not classifiable

Reproductive toxicity : Suspected of damaging fertility or the unborn child.  
 Specific target organ toxicity – single exposure : May cause drowsiness or dizziness. Causes damage to organs.

Specific target organ toxicity – repeated exposure : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

Potential Adverse human health effects and symptoms : Harmful if swallowed

Symptoms/injuries : Suspected of damaging fertility or the unborn child. Causes damage to organs.

Symptoms/injuries after inhalation : Shortness of breath. May cause drowsiness or dizziness.

Symptoms/injuries after skin contact : Causes skin irritation.





# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>Toluene (108-88-3)</b>	
LC50 fish 1	15.22 - 19.05 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	5.46 - 9.83 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 other aquatic organisms 1	> 433 mg/l (Exposure time: 96 h - Species: Pseudokirchneriella subcapitata)
LC50 fish 2	12.6 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	11.5 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 other aquatic organisms 2	12.5 mg/l (Exposure time: 72 h - Species: Pseudokirchneriella subcapitata [static])
<b>Acetone (67-64-1)</b>	
LC50 fish 1	4.74 - 6.33 ml/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	10294 - 17704 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
LC50 fish 2	6210 - 8120 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 2	12600 - 12700 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>n-Heptane (142-82-5)</b>	
LC50 fish 1	375 mg/l (Exposure time: 96 h - Species: Cichlid fish)
<b>Hexane (110-54-3)</b>	
LC50 fish 1	2.1 - 2.98 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
<b>Methyl alcohol (67-56-1)</b>	
LC50 fish 1	28200 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 fish 2	> 100 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

### 12.2. Persistence and degradability

<b>Waterproof Patch &amp; Seal Spray - White</b>	
Persistence and degradability	Not established.
<b>Toluene (108-88-3)</b>	
Persistence and degradability	Not established.
<b>Acetone (67-64-1)</b>	
Persistence and degradability	Not established.
<b>n-Heptane (142-82-5)</b>	
Persistence and degradability	Not established.
<b>Titanium dioxide (13463-67-7)</b>	
Persistence and degradability	Not established.
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Persistence and degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative potential

<b>Waterproof Patch &amp; Seal Spray - White</b>	
Bioaccumulative potential	Not established.
<b>Toluene (108-88-3)</b>	
Log Pow	2.65
Bioaccumulative potential	Not established.



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

<b>Acetone (67-64-1)</b>	
BCF fish 1	0.69
Log Pow	-0.24
Bioaccumulative potential	Not established.
<b>n-Heptane (142-82-5)</b>	
Log Pow	4.66
Bioaccumulative potential	Not established.
<b>Titanium dioxide (13463-67-7)</b>	
Bioaccumulative potential	Not established.
<b>Methyl alcohol (67-56-1)</b>	
BCF fish 1	< 10
Log Pow	-0.77
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
Bioaccumulative potential	Not established.

## 12.4. Mobility in soil

No additional information available

## 12.5. Other adverse effects

<b>Hexane (110-54-3)</b>	
1990 Hazardous Air Pollutant (Clean Air Act)	Yes

Other information : Avoid release to the environment.

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Container under pressure. Do not drill or burn even after use.

Additional information : Flammable vapors may accumulate in the container.



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

Ecology - waste materials : Avoid release to the environment.

## SECTION 14: Transport information

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

Proper Shipping Name : AEROSOLS  
Hazard Class : 2.1  
Identification Number : UN1950  
Label Codes : 2.1



ERG Number : 126

### 14.2. In Accordance with IMDG

Proper Shipping Name : AEROSOLS  
Hazard Class : 2.1  
Identification Number : UN1950  
Label Codes : 2.1



EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U

### 14.3. In Accordance with IATA

Proper Shipping Name : AEROSOLS, FLAMMABLE  
Hazard Class : 2.1  
Identification Number : UN1950  
Label Codes : 2.1



ERG Code (IATA) : 10L

### 14.4. In Accordance with TDG

Proper Shipping Name : AEROSOLS  
Hazard Class : 2.1  
Identification Number : UN1950  
Label Codes : 2.1



## SECTION 15: Regulatory information

### 15.1. US Federal regulations

Waterproof Patch & Seal Spray - White	
SARA Section 311/312 Hazard Classes	Flammable Skin corrosion or irritation Serious eye damage or irritation Carcinogenicity Reproductive toxicity Specific target organ toxicity Gas Under Pressure

Toluene (108-88-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Fire hazard Delayed (chronic) health hazard Immediate (acute) health hazard



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

<b>Acetone (67-64-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
SARA Section 311/312 Hazard Classes	Fire hazard
<b>n-Heptane (142-82-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
<b>Hexane (110-54-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
CERCLA RQ	5000 lb
<b>Titanium dioxide (13463-67-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Methyl alcohol (67-56-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Listed on United States SARA Section 313	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Immediate (acute) health hazard Fire hazard

## 15.2. International regulations

### CANADA

<b>Toluene (108-88-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Acetone (67-64-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>n-Heptane (142-82-5)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Hexane (110-54-3)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Titanium dioxide (13463-67-7)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Methyl alcohol (67-56-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Xylenes (o-, m-, p- isomers) (1330-20-7)</b>
Listed on the Canadian DSL (Domestic Substances List)

### EU-Regulations

<b>Toluene (108-88-3)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Acetone (67-64-1)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>n-Heptane (142-82-5)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)
<b>Hexane (110-54-3)</b>
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

### Titanium dioxide (13463-67-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Methyl alcohol (67-56-1)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances)

## National regulations

### Toluene (108-88-3)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Poisonous and Deleterious Substances Control Law  
Pollutant Release and Transfer Register Law (PRTR Law)

### Acetone (67-64-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)

### n-Heptane (142-82-5)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Listed on INSQ (Mexican national Inventory of Chemical Substances)  
Listed on Turkish inventory of chemical

### Hexane (110-54-3)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Japanese ISHL (Industrial Safety and Health Law)  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Pollutant Release and Transfer Register Law (PRTR Law)  
Listed on INSQ (Mexican national Inventory of Chemical Substances)  
Listed on Turkish inventory of chemical  
Listed on the TCSI (Taiwan Chemical Substance Inventory)

### Titanium dioxide (13463-67-7)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)



# Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

## FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

### Methyl alcohol (67-56-1)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Poisonous and Deleterious Substances Control Law

### Xylenes (o-, m-, p- isomers) (1330-20-7)

Listed on the AICS (Australian Inventory of Chemical Substances)  
Listed on IECSC (Inventory of Existing Chemical Substances Produced or Imported in China)  
Listed on the Japanese ENCS (Existing & New Chemical Substances) inventory  
Listed on the Korean ECL (Existing Chemicals List)  
Listed on NZIoC (New Zealand Inventory of Chemicals)  
Listed on PICCS (Philippines Inventory of Chemicals and Chemical Substances)  
Poisonous and Deleterious Substances Control Law  
Pollutant Release and Transfer Register Law (PRTR Law)

### 15.3. US State regulations

**⚠ WARNING:** This product can expose you to toluene, hexane, titanium dioxide and methyl alcohol which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov).

## SECTION 16: Other information

Other information : None.

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H280	Contains gas under pressure; may explode if heated
H301	Toxic if swallowed
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H311	Toxic in contact with skin
H312	Harmful in contact with skin
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H331	Toxic if inhaled
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H370	Causes damage to organs
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects





## Safety Data Sheet – Waterproof Patch & Seal Spray - White

Date Revised: NA  
Date Issued: 3/11/2019

Version: 1.0

### FOR CHEMICAL EMERGENCY:

During Business Hours: (800) 966-3458 | Outside Business Hours: (800) 420-7186

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations and according to the Hazardous Products Regulation (February 11, 2015).

*The information presented in this Safety Data Sheet was prepared by qualified personnel and to the best of our knowledge is true and accurate. The information and recommendations are furnished for this product with the understanding that the purchaser will independently determine the suitability of the product for this purpose. This data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which The Gorilla Glue Company assumes legal responsibility. The data is submitted for the user's information and consideration only. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial and local laws and regulations.*