



Safety Data Sheet

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: BAR & CHAIN
Product Code: 00C80020
Emergency Phone: CHEMTREC: (800) 424-9300
International: +011(703) 527-3887
Poison Control Center: (800) 222-1222
Company: Warren Distribution, Inc.
 727 S. 13th St.
 Omaha, NE 68102
Information Phone: (800) 825-1235 (402) 341-9397

II. HAZARDS IDENTIFICATION

Routes of Entry: Skin contact
Chemical Interactions: No chemical interaction known to affect toxicity.
Conditions Aggravated by Exposure: Personnel with pre-existing skin disorders should avoid contact with this product., Skin disease including eczema and sensitization, Respiratory disease including asthma and bronchitis, Eye disease

Acute Health Effects:

Inhalation Irritation: Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and headache.
Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.
Skin Absorption: Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.
Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.
Ingestion Irritation: Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea, vomiting and diarrhea.

Chronic Health Effects:

Carcinogenicity: Not a carcinogen according to NTP, IARC, or OSHA.
Reproductive Toxicity: No data available to indicate product or any components present at greater than 0.1% may cause birth defects.
Mutagenicity: No data available to indicate product or any components present at greater than 0.1% is mutagenic or genotoxic.

HMIS Ratings:

Health: 2
 Fire: 1
 Reactivity: 0
 PPE: B

NFPA Ratings:

Health: 2
 Fire: 1
 Reactivity: 0

KEY: 0 - Least 1 - Slight 2 - Moderate 3 - High 4 - Extreme



Safety Data Sheet

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #	OSHA Exposure Limits
Petroleum distillates, hydrotreated heavy paraffinic	30 - 60	64742-54-7	No PEL
Petroleum distillates, solvent dewaxed heavy paraffinic	5 - 10	64742-65-0	No PEL
Petroleum distillates, hydrotreated heavy naphthenic	3 - 7	64742-52-5	No PEL
Residual oils, petroleum, solvent-refined	1 - 5	64742-01-4	No PEL
Petroleum distillates, hydrotreated light naphthenic	1 - 5	64742-53-6	No PEL
Residual oils, (petroleum), hydrotreated	1 - 5	64742-57-0	No PEL
Petroleum distillates, hydrotreated middle	1 - 5	64742-46-7	No PEL
Residual Oils (petroleum) solvent-deasphalted	0.5 - 1.5	64741-95-3	No PEL
Petroleum distillates, hydrotreated light	0.5 - 1.5	64742-47-8	No PEL
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	0.5 - 1.5	72623-83-7	No PEL
Lubricating oils, (petroleum), C20-50	0.5 - 1.5	72623-85-9	No PEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C20-40	0.5 - 1.5	178603-65-1	No PEL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	0.5 - 1.5	72623-86-0	No PEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C25-55	0.5 - 1.5	178603-66-2	No PEL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	0.5 - 1.5	72623-87-1	No PEL
Mineral oil, white	0.5 - 1.5	8042-47-5	No PEL
Residual oils (petroleum), solvent dewaxed	0.5 - 1.5	64742-62-7	No PEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C10-25, branched and cyclic	0.5 - 1.5	445411-73-4	No PEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C15-30	0.5 - 1.5	178603-64-0	No PEL
Lubricating oils, Petroleum, C15-30 Hydrotreated Neutral	0.5 - 1.5	72623-84-8	No PEL
Petroleum distillates, hydrotreated light paraffinic	0.5 - 1.5	64742-55-8	No PEL
Kerosine, petroleum, hydrodesulfurized	0.1 - 1	64742-81-0	No PEL
Distillates, petroleum, hydrodesulfurized light catalytic cracked	0.1 - 1	68333-25-5	No PEL
Light hydrocracked distillate	0.1 - 1	64741-77-1	No PEL

Components not listed are not physical or health hazards as defined in 29 CFR 1910.1200 (Hazard Communication Standard).

IV. FIRST-AID MEASURES

Inhalation:	Remove to fresh air. If breathing is difficult, have a trained individual administer oxygen. If not breathing, give artificial respiration and have a trained individual administer oxygen and get medical attention immediately.
Eyes:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this MSDS.
Notes to Doctor:	No additional first aid information available.

V. FIRE FIGHTING MEASURES

Flammability	Combustible at elevated temperatures
Summary:	
Extinguishing Media:	Use alcohol resistant foam, carbon dioxide, or dry chemical when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the surface of the fire. Do not direct a stream of water into the hot burning liquid.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.



Safety Data Sheet

Fire Fighting Methods and Protection: Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Use methods for the surrounding fire.

Hazardous: Toxic fumes.

Combustion Products:

Flash Point: 193 °C (379 °F)

Autoignition Temperature: No data.

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment: Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods for Clean-up: No special spill clean up considerations. Collect and discard in regular trash. Avoid runoff into storm sewers and ditches that lead to waterways.

VII. HANDLING AND STORAGE

Handling Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. Empty containers may retain product residues/ vapors. Use proper bonding and grounding during bulk product transfer.

Storage Conditions: Store in a cool dry place. Isolate from incompatible materials.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls: Local exhaust ventilation or other engineering controls may be required when handling or using this product to avoid overexposure.

Respiratory Protection: Respiratory protection may be required to avoid overexposure when handling this product. General or local exhaust ventilation is the preferred means of protection. Use a respirator if general room ventilation is not available or sufficient to eliminate symptoms.

Respirator Type(s): None required where adequate ventilation is provided. If airborne concentrations are above the applicable exposure limits, use NIOSH/MSHA approved respiratory protection.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin Protection: Avoid skin contact by wearing chemically resistant gloves, an apron and other protective equipment depending upon conditions of use. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves: Neoprene, Nitrile

Control Parameters:

Chemical Name	ACGIH TLV-TWA	ACGIH IDLH	OSHA STEL
Petroleum distillates, hydrotreated heavy paraffinic	No TLV	No IDLH	No STEL
Petroleum distillates, solvent dewaxed heavy paraffinic	No TLV	No IDLH	No STEL
Petroleum distillates, hydrotreated heavy naphthenic	No TLV	No IDLH	No STEL
Residual oils, petroleum, solvent-refined	No TLV	No IDLH	No STEL
Petroleum distillates, hydrotreated light naphthenic	No TLV	No IDLH	No STEL
Residual oils, (petroleum), hydrotreated	No TLV	No IDLH	No STEL
Petroleum distillates, hydrotreated middle	No TLV	No IDLH	No STEL
Residual Oils (petroleum) solvent-deasphalted	No TLV	No IDLH	No STEL



Safety Data Sheet

Petroleum distillates, hydrotreated light	No TLV	No STL	No IDLH	No STEL
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	No TLV	No STL	No IDLH	No STEL
Lubricating oils, (petroleum), C20-50	No TLV	No STL	No IDLH	No STEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C20-40	No TLV	No STL	No IDLH	No STEL
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	No TLV	No STL	No IDLH	No STEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C25-55	No TLV	No STL	No IDLH	No STEL
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	No TLV	No STL	No IDLH	No STEL
Mineral oil, white	No TLV	No STL	No IDLH	No STEL
Residual oils (petroleum), solvent dewaxed	No TLV	No STL	No IDLH	No STEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C10-25, branched and cyclic	No TLV	No STL	No IDLH	No STEL
Gas oils, petroleum, vacuum, hydrocracked, hydroisomerized, hydrogenated, C15-30	No TLV	No STL	No IDLH	No STEL
Lubricating oils, Petroleum, C15-30 Hydrotreated Neutral	No TLV	No STL	No IDLH	No STEL
Petroleum distillates, hydrotreated light paraffinic	No TLV	No STL	No IDLH	No STEL
Kerosine, petroleum, hydrodesulfurized	200 mg/m3 TWA (application restricted to conditions in which there are negligible aerosol exposures, total hydrocarbon vapor)	No STL	No IDLH	No STEL
Distillates, petroleum, hydrodesulfurized light catalytic cracked	No TLV	No STL	No IDLH	No STEL
Light hydrocracked distillate	No TLV	No STL	No IDLH	No STEL

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid
Color:	Amber
Odor:	Mild
Viscosity:	11.00 cSt @100°C
Solubility in Water:	Insoluble
Evaporation Rate:	No data.
Vapor Pressure:	No data.
Boiling Point (°C):	No data.
Specific Gravity:	0.87
Density:	7.28
Flash Point (°C):	193
Flash Point Method:	COC
Upper Flammability	Unknown
Limit, % in air:	
Lower Flammability	Unknown
Limit, % in air:	



Safety Data Sheet

X. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition.
Materials to Avoid:	Strong oxidizing agents
Hazardous Decomp. Products:	Carbon monoxide, sulfur oxides, aldehydes, and other petroleum decomposition products in the case of incomplete combustion. Oxides of nitrogen, phosphorus, calcium, copper, magnesium, sodium, and hydrogen sulfide may also be present., Toxic fumes.
Hazardous Polymerization:	Will not occur.

XI. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Ingestion:	Although this product has a low order of acute oral toxicity, aspiration of minute amounts into the lungs during ingestion or vomiting may cause mild to severe pulmonary injury and possibly death.
Inhalation:	Harmful! Can cause systemic damage (see "Target Organs").
Absorption:	Minimal hazard in normal industrial use. May cause gastrointestinal discomfort.
Eyes (Draize score):	The material is likely to be moderately irritating to eyes based on animal data.
Skin (Draize score):	This material is likely to be moderately irritating to skin based on animal data.
Sensitization:	No data.

Component Toxicology Data (NIOSH):

Chemical Name	CAS #	LD₅₀/LC₅₀
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	Inhalation LC50 Rat 2.18 mg/L 4 h; Oral LD50 Rat >2000 mg/kg; Dermal LD50 Rabbit >2000 mg/kg
Residual oils (petroleum), solvent-refined	64742-01-4	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Petroleum distillates, hydrotreated middle	64742-46-7	Inhalation LC50 Rat 4.6 mg/L 4 h (Source: IUCLID); Oral LD50 Rat 7400 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Residual oils, petroleum, solvent deasphalted	64741-95-3	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Petroleum distillates, hydrotreated light	64742-47-8	Inhalation LC50 Rat >5.2 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Lubricating oils (petroleum), C>25, hydrotreated bright stock-based	72623-83-7	Oral LD50 Rat >5000 mg/kg (Source: IUCLID)
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit



Safety Data Sheet

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	>2000 mg/kg (Source: IUCLID) Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
White mineral oil	8042-47-5	Oral LD50 Rat >5000 mg/kg (Source: IUCLID)
Residual oils (petroleum), solvent dewaxed	64742-62-7	Inhalation LC50 Rat 2.18 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	Inhalation LC50 Rat 3900 mg/m ³ 4 h (Source: NLM_CIP)
Kerosine, petroleum, hydrodesulfurized	64742-81-0	Inhalation LC50 Rat >5.2 mg/L 4 h (Source: IUCLID); Oral LD50 Rat >5000 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Distillates, petroleum, hydrodesulfurized light catalytic cracked	68333-25-5	Inhalation LC50 Rat 4.65 mg/L 4 h (Source: IUCLID); Oral LD50 Rat 3200 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)
Distillates, petroleum, light hydrocracked	64741-77-1	Inhalation LC50 Rat 4.65 mg/L 4 h (Source: IUCLID); Oral LD50 Rat 3200 mg/kg (Source: IUCLID); Dermal LD50 Rabbit >2000 mg/kg (Source: IUCLID)

XII. ECOLOGICAL INFORMATION

Overview:	Moderate ecological hazard. This product may be dangerous to plants and/or wildlife.
Mobility:	This material is expected to have essentially no mobility in soil. It absorbs strongly to most soil types.
Persistence:	No data.
Bioconcentration:	Bioconcentration is not expected to occur.
Degradability:	Biodegrades slowly.



Safety Data Sheet

Toxicity to Aquatic Invertebrates:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	48 Hr EC50 Daphnia magna: >1000 mg/L
Residual oils (petroleum), solvent-refined	64742-01-4	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	48 Hr EC50 Daphnia magna: >1000 mg/L
Residual oils, petroleum, solvent deasphalted	64741-95-3	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated light Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity	64742-47-8 72623-85-9	96 Hr LC50 Den-dronereides heteropoda: 4720 mg/L 48 Hr EC50 Daphnia magna: >1000 mg/L
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0	48 Hr EC50 Daphnia magna: >1000 mg/L
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	48 Hr EC50 Daphnia magna: >1000 mg/L
Residual oils (petroleum), solvent dewaxed	64742-62-7	48 Hr EC50 Daphnia magna: >1000 mg/L
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	48 Hr EC50 Daphnia magna: >1000 mg/L
Kerosine, petroleum, hydrodesulfurized	64742-81-0	48 Hr LC50 Den-dronereides heteropoda: 4720 mg/L
Toxicity to Fish:	CAS #	Results
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated heavy naphthenic	64742-52-5	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Residual oils (petroleum), solvent-refined	64742-01-4	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated light naphthenic	64742-53-6	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated middle	64742-46-7	96 Hr LC50 Pimephales promelas: 35 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: >10000 mg/L [static]
Residual oils, petroleum, solvent deasphalted	64741-95-3	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated light	64742-47-8	96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 2.2 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.4 mg/L [static]
Lubricating oils, petroleum, C>25, hydrotreated bright stock-based	72623-83-7	96 Hr LC50 Lepomis macrochirus: >10000 mg/L
Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based, high-viscosity	72623-85-9	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Lubricating oils, petroleum, C15-30, hydrotreated neutral oil-based	72623-86-0	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L



Safety Data Sheet

Lubricating oils, petroleum, C20-50, hydrotreated neutral oil-based	72623-87-1	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
White mineral oil	8042-47-5	96 Hr LC50 Lepomis macrochirus: >10000 mg/L
Residual oils (petroleum), solvent dewaxed	64742-62-7	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Petroleum distillates, hydrotreated light paraffinic	64742-55-8	96 Hr LC50 Oncorhynchus mykiss: >5000 mg/L
Kerosine, petroleum, hydrodesulfurized	64742-81-0	96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 1740 mg/L [static]
Distillates, petroleum, hydrodesulfurized light catalytic cracked	68333-25-5	96 Hr LC50 Brachydanio rerio: 7.3 mg/L [semi-static]
Distillates, petroleum, light hydrocracked	64741-77-1	96 Hr LC50 Brachydanio rerio: 7.3 mg/L [semi-static]

XIII. DISPOSAL CONSIDERATIONS

Disposal of Packaging: Recycle containers whenever possible.
Disposal Methods: Dispose of by incineration following Federal, State, Local, or Provincial regulations.

XIV. TRANSPORTATION INFORMATION

Not classified as hazardous for transport (DOT, TDG, IMO/IMDG, IATA/ICAO).

XV. REGULATORY INFORMATION

TSCA Status: All components of this material are on the US TSCA Inventory or are exempt.
NAFTA Tariff Code: 2710.19.3080
State Restrictions: None Listed.
WHMIS: Uncontrolled product according to WHMIS classification criteria

Chemical Name	Regulation	CAS #	% Range
None Listed.	CERCLA RQ		
Phosphorus	SARA 313	7723-14-0	0.01 - 0.1
Zinc	SARA 313	7440-66-6	0.01 - 0.1
Naphthalene	SARA 313	91-20-3	0.01 - 0.1
Toluene	SARA 313	108-88-3	0.01 - 0.1
Xylene (mixed isomers)	SARA 313	1330-20-7	0.01 - 0.1
ethylbenzene	SARA 313	100-41-4	0.001-0.01
Benzene	SARA 313	71-43-2	0.001-0.01
Biphenyl	SARA 313	92-52-4	0.001-0.01
Cumene	SARA 313	98-82-8	0.001-0.01
Arsenic	SARA 313	7440-38-2	<10ppm
Methyl isobutyl ketone	SARA 313	108-10-1	<10ppm
Ethyl acrylate	SARA 313	140-88-5	<10ppm
Lead	SARA 313	7439-92-1	<10ppm
Cadmium	SARA 313	7440-43-9	<10ppm
None Listed.	SARA 302-EHS		
None Listed.	TSCA 12b export notification		
Naphthalene	CA Prop 65 – Cancer	91-20-3	0.01 - 0.1
ethylbenzene	CA Prop 65 – Cancer	100-41-4	0.001-0.01



Safety Data Sheet

Benzene	CA Prop 65 – Cancer	71-43-2	0.001-0.01
Cumene	CA Prop 65 – Cancer	98-82-8	0.001-0.01
ISOBUTYL METHYL KETONE	CA Prop 65 – Cancer	108-10-1	<10ppm
Ethyl acrylate	CA Prop 65 – Cancer	140-88-5	<10ppm
Lead	CA Prop 65 – Cancer	7439-92-1	<10ppm
Cadmium	CA Prop 65 – Cancer	7440-43-9	<10ppm
Toluene	CA Prop 65 - Dev. Toxicity	108-88-3	0.01 - 0.1
Benzene	CA Prop 65 - Dev. Toxicity	71-43-2	0.001-0.01
Lead	CA Prop 65 - Dev. Toxicity	7439-92-1	<10ppm
Cadmium	CA Prop 65 - Dev. Toxicity	7440-43-9	<10ppm
Toluene	CA Prop 65 - Reprod –fem	108-88-3	0.01 - 0.1
Lead	CA Prop 65 - Reprod –fem	7439-92-1	<10ppm
Benzene	CA Prop 65 - Reprod –male	71-43-2	0.001-0.01
Lead	CA Prop 65 - Reprod –male	7439-92-1	<10ppm
Cadmium	CA Prop 65 - Reprod –male	7440-43-9	<10ppm
Hydrotreated middle distillate (petroleum)	Canadian WHMIS List	64742-46-7	1 - 5
Lubricating oils, (petroleum), C15-30, hydrotreated neutral oil-based	Canadian WHMIS List	72623-86-0	0.5 - 1.5
White mineral oil	Canadian WHMIS List	8042-47-5	0.5 - 1.5
Kerosine (petroleum), hydrodesulfurized	Canadian WHMIS List	64742-81-0	0.1 - 1
Mineral oil, petroleum distillates, hydrotreated light naphthenic	Massachusetts RTK List	64742-53-6	1 - 5
Mineral oil, petroleum distillates, hydrotreated light paraffinic	Massachusetts RTK List	64742-55-8	0.5 - 1.5
None Listed.	New Jersey RTK List		
None Listed.	Pennsylvania RTK List		
None Listed.	Minnesota Hazardous Substance List		

Consumer Product Safety Improvement Act of 2008 General Conformity Certification:

This product has been evaluated and certified to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product container.

XVI. ADDITIONAL INFORMATION

Supersedes: 2013-07-04 10:58:53

Revision Date: 2013-07-05 12:10:21

Created by: HAZEMS

Disclaimer: This material safety data sheet and the information it contains is offered to you in good faith as accurate. We have reviewed any information contained in the data sheet which we have received from outside sources and we believe the information to be correct, but cannot guarantee its accuracy or completeness. Health and safety precautions in this data sheet may not be adequate for all individuals and/or situations. It is the user's obligation to evaluate and use this product in a safe manner and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as permission or recommendation for the use of any product in a manner that might infringe existing patents. No warranty is made, either expressed or implied.