Version: V1.4

MSDS

MATERIAL SAFETY DATA SHEET

Prepared For : Shenzhen Jin yu zhou Energy Co., Ltd.

2/F, A Building, JinHeRuiYiQuan Industrial

Area, Tangqian Village, Guanlan Street, Longhua

New District, Shenzhen City

Prepared By : Shenzhen LCS Compliance Testing Laboratory Ltd.

101, 201 Building A and 301 Building C, Juji

Industrial Park, Yabianxueziwei, Shajing Street,

Baoan District, Shenzhen, Guangdong, China

Issue Date : 2020.01.10

Report Number : LCS190902241ASD

Written by: _______Quan

Approved by:

REPORT NO.: LCS190902241ASD

* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

client's request.					
Section 1-Chemical Product and Company Identification					
Product Name	Polymer Li-ion Battery				
Model	502025				
Trade Mark	N/A				
Ratings	3.7V, 200mAh, 0.74Wh				
Weight	4.2g	4.2g			
Manufacturer	Shenzher	ı Jin yu zhou Energy	Co., Ltd.		
Manufacturer address		2/F, A Building, JinHeRuiYiQuan Industrial Area,Tangqian Village,Guanlan Street, Longhua New District, Shenzhen City			
Emergency Telephone	+86-755-2	+86-755-28230503			
Fax	+86-755-2	+86-755-29782182			
Section 2- Composition Information					
Chemical Composition		CAS No.	Weight (%)	Trade Secret	
Lithium cobaltate	1	2190-79-3	15 - 40	*	
Graphite	7	782-42-5	10 - 30	*	
Phosphate(1-), hexafluoro-, lithium	2	1324-40-3	10 - 30	*	
Copper	7440-50-8		7-13	*	
Aluminium	7429-90-5		5-10	*	
Nickel	7440-02-0		1-5	*	
" * " The exact	percentage	(concentration) of c	omposition has been withhe	ld as a trade secret.	
	Section 3- Hazards Identification				
Emergency overview:		N/A			
Classification according	to GHS	Not a dangerous s	substance according to GHS		
Label elements:	Label elements:				
Hazard pictogram(s)		Not Available			
Signal word		Not Available			
Hazard statement(s) Not Available					

REPORT NO.: LCS190902241ASD

	REPORT NO.: LCS190902241ASD		
Precautionary statement(s):			
Prevention	Not Available		
Response	Not Available		
Disposal	Not Available		
Environmental hazards:	No relevant information		
Important symptoms:	See section 11 for more information		
Se	ection 4- First Aid Measures		
Eye contact	Flush eyes with plenty of water for least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.		
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.		
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.		
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.		
Section 5- Fire Fighting Measures			
Flash Point	N/A		
Auto-Ignition Temperature	N/A		
Extinguishing Media	H ₂ O, CO ₂		
Special Fire-Fighting Procedures	Self-contained breathing apparatus		
Unusual Fire and Explosion Hazards	Cell may vent when subjected to excessive heat-exposing battery contents		
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.		

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

REPORT NO.: LCS190902241ASD

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters

canalization or waters.		
Sec	ction 7- Handling and Storage	
Handling	The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.	
Storage	Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.	
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.	
Section 8- E	xposure Controls/Personal Protection	
Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.	
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear suitable protective clothing and gloves if handling an open or leaking battery. Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.	
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.	
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.	
Section 9- Physical and Chemical Properties		
Form	Solid	
Color	Silver	
Odour	Not Available	
рН	Not Available	
Melting point/freezing point	Not Available	

REPORT NO.: LCS190902241ASD

B. W. B. ()	N. 4
Boiling Point and Boiling range	Not Available
Flash Point	Not Available
Upper/lower flammability or explosive limits	Not Available
Vapor Pressure	Not Available
Vapor Density	Not Available
Relative density	Not Available
Solubility in Water	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Evaporation rate	Not Available
Flammability (soil, gas)	Not Available
Viscosity	Not Available
Sec	tion 10- Stability and reactivity
Stability	The product is stable under conditions described Section 7
Conditions to Avoid	Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.
Incompatible Materials	Oxidizing agents, acid, base.
Hazardous Decomposition Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.
Possibility of Hazardous Reaction	Not Available
Sectio	n 11 – Toxicological Information
Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratogenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available

REPORT NO.: LCS190902241ASD

Toxicologically Synergistic Materials	Not Available	3190902241A3D		
Section 12- Ecological Information				
Ecological Toxicity	Not Available			
Mobility in soil	Not Available			
Persistence and Degradability	Not Available			
Bioaccumulation potential	Not Available			
Other Adverse Effects	Not Available			
Section 13- Disposal Considerations				
Product disposal recommendation	Observe local, state and federal laws and regulations.			
Uncleaned packaging recommendation	Disposal must be made according to official regulations			
Sec	tion 14 – Transport Information			
Label for conveyance	Lithium Battery Label			
UN Number	UN 3480 or UN 3481			
Transport hazard class(es)	9			
Packing group				
Marine pollutant	No			
UN Proper shipping name	Lithium ion Batteries (Including lithium ion polymer batteries) Lithium ion Batteries packed with equipment (Including lithium ion polymer batteries) Lithium ion Batteries contained in equipments (Including lithium ion polymer batteries)			
ICAO/IATA	Can be shipped by air in accordance with international Civil Aviation Organization (ICAO), TI or International Air Transport Association (IATA) DGR Packing Instructions Section IB~II of 965 or Section II of 966 967 appropriately.	DGR 61 st		
IMDG CODE	International Maritime Dangerous Goods Code under Special Provision 188	IMDG CODE (Amdt.39-18)		
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road under Special Provision 188	ADR 2019		
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail under Special Provision 188	RID 2019		

REPORT NO.: LCS190902241ASD

May be shipped without being declared as Class 9 dangerous goods, when meet to the requirements above.

The dangerous goods regulations require that each battery design be subject to tests contained in Section 38.3 of the UN Manual ofTests and Criteria prior to being offered fortransport.

Section 15- Regulatory information

Law information

《Dangerous Goods Regulations》

《Recommendation on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous Goods》

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《Resource Conservation and Recovery Act》(RCRA)

《European Agreement concerning the International Carriage of Dangerous》

《Regulations concerning the International Carriage of Dangerous》

In according with all Federal, State and local laws.

Section 16- Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

-- End of Report --

Version: V1.2

MSDS

MATERIAL SAFETY DATA SHEET

Prepared For : Shenzhen Jin yu zhou Energy Co., Ltd.

2/F, A Building, Jin Herui Industrial Area, Tang Qian village, Guanlan,

Longhua New District, Shenzhen

Prepared By : Shenzhen LCS Compliance Testing Laboratory Ltd.

101, 601, Xingyuan Industrial Park, Gushu Community, Xixiang Street,

Bao'an District, Shenzhen, Guangdong, China

Issue Date : 2019.06.06

Report Number : LCS190513083ASD100

Written by: Blaire Pang

Approved by:



REPORT NO.: LCS190513083ASD100

* The MSDS is prepared based on the information provided by client. The contents and formats of this MSDS are revised as per client's request.

client's request.					
Section 1-Chemical Product and Company Identification					
Product Name	Polymer Lithium ion Battery				
Model	502030				
Trade Mark	N/A				
Ratings	3.7V, 250mAh, 0.925Wh				
Weight	5.3g				
Manufacturer	Shenzher	Jin yu zhou Energ	y Co., Ltd.		
Manufacturer address	2/F, A Building, Jin Herui Industrial Area, Tang Qian village, Guanlan, Longhua New District, Shenzhen				
Emergency Telephone	+86-755-28230503				
Fax	+86-755-29782182				
Section 2- Composition Information					
Chemical Composition	(CAS No.	Weight (%)	Trade Secret	
Lithium cobaltate	12190-79-3		15 - 40	*	
Graphite	7782-42-5		10 - 30	*	
Phosphate(1-), hexafluoro-, lithium	21324-40-3		10 - 30	*	
Copper	7440-50-8		7-13	*	
Aluminium	7429-90-5		5-10	*	
Nickel	7	440-02-0	1-5	*	
" * " The exact p	percentage	(concentration) of c	composition has been withheld	d as a trade secret.	
	Sec	tion 3- Haza	rds Identification		
Emergency overview:		N/A			
Classification according	to GHS	Not a dangerous s	substance according to GHS		
Label elements:					
Hazard pictogram(s) No available		No available			
Signal word	Signal word No available				
Hazard statement(s)	nt(s) No available				

REPORT NO.: LCS190513083ASD100

	REPORT NO.: LCS190513083ASD100
Precautionary statement(s):	
Prevention	No available
Response	No available
Disposal	No available
Environmental hazards:	No relevant information
Important symptoms:	See section 11 for more information
Se	ection 4- First Aid Measures
Eye contact	Flush eyes with plenty of water for least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical aid.
Skin contact	Remove contaminated clothes and rinse skin with plenty of water or shower for 15 minutes. Get medical aid.
Inhalation	Remove from exposure and move to fresh air immediately. Use oxygen if available.
Ingestion	Give at least 2 glasses of milk or water. Induce vomiting unless patient is unconscious. Call a physician.
Sec	tion 5- Fire Fighting Measures
Flash Point	N/A
Auto-Ignition Temperature	N/A
Extinguishing Media	H ₂ O, CO ₂
Special Fire-Fighting Procedures	Self-contained breathing apparatus
Unusual Fire and Explosion Hazards	Cell may vent when subjected to excessive heat-exposing battery contents
Hazardous Combustion Products	Carbon monoxide, carbon dioxide, lithium oxide fumes.

Section 6- Accidental Release Measures

Personal precautions, protective equipment and emergency procedures:

If the battery is released, remove personnel from area until fumes dissipate. Provide maximum ventilation to clear out hazardous gases. The preferred response is to leave the area and allow the vapors to dissipate. Avoid skin and eyes contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerated. If leakage of the battery happens, liquid could be absorbed with sand, earth or other inert substance and contaminated area should be ventilated meantime.

Environment precautions:

Do not allow product to reach sewage system or any water source.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

REPORT NO.: LCS190513083ASD100

Methods and material for containment and cleaning up:

If battery casing is dismantled, small amounts of electrolyte may leak. Collect all released material in a plastic lined container. Dispose off according to the local law and rules. Avoid leached substances to get into the earth, canalization or waters.

Section 7- Handling and Storage		
Handling	The battery should not be opened, destroyed or incinerate, since they may leak or rupture and release to the environment the ingredients that they contain in the hermetically sealed container. Do not short circuit terminals, or over charge the battery, forced over-discharge, throw to fire. Do not crush or puncture the battery, or immerse in liquids.	
Storage	Avoid mechanical or electrical abuse. Storage preferably in cool, dry and ventilated area, which is subject to little temperature change. Storage at high temperatures should be avoided. Do not place the battery near heating equipment, nor expose to direct sunlight for long periods.	
Other Precautions	The battery may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.	
Section 8- E	xposure Controls/Personal Protection	
Engineering Controls	Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor. Keep away from heat and open flame. Store in a cool, dry place.	
Personal Protective Equipment	Respiratory Protection: Not necessary under normal conditions. Skin and body Protection: Not necessary under normal conditions, Wear suitable protective clothing and gloves if handling an open or leaking battery. Hand protection: Wear suitable gloves if handling an open or leaking battery. Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.	
Other Protective Equipment	Have a safety shower and eye wash fountain readily available in the immediate work area.	
Hygiene Measures	Do not eat, drink, or smoke in work area. Maintain good housekeeping.	
Section 9- Physical and Chemical Properties		
Form	Solid	
Color	Silver	
Odour	No available	
рН	No available	

REPORT NO.: LCS190513083ASD100

Melting point/freezing point	No available	
Boiling Point and Boiling range	No available	
Flash Point	No available	
Upper/lower flammability or explosive limits	No available	
Vapor Pressure	No available	
Vapor Density	No available	
Relative density	No available	
Solubility in Water	No available	
Auto-ignition temperature	No available	
Decomposition temperature	No available	
Evaporation rate	No available	
Flammability (soil, gas)	No available	
Viscosity	No available	
Section 10- Stability and reactivity		
	ion to- Stability and reactivity	
Stability	The product is stable under conditions described Section 7	
	-	
Stability	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble,	
Stability Conditions to Avoid	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions.	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base.	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition Products Possibility of Hazardous Reaction	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base. Carbon monoxide, carbon dioxide, lithium oxide fumes.	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition Products Possibility of Hazardous Reaction	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base. Carbon monoxide, carbon dioxide, lithium oxide fumes. Not Available	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition Products Possibility of Hazardous Reaction Sectio	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base. Carbon monoxide, carbon dioxide, lithium oxide fumes. Not Available n 11 — Toxicological Information Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition Products Possibility of Hazardous Reaction Sectio	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base. Carbon monoxide, carbon dioxide, lithium oxide fumes. Not Available n 11 — Toxicological Information Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur.	
Stability Conditions to Avoid Incompatible Materials Hazardous Decomposition Products Possibility of Hazardous Reaction Sectio Irritation Sensitization	The product is stable under conditions described Section 7 Heat above 70°C or incinerate. Deform, Mutilate, Crush, Disassemble, Overcharge, Short circuit, Expose over a long period to humid conditions. Oxidizing agents, acid, base. Carbon monoxide, carbon dioxide, lithium oxide fumes. Not Available n 11 — Toxicological Information Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory tract may occur. Not Available	

REPORT NO.: LCS190513083ASD100

	REPORT NO.: LCS190513083ASD100		
Mutagenicity (Genetic Effects)	Not Available		
Toxicologically Synergistic Materials	Not Available		
Sec	tion 12- Ecological Information		
Ecological Toxicity	Not Available		
Mobility in soil	Not Available		
Persistence and Degradability	Not Available		
Bioaccumulation potential	Not Available		
Other Adverse Effects	Not Available		
Sect	Section 13- Disposal Considerations		
Product disposal recommendation	Observe local, state and federal laws and regulations.		
Uncleaned packaging recommendation	Disposal must be made according to official regulations		
Sec	tion 14 – Transport Information		
Label for conveyance	Lithium Battery Label		
UN Number	UN 3480 or UN 3481		
Transport hazard class(es)	9		
Packing group			
Marine pollutant	No		
UN Proper shipping name	Lithium ion Batteries (Including lithium ion polymer batteries) Lithium ion Batteries packed with equipment (Including lithium ion polymer batteries) Lithium ion Batteries contained in equipments (Including lithium ion polymer		
Transport information:	batteries)		

Transport information:

Polymer Lithium ion Battery (Sample Model: 502030) is tested and has passed in accordance with UN manual of Tests and Criteria, Part III, subsection 38.3.

The goods shall be complied with the requirements of Section IB~II of Packing Instruction 965 or of Section II of Packing Instruction 966 967 of 60th DGR Manual of IATA or special provision 188 of IMDG CODE (Amdt. 39-18).

Separate Lithium-ion batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport, ensure that the goods will not falling, dropping, and breakage, Prevent collapse of cargo piles and wet by rain.

Transport Fashion: By air, by sea, by railway, by road.

REPORT NO.: LCS190513083ASD100

Section 15- Regulatory information

Law information

《Dangerous Goods Regulations》

《Recommendation on the Transport of Dangerous Goods Model Regulations》

《International Maritime Dangerous Goods》

《Technical Instructions for the Safe Transport of Dangerous Goods》

《Classification and code of dangerous Goods》

《Occupational Safety and Health Act》(OSHA)

《Toxic Substance Control Act》 (TSCA)

《Consumer Product Safety Act》(CPSA)

《Federal Environmental Pollution Control Act》(FEPCA)

《The Oil Pollution Act》(OPA)

《Superfund Amendments and Reauthorization Act Title III (302/311/312/313)》(SARA)

《Resource Conservation and Recovery Act》(RCRA)

《Safety Drinking Water Act》(CWA)

《California Proposition 65》

《Code of Federal Regulations》(CFR)

In according with all Federal, State and local laws.

Section 16- Other Information

The information above is believed to be accurate and represents the best information currently available to us. However, concorde makes no warranty of merchantability or any other warranty, express or implied, with respect to such information, and we assume no liability resulting from its use. Users should make their own investigations to determine the suitability of the information for their particular purposes. Although reasonable precautions have been taken in the preparation of the data contained herein, it is offered solely for your information, consideration and investigation. This material safety data sheet provides guidelines for the safe handling and use of this product; it does not and cannot advise on all possible situations, therefore, your specific use of this product should be evaluated to determine if additional precautions are required.

-- End of Report --