



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 1 of 10

**Applicant** : SHENZHEN UQUAN ELECTRONICS CO.,LTD  
**Address** : 5/F BUILDING 5,ZHONG LIANG INDUSTRIAL PARK,DA YANG TIAN,  
FU YONG STREET ,BAO AN DISTRICT,SHEN ZHEN CITY  
**Sample Name** : Polymer lithium battery  
**Model No.** : UQUAN 18650/2400mAh  
**Product Specification** : 3.7V 2400mAh 8.88Wh  
**Manufacturer** : SHENZHEN UQUAN ELECTRONICS CO.,LTD  
**Address** : 5/F BUILDING 5,ZHONG LIANG INDUSTRIAL PARK,DA YANG TIAN,  
FU YONG STREET ,BAO AN DISTRICT,SHEN ZHEN CITY  
**Sample Received Date** : Dec. 31, 2021  
**Completed Date** : Jan. 05, 2022



Signed for and on Behalf of ZCT



Tomy Wu/Laboratory manager  
Shenzhen ZCT Technology Co.,Ltd.



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 2 of 10


## Material Safety Data Sheet

### Section 1 - Chemical Product and Company Identification

#### Product Identification

Product Name:	Polymer lithium battery
Model No.:	UQUAN 18650/2400mAh
Applicant:	SHENZHEN UQUAN ELECTRONICS CO.,LTD
Address:	5/F BUILDING 5,ZHONG LIANG INDUSTRIAL PARK,DA YANG TIAN, FU YONG STREET ,BAO AN DISTRICT,SHEN ZHEN CITY
Manufacturer:	SHENZHEN UQUAN ELECTRONICS CO.,LTD
Address:	5/F BUILDING 5,ZHONG LIANG INDUSTRIAL PARK,DA YANG TIAN, FU YONG STREET ,BAO AN DISTRICT,SHEN ZHEN CITY
Contact Person:	Xie Jian Ping
E-mail:	N/A
TEL :	13423929293
FAX:	N/A

### Section 2- Hazard identification

Classification of the substance or mixture:	<p>Flammable liquids (Category 3), H226</p> <p>Flammable solids (Category 1), H228</p> <p>Acute toxicity, Oral (Category 4), H302</p> <p>Skin corrosion (Category 1A), H314</p> <p>Specific target organ toxicity - repeated exposure (Category 1), H372</p> <p>Acute aquatic toxicity (Category 1), H400</p> <p>Chronic aquatic toxicity (Category 3), H412</p> <p>Skin sensitisation (Category 1), H317</p> <p>Carcinogenicity (Category 1B), H350</p>
GHS label elements, including precautionary statements :	<p>Pictogram:</p> 



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 3 of 10

	<p><b>Signal word:</b> Danger</p>
<p><b>GHS label elements, including precautionary statements :</b></p>	<p><b>Hazard statement(s) :</b>            H226 Flammable liquid and vapour.            H228 Flammable solid.            H302 Harmful if swallowed.            H314 Causes severe skin burns and eye damage.            H372 Causes damage to organs through prolonged or repeated exposure.            H410 Very toxic to aquatic life with long lasting effects.            H317 May cause an allergic skin reaction.            H350 May cause cancer.            H351 Suspected of causing cancer.</p> <p><b>Precautionary statement(s) :</b>            P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking            P201 Obtain special instructions before use.            P260 Do not breathe dust/fume/gas/mist/vapours/spray.            P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.            P273 Avoid release to the environment            P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.            P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove            P370 + P378 In case of fire: Use dry powder or dry sand to extinguish            P308 + P313 IF exposed or concerned: Get medical advice/ attention.</p> <p><b>Supplemental Hazard :</b>none</p>
<p><b>Other hazards which do not result in classification</b></p>	<p>This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.</p>



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 4 of 10

## Section 3 - Composition/Information on Ingredients

Chemical Name	CAS No.	Composition In %by weight
1. Lithium Cobalt Dioxide (LiCoO <sub>2</sub> )	12190-79-3	36.5
2. Graphite (C)	7782-42-5	17
3.Ethylene carbonate	96-49-1	5
4. Styrene-Butadiene polymer	9003-55-8	1.5
5. Nickel	7440-02-0	2.2
6. Aluminum	7429-90-5	9
7. Copper	7440-50-8	15

## Section 4 - First-aid Measures

<b>General Advice</b>	The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused.
<b>Eyes</b>	If battery is leaking and material contacts the eye, flush thoroughly with copious amounts of running water for 30 minutes. Seek immediate medical advice.
<b>Skin</b>	If battery is leaking and material contacts the skin, remove any contaminated clothing and flush exposed skin with copious amounts of running water for at least 15 minutes. If irritation, injury or pain persists, seek medical advice.
<b>Inhaled</b>	If battery is leaking, contents may be irritating to respiratory passages. Move to fresh air. If irritation persists, seek medical advice.
<b>Swallowed</b>	If battery is swallowed seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. If mouth area irritation or burning has occurred, rinse the mouth and surrounding area with tepid water for at least 15 minutes. Do not give ipecac.

## Section 5 - Fire Fighting Measures

<b>Fire and Explosion Hazards</b>	Batteries may burst and release hazardous decomposition products when exposed to a fire situation.
<b>Extinguishing Media</b>	Use any extinguishing media that is appropriate for the surrounding fire.
<b>Special Fire Fighting Procedures</b>	Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Fight fire from a distance or protected area. Cool fire exposed batteries to prevent rupture. Use caution when handling fire-exposed containers (batteries may explode in heat of fire).





# MSDS

Report No.:22ZCTB0105013SP

Issue Date: Jan. 05, 2022

Page 5 of 10

<b>Hazardous Combustion Products</b>	Thermal degradation may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products.
--------------------------------------	---

## Section 6 - Accidental Release Measures

Notify safety personnel of large spills. Irritating vapors and flammable may be released from leaking or ruptured batteries. Eliminate all ignition sources. Evacuate the area and allow the vapors to dissipate. Clean-up personnel should wear appropriate protective clothing to avoid eye and skin contact and inhalation of vapors or fumes. Increase ventilation. Carefully collect batteries and place in an appropriate container for disposal. Remove spilled liquid with absorbent and contain for disposal.

## Section 7 - Handling And Storage

<b>Handling</b>	Avoid mechanical or electrical abuse. DO NOT short circuit or install incorrectly. Batteries may explode, pyrolyze or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions. Replace all batteries in equipment at the same time. Do not carry batteries loose in a pocket or bag.
<b>Storage</b>	Store batteries in a dry place at normal room temperature.

## Section 8 - Exposure Controls/Personal Protection

<b>Respiratory Protection</b>	In case of battery venting, provide as much ventilation as possible. Avoid confined areas with venting cell cores. Respiratory Protection is not necessary under conditions of normal use.
<b>Ventilation</b>	Not necessary under conditions of normal use.
<b>Other Protective Clothing or Equipment</b>	Not necessary under conditions of normal use.
<b>Personal Protection is</b>	Respiratory Protection, Protective Gloves, Protective Clothing and safety glass





# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 6 of 10

recommended for venting battery	with side shields.
---------------------------------	--------------------

## Section 9 - Physical and Chemical Properties

Appearance	square
Odour	Odorlessness
Colour	blue
pH	Not applicable
Flash Point	Not applicable
Flammability	Not applicable
Relative density	Not applicable
Solubility (water)	Not applicable
Solubility (other)	Not applicable

## Section 10 - Stability and Reactivity

Stability	This product is stable.
Incompatibility/Conditions to Avoid	Contents are incompatible with strong oxidizing agents. Do not heat, crush, disassemble, short circuit or recharge.
Hazardous Decomposition Products	Thermal decomposition may produce hazardous fumes of lithium and manganese; hydrofluoric acid, oxides of carbon and sulfur and other toxic by-products.
Hazardous Polymerization	Will not occur

## Section 11 - Toxicological Information

Potential Health Effects	The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused.
Eye Contact	Contact with battery contents may cause irritation.
Skin Contact	Contact with battery contents may cause irritation.
Inhalation	Inhalation of vapors or fumes released due to heat or a large number of leaking batteries may cause respiratory and eye irritation.



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 7 of 10

<b>Ingestion</b>	Swallowing is not anticipated for larger batteries due to battery size. Smaller batteries may be swallowed. If battery is swallowed, seek immediate medical advice. Batteries lodged in the esophagus should be removed immediately since leakage, caustic burns and perforation can occur as soon as two hours after ingestion. Irritation to the internal/external mouth areas, may occur following exposure to a leaking battery.
<b>Chronic Effects</b>	The chemicals in this product are contained in a sealed can and exposure does not occur during normal handling and use. No chronic effects would be expected from handling a leaking battery.
<b>Target Organs</b>	Skin, eyes and respiratory system.
<b>Carcinogenicity</b>	None of the components of this product are listed as carcinogens by the EU Directive on the classification and labeling of substances.

## Section 12 - Ecological Information

No ecotoxicity data is available. This product is not expected to present an environmental hazard.

## Section 13 - Disposal

Do not incinerate or subject cells to temperature in excess of 80°C. Dispose of in accordance with local regulations.

## Section 14 - Transport Information

All lithium, lithium ion and lithium polymer cells and batteries must be tested in accordance with the "UN Manual of Tests and Criteria, Part III, Subsection 38.3 2017.

The 63rd edition of the IATA Dangerous Goods Regulations incorporates all amendments made by the ICAO Dangerous Goods Panel in developing the content of the 2022 edition of the ICAO Technical Instructions as well as changes adopted by the IATA Dangerous Goods Board.



# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 8 of 10

Their regulations are based on the UN Recommendations. The UN Recommendations require that lithium ion cells and batteries shall be manufactured under a quality management program and this requirement is adopted by IMDG Code and ICAO TI/IATA DGR.

The following list is intended to assist the user to identify the main changes introduced in this edition and must not be considered an exhaustive listing. The changes have been prefaced by the section or subsection in which the change occurs.

## UN number

UN3480. PACKING INSTRUCTION 965 Single Lithium-ion Batteries only.

## Proper shipping name

Air transport (ICAO/IATA)	Polymer lithium battery
Sea transport (IMDG)	Polymer lithium battery
Inland waterway transport (ADN)	Polymer lithium battery
Land transport (ADR/RID)	Polymer lithium battery

## Hazard Class

Air transport (ICAO/IATA)	9
Sea transport (IMDG)	9
Inland waterway transport (ADN)	9
Land transport (ADR/RID)	9

## Packing Group

Air transport (ICAO/IATA)	
Sea transport (IMDG)	
Inland waterway transport (ADN)	
Land transport (ADR/RID)	

## Environmental Hazards

Dangerous goods

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Worldwide air transportation: The goods are packaged according to Section 1A of PACKING INSTRUCTION 965 of the 2019 IATA Dangerous Goods. Lithium-ion batteries may be air transported on CARGO AIRCRAFT ONLY and are forbidden in passenger aircraft.

Worldwide sea transportation: The goods are packaged according to the special provision 188 of IMDG. IMO-IMDG Code [P903]

## Labeling

Use Class 9 Miscellaneous Dangerous Goods and UN Identification labels for transportation of lithium-ion batteries which are assigned Class 9. Refer to relevant transportation documents. Lithium and lithium-ion





# MSDS

Report No.:22ZCTB0105013SP

Issue Date: Jan. 05, 2022

Page 9 of 10

cells and batteries are regulated in the USA in accordance with Part 49 Regulations of the Code of Federal Regulations, (49 CFR Sections 105-180) of the U.S. Hazardous Materials Regulations.

Lithium-ion batteries, under UN3480, PI 965, Section IB



Cells and batteries must be packed in inner packaging that completely encloses the cell or battery.

Cells and batteries must be protected so as to prevent short circuits. This includes protection against contact with conductive materials within the same packaging that could lead to a short circuit.

Each consignment must be accompanied with a document such as an air waybill with an indication that:

- the package contains lithium ion cells or batteries;
- the package must be handled with care, and that a flammability hazard exists if the package is damaged;
- special procedures should be followed in the event the package is damaged, to include inspection and repacking if necessary; and
- a telephone number for additional information.

Each package must be labelled with a lithium battery handling label;

Any person preparing or offering cells or batteries for transport must receive adequate instruction on these requirements commensurate with their responsibilities.

## Section 15 - Regulatory Information

Special requirement be according to the local regulations.

« Dangerous Goods Regulations »

« Recommendations on the Transport of Dangerous Goods Model Regulations »

« International Maritime Dangerous Goods »

« Technical Instructions for the Safe Transport of Dangerous Goods »

« Classification and code of dangerous goods »





# MSDS

Report No.:22ZCTB0105013SP

Issue Date:Jan. 05, 2022

Page 10 of 10

- « Occupational Safety and Health Act » (OSHA)
- « Toxic Substance Control Act » (TSCA)
- « Consumer Product Safety Act » (CPSA)
- « Federal Environmental Pollution Control Act » (FEPCA)
- « The Oil Pollution Act » (OPA)
- « Superfund Amendments and Reauthorization Act Title III(302/311/312/313) » (SARA)
- « Resource Conservation and Recovery Act » (RCRA)
- « Safety Drinking Water Act » (CWA)
- « California Proposition 65 »
- « Code of Federal Regulations » (CFR)
- « 2019 Lithium battery guidance document, revision 1 »

## Section 16 - Other Information

<b>Note</b>	This Sheet is provided as technical information only. The information and recommendations set forth are made in good faith and believed to be accurate as of the date of preparation. Shenzhen ZCT Technology Co., Ltd. makes no warranty, expressed or implied, with respect to this information and disclaims all liabilities from reliance on it.
-------------	--

\*\*\*End of MSDS\*\*\*

