



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

SECTION 1: Identification

1.1 Product identifier

Trade name **AXE Fibreboard Can Apollo**

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Consumer uses: Air Freshener

1.3 Details of the supplier of the safety data sheet

Energizer Manufacturing, Inc.
25225 Detroit Rd.
Westlake OH 44145
United States

Telephone: 800-383-7323; 314-985-2000 (USA / CANADA)
e-mail: Autocare.regulatory@energizer.com
Website: <http://data.energizer.com>

1.4 Emergency telephone number

Emergency information service 1-314-985-1511 Int'l: 1-800-526-4727
This number is only available during the following office hours: Mon-Fri 09:00 AM - 05:00 PM

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.4S	skin sensitization	1	Skin Sens. 1	H317
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word warning

- Pictograms

GHS07





Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

- Hazard statements

H227 Combustible liquid.
H317 May cause an allergic skin reaction.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P261 Avoid breathing mist/vapors.
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling 2,4-dimethylcyclohex-3-ene-1-carbaldehyde, (R)-p-mentha-1,8-diene

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Contains (R)-p-mentha-1,8-diene, Methyl atrarate, 2,4-dimethylcyclohex-3-ene-1-carbaldehyde, Methoxy dicyclopentadiene carboxaldehyde, Cineole, Dynascone. May produce an allergic reaction.
Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures








Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
Dihydromyrcenol	CAS No 18479-58-8	1 - < 5	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319 Flam. Liq. 4 / H227	
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	CAS No 319002-92-1	1 - < 5	Flam. Liq. 4 / H227	

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Name of substance	Identifier	Wt%	Classification acc. to GHS	Pictograms
3-Methyl-5-phenylpentanol	CAS No 55066-48-3	1 - <5	Acute Tox. 4 / H302	
Methoxy dicyclopentadiene carboxaldehyde	CAS No 86803-90-9	< 1	Skin Sens. 1B / H317	
2,4-dimethylcyclohex-3-ene-1-carbaldehyde	CAS No 68039-49-6	< 1	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Flam. Liq. 4 / H227	
Methyl atrarate	CAS No 4707-47-5	< 1	Skin Sens. 1B / H317	
Dynascone	CAS No 56973-85-4	< 1	Skin Sens. 1B / H317	
Cineole	CAS No 470-82-6	< 1	Skin Sens. 1B / H317 Flam. Liq. 3 / H226	
(R)-p-mentha-1,8-diene	CAS No 5989-27-5	< 1	Skin Irrit. 2 / H315 Skin Sens. 1 / H317 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226	

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	cellulose	9004-34-6	TLV®		10						AC-GIH® 2022
US	cellulose	9004-34-6	REL		10 (10 h)					i	NIOSH REL
US	cellulose	9004-34-6	PEL		15					i, dust	29 CFR 1910.1000
US	cellulose	9004-34-6	REL		5 (10 h)					r	NIOSH REL
US	cellulose	9004-34-6	PEL		5					r, dust	29 CFR 1910.1000

Notation

- Ceiling-C ceiling value is a limit value above which exposure should not occur
- dust as dust
- i inhalable fraction
- r respirable fraction
- STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)
- TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Relevant DNELs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Dihydromyrcenol	18479-58-8	DNEL	24.7 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Dihydromyrcenol	18479-58-8	DNEL	7 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	DNEL	8.8 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	DNEL	2.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
3-Methyl-5-phenylpentanol	55066-48-3	DNEL	0.88 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
3-Methyl-5-phenylpentanol	55066-48-3	DNEL	5.3 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
3-Methyl-5-phenylpentanol	55066-48-3	DNEL	0.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
3-Methyl-5-phenylpentanol	55066-48-3	DNEL	3 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
Methyl atrarate	4707-47-5	DNEL	2,500 µg/cm ²	human, dermal	worker (industry)	chronic - local effects
Cineole	470-82-6	DNEL	7.05 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Cineole	470-82-6	DNEL	2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
Dynascone	56973-85-4	DNEL	2.52 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Dynascone	56973-85-4	DNEL	0.714 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
(R)-p-mentha-1,8-diene	5989-27-5	DNEL	66.7 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
(R)-p-mentha-1,8-diene	5989-27-5	DNEL	9.5 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Dihydromyrcenol	18479-58-8	PNEC	111 mg/kg	aquatic organisms	water	short-term (single instance)
Dihydromyrcenol	18479-58-8	PNEC	0.278 mg/l	aquatic organisms	water	intermittent release
Dihydromyrcenol	18479-58-8	PNEC	27.8 µg/l	aquatic organisms	freshwater	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Dihydromyrcenol	18479-58-8	PNEC	2.78 µg/l	aquatic organisms	marine water	short-term (single instance)
Dihydromyrcenol	18479-58-8	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Dihydromyrcenol	18479-58-8	PNEC	0.594 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Dihydromyrcenol	18479-58-8	PNEC	0.059 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Dihydromyrcenol	18479-58-8	PNEC	0.103 mg/kg	terrestrial organisms	soil	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	0.013 mg/l	aquatic organisms	freshwater	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	0.117 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	0.012 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	PNEC	0.016 mg/kg	terrestrial organisms	soil	short-term (single instance)
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	0.013 mg/l	aquatic organisms	freshwater	short-term (single instance)
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	1.034 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	0.103 mg/kg	aquatic organisms	marine sediment	short-term (single instance)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
3-Methyl-5-phenylpentanol	55066-48-3	PNEC	0.199 mg/kg	terrestrial organisms	soil	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	3.3 µg/l	aquatic organisms	freshwater	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	0.33 µg/l	aquatic organisms	marine water	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	89 µg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	8.9 µg/kg	aquatic organisms	marine sediment	short-term (single instance)
Methyl atrarate	4707-47-5	PNEC	16 µg/kg	terrestrial organisms	soil	short-term (single instance)
Cineole	470-82-6	PNEC	0.57 mg/l	aquatic organisms	water	intermittent release
Cineole	470-82-6	PNEC	57 µg/l	aquatic organisms	freshwater	short-term (single instance)
Cineole	470-82-6	PNEC	5.7 µg/l	aquatic organisms	marine water	short-term (single instance)
Cineole	470-82-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Cineole	470-82-6	PNEC	1.425 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Cineole	470-82-6	PNEC	0.142 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Cineole	470-82-6	PNEC	0.25 mg/kg	terrestrial organisms	soil	short-term (single instance)
Dynascone	56973-85-4	PNEC	1.7 µg/l	aquatic organisms	freshwater	short-term (single instance)
Dynascone	56973-85-4	PNEC	0.17 µg/l	aquatic organisms	marine water	short-term (single instance)
Dynascone	56973-85-4	PNEC	4.6 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Dynascone	56973-85-4	PNEC	0.242 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
Dynascone	56973-85-4	PNEC	0.024 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Dynascone	56973-85-4	PNEC	0.047 mg/kg	terrestrial organisms	soil	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	14 µg/l	aquatic organisms	freshwater	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	1.4 µg/l	aquatic organisms	marine water	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	1.8 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	3.85 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	0.385 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
(R)-p-mentha-1,8-diene	5989-27-5	PNEC	0.763 mg/kg	terrestrial organisms	soil	short-term (single instance)

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Type of material

PVA: polyvinyl alcohol, Nitrile

- Material thickness

>0.5 mm

- Breakthrough times of the glove material

>120 minutes (permeation: level 4)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	Colorless to pale yellow
Particle	not relevant (liquid)
Odor	characteristic

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>40 °C
Flash point	93 °C
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)
Vapor pressure	65.5 Pa at 25 °C
Density	not determined
Vapor density	this information is not available
Relative density	1.041 – 1.051 (air = 1)



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	not determined
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
9.2 Other information	there is no additional information

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
3-Methyl-5-phenylpentanol	55066-48-3	oral	1,850 mg/kg

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

May cause an allergic skin reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
(R)-p-mentha-1,8-diene	5989-27-5	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Dihydromyrcenol	18479-58-8	LC50	27.8 mg/l	fish	96 h
Dihydromyrcenol	18479-58-8	EC50	38 mg/l	aquatic invertebrates	48 h
Dihydromyrcenol	18479-58-8	ErC50	80 mg/l	algae	72 h
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	LC50	13 mg/l	fish	96 h
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	EC50	>100 mg/l	aquatic invertebrates	24 h
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	ErC50	>85 mg/l	algae	72 h
3-Methyl-5-phenylpentanol	55066-48-3	LC50	13.3 mg/l	fish	96 h
3-Methyl-5-phenylpentanol	55066-48-3	EC50	20 mg/l	aquatic invertebrates	24 h
3-Methyl-5-phenylpentanol	55066-48-3	ErC50	16 mg/l	algae	72 h
Methyl atrarate	4707-47-5	LC50	5.2 mg/l	fish	96 h
Methyl atrarate	4707-47-5	EC50	9.3 mg/l	aquatic invertebrates	48 h
Methyl atrarate	4707-47-5	ErC50	3.3 mg/l	algae	96 h
Cineole	470-82-6	LC50	57 mg/l	fish	96 h
Cineole	470-82-6	EC50	>100 mg/l	aquatic invertebrates	48 h
Cineole	470-82-6	ErC50	>74 mg/l	algae	72 h

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Dynascone	56973-85-4	LC50	1.904 mg/l	fish	96 h
Dynascone	56973-85-4	EC50	1.7 mg/l	aquatic invertebrates	48 h
Dynascone	56973-85-4	ErC50	3.4 mg/l	algae	72 h
(R)-p-mentha-1,8-diene	5989-27-5	LC50	720 µg/l	fish	96 h
(R)-p-mentha-1,8-diene	5989-27-5	EC50	688 µg/l	fish	96 h
(R)-p-mentha-1,8-diene	5989-27-5	ErC50	0.32 mg/l	algae	72 h

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Dihydromyrcenol	18479-58-8	EC50	17 mg/l	aquatic invertebrates	21 d
propyl (2S)-2-[(2-methylbutan-2-yl)oxy]propanoate	319002-92-1	EC50	>100 mg/l	microorganisms	3 h
3-Methyl-5-phenylpentanol	55066-48-3	EC50	20 mg/l	aquatic invertebrates	24 h
Cineole	470-82-6	EC50	>100 mg/l	microorganisms	3 h
Dynascone	56973-85-4	EL50	960 mg/l	microorganisms	3 h
(R)-p-mentha-1,8-diene	5989-27-5	EC50	<0.67 mg/l	fish	8 d
(R)-p-mentha-1,8-diene	5989-27-5	LC50	0.41 mg/l	fish	8 d

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

12.6 Endocrine disrupting properties

None of the ingredients are listed.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number	not subject to transport regulations
14.2 UN proper shipping name	not relevant
14.3 Transport hazard class(es)	not assigned
14.4 Packing group	not assigned
14.5 Environmental hazards	non-environmentally hazardous acc. to the dangerous goods regulations
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to IMO instruments	
The cargo is not intended to be carried in bulk.	

Information for each of the UN Model Regulations

DOT

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not subject to transport regulations.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

International Maritime Dangerous Goods Code (IMDG) - Additional information

Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

none of the ingredients are listed

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

none of the ingredients are listed

Clean Air Act

none of the ingredients are listed

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
Cellulose	9004-34-6	substrate	
Dihydromyrcenol	18479-58-8	fragrance	
Methoxy dicyclopentadiene carboxaldehyde	86803-90-9	fragrance	
2,4-dimethylcyclohex-3-ene-1-carbaldehyde	68039-49-6	fragrance	
Methyl atrarate	4707-47-5	fragrance	
Allyl (cyclohexyloxy)acetate	68901-15-5	fragrance	
Cineole	470-82-6	fragrance	
(R)-p-mentha-1,8-diene	5989-27-5	fragrance	EU Fragrance Allergens
(E)-1-(2,6,6-trimethyl-1,3-cyclohexadien-1-yl)-2-buten-1-one	23726-93-4 23696-85-7	fragrance	
citral	5392-40-5	fragrance	EU Fragrance Allergens



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

- Toxic or Hazardous Substance List (MA-TURA)

none of the ingredients are listed

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
(R)-p-mentha-1,8-diene	138-86-3		F2

Legend

F2 Flammable - Second Degree

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

none of the ingredients are listed

Drug precursors, Chemicals designated within the Controlled Substances Act, 21 U.S.C. § 802, paragraphs 34 (list I) and 35 (list II)

none of the ingredients are listed

Industry or sector specific available guidance(s)

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	/	none
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Category	Degree of hazard	Description
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
AU	AIIC	not all ingredients are listed
CA	DSL	not all ingredients are listed
CA	NDSL	not all ingredients are listed
CN	IECSC	not all ingredients are listed
EU	ECSI	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
JP	CSCL-ENCS	not all ingredients are listed
JP	ISHA-ENCS	not all ingredients are listed
KR	KECI	not all ingredients are listed
MX	INSQ	not all ingredients are listed
NZ	NZIoC	not all ingredients are listed
PH	PICCS	not all ingredients are listed
TR	CICR	not all ingredients are listed
TW	TCSI	not all ingredients are listed
US	TSCA	not all ingredients are listed

Legend

AIIC	Australian Inventory of Industrial Chemicals
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EINECS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
ISHA-ENCS	Inventory of Existing and New Chemical Substances (ISHA-ENCS)
KECI	Korea Existing Chemicals Inventory
NDSL	Non-domestic Substances List (NDSL)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances (PICCS)
REACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Indication of changes (revised safety data sheet)

Section	Former entry (text/value)	Actual entry (text/value)	Safety-relevant
2.2		- Precautionary statements: change in the listing (table)	yes

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH® 2022	From ACGIH®, 2022 TLVs® and BEIs® Book. Copyright 2022. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EINECS	European Inventory of Existing Commercial Chemical Substances
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
ELINCS	European List of Notified Chemical Substances
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Abbr.	Descriptions of used abbreviations
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NLP	No-Longer Polymer
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
TLV®	Threshold Limit Values
TWA	Time-weighted average
vPvB	Very Persistent and very Bioaccumulative

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.



Safety Data Sheet

acc. to 29 CFR 1910.1200 App D

AXE Fibreboard Can Apollo

Version number: 2.0
Replaces version of: 2022-06-14 (1)

Revision: 2022-11-21

Transport of dangerous goods by road or rail (49 CFR US DOT), International Maritime Dangerous Goods Code (IMDG), Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.
Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in section 2 and 3)

Code	Text
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.