

Great Stuff[™] **Multi-Use Adhesive**

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier Chemical Name CAS No. Trade Name Product Code

Not Applicable Mixture Great Stuff® Multi-Use Adhesive None

Relevant identified uses of the substance or mixture and uses advised against Identified Use(s) Uses Advised Against

Company Identification

Telephone Fax E-Mail (competent person)

Emergency telephone number Emergency Phone No.

Adhesive Product None

Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11733

(631) 666-7300 (631) 666-7391 SDSinfo@finishlineusa.com

Medical Emergency: ProPharma Group: 24 hr: 1-800-217-5157 / 1-651-523-0304 Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200) Label elements Hazard Symbol

Signal word(s)

Hazard Statement(s)

Flam. Aerosol 1; Liquefied gas; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1



Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation. Repeated exposure may cause skin dryness or cracking.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use.

Use only outdoors or in a well-ventilated area.

Avoid breathing spray.

Wear protective gloves/eye protection.

Wash hands and exposed skin after use.

Protect from sunlight and do not expose to temperatures exceeding 50 $^{\circ}\text{C}/122\ ^{\circ}\text{F}.$

Other hazards

Toxic to aquatic life. Harmful to aquatic life with long lasting effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
			Flam. Liq. 2; H225
Acetone	10-20	67-64-1	Eye Irrit. 2; H319
			STOT SE 3; H336
			Flam. Liq. 2, H225
			Asp. Tox. 1; H304
Lintens, breached, such and linear	27-37	400000 70 0	Skin Irrit. 2, H315
Heptane, branched, cyclic and linear	21-31	426260-76-6	STOT SE 3, H336
			Aquatic Acute 2, H401
			Aquatic Chronic 3, H412
			Flam. Gas 1; H220
1,1-Difluoroethane	30-40	75-37-6	Liquified Gas; H280
			Simple Asphyxiant
Resin acids and Rosin acids,	0.45	8050-31-5	Not classified as dangerous for
esters with glycerol	8-15	6000-31-0	supply/use.
Styrong bytadiana divinul banzana palymar	5-10	00474 45 4	Not classified as dangerous for
Styrene-butadiene-divinyl benzene polymer	5-10	26471-45-4	supply/use.
Thermoplastic Elastomer Polymer	<1	Trade secret	Not classified as dangerous for
	~ 1	TAUE SECIEL	supply/use.
Para-aramid fiber	<1	26125-61-1	Not classified as dangerous for
			supply/use.

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

Move person to fresh air. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention.

Wash affected skin with soap and water. If irritation (redness, rash, blistering) develops, get medical attention.

Skin Contact

Eye Contact

Ingestion

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Do not induce vomiting. Do not give anything by mouth to an unconscious person. Get immediate medical attention.

Most important symptoms and effects, both acute and delayed

Indication of any immediate medical attention and special treatment needed

May be fatal if swallowed and enters airways. Do NOT induce vomiting.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media -Unsuitable Extinguishing Media

Special hazards arising from the substance or mixture

Advice for fire-fighters

Extinguish with carbon dioxide, dry chemical, foam or water spray. Do not use water jet.

Pressurised container: May burst if heated

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Eliminate sources of ignition. Avoid contact with skin and eyes. Avoid breathing spray. Wear protective gloves/eye protection.
Environmental precautions	Prevent liquid entering sewers, basements and work pits.
Methods and material for containment and cleaning up	Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.
Reference to other sections	None
Additional Information	None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling	Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Use only outdoors or in a well-ventilated area. Avoid contact with skin and eyes. Avoid breathing vapors.
Conditions for safe storage, including any incompatibil	ities
-Storage temperature	Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/ 122°F.
-Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Specific end use(s)	Lubricant

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(STEL)		
		PEL		PEL	TLV	
SUBSTANCE.	CAS No.	(OSHA)	TLV (ACGIH)	(OSHA)	(ACGIH)	Note:
Acetone	67-64-1	1000	500		750	^NIC
Heptane, branched, cylic and linear	426260-76-6	500 ppm*	1500 mg/m ³			*n-heptane

Recommended monitoring method

Exposure controls

Appropriate engineering controls

Personal protection equipment

Eye/face protection



Skin protection (Hand protection/ Other)



Respiratory protection



Thermal hazards

Environmental Exposure Controls

NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C);

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Wear protective eyewear (goggles, face shield, or safety glasses).

Wear suitable gloves if prolonged skin contact is likely (Butyl rubber). Check with protective equipment manufacturer's data.

Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with protective equipment manufacturer's data.

Not normally required. Use gloves with insulation for thermal protection, when needed.

Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Color. Odor Odor Threshold (ppm) pH (Value) Melting Point (°C) / Freezing Point (°C) Boiling point/boiling range (°C): Flash Point (°C) Evaporation Rate (Ethyl ether =1) Flammability (solid, gas) Explosive Limit Ranges Vapor pressure (Pascal) Vapor Density (Air=1) Density (g/ml) Calubility (Matac)

Vapor Density (Air=1) Density (g/ml) Solubility (Water) Solubility (Other) Partition Coefficient (n-Octanol/water)

Aerosol spray Colourless Slightly ethereal Not available Not available Not available. -25 (1,1-Difluoroethane) -50, est. (1,1-Difluoroethane) >1 (1,1-Difluoroethane) Extremely flammable 3.9% - 16.9% v/v (1,1-Difluoroethane) 5.3 x 10⁵ @ 21°C (1,1-Difluoroethane) 2.4 (1,1-Difluoroethane) Not available. 0.28% @ 21°C (1,1-Difluoroethane) Not available Not available

Auto Ignition Point (°C) Decomposition Temperature (°C) Kinematic Viscosity (cSt) Explosive properties Oxidizing properties

Other information

440 (1,1-Diflouroethane) Not available < 20.5 Not explosive. Not oxidizing.

Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	This product should be stored away from sources of strong heat or oxidizing chemicals.
Hazardous decomposition product(s)	Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Acetone (CAS No. 67-64-1) Acute toxicity

Sensitisation

Repeated dose toxicity

Carcinogenicity

Oral LD50 = 5800 mg/kg (rat) Dermal LD50 >15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness. Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking. It is not a skin sensitiser. Oral NOAEL = 900 mg/kg/day (rat) (90-days) Inhalation NOAEL ≥ 19,000 ppm (rat)

It is unlikely to present a carcinogenic hazard to man.

Γ	NTP	IARC	ACGIH	OSHA	NIOSH
	No.	No.	No.	No.	No.

Mutagenicity	
Toxicity for reproduction	
Other information	

Negative Negative None known.

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity

Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapour), 4-hr. rat May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Irritation/Corrosivity

Sensitisation

Repeated dose toxicity

Carcinogenicity

Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.

It is not a skin sensitiser.

NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects) LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects) May cause drowsiness or dizziness. No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity

Toxicity for reproduction

There is no evidence of mutagenic potential. No information available

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Heptane, branched, cylic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 3 mg/l (<i>Daphnia magna,</i> mobility <i>)</i> EC50 (96 hour): 13 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Long Term	NOELR (28 days) 1.5 mg/l <i>(Fish</i>) QSAR LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>) NOEL (96 hour) 6.3 mg/l (Algae)
Persistence and degradability	Readily biodegradable.
Bioaccumulative potential	The product has no potential for bioaccumulation.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not classified as PBT or vPvB.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

UN number Proper Shipping Name Transport hazard class(es) Packing group Environmental hazards Special precautions for user

<u>U.S. DOT</u>

1950 Aerosols, flammable 2.1 Not applicable None assigned None assigned

Sea transport (IMDG)

1950 Aerosols, flammable 2.1 Not applicable None assigned None assigned

Air transport (ICAO/IATA)

1950 Aerosols, flammable 2.1 Not applicable None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	20	5000

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None		

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
None		

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16. Date of preparation: December 22, 2022

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.