



Great Stuff™ Heavy-Duty Adhesive

SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name	Not Applicable
CAS No.	Mixture
Trade Name	Great Stuff® Heavy-Duty Adhesive
Product Code	None

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s)	Adhesive Product
Uses Advised Against	None
Company Identification	Finish Line Technologies, Inc. 50 Wireless Blvd. Hauppauge, NY 11733
Telephone	(631) 666-7300
Fax	(631) 666-7391
E-Mail (competent person)	SDSinfo@finishlineusa.com

Emergency telephone number

Emergency Phone No.

Medical Emergency: ProPharma Group:
24 hr: 1-800-217-5157 / 1-651-523-0304
Transportation Emergency: CHEMTREC 24 hr. 1-800-424-9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Flam. Aerosol 1; Liquefied gas; Eye Irrit. 2; Skin Irrit. 2; STOT SE 3; Asp. Tox. 1

Label elements

Hazard Symbol



DANGER

Signal word(s)

Hazard Statement(s)

Extremely flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye irritation.
Causes skin irritation.
May cause drowsiness or dizziness.
May be fatal if swallowed and enters airways.

Precautionary Statement(s)

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid breathing spray.
Use only outdoors or in a well-ventilated area.
Protect from sunlight and do not expose to temperatures exceeding 50

Great Stuff™ Heavy-Duty Adhesive

°C/122 °F.

Wash hands and exposed skin after use.

Wear protective eyewear (goggles, face shield, or safety glasses).

Wear protective gloves.

Avoid release to the environment.

Keep out of reach of children.

Harmful to aquatic life. Harmful to aquatic life with long lasting effects.

Other hazards

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
Acetone	15-25	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Heptane, branched, cyclic, and linear	18-28	426260-76-6	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Skin Irrit. 2; H315 STOT SE 3; H336 Aquatic Acute 2; H401 Aquatic Chronic 3; H412
Methyl Acetate	10-20	79-20-9	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336
Propane	15-25	74-98-6	Flam. Gas 1; H220 Liquefied gas; H280
Rosin ester	1 - 5	Proprietary	Not classified as hazardous for supply/use
Poly-(para-phenylene terephthalamide)	<1	26125-61-1	Not classified as hazardous for supply/use

Additional Information - None

* The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing is labored, administer oxygen. If symptoms develop, obtain medical attention. Call a POISON CENTER/doctor if you feel unwell.

Skin Contact

Wash affected skin with soap and water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion

Do not give anything by mouth to an unconscious person. Seek medical treatment. Do NOT induce vomiting.

Great Stuff™

Heavy-Duty Adhesive

Most important symptoms and effects, both acute and delayed May cause drowsiness and dizziness. Aspiration of droplets may cause pulmonary oedema.

Indication of any immediate medical attention and special treatment needed IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media Extinguish with carbon dioxide, dry chemical, foam or water spray.
-Unsuitable Extinguishing Media Do not use water jet.

Special hazards arising from the substance or mixture

Highly flammable vapor (flash point below 23°C).

Advice for fire-fighters

A self contained breathing apparatus and suitable protective clothing should be worn in fire conditions. Keep containers cool by spraying with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Take precautionary measures against static discharges. Avoid contact with skin and eyes. Avoid breathing vapors.

Environmental precautions

Prevent liquid entering sewers, basements and work pits.

Methods and material for containment and cleaning up

Cover spills with inert absorbent material. Transfer to a container for disposal or recovery.

Reference to other sections

None

Additional Information

None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Avoid contact with skin and eyes. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Store locked up. Keep in a cool, well ventilated place. Protect from sunlight. Store at temperatures not exceeding 50 °C / 122 °F. Keep container tightly closed.

-Incompatible materials This product should be stored away from sources of strong heat or oxidizing chemicals.

Specific end use(s)

Adhesive Product

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

Great Stuff™ Heavy-Duty Adhesive

SUBSTANCE.	CAS No.	(8hr TWA)		(STEL)		Note:
		PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	
Heptane, branched, cyclic, and linear	426260-76-6	500 ppm*	1500 mg/m ³	-----	-----	*n-heptane
Acetone	64-64-1	-----		-----	-----	
Propane	74-98-6	1000 ppm	Aspyx.#	-----	-----	#

*Assure minimum oxygen content of work atmosphere.

Recommended monitoring method

NIOSH 1550 (Naphthas); NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1300 (Ketones I).

Exposure controls

Appropriate engineering controls

Provide adequate ventilation to ensure that the occupational exposure limit is not exceeded.

Personal protection equipment

Eye/face protection



Wear protective eyewear (goggles, face shield, or safety glasses).

Skin protection (Hand protection/ Other)



Wear suitable gloves if prolonged skin contact is likely (Butyl rubber)

Respiratory protection



Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Not normally required. Use gloves with insulation for thermal protection, when needed.

Environmental Exposure Controls

None known

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Aerosol spray
Color.	Colorless
Odor	Not available
Odor Threshold (ppm)	Not available
pH (Value)	Not available
Melting Point (°C) / Freezing Point (°C)	Not available
Boiling point/boiling range (°C):	Not available
Flash Point (°C)	-104 (Propane)
Evaporation Rate	Not available
Flammability (solid, gas)	Highly flammable
Explosive Limit Ranges	2.1% - 9.5% v/v (Propane)
Vapor pressure (Pascal)	ca. 95 x 10 ⁴ (Propane)
Vapor Density (Air=1)	ca. 1.56 @ 0°C (Propane)
Density (g/ml)	Not available
Solubility (Water)	Not available
Solubility (Other)	Not available
Partition Coefficient (n-Octanol/water)	Not available
Auto Ignition Point (°C)	450 (Propane)
Decomposition Temperature (°C)	Not available
Kinematic Viscosity @38.7°C	0.83 mm ² /sec (Heptane, branched,cyclic, and linear)

Great Stuff™

Heavy-Duty Adhesive

Explosive properties
Oxidizing properties

Not explosive.
Not oxidizing.

Other information

Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Stable.
Possibility of hazardous reactions	None anticipated.
Conditions to avoid	Avoid contact with heat and ignition sources.
Incompatible materials	Strong oxidizing agents. Reducing agents. Acids. Bases. Chlorinated compounds. Aldehydes. Acetone may form explosive mixtures in contact with chromic anhydride, chromyl alcohol, hexachloromelamine, hydrogen peroxide, permonosulfuric acid, potassium tertbutoxide and thioglycol.
Hazardous decomposition product(s)	Forms carbon oxides under fire conditions.

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Acute toxicity (calculated / estimated)	Oral: LD50 >5 g/kg-bw Dermal: LD50 >2 g/kg-bw Inhalation: LC50 = 65 - 103 mg/L (Vapor), 4-hr. rat May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.
Irritation/Corrosivity	Causes skin irritation. Repeated exposure may cause skin dryness or cracking. May cause eye irritation.
Sensitization	It is not a skin sensitizer.
Repeated dose toxicity	NOAEC: 12350 mg/m3 (2 yr, inhal., rat, Systemic effects) LOAEC: 1650 mg/m3 (2 hr, inhal., rat, CNS effects) May cause drowsiness or dizziness.
Carcinogenicity	No data. It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	There is no evidence of mutagenic potential.
Reproductive toxicity	No information available

Acetone (CAS No. 67-64-1):

Acute toxicity	Oral LD50 = 5800 mg/kg (rat) Dermal LD50 >15800 mg/kg (rabbit) Inhalation LC50 76 mg/L (4 hour(s)) (rat) - Vapours may cause drowsiness and dizziness.
Irritation / Corrosivity	Causes serious eye irritation. Repeated exposure may cause skin dryness or cracking.
Sensitisation	It is not a skin sensitiser.
Repeated dose toxicity	Oral NOAEL = 900 mg/kg/day (rat) (90-days) Inhalation NOAEL ≥ 19,000 ppm (rat)
Carcinogenicity	It is unlikely to present a carcinogenic hazard to man.

Great Stuff™

Heavy-Duty Adhesive

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity	Negative
Toxicity for reproduction	Negative
Other information	None known.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Heptane, branched, cyclic and linear (CAS# 426260-76-6) - By analogy with similar materials:

Short term	LL50 (96 hour): >13.4 mg/L (<i>Oncorhynchus mykiss</i>) EL50 (48 hour): 3 mg/l (<i>Daphnia magna</i> , mobility) EC50 (96 hour): 13 mg/l (<i>Pseudokirchnerella subcapitata</i>)
Long Term	NOELR (28 days) 1.5 mg/l (<i>Fish</i>) QSAR LOEC (21 days): 0.32 mg/l (<i>Daphnia magna</i>) NOEL (96 hour) 6.3 mg/l (<i>Algae</i>)

Acetone (CAS No. 67-64-1):

Short term	LC50 (96 hour): 5,540 mg/l (Rainbow Trout (<i>Oncorhynchus mykiss</i>)) LC50 (96 hour): 8,300 mg/l (Bluegill Sunfish (<i>Lepomis macrochirus</i>)) LC50 (48 hour(s)): 12,600 – 12,700 mg/l (<i>Daphnia magna</i>) EC50 (14 d): 3,020 mg/l (Algae (<i>Chlorella pyrenoidosa</i>)) EC50 (15 min): 14,500 mg/l (Bacteria (<i>Photobacterium phosphoreum</i>))
Long Term	Not available.

Persistence and degradability	Readily biodegradable. (anaerobic) 78%; OECD 301 D
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Results of PBT and vPvB assessment	Not available.
Other adverse effects	None known.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods	Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.
--------------------------------	--

SECTION 14: TRANSPORT INFORMATION

	<u>U.S. DOT</u>	<u>Sea transport (IMDG)</u>	<u>Air transport (ICAO/IATA)</u>
UN number	1950	1950	1950
Proper Shipping Name	Aerosols, flammable	Aerosols, flammable	Aerosols, flammable
Transport hazard class(es)	2.1	2.1	2.1
Packing group	Not applicable	Not applicable	Not applicable
Environmental hazards	None assigned	None assigned	None assigned
Special precautions for user	None assigned	None assigned	None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

Great Stuff™ Heavy-Duty Adhesive

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Acetone	67-64-1	23	5000

SARA 311/312 - Hazard Categories: See SECTION 2: HAZARDS IDENTIFICATION

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
None	----	----

SARA 302 - Extremely Hazardous Substances(40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None	----	----	----

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
NONE	-----	-----

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: December 18, 2020

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.