

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**GHS product identifier****Product Name** Mothers PowerPlastic 4Lights**Other means of identification****Product Code(s)** 08808, 38808**Synonyms** None**Recommended use of the chemical and restrictions on use****Recommended Use** Car care**Uses advised against** No information available**Supplier's details****Supplier Address**
MOTHERS POLISHES WAXES
CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827**Company**
MOTHERS POLISHES WAXES CLEANERS
5456 Industrial Drive
Huntington Beach, CA 92649
TEL: 714-891-3364
FAX: 714-893-1827**Emergency telephone number****Emergency Telephone Number** Chemtrec Phone: 1-800-424-9300 (within the U.S.) or +1 703-527-3887 (outside the U.S.)**2. HAZARDS IDENTIFICATION****Classification**

This product is considered hazardous according to the criteria set within the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

Flammable Liquid Category 4
Skin Sensitization Category 1**Signal Word**Warning
Flammable Liquid
May be fatal if swallowed and enters airways.

Label Elements**Hazard Statements**

May cause an allergic skin reaction

Physical and Health Hazards Not Otherwise Classified

Not applicable.

Precautionary Statements**Prevention**

- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Contaminated work clothing should not be allowed out of the workplace.
- Wear protective gloves

General Advise

Specific treatment (see supplemental first aid instructions on this label).

Skin

- IF ON SKIN: Wash with plenty of soap and water.
- If skin irritation or rash occurs: Get medical advise/attention.
- Wash contaminated clothing before reuse.

Disposal

- Dispose of contents/container to an approved waste disposal plant.

Other information

Prolonged or repeated contact may dry skin and cause irritation.

Harmful to aquatic life with long lasting effects. Harmful to aquatic life.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Deodorized kerosene	8008-20-6	10-25	-	-
Calcined kaolin clay	66402-68-4	10-25	-	-
Isopropyl alcohol	67-63-0	< 10	-	-
Siloxanes and Silicones, dimethyl, [[[3-[(2-aminoethyl)amino]propyl]dimethoxysilyl]oxy]-terminated	71750-80-6	1-5	-	-
Mineral Spirits	8052-41-3	< 10	-	-
Oleamide dea	93-83-4	< 10	-	-
D-Limonene	5989-27-5	< 10	-	-
Methyl alcohol	67-56-1	< 10	-	-

4. FIRST AID MEASURES

Description of necessary first-aid measures**General Advice**

Show this safety data sheet to the doctor in attendance. If symptoms persist, call a physician.

Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if symptoms occur.
Skin Contact	Wash off immediately with soap and plenty of water. In the case of skin irritation or allergic reactions see a physician.
Inhalation	Move to fresh air.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Drink plenty of water. Get medical attention if symptoms occur.
Protection of First-aiders	Use personal protective equipment.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects May cause allergic skin reaction. Itching. Rashes.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

<u>Suitable Extinguishing Media</u>	Carbon dioxide (CO ₂). Foam. Dry powder. Dry chemical.
<u>Unsuitable Extinguishing Media</u>	No information available.
<u>Specific Hazards Arising from the Chemical</u>	May cause sensitization by skin contact. Thermal decomposition can lead to release of irritating gases and vapors. In the event of fire and/or explosion do not breathe fumes.
Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	None.
<u>Protective Equipment and Precautions for Firefighters</u>	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. If spilled, take caution, as material can cause surfaces to become very slippery.

Environmental Precautions

Environmental Precautions Prevent further leakage or spillage if safe to do so. Do not flush into surface water or sanitary sewer system. Avoid release to the environment. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Cleaning Up Soak up with inert absorbent material. Take up mechanically and collect in suitable container for disposal. Clean contaminated surface thoroughly.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Avoid contact with skin, eyes and clothing. Do not breathe vapors or spray mist. Ensure adequate ventilation.

Conditions for safe storage, including any incompatibilities

Storage Keep in properly labeled containers. Keep containers tightly closed in a cool, well-ventilated place. Keep out of the reach of children.

Incompatible Products Acids. Strong oxidizing agents.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Deodorized kerosene 8008-20-6	TWA: 200 mg/m ³ total hydrocarbon vapor application restricted to conditions in which there are negligible aerosol exposures S*	-	TWA: 100 mg/m ³
Calcined kaolin clay 66402-68-4	STEL: 10 mg/m ³ Zr TWA: 5 mg/m ³ Zr TWA: 0.02 mg/m ³ Mn respirable particulate matter TWA: 0.1 mg/m ³ Mn inhalable particulate matter	TWA: 5 mg/m ³ Zr (vacated) TWA: 5 mg/m ³ Zr (vacated) STEL: 10 mg/m ³ Zr	TWA: 5 mg/m ³ respirable dust TWA: 10 mg/m ³ total dust
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m ³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m ³
Mineral Spirits 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
Methyl alcohol 67-56-1	STEL = 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 325 mg/m ³ STEL: 250 ppm

Legend

S* - Skin Absorber

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value. OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits. NIOSH IDLH: Immediately Dangerous to Life or Health.

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Measures Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection Goggles.
Skin and Body Protection Wear protective gloves/clothing.
Respiratory Protection When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes and clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid.	Appearance	White.
Odor	Perfume.	Odor Threshold	No information available.

<u>Property</u>	<u>Values</u>	<u>Remarks/ - Method</u>
pH	9.0	None known
Melting Point/Range	No data available	None known
Boiling Point/Boiling Range	93.3 °C / 200 °F	None known
Flash Point	> 80°C and <=93°C	Closed Cup Method
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limits in Air		
upper flammability limit	No data available	
lower flammability limit	No data available	
Vapor Pressure	No data available	None known
Vapor Density	No data available	None known
Relative Density	No data available	None known
Specific Gravity	1.008	None known
Water Solubility	No data available	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition Temperature	No data available	None known
Decomposition Temperature	No data available	None known
Viscosity	600-900 cps	None known
Flammable Properties	Not flammable	
Explosive Properties	No data available	
Oxidizing Properties	No data available	

Other information

VOC Content (%) No data available

10. STABILITY AND REACTIVITY

<u>Reactivity</u>	No data available.
<u>Chemical stability</u>	Stable under recommended storage conditions.
<u>Possibility of hazardous reactions</u>	None under normal processing.
<u>Hazardous Polymerization</u>	Hazardous polymerization does not occur.
<u>Conditions to avoid</u>	Do not freeze. Heat, flames and sparks.
<u>Incompatible materials</u>	Acids. Strong oxidizing agents.
<u>Hazardous decomposition products</u>	None under normal use. Thermal decomposition can lead to release of irritating gases and vapors. Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation	Avoid breathing vapors or mists.
Eye Contact	Contact with eyes may cause irritation.
Skin Contact	Repeated exposure may cause skin dryness or cracking. May cause allergic skin reaction.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document: Not applicable.

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Deodorized kerosene	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
Isopropyl alcohol	= 1870 mg/kg (Rat)	12800 mg/kg (Rat) 12870 mg/kg (Rabbit)	72.6 mg/L (Rat) 4 h
Mineral Spirits	-	-	-
Oleamide dea	= 12400 µL/kg (Rat)	-	-
D-Limonene	5000 mg/kg (Rat)	>5000 mg/kg (Rabbit)	-
Methyl alcohol	5628 mg/kg (Rat)	15800 mg/kg (Rabbit)	83.2 mg/L (Rat) 4 h 64000 ppm (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Allergic skin reactions or irritation. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.

Delayed and immediate effects and also chronic effects from short and long term exposure

Respiratory or Skin Sensitization May cause sensitization of susceptible persons. May cause sensitization by skin contact.
Germ Cell Mutagenicity Does not contain substances that are known or suspected to be mutagens.
Carcinogenicity Occupational health effects due to inhalation of mineral dusts incorporating crystalline silica (quartz, cristobalite, tridymite), crystalline silicates (kaolin, talc) graphite or coal unlikely to occur from exposure to this product.

Chemical Name	ACGIH	IARC	NTP	OSHA
Deodorized kerosene	A3	Group 3		
Isopropyl alcohol		Group 3		X
D-Limonene		Group 3	-	-

ACGIH: (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC: (International Agency for Research on Cancer)

Group 3 - Not Classifiable as to its Carcinogenicity to Humans

OSHA: (Occupational Safety & Health Administration)

X - Present

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure

This product does not contain any known or suspected reproductive hazards.

Based on available data, the classification criteria are not met.

None of the ingredients are known to cause specific target organ effects through prolonged or repeated exposure.

Chronic Toxicity

Repeated exposure may cause skin dryness or cracking. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Kidney. Respiratory system. Eyes. Skin. Central nervous system (CNS). Blood. Gastrointestinal tract (GI).

Target Organ Effects**Aspiration Hazard**

Based on product level data, this product does not meet the requirement to be classified as an aspiration hazard. However, this product contains an ingredient that may cause aspiration if swallowed.

12. ECOLOGICAL INFORMATION

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Isopropyl alcohol 67-63-0	EC50 72 h: > 1000 mg/L (Desmodesmus subspicatus) EC50 96 h: > 1000 mg/L (Desmodesmus subspicatus)	LC50 96 h: = 11130 mg/L static (Pimephales promelas) LC50 96 h: = 9640 mg/L flow-through (Pimephales promelas) LC50 96 h: > 1400000 µg/L (Lepomis macrochirus)		EC50 48 h: = 13299 mg/L (Daphnia magna)
D-Limonene 5989-27-5		LC50 96 h: 0.619 - 0.796 mg/L flow-through (Pimephales promelas) LC50 96 h: = 35 mg/L (Oncorhynchus mykiss)		
Methyl alcohol 67-56-1	-	LC50 96 h: 13500 - 17600 mg/L flow-through (Lepomis macrochirus) LC50 96 h: 18 - 20 mL/L static (Oncorhynchus mykiss) LC50 96 h: 19500 - 20700 mg/L flow-through (Oncorhynchus mykiss) LC50 96 h: = 28200 mg/L flow-through (Pimephales promelas) LC50 96 h: > 100 mg/L static (Pimephales promelas)	EC50 = 39000 mg/L 25 min EC50 = 40000 mg/L 15 min EC50 = 43000 mg/L 5 min	-

Persistence and Degradability No information available.

Bioaccumulation No information available.

Chemical Name	Log Pow
Isopropyl alcohol	0.05
Methyl alcohol	-0.77

Mobility No information available.

Other Adverse Effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated Packaging Dispose of in accordance with local regulations.

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Calcined kaolin clay	Toxic
Isopropyl alcohol	Toxic Ignitable
D-Limonene	Toxic

14. TRANSPORT INFORMATION

DOT Not regulated

TDG Not regulated

MEX Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substances Not applicable

Persistent Organic Pollutants Not applicable

Hazardous Waste

Chemical Name	Basel Convention (Hazardous Wastes)
Calcined kaolin clay	Y23
Isopropyl alcohol	Y42

The Rotterdam Convention (Prior Informed Consent) Not applicable

International Convention for the Prevention of Pollution from Ships (MARPOL) Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status

DSL/NDSL Contact supplier for inventory compliance status

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

Chemical Name	CAS-No	Weight %	SARA 313 - Threshold Values %
Calcined kaolin clay	66402-68-4	10-25	1.0
Isopropyl alcohol	67-63-0	< 10	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Calcined kaolin clay		X		

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

U.S. State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals:

Chemical Name	CAS-No	California Prop. 65
Methyl alcohol	67-56-1	Developmental

Diethanolamine	111-42-2	Carcinogen
----------------	----------	------------

U.S. State Right-to-Know Regulations

"X" designates that the ingredients are listed on the state right to know list.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
Deodorized kerosene	X	X	X		X
Calcined kaolin clay	X		X	X	X
Isopropyl alcohol	X	X	X		X
Mineral Spirits	X	X	X		X
D-Limonene	X			X	

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA Health Hazard 2 Flammability 1 Instability 0 Physical and Chemical Hazards -

HMIS Health Hazard 2 Flammability 1 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 31-Aug-2018

Revision Date 31-Aug-2018

Revision Note New regional format.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet