Revision Date: 06/21/2022

# **SAFETY DATA SHEET**

Classified in accordance 29 CFR 1910.1200

# 1. Identification

Product identifier: Flood Protection Seal & Peel - Safety Yellow

Other means of identification

**SDS number:** RE1000047097

Recommended restrictions
Recommended use: Coating
Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Company Name: SWIFT RESPONSE, LLC Address: 2690 WESTON RD.

WESTON, FL 33331

US

Telephone: 800-307-6201

Emergency telephone number: 1-866-836-8855

# 2. Hazard(s) identification

#### **Hazard Classification**

# **Physical Hazards**

Flammable aerosol Category 1
Gases under pressure Liquefied gas

#### **Health Hazards**

Skin Corrosion/Irritation

Toxic to reproduction

Specific Target Organ Toxicity - Category 2

Single Exposure

Specific Target Organ Toxicity - Category 2

Category 3

(Narcotic effect.)

Category 2

Repeated Exposure

Aspiration Hazard Category 1

#### **Environmental Hazards**

Acute hazards to the aquatic Category 2 environment

## **Label Elements**

# **Hazard Symbol:**



Signal Word:

Danger

SDS US - RE1000047097 1/15

Revision Date: 06/21/2022

**Hazard Statement:** Extremely flammable aerosol.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

Toxic to aquatic life.

Contains gas under pressure; may explode if heated.

Precautionary Statements

**Prevention:** Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid

release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for

breathing. IF ON SKIN: Wash with plenty of water If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor Do NOT induce vomiting. Call a POISON CENTER/doctor

if you feel unwell. Specific treatment (see on this label). Take off

contaminated clothing.

Storage: Protect from sunlight. Do not expose to temperatures exceeding

50°C/122°F. Store locked up. Store in a well-ventilated place. Keep

container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

# 3. Composition/information on ingredients

#### Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	25 - <50%
Propane	74-98-6	10 - <20%
Propane, 2-methyl-	75-28-5	10 - <20%
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	10 - <25%
Naphtha (petroleum), heavy alkylate	64741-65-7	1 - <5%
Limestone	1317-65-3	1 - <5%

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

The exact concentration has been withheld as a trade secret.

#### 4. First-aid measures

## Description of necessary first-aid measures

Inhalation: Move to fresh air.

Revision Date: 06/21/2022

**Skin Contact:** Immediately flush with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Wash contaminated

clothing before reuse. Get medical attention.

**Eye contact:** Immediately flush with plenty of water for at least 15 minutes. If easy

to do, remove contact lenses. Get medical attention.

**Ingestion:** Call a physician or poison control center immediately. Rinse mouth.

Never give liquid to an unconscious person. If vomiting occurs, keep

head low so that stomach content doesn't get into the lungs.

**Personal Protection for First-**

aid Responders:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

Most important symptoms/effects, acute and delayed

**Symptoms:** No data available.

**Hazards:** No data available.

Indication of immediate medical attention and special treatment needed

**Treatment:** Get medical attention if symptoms occur.

5. Fire-fighting measures

**General Fire Hazards:** Use water spray to keep fire-exposed containers cool. Fight fire from a

protected location. Move containers from fire area if you can do so without

risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

Vapors may travel considerable distance to a source of ignition and flash

back.

Special protective equipment and precautions for firefighters

Special fire fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in

enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.

Accidental release measures: ELIMINATE all ignition sources (no smoking, flares, sparks or flames in

immediate area). Stop leak if you can do so without risk. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material,

if this is without risk.

Revision Date: 06/21/2022

Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container

for chemical waste.

**Environmental Precautions:** Avoid release to the environment. Prevent further leakage or spillage if safe

to do so. Do not contaminate water sources or sewer.

# 7. Handling and storage

# Handling

Technical measures (e.g. Local and general ventilation):

No data available.

Safe handling advice: Keep away from heat, hot surfaces, sparks, open flames and other ignition

> sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin. Wash hands thoroughly after handling.

Contact avoidance measures: No data available.

**Storage** 

Safe storage conditions: Store locked up. Pressurized container: protect from sunlight and do not

expose to temperatures exceeding 50°C. Do not pierce or burn, even after

use. Aerosol Level 2

No data available. Safe packaging materials:

**Storage Temperature:** No data available.

# 8. Exposure controls/personal protection

# **Control Parameters**

**Occupational Exposure Limits** 

Chemical Identity	Туре	Exposure Limit Values		Source	
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended	
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended	
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended	
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended	
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended	
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended	
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended	
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended	
Propane, 2-methyl-	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
	STEL	1,000 ppm		US. ACGIH Threshold Limit Values, as amended	
Distillates (petroleum), light distillate hydrotreating process, low-boiling - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended	
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended	
	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended	

Revision Date: 06/21/2022

Naphtha (petroleum), heavy alkylate	PEL	100 ppm	400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA REL	100 ppm 100 ppm	400 mg/m3 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended US. NIOSH: Pocket Guide to Chemical Hazards, as
		.00 pp		amended
Limestone - Total	REL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Limestone - Respirable.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Limestone - Total dust.	PEL		15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Limestone - Respirable fraction.	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Limestone - Total dust.	TWA		15 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Limestone - Respirable fraction.	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Zeolites - Respirable fraction.	TWA		1 mg/m3	US. ACGIH Threshold Limit Values, as amended
White mineral oil (petroleum) - Mist.	REL		5 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
<u> </u>	STEL		10 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL		5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
<del></del>	TWA		5 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
White mineral oil (petroleum) - Inhalable fraction.	TWA		5 mg/m3	US. ACGIH Threshold Limit Values, as amended
Benzene, dimethyl-	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	STEL	150 ppm	655 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	150 ppm	655 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Ota dalamina alimant	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Stoddard solvent	TWA	100 ppm	525 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	100 ppm	350 mg/m3	US. ACGIH Threshold Limit Values, as amended US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	Ceil_ Time		1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	PEL	500 ppm	2,900 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable dust.	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
Crystalline Silica -	TWA		2.4 millions	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended
Respirable.			of particles per cubic	
			foot of air	
0	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended
Crystalline Silica - Respirable fraction.	TWA		0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended
Crystalline Silica - Respirable dust. Crystalline Silica -	TWA		0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Respirable dust.  Crystalline Silica -	TWA		0.05 mg/m3 0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR
Respirable dust. Crystalline Silica -	OSHA		0.03 mg/m3	1910.1000), as amended  US. OSHA Specifically Regulated Substances (29 CFR
Respirable dust. Acetic acid, butyl ester	_ACT	150 ppm	710 mg/m3	1910.1001-1053), as amended  US. NIOSH: Pocket Guide to Chemical Hazards, as
2007	STEL	200 ppm	950 mg/m3	amended US. NIOSH: Pocket Guide to Chemical Hazards, as
	TWA	150 ppm	710 mg/m3	amended US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	PEL	150 ppm	710 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	200 ppm	950 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	STEL	150 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, ethyl-	STEL	125 ppm	545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	REL	100 ppm	435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended

Revision Date: 06/21/2022

	PEL	100 ppm	435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR
	OTEL	405	5.45 ··· ·· /·· · 0	1910.1000), as amended
	STEL	125 ppm	545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	100 ppm	435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	20 ppm		US. ACGIH Threshold Limit Values, as amended
Benzene, 1,2,4-trimethyl-	TWA	25 ppm		US. ACGIH Threshold Limit Values, as amended
	TWA	25 ppm	125 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	REL	25 ppm	125 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
December 14 as all all all all all	DEL	50	0.45/0	
Benzene, (1-methylethyl)-	REL	50 ppm	245 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as amended
	TWA	50 ppm		US. ACGIH Threshold Limit Values, as amended
	PEL	50 ppm	245 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended
	TWA	50 ppm	245 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. ACGIH Notice of Intended Changes (NIC) to Threshold
	1			Limit Values, as amended
Naphthalene	STEL	15 ppm	75 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as
тартинатого	0.22	ТО РРПП	7 0 111g/1110	amended
	REL	10 ppm	50 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards, as
	IXEE	ТО РРПП	oo mg/mo	amended
	PEL	10 ppm	50 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR
	'	то ррпп	30 mg/m3	1910.1000), as amended
	TWA	10 ppm	50 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	10 ppm	<u> </u>	US. ACGIH Threshold Limit Values, as amended
	STEL	15 ppm	75 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
Benzene	REL	0.1 ppm	ro mg/mo	US. NIOSH: Pocket Guide to Chemical Hazards, as
201120110	112	o.i ppiii		amended
	TWA	1 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	Ceiling	25 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	TWA	0.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	2.5 ppm		US. ACGIH Threshold Limit Values, as amended
	STEL	5 ppm		US. OSHA Specifically Regulated Substances (29 CFR
	OILL	о рріп		1910.1001-1053), as amended
	OSHA	0.5 ppm		US. OSHA Specifically Regulated Substances (29 CFR
	_ACT	0.5 ppm		1910.1001-1053), as amended
	TWA	10 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	MAX.	50 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000), as amended
	CONC	эо ррпі		
	STEL	5 ppm		US. OSHA Table Z-1-A (29 CFR 1910.1000), as amended
	TWA	1 ppm		US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended
	STEL	1 ppm		US. NIOSH: Pocket Guide to Chemical Hazards, as amended

**Biological Limit Values** 

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL
Benzene, dimethyl- (Methylhippuric acids: Sampling time: End of shift.)	1.5 g/g (Creatinine in urine)	ACGIH BEL
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 μg/g (Creatinine in urine)	ACGIH BEL
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 μg/g (Creatinine in urine)	ACGIH BEL

**Exposure guidelines** 

Naphthalene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.
Benzene	US. ACGIH Threshold Limit Values, as amended	Can be absorbed through the skin.

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

**Eye/face protection:** Wear safety glasses with side shields (or goggles).

**Skin Protection** 

**Hand Protection:** No data available.

Revision Date: 06/21/2022

**Skin and Body Protection:** Wear chemical-resistant gloves, footwear, and protective clothing

appropriate for the risk of exposure. Contact health and safety professional

or manufacturer for specific information.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

**Hygiene measures:** When using do not smoke. Observe good industrial hygiene practices. Do

not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately

after handling the product.

# 9. Physical and chemical properties

**Appearance** 

Physical state: liquid

Form: Spray Aerosol Color: No data available. Odor: No data available. Odor Threshold: No data available. pH: No data available. Freezing point: No data available. **Boiling Point:** No data available. Flash Point: Estimated -104 °C **Evaporation Rate:** No data available. Flammability (solid, gas): No data available. **Explosive limit - upper (%):** Estimated 9.5 %(V) **Explosive limit - lower (%):** Estimated 1.8 %(V)

**Vapor pressure:** 3,792 - 5,171 hPa (20 °C)

7,584 - 8,963 hPa (54 °C)

Vapor density (air=1): No data available. Density: No data available. Relative density: No data available. Solubility in Water: No data available. Solubility (other): No data available. Partition coefficient (n-octanol/water): No data available. **Self Ignition Temperature:** No data available. **Decomposition Temperature:** No data available. Kinematic viscosity: No data available. Dynamic viscosity: No data available. **Explosive properties:** No data available. Oxidizing properties: No data available.

# 10. Stability and reactivity

**Reactivity:** No data available.

**Chemical Stability:** Material is stable under normal conditions.

Possibility of hazardous

reactions:

No data available.

**Conditions to avoid:** Avoid heat or contamination.

Incompatible Materials: No data available.

Revision Date: 06/21/2022

**Hazardous Decomposition** 

**Products:** 

No data available.

# 11. Toxicological information

### Information on likely routes of exposure

Inhalation: No data available.

**Skin Contact:** No data available.

Eye contact: No data available.

Ingestion: No data available.

# Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

**Skin Contact:** No data available.

Eye contact: No data available.

Ingestion: No data available.

# Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral

**Product:** ATEmix: 47,619.05 mg/kg

**Dermal** 

**Product:** ATEmix: 17,958.16 mg/kg

Inhalation

**Product:** Not classified for acute toxicity based on available data.

Repeated dose toxicity

**Product:** No data available.

Components:

Benzene, methyl-LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target

> Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation

Experimental result, Key study

Propane NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation

Experimental result, Key study

LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 42 d): 16,000 ppm(m) Inhalation Propane, 2-methyl-

Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation): 21,394 mg/m3 Inhalation

Experimental result, Key study

Distillates (petroleum).

light distillate

NOAEL (Rat(Female, Male), Inhalation): 9,840 mg/m3 Inhalation

Experimental result, Key study

hydrotreating process,

low-boiling

NOAEL (Rat(Male), Oral, 28 d): < 500 mg/kg Oral Experimental result,

Supporting study

NOAEL (Rat(Female, Male), Dermal, 5 - 28 d): 3,750 mg/kg Dermal

Experimental result, Key study

Revision Date: 06/21/2022

Skin Corrosion/Irritation

**Product:** No data available.

Components:

Benzene, methylDistillates (petroleum),
Assessment Not irritating

light distillate

hydrotreating process,

low-boiling

Serious Eye Damage/Eye Irritation

**Product:** No data available.

Components:

Benzene, methyl- Rabbit, 24 - 72 hrs: Not irritating Distillates (petroleum), Rabbit, 24 - 72 hrs: Not irritating

light distillate

hydrotreating process,

low-boiling

Respiratory or Skin Sensitization

**Product:** No data available.

Components:

Benzene, methyl- Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising

light distillate hydrotreating process,

low-boiling

Carcinogenicity

**Product:** No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

**US. National Toxicology Program (NTP) Report on Carcinogens:** 

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

**Germ Cell Mutagenicity** 

In vitro

**Product:** No data available.

In vivo

**Product:** No data available.

Reproductive toxicity

**Product:** No data available.

Components:

Benzene, methyl- Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

**Product:** No data available.

Components:

Benzene, methyl- Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.

Revision Date: 06/21/2022

**Specific Target Organ Toxicity - Repeated Exposure** 

Product: No data available.

Components:

Benzene, methyl- Category 2

**Target Organs** 

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

**Aspiration Hazard** 

**Product:** No data available.

Components:

Benzene, methyl- May be fatal if swallowed and enters airways. Distillates (petroleum), May be fatal if swallowed and enters airways.

light distillate

hydrotreating process,

low-boiling

Naphtha (petroleum),

heavy alkylate

May be fatal if swallowed and enters airways.

Other effects: No data available.

# 12. Ecological information

#### **Ecotoxicity:**

# Acute hazards to the aquatic environment:

Fish

**Product:** No data available.

Components:

Benzene, methyl- LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study

Propane LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

LL 50 (Pimephales promelas, 96 h): 8.2 mg/l Experimental result, Key study

**Aquatic Invertebrates** 

**Product:** No data available.

Components:

Benzene, methyl- LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality

LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study NOAEL (Daphnia magna, 48 h): 0.5 mg/l Experimental result, Key study

# Chronic hazards to the aquatic environment:

Fish

**Product:** No data available.

Components:

Benzene, methyl- NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study

LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study

Revision Date: 06/21/2022

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

NOAEL (Pimephales promelas): 2.6 mg/l Experimental result, Supporting

study

**Aquatic Invertebrates** 

Product:

No data available.

Components:

Benzene, methyl- LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study

NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study

**Toxicity to Aquatic Plants** 

Product:

No data available.

Persistence and Degradability

**Biodegradation** 

**Product:** No data available.

Components:

Benzene, methyl- 100 % (14 d) Detected in water. Experimental result, Weight of Evidence

study

86 % Detected in water. Experimental result, Weight of Evidence study

Propane 100 % (385.5 h) Detected in water. Experimental result, Key study

50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study

Propane, 2-methyl- 100 % Detected in water. QSAR, Weight of Evidence study

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

90.35 % (28 d) Detected in water. Experimental result, Supporting study

**BOD/COD Ratio** 

**Product:** No data available.

**Bioaccumulative potential** 

**Bioconcentration Factor (BCF)** 

**Product:** No data available.

Components:

Benzene, methyl- Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment

Experimental result, Key study

Distillates (petroleum),

light distillate

hydrotreating process,

low-boiling

Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by

calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

**Product:** No data available.

Revision Date: 06/21/2022

Mobility in soil: No data available.

Components:

Benzene, methyl-No data available. Propane No data available. Propane, 2-methyl-No data available. Distillates (petroleum), light distillate hydrotreating process, low-boiling No data available.

Naphtha (petroleum), heavy alkylate No data available. Limestone No data available.

Other adverse effects: Toxic to aquatic organisms.

13. Disposal considerations

**Disposal instructions:** Discharge, treatment, or disposal may be subject to national, state, or local

laws.

**Contaminated Packaging:** No data available.

14. Transport information

DOT

**UN Number:** UN 1950

UN Proper Shipping Name: Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1 Label(s):

EmS No.:

Packing Group:

Special precautions for user: None known.

IATA

**UN Number:** UN 1950

**UN Proper Shipping Name:** Aerosols, flammable

Transport Hazard Class(es):

Class: 2.1 Label(s): Packing Group:

Special precautions for user: None known.

Other information

Passenger and cargo aircraft: Allowed, 203 Cargo aircraft only: Allowed, 203

**IMDG** 

**UN Number:** UN 1950

**UN Proper Shipping Name:** Aerosols, flammable

Transport Hazard Class(es)

Class: 2.1 Label(s): EmS No.: F-D, S-U

Packing Group:

Special precautions for user: None known.

The classification shown in this section may be eligible for use of an exception, such as "Limited Quantity", per the dangerous goods regulations. The shipper of this product should consult the applicable mode's regulation for the UN number displayed above to determine if any exceptions are available and may be utilized, at the shipper's discretion.

Revision Date: 06/21/2022

# 15. Regulatory information

# **US Federal Regulations**

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

<u>Chemical Identity</u> <u>OSHA hazard(s)</u>

Crystalline Silica lung effects

immune system effects

Cancer

kidney effects

Benzene Flammability

Cancer Aspiration Eye Blood Skin

respiratory tract irritation Central nervous system

#### CERCLA Hazardous Substance List (40 CFR 302.4):

# **Chemical Identity**

BENZENE, METHYLUNLISTED HAZARDOUS WASTES CHARACTERISTIC OF IGNITABILITY
RCRA HAZARDOUS WASTE NO. D001
XYLENE (MIXED)
BUTYL ACETATE
ETHYLBENZENE
BENZENE,1-METHYLETHYLCUMENE
NAPHTHALENE

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

### **Hazard categories**

**BENZENE** 

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Reproductive toxicity, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

# US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

None present or none present in regulated quantities.

# US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

<u>Chemical Identity</u> Benzene, methyl
\*\*September 1.0%

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

Revision Date: 06/21/2022

# **US State Regulations**

#### **US. California Proposition 65**



**WARNING:** This product can expose you to chemicals including, Benzene which is [are] known to the State of California to cause cancer and birth defects or other reproductive harm.

This product can expose you to chemicals including, Crystalline Silica, Benzene, ethyl-, Benzene, (1-methylethyl)-, and Naphthalene, which is [are] known to the State of California to cause cancer.

This product can expose you to chemicals including, Benzene, methylwhich is [are] known to the State of California to cause birth defects or other reproductive harm.

For more information go to www.P65Warnings.ca.gov.

# **US. New Jersey Worker and Community Right-to-Know Act Chemical Identity**

Benzene, methyl-

Propane

Propane, 2-methyl-

Distillates (petroleum), light distillate hydrotreating process, low-boiling

Naphtha (petroleum), heavy alkylate

Limestone

White mineral oil (petroleum)

# **US. Massachusetts RTK - Substance List**

# **Chemical Identity**

Crystalline Silica

Benzene

# US. Pennsylvania RTK - Hazardous Substances

# **Chemical Identity**

Benzene, methyl-

Propane

Propane, 2-methyl-

Distillates (petroleum), light distillate hydrotreating process, low-boiling

Naphtha (petroleum), heavy alkylate

Limestone

#### **US. Rhode Island RTK**

No ingredient regulated by RI Right-to-Know Law present.

# International regulations

# **Montreal protocol**

Not applicable

# Stockholm convention

Not applicable

#### **Rotterdam convention**

Not applicable

# **Kyoto protocol**

Not applicable

Revision Date: 06/21/2022

**Inventory Status:** 

Australia AICS Not in compliance with the inventory.

On or in compliance with the inventory. Canada DSL Inventory List

Canada NDSL Inventory Not in compliance with the inventory.

Ontario Inventory Not in compliance with the inventory.

China Inv. Existing Chemical Substances On or in compliance with the inventory

Japan (ENCS) List Not in compliance with the inventory.

Not in compliance with the inventory. Japan ISHL Listing

Japan Pharmacopoeia Listing Not in compliance with the inventory.

Korea Existing Chemicals Inv. (KECI) On or in compliance with the inventory

Not in compliance with the inventory. Mexico INSQ

New Zealand Inventory of Chemicals On or in compliance with the inventory

Philippines PICCS On or in compliance with the inventory

Taiwan Chemical Substance Inventory On or in compliance with the inventory

**US TSCA Inventory** On or in compliance with the inventory

EINECS, ELINCS or NLP Not in compliance with the inventory.

# 16.Other information, including date of preparation or last revision

**Issue Date:** 04/19/2022

**Revision Information:** No data available.

Version #: 2.0

**Further Information:** No data available.

Disclaimer: This information is provided without warranty. The information is believed to

be correct. This information should be used to make an independent

determination of the methods to safeguard workers and the environment.