SAFETY DATA SHEET

41000

Section 1. Identification

Product name	: Expressions® Select Interior Flat White
Product code	: 41000
Other means of identification	: Not available.
Product type	: Liquid.
Relevant identified uses of	the substance or mixture and uses advised against
Paint or paint related materia	Ι.
Manufacturer	: Valspar 101 W. Prospect Avenue Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Pagulatory Information	(216) 566 2002

	101 W. Prospect Avenu Cleveland, OH 44115
Emergency telephone number of the company	: (800) 424-9300
Product Information Telephone Number	: 1-877-825-7727
Regulatory Information Telephone Number	: (216) 566-2902
Transportation Emergency Telephone Number	: (800) 424-9300

Section 2. Hazards identification

OSHA/HCS status	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
Classification of the substance or mixture	: CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1
	Percentage of the mixture consisting of ingredient(s) of unknown acute toxicity: 6.9% (oral), 6.9% (dermal), 6.9% (inhalation)
GHS label elements	
Hazard pictograms	
Signal word	
Signal word	: Danger
Hazard statements	: May cause cancer. Causes damage to organs through prolonged or repeated exposure.
Precautionary statements	
General	: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.
Prevention	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Do not breathe vapor. Do not eat, drink or smoke when using this product. Wash thoroughly after handling.

Date of issue/Date	of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version : 2.01	1/13
41000	Expressions® Sel White	ect Interior Flat			SHW-85-NA-GHS-US	

Section 2. Hazards identification

Response	: IF exposed or concerned: Get medical advice or attention.
Storage	: Store locked up.
Disposal	: Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. Adequate ventilation required when sanding or abrading the dried film. If Adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release Crystalline Silica which has been shown to cause lung damage and cancer under long term exposure.
	Please refer to the SDS for additional information. Keep out of reach of children. Do not transfer contents to other containers for storage.
Hazards not otherwise classified	: None known.

Section 3. Composition/information on ingredients

Substance/mixture	: Mixture
Other means of identification	: Not available.

CAS number/other identifiers

Ingredient name	% by weight	CAS number
Titanium Dioxide	≥10 - ≤25	13463-67-7 🥄
Crystalline Silica, respirable powder	≤10	14808-60-7
Heavy Paraffinic Oil	≤1	64742-54-7
Cristobalite, respirable powder	≤0.3	14464-46-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Date of issue/Date	of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version : 2.01	2/13
41000	Expressions® Select White	Interior Flat			SHW-85-NA-GHS-U	JS

Section 4. First aid measures

Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Most important symptoms/	effects, acute and delayed
Potential acute health effe	<u>cts</u>
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Over-exposure signs/sym	<u>otoms</u>
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Indication of immediate me	dical attention and special treatment needed, if necessary
Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Date of issue/Date of revision	: 6/22/2023 Date of previous issue : 12/10/2022 Version : 2.01 3/13
41000 Expressions® Se White	lect Interior Flat SHW-85-NA-GHS-US

Section 6. Accidental release measures

Personal precautions, protect	ctiv	e equipment and emergency procedures
For non-emergency personnel	-	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	:	If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and materials for co	ont	ainment and cleaning up
Small spill	-	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal

Section 7. Handling and storage

Precautions for safe handling

- reconditione for ouro mananing	
Protective measures	: Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Date of issue/Date	e of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version : 2.01	4/13
41000 Expressions® Select Interior Flat White				SHW-85-NA-GHS-US		

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits (OSHA United States)

Ingredient name	CAS #	Exposure limits
Titanium Dioxide	13463-67-7	OSHA PEL (United States, 5/2018). TWA: 15 mg/m ³ 8 hours. Form: Total dust ACGIH TLV (United States, 1/2022). TWA: 2.5 mg/m ³ 8 hours. Form: respirable fraction, finescale particles
Crystalline Silica, respirable powder	14808-60-7	 OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / (%SiO2+2) 8 hours. Form: Respirable OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 μg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2022). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)] TWA: 0.05 mg/m³ 10 hours. Form: respirable dust
Heavy Paraffinic Oil	64742-54-7	ACGIH TLV (United States, 1/2022). [Mineral Oil, pure, highly and severely refined] TWA: 5 mg/m ³ 8 hours. Form: Inhalable fraction OSHA PEL (United States, 5/2018). [Oil mist, mineral] TWA: 5 mg/m ³ 8 hours. NIOSH REL (United States, 10/2020). [OIL MIST MINERAL] TWA: 5 mg/m ³ 10 hours. Form: Mist STEL: 10 mg/m ³ 15 minutes. Form: Mist
Cristobalite, respirable powder	14464-46-1	 OSHA PEL Z3 (United States, 6/2016). TWA: 250 mppcf / 2 x (%SiO2+5) 8 hours. Form: Respirable TWA: 10 mg/m³ / 2 x (%SiO2+2) 8 hours. Form: Respirable TWA: 30 mg/m³ / 2 x (%SiO2+2) 8 hours. Form: Total dust OSHA PEL (United States, 5/2018). [Silica, crystalline] TWA: 50 µg/m³ 8 hours. Form: Respirable dust ACGIH TLV (United States, 1/2022). [Silica, crystalline] TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 10/2020). [SILICA, CRYSTALLINE (AS RESPIRABLE DUST)]
ate of issue/Date of revision : 6/22/2023	Date of previous issue	: 12/10/2022 Version : 2.01 5/13
1000 Expressions® Select Interior Flat White		SHW-85-NA-GHS-US

Section 8. Exposure controls/personal protection

		TWA: 0.05 mg/m³ 10 hours. Form: respirable dust

Occupational exposure limits (Canada)

Ingredient name	CAS #	Exposure limits
Quartz	14808-60-7	CA British Columbia Provincial (Canada, 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m ³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). [Silica Crystalline -Quartz] TWAEV: 0.1 mg/m ³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m ³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). [Silica, Crystalline (Quartz/Tripoli)] TWA: 0.1 mg/m ³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m ³ 8 hours. Form: respirable fraction
Cristobalite	14464-46-1	 CA British Columbia Provincial (Canada, 6/2022). [Silica, Crystalline - alpha quartz and Cristobalite Respirable] TWA: 0.025 mg/m³ 8 hours. Form: Respirable CA Quebec Provincial (Canada, 6/2022). TWAEV: 0.05 mg/m³ 8 hours. Form: Respirable dust. CA Alberta Provincial (Canada, 6/2018). 8 hrs OEL: 0.025 mg/m³ 8 hours. Form: Respirable particulate CA Ontario Provincial (Canada, 6/2019). TWA: 0.05 mg/m³ 8 hours. Form: Respirable particulate matter. CA Saskatchewan Provincial (Canada, 7/2013). TWA: 0.05 mg/m³ 8 hours. Form: respirable fraction

Occupational exposure limits (Mexico)

	CAS #	Exposure limits	
Crystalline Silica, respirable powder		NOM-010-STPS-2014 (Mexico, 4/2016). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction	

Appropriate engineering controls

: If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Date of issue/Date	of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version : 2.01	6/13
41000	Expressions® Select Ir	nterior Flat			SHW-85-NA-GHS-US	
	White					

Section 8. Exposure controls/personal protection

Environmental exposure controls	: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
Individual protection meas	<u>ures</u>
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Date of issue/Date of revision	: 6/22/2023 Date of previous issue : 12/10/2022	Version : 2.01	
Vapor pressure	: 2.3 kPa (17.5 mm Hg)		
Lower and upper explosion limit/flammability limit	: Not available.		
Flammability	: Not available.		
Evaporation rate	: 0.09 (butyl acetate = 1)		
Flash point	: Closed cup: Not applicable.		
Boiling point, initial boiling point, and boiling range	: 100°C (212°F)		
Melting point/freezing point	: Not available.		
рН	: 8.9		
Odor threshold	: Not available.		
Odor	: Not available.		
Color	: Not available.		
Physical state	: Liquid.		

41000

: 12/10/2022

Section 9. Physica	l and	d chemical properties		
Relative vapor density	: 1[A	sir = 1]		
Relative density	: 1.3			
Solubility(ies)	:			
Media		Result		
cold water		Partially soluble		
Partition coefficient: n- octanol/water	: Not	applicable.	1	
Auto-ignition temperature	: Not	available.		
Decomposition temperature	: Not	available.		
Viscosity	: Kinematic (40°C (104°F)): >20.5 mm²/s (>20.5 cSt)			
Molecular weight	: Not applicable.			
Aerosol product				
Heat of combustion	: 0.1	57 kJ/g	~	

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredients.
Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Incompatible materials	: No specific data.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Not available.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
Titanium Dioxide	Skin - Mild irritant	Human	-	72 hours 300 ug l	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Date of issue/Date	of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version	: 2.01
41000	Expressions® Select Ir	nterior Flat			SHW-85	-NA-GHS-US
	White					

8/13

Section 11. Toxicological information

	<u> </u>		
Product/ingredient name	OSHA	IARC	NTP
Titanium Dioxide Crystalline Silica, respirable powder Cristobalite, respirable powder	-	2B 1 1	- Known to be a human carcinogen. Known to be a human carcinogen.

Reproductive toxicity

Not available.

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Name		Route of exposure	Target organs
Crystalline Silica, respirable powder	Category 1	inhalation	-
Cristobalite, respirable powder	Category 1	inhalation	respiratory tract

Aspiration hazard

Name	Result
Heavy Paraffinic Oil	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure	: Not available.
Potential acute health effe	octs
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the p	physical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.
Delayed and immediate ef	fects and also chronic effects from short and long term exposure
Short term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Long term exposure	
Potential immediate effects	: Not available.
Potential delayed effects	: Not available.
Potential chronic health e	ffects

Date of issue/	Date of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version	: 2.01	9/13
41000	Expressions® Se	lect Interior Flat			SHW-85-N	NA-GHS-US	
	White						

Section 11. Toxicological information

General Carcinogenicity Mutagenicity	 Causes damage to organs through prolonged or repeated exposure. May cause cancer. Risk of cancer depends on duration and level of exposure. No known significant effects or critical hazards.
Teratogenicity Developmental effects	 No known significant effects or critical hazards. No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.

Numerical measures of toxicity Acute toxicity estimates Not available.

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
Titanium Dioxide	Acute LC50 >1000000 μg/l Marine water	Fish - Fundulus heteroclitus	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition: Not available.coefficient (Koc)

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods	: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
------------------	--

Date of iss	ue/Date of revision	: 6/22/2023	Date of previous issue	: 12/10/2022	Version : 2.01	10/13
41000	Expressions® Se	elect Interior Flat			SHW-85-NA-GHS-U	S
	White					

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	ΙΑΤΑ	IMDG
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-
pecial precautions ansport in bulk ac IMO instruments	conside mode o suitably to shipn of the p dangero and on	odal shipping descrip r container sizes. Th f transport (sea, air, for that mode of train nent, and compliance erson offering the pr bus goods must be to all actions in case of able.	e presence of a shi etc.), does not indic nsport. All packaging e with the applicable oduct for transport. rained on all of the r	pping description for ate that the produce g must be reviewed regulations is the People loading and isks deriving from t	or a particular t is packaged I for suitability prior sole responsibility I unloading

Section 15. Regulatory information

TSCA 5(a)2 proposed significant new use rules: 2-Methyl-4-isothiazolin-3-one; reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

SARA 313

SARA 313 (40 CFR 372.45) supplier notification can be found on the Environmental Data Sheet.

California Prop. 65

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

International regulations


: 12/10/2022

Section 15. Regulatory information

International lists	: Australia inventory (AIIC): Not determined.
	China inventory (IECSC): Not determined.
	Japan inventory (CSCL): Not determined.
	Japan inventory (ISHL): Not determined.
	Korea inventory (KECI): Not determined.
	New Zealand Inventory of Chemicals (NZIoC): Not determined.
	Philippines inventory (PICCS): Not determined.
	Taiwan Chemical Substances Inventory (TCSI): Not determined.
	Thailand inventory: Not determined.
	Turkey inventory: Not determined.
	Vietnam inventory: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

Procedure used to derive the classification

CARCINOGENICITY - Category 1A SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) - Category 1 Calculation method Calculation method History Date of printing : 6/22/2023 Date of issue/Date of : 6/22/2023 revision Date of provision			
Date of printing: 6/22/2023Date of issue/Date of: 6/22/2023revision: 6/22/2023			
Date of issue/Date of : 6/22/2023 revision			
revision			
Date of providuo isque : 12/10/2022			
Date of previous issue : 12/10/2022			
Version : 2.01			
Key to abbreviations : ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Internediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 19 as modified by the Protocol of 1978. ("Marpol" = marine pollution) N/A = Not available SGG = Segregation Group UN = United Nations			

Indicates information that has changed from previously issued version.

Notice to reader

Date of issue/Date of revision		: 6/22/2023	Date of previous issue	: 12/10/2022	Version	: 2.01	12/13
41000 Expressions® Select Interior Flat					SHW-85-NA-GHS-US		
	White						

Section 16. Other information

It is recommended that each customer or recipient of this Safety Data Sheet (SDS) study it carefully and consult resources, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. This information is provided in good faith and believed to be accurate as of the effective date herein. However, no warranty, express or implied, is given. The information presented here applies only to the product as shipped. The addition of any material can change the composition, hazards and risks of the product. Products shall not be repackaged, modified, or tinted except as specifically instructed by the manufacturer, including but not limited to the incorporation of products not specified by the manufacturer, or the use or addition of products in proportions not specified by the manufacturer. Regulatory requirements are subject to change and may differ between various locations and jurisdictions. The customer/buyer/user is responsible to ensure that his activities comply with all country, federal, state, provincial or local laws. The conditions for use of the product are not under the control of the manufacturer; the customer/buyer/user is responsible to determine the conditions necessary for the safe use of this product. The customer/buyer/user should not use the product for any purpose other than the purpose shown in the applicable section of this SDS without first referring to the supplier and obtaining written handling instructions. Due to the proliferation of sources for information such as manufacturer-specific SDS, the manufacturer cannot be responsible for SDSs obtained from any other source.