

**Material Safety Data Sheet**

May be used to comply with  
 OSHA's Hazard Communication Standard  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form-Approved  
 OMB No. 1218.0072

IDENTITY (As Used on Label and List) <b>LIQUID PASTE WAX #3208</b>	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
---	---

**Section I**

Manufacturer's Name : <b>Lundmark Wax Company, Inc.</b>	Emergency Telephone Number : <b>(630) 628-1199</b>
Address(Number, Street, City, and Zip Code): <b>350 S. LaLonde Ave.</b>	Telephone Number for Information: <b>(630) 628-1199</b>
<b>Addison, IL 60101</b>	Date Prepared: <b>November 05, 1997</b>
	Signature of preparer (optional) :

**Section II-Hazardous Ingredients/Identity Information**

Hazardous Components (specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (optional)
Petroleum Distillate      Cas. No.	8030-30-6	500ppm		< 85%
Turpentine                    Cas. No.	8006-64-2	100ppm		< 25%

**Section III-Physical/Chemical Characteristics**

Boiling Point:	300° F	Specific Gravity (H <sub>2</sub> O =1):	.75 - .80
Vapor Pressure (mm Hg.):	Unknown	Melting Point:	N.A.
Vapor Density (AIR =1):	Unknown	Evaporation Rate (Butyl Acetate = 1)	Unknown
Solubility in Water:	Nil		
Appearance and Odor:	White, opaque, viscous liquid, solvent odor		

**Section IV--Fire and Explosion Hazard Data**

Flash Point (Method Used):      104° F	Flammable Limits:	LEL:	UEL:
Extinguishing Media:	Water fog, dry chemical, CO <sub>2</sub> .		
Special Fire Fighting Procedures:	None		
Unusual Fire and Explosion Hazards:	None		

Section V--Reactivity Data			LIQUID PASTE WAX		#3208		
Stability:	Unstable		Conditions to Avoid:				
	Stable	X					
Incompatibility (Materials to Avoid): <b>None</b>							
Hazardous Decomposition or By-products: <b>On burning, carbon monoxide and dioxide</b>							
Hazardous Polymerization	May Occur		Conditions to Avoid:				
	Will Not Occur	X					
Section VI--Health Hazard Data							
Route(s) of Entry:	Eyes	Inhalation?	X	Skin?	X	Ingestion?	X
Health Hazards (Acute and Chronic): <b>May cause burns to skin &amp; eyes. Harmful if swallowed. Vapors harmful.</b>							
Carcinogenicity: <b>None</b>		NIP?	IARC Monographs?		OSHA Regulated?		
Signs and Symptoms of Exposure: <b>Eyes and skin: Burning. Vapors: Headache, nausea and dizziness.</b>							
<b>Ingestion: Gastro intestinal irritation.</b>							
Medical Conditions Generally Aggravated by Exposure:		Unknown					
Emergency and First Aid Procedures: <b>Eyes and skin - Flush with water for 10 minutes. Vapors: Remove to fresh air. If irritation persists, call physician. Ingestion: Do not induce vomiting. CALL PHYSICIAN.</b>							
Section VII--Precautions for Safe Handling and Use							
Steps to be Taken in Case Material is Released or Spilled: <b>Absorb on clay or rags.</b>							
Waste Disposal Method: <b>Sanitary land fill. Check with Federal, Local and State regulations.</b>							
Precautions to be Taken in Handling and Storing: <b>Keep away from spark or flame.</b>							
Other Precautions: <b>Keep out of the reach of children.</b>							
Section VIII--Control Measures							
Respiratory Protection (Specific Type): <b>None</b>							
Ventilation:	Local Exhaust:	Optional		Special:	N.A.		
	Required	Mechanical (General):	N.A.		Other:	N.A.	
Protective Gloves: <b>Required</b>				Eye Protection: <b>Required</b>			
Other Protective Clothing or Equipment: <b>None</b>							
Work/Hygienic Practices: <b>Observe personal hygiene.</b>							
Page 2				*U.S.G.P.O. 1986-491529/15775			