



The Armor All/STP Products Company
 39 Old Ridgebury Road
 Danbury, CT 06810
 Tel. 1-203-205-2900

Material Safety Data Sheet

| I Product: STP® GAS TREATMENT | | | | | | | | | | | | | | | | | | | | | | |
|--|--|---|---------------|-----------------------|-----------------------------|-----------|---|--|--------|---|--|--------|-----------------|---|------------|---------------------------------|------------------------------|------------|---|--------------------------------|--------|---|
| Description: CLEAR, COLORLESS-TO-LIGHT-AMBER, THIN LIQUID WITH A HYDROCARBON ODOR | | | | | | | | | | | | | | | | | | | | | | |
| Other Designations | Distributor | | | | | | | | | | | | | | | | | | | | | |
| | The Armor All/STP Products Company 39 Old Ridgebury Road Danbury, CT 06810 | | | | | | | | | | | | | | | | | | | | | |
| Emergency Telephone Nos. | | | | | | | | | | | | | | | | | | | | | | |
| For Medical Emergencies, call 1-866-949-6465. For Transportation Emergencies, call 1-800-424-9300 (Chemtrec). | | | | | | | | | | | | | | | | | | | | | | |
| II Health Hazard Data | III Hazardous Ingredients | | | | | | | | | | | | | | | | | | | | | |
| <p>May cause eye and skin irritation. Vapors or mists may cause irritation to the eyes, nose, throat, and respiratory tract. Repeated or prolonged exposure to vapor concentrations above the worker exposure limits may cause central nervous system depression (e.g. dizziness, weakness, nausea, headaches, unconsciousness, and/or death). Small amounts of liquid aspirated into the lungs can cause chemical pneumonitis, which can be fatal. Besides being an aspiration hazard, ingestion may cause gastrointestinal disturbances (e.g. irritation, nausea, vomiting, and diarrhea) and central nervous system depression.</p> <p>Preexisting eye, skin, and respiratory disorders may be aggravated by exposure to this product.</p> <p>FIRST AID:</p> <p>EYE CONTACT: Rinse with water for 15 minutes. If irritation persists, call a doctor.</p> <p>SKIN CONTACT: Wash with soap and water. If irritation persists, call a doctor.</p> <p>INGESTION: DO NOT INDUCE VOMITING. Immediately call a doctor or poison control center.</p> <p>INHALATION: Move to fresh air. If breathing problems develop, call a doctor.</p> | <table border="1"> <thead> <tr> <th>Ingredients</th> <th>Concentration</th> <th>Worker Exposure Limit</th> </tr> </thead> <tbody> <tr> <td>Kerosene CAS # 8008-20-6</td> <td>80 - 100%</td> <td>200 mg/m³ - skin - TLV-TWA^a</td> </tr> <tr> <td>Petroleum naphtha, light aromatic CAS # 64742-95-6</td> <td>1 - 5%</td> <td>2000 mg/m³ - PEL^{b,d}</td> </tr> <tr> <td>Proprietary additives CAS # Proprietary</td> <td>1 - 5%</td> <td>Not applicable.</td> </tr> <tr> <td>1,2,4-Trimethylbenzene CAS # 95-63-6</td> <td>0.5 - 1.5%</td> <td>25 ppm - TLV-TWA^{a,e}</td> </tr> <tr> <td>Naphthalene CAS # 91-20-3</td> <td>0.5 - 1.5%</td> <td>10 ppm - skin - TLV-TWA^a 10 ppm - PEL^b 15 ppm - TLV-STEL^c</td> </tr> <tr> <td>Ethylbenzene CAS # 100-41-4</td> <td>< 0.2%</td> <td>100 ppm - TLV-TWA^a 100 ppm - PEL^b 125 ppm - TLV-STEL^c</td> </tr> </tbody> </table> <p>Note that skin contact can contribute to overall exposure.</p> <p>^aTLV-TWA = ACGIH Threshold Limit Value - Time Weighted Average ^bPEL = OSHA Permissible Exposure Limit - Time Weighted Average ^cTLV-STEL = ACGIH Threshold Limit Value - Short Term Exposure Limit ^dBased on the exposure limit for petroleum distillates. ^eBased on the exposure limit for trimethylbenzene (mixed isomers).</p> <p>IARC Monographs (Volume 82 (2002), Volume 77 (2000)) state that there is inadequate evidence in humans and sufficient evidence in experimental animals of the carcinogenicity of naphthalene and ethylbenzene. IARC classification - Group 2B.</p> <p>None of the other ingredients in the product are on the IARC, NTP, or OSHA carcinogen lists.</p> | Ingredients | Concentration | Worker Exposure Limit | Kerosene CAS # 8008-20-6 | 80 - 100% | 200 mg/m ³ - skin - TLV-TWA ^a | Petroleum naphtha, light aromatic CAS # 64742-95-6 | 1 - 5% | 2000 mg/m ³ - PEL ^{b,d} | Proprietary additives CAS # Proprietary | 1 - 5% | Not applicable. | 1,2,4-Trimethylbenzene CAS # 95-63-6 | 0.5 - 1.5% | 25 ppm - TLV-TWA ^{a,e} | Naphthalene CAS # 91-20-3 | 0.5 - 1.5% | 10 ppm - skin - TLV-TWA ^a 10 ppm - PEL ^b 15 ppm - TLV-STEL ^c | Ethylbenzene CAS # 100-41-4 | < 0.2% | 100 ppm - TLV-TWA ^a 100 ppm - PEL ^b 125 ppm - TLV-STEL ^c |
| Ingredients | Concentration | Worker Exposure Limit | | | | | | | | | | | | | | | | | | | | |
| Kerosene CAS # 8008-20-6 | 80 - 100% | 200 mg/m ³ - skin - TLV-TWA ^a | | | | | | | | | | | | | | | | | | | | |
| Petroleum naphtha, light aromatic CAS # 64742-95-6 | 1 - 5% | 2000 mg/m ³ - PEL ^{b,d} | | | | | | | | | | | | | | | | | | | | |
| Proprietary additives CAS # Proprietary | 1 - 5% | Not applicable. | | | | | | | | | | | | | | | | | | | | |
| 1,2,4-Trimethylbenzene CAS # 95-63-6 | 0.5 - 1.5% | 25 ppm - TLV-TWA ^{a,e} | | | | | | | | | | | | | | | | | | | | |
| Naphthalene CAS # 91-20-3 | 0.5 - 1.5% | 10 ppm - skin - TLV-TWA ^a 10 ppm - PEL ^b 15 ppm - TLV-STEL ^c | | | | | | | | | | | | | | | | | | | | |
| Ethylbenzene CAS # 100-41-4 | < 0.2% | 100 ppm - TLV-TWA ^a 100 ppm - PEL ^b 125 ppm - TLV-STEL ^c | | | | | | | | | | | | | | | | | | | | |
| IV Special Protection and Precautions | V Transportation and Regulatory Data | | | | | | | | | | | | | | | | | | | | | |
| <p>Hygienic Practices: Wash hands after direct contact. Do not wear product-contaminated clothing for prolonged periods.</p> <p>Engineering Controls: Use local or general ventilation to minimize exposure to product vapors.</p> <p>Personal Protective Equipment: Wear safety glasses. Wear chemical resistant (e.g. nitrile or neoprene) gloves if there is the potential for repeated or prolonged skin contact. In situations where exposure limits may be exceeded, a NIOSH-approved respirator is advised.</p> | <p>DOT: Not restricted.</p> <p>IATA: UN1268, Petroleum distillates, n.o.s., Class 3, PG III.</p> <p>IMDG: UN1268, Petroleum distillates, n.o.s. (kerosene), Class 3, PG III, limited quantity.</p> <p>EPA - SARA Title III/CERCLA: This product is regulated under Sections 311/312. This product contains 1,2,4-trimethylbenzene, which is regulated under Section 313; naphthalene, xylene (CAS # 1330-20-7, <0.4%), cumene (CAS # 98-82-8, <0.4%), and ethylbenzene, which are regulated under Section 313 and Section 304/CERCLA.</p> <p>TSCA 8(b): All components of this product are either on the TSCA 8(b) Inventory or otherwise exempt from listing.</p> <p>TSCA 12(b): This product is subject to TSCA 12(b) reporting requirements for the following materials: Naphthalene - CAS # 91-20-3, Confidential chemical - Acc. # 141323.</p> | | | | | | | | | | | | | | | | | | | | | |
| VI Spill Procedures/Waste Disposal | VII Reactivity Data | | | | | | | | | | | | | | | | | | | | | |
| <p>Spill Procedures: CAUTION - COMBUSTIBLE. Eliminate potential sources of ignition. Absorb and containerize. Prevent product from entering sewer or waterways by diking or impounding. Notify the National Response Center if a spill of any amount enters navigable waters, the contiguous zone, or adjoining shorelines.</p> <p>Waste Disposal: Dispose of in accordance with all applicable federal, state, and local regulations.</p> | <p>Stable under normal use and storage conditions.</p> <p>Avoid contact with strong oxidizing agents.</p> | | | | | | | | | | | | | | | | | | | | | |
| VIII Fire and Explosion Data | IX Physical Data | | | | | | | | | | | | | | | | | | | | | |
| <p>Flashpoint: 61°C (closed cup)</p> <p>Fire Extinguishing Agents: Dry chemical, carbon dioxide (CO₂), foam, or water spray.</p> | <p>Specific gravity (16°C)..... 0.82</p> <p>Solubility in water..... Negligible</p> | | | | | | | | | | | | | | | | | | | | | |