



**Manufacturers of  
Professional Grade Cement &  
Construction Products Since 1967**

**HMIS CODE**

HEALTH	1
REACTIVITY	0
FLAMMABILITY	0

**MATERIAL SAFETY DATA SHEET  
POR-ROK<sup>®</sup> DASH PATCH**

	<b>Emergency Telephone Number</b> 215-638-4400 OR 800-523-6570
<b>Address:</b> 1445 Ford Rd., Bensalem, Pa. 19020	<b>Telephone Number for Information</b> 215-638-4400
<b>Prepared By:</b> Fred Kinney, Tech. Director. <b>Updated By:</b> Lisa Terreri, Tech Coordinator.	<b>Date Prepared</b> February 2004 <b>Date Updated:</b> March 2012
<b>Signature:</b>	<b>Title:</b> Technical Coordinator

**SECTION II - HAZARD INGREDIENTS/IDENTITY INFORMATION**

MATERIAL OR COMPONENT	CAS #	%	HAZARDOUS DATA
Calcium Sulphate	7778-18-9	66	OSHA PEL: 5mg/M <sup>3</sup> OSHA TLV: 5mg/M <sup>3</sup> ACGIH TLV: 10 mg/M <sup>3</sup> TOTAL DUST
Lime Stone	1317-65-3.	34	50mppcf
<b>Vapor Density</b> (AIR = 1) N/A <b>Freezing Point:</b> N/A <b>Evaporation Rate</b> (Butyl Acetate = 1)N/A <b>Solubility in Water:</b> Partial	<b>Boiling Point</b> N/A <b>Specific Gravity</b> (H <sub>2</sub> O = 1) N/A <b>Vapor Pressure</b> (mm Hg.) None <b>Appearance and Odor:</b> Grey Powder, no odor		

**SECTION III - FIRE AND EXPLOSION HAZARD DATA**

<b>Flash Point:</b> None	<b>Hazardous Decomposition Products:</b> None
<b>Flammable Limits:</b>	<b>Upper</b> N/A <b>Lower</b> N/A
<b>Sensitivity to Impact:</b> N/A	<b>Flammability:</b> None
<b>Autoignition Temperature:</b> N/A	<b>Explosion Data:</b> N/A

**SECTION IV – HEALTH HAZARD DATA**

<b>Route(s) of Entry:</b> Yes	<b>Inhalation</b> Yes	<b>Skin</b> Yes	<b>Ingestion</b> Yes
<b>Health Hazards</b> ( <i>Acute and Chronic</i> ) Excessive and/or long term inhalation may cause silicosis and/or lung disease. Short Term exposure may cause irritation to nose, throat, and respiratory passages.			
<b>Symptoms of Exposure:</b> Exposure to skin may cause rash and redness. Inhalation may cause coughing, shortness of breath, wheezing and pulmonary disorders.			
<b>Emergency First Aid:</b> <b>Inhalation:</b> Seek medical attention and remove person to fresh air.			
<b>Skin:</b> Wash with soap and water		<b>Eyes:</b> Flush with copious amounts of clean water for fifteen minutes	

**Ingestion:** immediately seek medical advise. Give milk or egg white beaten with water until vomit fluid is clear. If vomiting does not occur, induce vomiting by gagging the victim (by placing a finger at the back of the throat) **DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON**

**Carcinogenicity:** NO

## SECTION V – EMERGENCY AND FIRST AID PROCEDURES

### Emergency and First Aid Procedures:

**Eyes:** Immediately flush affected eye/eyes with copious amounts of clean water for at least 15 minutes. If irritation persists, seek immediate medical attention.

**Skin:** Contact with skin may cause irritation and/or rash. Always wash exposed areas twice with soap and water. If irritation continues, seek medical attention. Product is alkaline and will cause burns if not thoroughly rinsed from affected area.

**Ingestion:** Immediately seek medical attention. Give milk or egg whites mixed with water until vomit is clear. If vomiting does not occur, induce by gagging the victim by placing a clean gloved finger at the back of the throat **NEVER INDUCE VOMITING TO AN UNCONSCIOUS PERSON.**

## SECTION VI – REACTIVITY DATA

**Conditions Known to Cause Instability:** Product is stable  
dioxide

**Hazardous Decomposition:** Calcium oxide and carbon

**Incompatibility/Materials to avoid:** Product is incompatible with organic and inorganic acids. Acid will react with cement and carbonates.

## SECTION VII – SPECIAL PROTECTION INFORMATION

**Personal Protection Equipment:** Safety glasses, neoprene gloves, protective clothing and a respirator is recommended.

**Gloves:** Neoprene or Rubber

**Respirator:** A NIOSH approved particulate mask is recommended.

**Footwear:** N/A

**Eyes:** Safety glasses. A face shield may not protect air born dusts from entering the eyes. **Clothing:** Normal work clothes.

**Handling Procedures and Equipment:** Avoid direct and prolonged exposure to eyes and skin. Always wash after use.

**Engineering Controls:** Normal mechanical ventilation and exhaust are preferred.

## SECTION VIII – SPILL, LEAK AND DISPOSAL

**Storage Requirements:** Material is very stable in its un-opened bag. Repair any broken or torn bags immediately. Store in a dry, cool area. Material will harden with high humidity or wetness during storage.

**Spill and Leak Disposal:** Sweep up. Avoid creating dust.

**Waste Disposal:** Dispose as a non-hazardous waste, in compliance with local, state and federal regulations. To contain any dusts, water down the empty bags with water to harden the material in a solid waste

*The information provided in this Material Safety Data Sheet has been obtained from source(s) believed to be reliable. CGM, Inc. provides no warranties, express or implied and assumes no responsibility for the accuracy or completeness of the information contained herein*