

# MSDS

## SECTION 1 – Chemical Product and Company Identification

J-B Weld Co.  
P.O. Box 483  
1130 Como St.  
Sulphur Springs, Texas 75482  
PH 903-885-7696 - FAX 903-885-5911

For Chemical Emergency:  
CHEMTREC: 1-800-424-9300  
CANUTEC: 1-613-996-6666  
(For Canada call collect)

**PRODUCT NAME:** JB Weld Wood Restore Liquid Hardener  
**PRODUCT CODE:** 40001  
**SCHEDULE B NUMBER:** 3208.20.0000

## SECTION 2 – Hazard Identification

OVEREXPOSURE EFFECTS:

ACUTE EFFECTS:

EYES: Contact with eyes can cause irritation, redness, tearing, blurred vision, and/or swelling.

SKIN: Contact with skin can cause irritation, (minor itching, burning and/or redness), dermatitis, defatting may be readily absorbed through the skin.

INHALATION: Inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness and/or asphyxiation. Aspiration of material into lungs may result in chemical pneumonitis which can be fatal. May be toxic.

INGESTION: Ingestion can cause gastrointestinal irritation, nausea, vomiting, diarrhea.

PRIMARY ROUTES OF EXPOSURE: Inhalation, skin, eyes

## SECTION 3 – Composition, Information or Ingredients

### INGREDIENTS

<u>INGREDIENTS</u>	<u>WGT%</u>	<u>CAS #</u>
Acetone	70-80%	67-64-1
Proprietary Resins	20-30%	Supplier Trade Secret

## SECTION 4 – First Aid Measures

**INHALATION:** If inhaled, remove victim from exposure to a well-ventilated area. Make them comfortably warm, but not hot. Use oxygen or artificial respiration as required. Consult a physician.

**SKIN:** For skin contact, wash promptly with soap and excess water.

**EYES:** For eye contact, flush promptly with excess water for at least fifteen minutes. Consult a physician.

**INGESTION:** If ingested, do not induce vomiting. Give victim a glass of water. Call a physician immediately.

## SECTION 5 – Fire-Fighting Measures

**FIRE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam

**SPECIAL FIRE FIGHTING PROCEDURES:** Fight like a fuel oil fire. Cool fire exposed containers with water spray. Firefighter should wear OSHA/NIOSH approved self-contained breathing apparatus.

**UNUSUAL FIRE AND EXPLOSION HAZARD:** Closed containers exposed to high temperatures, such as fire conditions may rupture.

# MSDS

## SECTION 6 – Accidental Release Measures

SPILLS, LEAK OR RELEASE: Ventilate area. Remove all possible sources of ignition. Avoid prolonged breathing of vapor. Contain spill with inert absorbent.

## SECTION 7 – Handling and Storage

STORAGE AND HANDLING: Use with adequate ventilation. Harmful or fatal if swallowed. Avoid contact with eyes and skin. Avoid breathing vapors. Do not store the product above 100°F/38°C. Do not flame, cut, braze weld or melt empty containers. Keep the product away from heat, open flame, and other sources of ignition. Avoid contact with strong acids, alkalis, and oxidizers.

## SECTION 8 – Exposure Controls and Personal Protection

### INGREDIENTS

Acetone  
Proprietary Resins

### CAS #

67-64-1  
Supplier Trade Secret

### TLV/PEL

TLV: 500 ppm, PEL: 1000 ppm  
N/E

RESPIRATORY PROTECTION: If component exposure limits are exceeded, use NIOSH/MSHA approved air purifying or fresh air supplied respirator to remove vapors. Use an air-supplied respirator if necessary.

VENTILATION: Use adequate ventilation in volume and pattern to keep TLV/PEL below recommended levels. Explosion-proof ventilation may be necessary.

PROTECTIVE GLOVES: To prevent prolonged exposure use rubber gloves; solvents may be absorbed through the skin.

EYE PROTECTION: Safety Glasses or goggles with splash guards or side shields.

OTHER PROTECTIVE EQUIPMENT: Wear protective clothing as required to prevent skin contact.

## SECTION 9 – Physical and Chemical Properties

FLASH POINT: 0°F/-17°C Seta Flash Closed cup

LOWER FLAMMABLE LIMIT %: N/E

UPPER FLAMMABLE LIMIT %: N/E

APPEARANCE: Clear to amber liquid, solvent odor

SPECIFIC GRAVITY: 0.87

VAPOR PRESSURE (mmHG): N/E

BOILING POINT: N/E

VAPOR DENSITY: Heavier than air

EVAPORATION RATE (Ethyl Ether = 1): Slower than Ethyl Ether

VOLATILES BY WEIGHT: Approximately 75%

SOLUBILITY IN WATER: Soluble

VOC (less water & exempts): Nil

## SECTION 10 – Stability and Reactivity

STABILITY: Stable

CONDITIONS TO AVOID: Open flames, sparks, heat, electrical and static discharge.

INCOMPATIBILITY MATERIALS TO AVOID: Strong acids, alkalis, oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide, and Carbon.

HAZARDOUS POLYMERIZATION: Will not occur.

## SECTION 11 – Toxicological Information

WR liquid hardener 40001(JB Weld Ver.)

Print Date: 12/9/2010

Page 2 of 4

# MSDS

## **CHRONIC EFFECTS:**

Overexposure to this material has apparently been known to cause the following effects in lab animals: Anemia, liver abnormalities, kidney, eye, and central nervous system damage.

CARCINOGEN: YES  NO

TERATOGEN: YES  NO

MUTAGEN: YES  NO

## **SECTION 12 – Ecological Information**

N/E

## **SECTION 13 – Disposal Considerations**

WASTE DISPOSAL: Dispose of in accordance with local, state, and federal regulations.

## **SECTION 14 – Transport Information**

### **For Ground Transport: In USA**

Consumer Commodity ORM-D in cases with inner containers 1 gallon or less.

### **For Air Transport:**

Must be re-boxed to UN specified packaging.

UN1263, Paint, 3, PG II

Packing Instruction 305, 307

### **For Ocean Transport:**

With inner containers of 5L or less:

UN1263, Paint, 3, PG II, F/P -17C

EMS # F-E, S-E

In limited quantity

## **SECTION 15 – Regulatory Information**

### **CALIFORNIA PROPOSITION 65:**

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

### **SECTION 313 SUPPLIER NOTIFICATION:**

This product contains the following toxic chemicals subject to the reporting requirements of the Emergency Planning and Community Right-To-Know Act of 1986 and 40 CFR 372:

<u>CHEMICAL NAME</u>	<u>CAS</u>	<u>% BY WGT</u>
----------------------	------------	-----------------

N/Ap

This information must be included in all MSDS that are copied and distributed for this chemical.

**DO NOT FLAME CUT, WELD OR MELT EMPTY CONTAINERS.**

WR liquid hardener 40001(JB Weld Ver.)

Print Date: 12/9/2010

Page 3 of 4

# MSDS

## SECTION 16 – Other Information

HMIS RATING:      Health            2                    4 = Extreme  
                         Fire                 3                    3 = High  
                         Reactivity        1                    2 = Moderate  
   1 = Slight  
   0 = Insignificant

Personal Protection - See Section VIII

## ABBREVIATIONS

IARC      = International Agency for Research on Cancer  
ACGIH    = American Conference of Governmental Industrial Hygienists  
NIOSH    = National Institute of Occupational Safety and Health  
TLV      = Threshold Limit Value  
PEL      = Permissible Emission Level  
DOT      = Department of Transportation  
NTP      = National Toxicology Program  
N/AV     = Not Available  
N/AP     = Not Applicable  
N/E      = Not Established  
N/D      = Not Determined

PREPARED BY:                    J-B Weld Co.  
   P.O. Box 483  
   1130 Como St.  
   Sulphur Springs, Texas 75482  
  
   TELEPHONE NBR: 903-885-7696  
   FAX NBR: 903-885-5911

DATE REVIEWED:                May 5, 2010  
DATE REVISED:                    n/a  
REVISION:                         TEST

The information in the Material Safety Data Sheet has been compiled from our experience and from data presented in various technical publications. It is the user's responsibility to determine the suitability of this information for the adoption of the safety precautions as may be necessary. We reserve the right to revise Material Safety Data Sheets from time to time as new technical information becomes available. The user has the responsibility to contact the Company to make sure that the MSDS is the latest one issued.