



MATERIAL SAFETY DATA SHEET

Page 1 of 7

HE505 - FLASHMASTER

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 08/22/2008 Product Name: HE505 - FLASHMASTER Product Code: HE505	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
1,2,4-trimethylbenzene	95-63-6		1 - 5
1,3,5-trimethylbenzene	108-67-8		0.5 - 1.5
aromatic petroleum distillates	64742-95-6		1 - 5
petroleum asphalt	8052-42-4		30 - 60
attapulgite	12174-11-7		5 - 15
calcium carbonate	1317-65-3		5 - 15
cellulose fiber	9004-34-6		7 - 13
silica, quartz	14808-60-7		0.1 - 1
stoddard solvent	8052-41-3		10 - 30
xylene	1330-20-7		0.1 - 1

EMERGENCY OVERVIEW

CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.

Appearance/Odor: Black paste, strong petroleum solvent odor

3. Hazards Identification
Primary Route(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).



HE505 - FLASHMASTER

3. Hazards Identification - Continued

Skin Hazards

May cause skin irritation and contact dermatitis upon prolonged contact.

Ingestion Hazards

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

Inhalation Hazards

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic/Carcinogenicity Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: 120 °F

Flash Point Method: Setaflash

Lower Explosive Limit: 0.9

Upper Explosive Limit: 6.0

Fire And Explosion Hazards

Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Extinguishing Media

Chemical foam, carbon dioxide (CO2), water fog or dry chemical.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations.

7. Handling And Storage

Handling And Storage Precautions

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near strong oxidants or strong acids. Use only with adequate ventilation.



HE505 - FLASHMASTER

8. Exposure Controls/Personal Protection

Engineering Controls

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

Eye/Face Protection

Safety glasses with side shields or goggles recommended.

Skin Protection

Use with chemical-protective gloves to prevent skin contact.

Respiratory Protection

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

Ingredient(s) - Exposure Limits

- 1,2,4-trimethylbenzene
ACGIH TLV-TWA 25 ppm
- 1,3,5-trimethylbenzene
ACGIH TLV-TWA 25 ppm
- aromatic petroleum distillates
OSHA PEL-TWA 500 ppm
- petroleum asphalt
ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)
- calcium carbonate
OSHA PEL-TWA 15 mg/m3 (total dust)
OSHA PEL-TWA 5 mg/m3 (respirable dust)
- cellulose fiber
ACGIH TLV-TWA 10 mg/m3
- silica, quartz
ACGIH TLV-TWA 0.025 mg/m3
OSHA PEL-TWA 30mg/m3 / (%SiO2+2) (total dust)
OSHA PEL-TWA 10 mg/m3/ (%SiO2+2) (respirable dust)
- stoddard solvent
ACGIH TLV-TWA 100 ppm
OSHA PEL-TWA 500 ppm
- xylene
ACGIH TLV-STEL 150 ppm
ACGIH TLV-TWA 100 ppm
OSHA PEL-TWA 100 ppm

9. Physical And Chemical Properties

Appearance

Black Paste

Odor


Strong Petroleum Solvent Odor

Chemical Type: Mixture

HE505 - FLASHMASTER

<p>9. Physical And Chemical Properties - Continued</p>
<p><u>Odor - Continued</u> Physical State: Liquid Boiling Point: 310-400 °F Specific Gravity: 1.04 Percent Volatiles: 38 Vapor Pressure: 2@68°F Vapor Density: >1 pH Factor: not applicable Solubility: insoluble in water Evaporation Rate: <1</p>
<p>10. Stability And Reactivity</p>
<p>Stability: Stable Hazardous Polymerization: Will not occur <u>Incompatible Materials</u> Avoid contact with strong oxidizing agents and acids. <u>Hazardous Decomposition Products</u> Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO2).</p>
<p>11. Toxicological Information</p>
<p><u>Chronic/Carcinogenicity</u> IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): titanium dioxide ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz Risk of cancer depends on duration and level of exposure to this product as a dust. <u>Miscellaneous Toxicological Information</u> Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below. <u>Ingredient(s) - Toxicological Data</u> 1,2,4-trimethylbenzene LD50 (oral, rat): 5000 mg/kg LC50 (rat): 18 g/m3 (4-hour exposure) 1,3,5-trimethylbenzene Lethal dose (oral, rat): 23 g/kg lethal to 7 of 10 test animals LC50 (rat): 24 g/m3 (4-hour exposure) aromatic petroleum distillates LD50 (oral, rat): 2900 mg/kg calcium carbonate oral-rat LD50: 6450 mg/kg cellulose fiber LD50 (oral, rat): >2000 mg/kg LC50 (rat): >5800 mg/m3 (4-hour exposure) silica, quartz iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um) stoddard solvent</p>

HE505 - FLASHMASTER

11. Toxicological Information - Continued
<p><u>Ingredient(s) - Toxicological Data - Continued</u></p> <p>oral-rat LD50: >5000 mg/kg dermal-rabbit LD50: >3000 mg/kg inhal-rat LC50: >5500 mg/m3 (880 ppm) inhal-rat LC50: >1300 ppm</p> <p>xylene LD50 (oral, rat): 5400 mg/kg LD50 (dermal, rabbit): 12180 mg/kg LC50 (rat): 6350 ppm (4-hour exposure)</p>
12. Ecological Information
No specific information available.
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations.
14. Transport Information
<p>Ground or Water Domestic Voyage</p> <p>Not restricted if shipped in containers <450L (119 gallons) Restricted if shipped in containers >450L (119 gallons)</p> <p>US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III</p> <p>Canada UN1999, Tars liquid, 3, III</p> <p>Unless departs >flash point:</p> <p>Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III</p> <p>IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages</p> <p>IATA UN1999, Tars liquid, 3, III</p>
<p><u>DOT (Pictograms)</u></p> 
15. Regulatory Information
<p><u>U.S. Regulatory Information</u></p> <p>Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.</p> <p><u>Ingredient(s) - U.S. Regulatory Information</u></p> <p>1,2,4-trimethylbenzene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical</p> <p>xylene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical</p>



HE505 - FLASHMASTER

15. Regulatory Information - Continued

Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

- New Jersey - Workplace Hazard
- New Jersey - Environmental Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

1,3,5-trimethylbenzene

- New Jersey - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

aromatic petroleum distillates

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard

petroleum asphalt

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

attapulgit

- California - Proposition 65

calcium carbonate

- Pennsylvania - Workplace Hazard

cellulose fiber

- Pennsylvania - Workplace Hazard

silica, quartz

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- California - Proposition 65
- Massachusetts - Hazardous Substance

stoddard solvent

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

xylene

- New Jersey - Workplace Hazard
- New Jersey - Environmental Hazard
- New Jersey - Special Hazard
- Pennsylvania - Workplace Hazard
- Pennsylvania - Environmental Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic

Ingredient(s) - Canadian Regulatory Information

1,2,4-trimethylbenzene

- WHMIS - Ingredient Disclosure List

1,3,5-trimethylbenzene

- WHMIS - Ingredient Disclosure List

HE505 - FLASHMASTER

15. Regulatory Information - Continued

Ingredient(s) - Canadian Regulatory Information - Continued

silica, quartz

WHMIS - Ingredient Disclosure List


stoddard solvent

WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 03/04/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).