30016 01 00

\_\_\_\_\_\_

Section 1 -- PRODUCT AND COMPANY IDENTIFICATION

-----

PRODUCT NUMBER HMIS CODES

30016 Flammability 2

Health

Reactivity

PRODUCT NAME

FORMBY'S\* Build-Up Remover

MANUFACTURER'S NAME EMERGENCY TELEPHONE NO.

FORMBY'S (216) 566-2917

10 Mountainview Road

Upper Saddle River, NJ 07458

DATE OF PREPARATION INFORMATION TELEPHONE NO.

22-SEP-03 (800) 523-9299

\_\_\_\_\_\_

Section 2 -- COMPOSITION/INFORMATION ON INGREDIENTS

% by WT CAS No. INGREDIENT UNITS VAPOR PRESSURE

94 64742-88-7 Mineral Spirits

ACGIH TLV 100 ppm 2 mm

ACGIH TLV 100 ppm OSHA PEL 100 ppm

5 64741-89-5 Paraffin Oil

ACGIH TLV 5 mg/m3 as Mist OSHA PEL 5 mg/m3 as Mist

-----

Section 3 -- HAZARDS IDENTIFICATION

\_\_\_\_\_\_

ROUTES OF EXPOSURE

INHALATION of vapor or spray mist.

EYE or SKIN contact with the product, vapor or spray mist.

EFFECTS OF OVEREXPOSURE

EYES: Irritation.

SKIN: Prolonged or repeated exposure may cause irritation.

INHALATION: Irritation of the upper respiratory system.

May cause nervous system depression. Extreme overexposure may result in unconsciousness and possibly death.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

Headache, dizziness, nausea, and loss of coordination are indications of excessive exposure to vapors or spray mists.

Redness and itching or burning sensation may indicate eye or excessive skin exposure.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

None generally recognized.

CANCER INFORMATION

For complete discussion of toxicology data refer to Section 11.

30016 page 2

Section 4 -- FIRST AID MEASURES

\_\_\_\_\_\_

EYES: Flush eyes with large amounts of water for 15 minutes.

Get medical attention.

SKIN: Wash affected area thoroughly with soap and water.

Remove contaminated clothing and launder before re-use.

INHALATION: If affected, remove from exposure. Restore breathing.

Keep warm and quiet.

INGESTION: Do not induce vomiting.

Get medical attention immediately.

\_\_\_\_\_\_

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT LEL UEL 100 F PMCC 1.0 6.0

FLAMMABILITY CLASSIFICATION

Combustible, Flash above 99 and below 200 F

EXTINGUISHING MEDIA

Carbon Dioxide, Dry Chemical, Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS

Closed containers may explode when exposed to extreme heat.

Application to hot surfaces requires special precautions.

During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES

Full protective equipment including self-contained breathing apparatus should be used.

Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

\_\_\_\_\_\_

Section 6 -- ACCIDENTAL RELEASE MEASURES

\_\_\_\_\_

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED Remove all sources of ignition. Ventilate the area.

Remove with inert absorbent.

\_\_\_\_\_\_

Section 7 -- HANDLING AND STORAGE

-----

STORAGE CATEGORY

DOL Storage Class II

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Contents are COMBUSTIBLE. Keep away from heat and open flame.

Consult NFPA Code. Use approved Bonding and Grounding procedures.

Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

30016

\_\_\_\_\_\_

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

# PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

# VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2.

EYE PROTECTION

Wear safety spectacles with unperforated sideshields. OTHER PRECAUTIONS

Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

\_\_\_\_\_\_

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

6.40 lb/gal PRODUCT WEIGHT 766 g/l SPECIFIC GRAVITY

0.77

300 - 395 F BOILING POINT 148 - 201 C

MELTING POINT Not Available

VOLATILE VOLUME 95 %

EVAPORATION RATE Slower than ether Heavier than air VAPOR DENSITY SOLUBILITY IN WATER N.A.

VOLATILE ORGANIC COMPOUNDS (VOC Theoretical)

6.08 lb/gal 728 g/l Less Water and Federally Exempt Solvents

6.08 lb/gal 728 g/l Emitted VOC

\_\_\_\_\_\_

Section 10 -- STABILITY AND REACTIVITY

\_\_\_\_\_

STABILITY -- Stable CONDITIONS TO AVOID

None known.

INCOMPATIBILITY

None known.

HAZARDOUS DECOMPOSITION PRODUCTS

By fire: Carbon Dioxide, Carbon Monoxide

HAZARDOUS POLYMERIZATION

Will not occur

30016 page 4

Section 11 -- TOXICOLOGICAL INFORMATION

\_\_\_\_\_

\_\_\_\_\_\_

# CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Prolonged overexposure to solvent ingredients in Section 2 may cause adverse effects to the liver and urinary systems.

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

\_\_\_\_\_\_

# TOXICOLOGY DATA

CAS No.	Ingredient N	ame			
  64742-88-7	Mineral Spirits				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available
64741-89-5	Paraffin Oil				
		LC50	RAT	4HR	Not Available
		LD50	RAT		Not Available

\_\_\_\_\_\_

\_\_\_\_\_\_

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

No data available.

-----

Section 13 -- DISPOSAL CONSIDERATIONS

\_\_\_\_\_

# WASTE DISPOSAL METHOD

Waste from this product may be hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261.

Waste must be tested for ignitability to determine the applicable EPA hazardous waste numbers.

Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

\_\_\_\_\_\_

Section 14 -- TRANSPORT INFORMATION

\_\_\_\_\_\_

No data available.

\_\_\_\_\_\_

Section 15 -- REGULATORY INFORMATION

-----

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION

CAS No. CHEMICAL/COMPOUND % by WT % Element

No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

# TSCA CERTIFICATION

All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

30016 page 5

Section 16 -- OTHER INFORMATION

\_\_\_\_\_\_

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.