# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/06/2010 Revised On 10/06/2010

### 1 Identification of substance

Trade name: PIROGUE GREEN
Product codes: PG000A0746

Manufacturered for: SEYMOUR OF SYCAMORE

917 Crosby Avenue Sycamore, IL 60178

(815)-895-9101, www.seymourpaint.com

Emergency information: CHEMTEL 1-800-255-3924, 813-248-0585 \*if located outside the U.S.\*

## 2 Composition/Data on components

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
	Acetone	23.47%
74-98-6	propane	18.97%
108-88-3		14.93%
106-97-8		11.14%
	VM&P Naphtha	6.6%
	PM acetate	5.62%
112926-00-8	Silicon Dioxide	2.48%

## 3 Hazards identification

Hazard description:

2 %

Harmful

Extremely flammable

Physical dangers: Extremely flammable liquid and vapor in a pressurized container. Keep away from heat, sparks, and

flame.

Has narcotizing effect. Extremely flammable. Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Do not spray on a naked flame or any incandescent material. Buildup of explosive mixtures possible without sufficient ventilation.

Effects of chronic

overexposure:

May cause permanent brain and nervous system damage. Repeated overexposure can also damage kidneys, lungs, liver, heart, and blood. Intentional misuse by deliberately inhaling the contents may be

harmful or fatal.

NFPA ratings (0 - 4): Health = 1

Fire = 4 Reactivity = 3

HMIS-ratings (0 - 4): Health=

Fire= 4 Physical Hazard= 3

#### 4 First aid measures

**After inhalation:** Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

After eye contact: Move to fresh air. Rinse opened eye for several minutes under running water. If symptoms persist, consult

a doctor.

**After swallowing:** Contact physician or poison control center.

#### 5 Fire fighting measures

**Extinguishing agents:** CO2, sand, extinguishing powder, or water spray. Fight larger fires with water spray or alcohol resistant

foam.

Protective equipment: No special measures required.

# 6 Accidental release measures

**Personal safety:** Wear protective equipment. Keep unprotected persons away. **Environmental safety:** Do not allow product to reach sewage systems or ground water.

Clean-up/collection: Ensure adequate ventilation.

### 7 Handling and storage

Fire/explosion protection: Do not spray on a naked flame or any incandescent material. Do not smoke. Protect from electrostatic

discharges.

**Storage requirements:** Observe pressurized container storage regulations. Consult with your local authorities.

- USA

## **Material Safety Data Sheet** acc. to ISO/DIS 11014

Printing date 10/06/2010 Revised On 10/06/2010

Trade name: PIROGUE GREEN

(Contd. of page 1)

8 Exposure controls and personal protection
---

8 Exposure controls and personal protection:		
Components with limit values that require monitoring at the workplace:		
67-64-1 Acetone		
REL TLV	2400 mg/m³, 1000 ppm 590 mg/m³, 250 ppm Short-term value: 1782 mg/m³, 750 ppm Long-term value: 1188 mg/m³, 500 ppm BEI	
74-98-6 propane		
REL	1800 mg/m³, 1000 ppm 1800 mg/m³, 1000 ppm Varies mg/m³, 1000 ppm	
108-88-3 Toluene		
PEL	Short-term value: C 300; 500* ppm Long-term value: 200 ppm *10-min peak per 8-hr shift	
REL	Short-term value: 560 mg/m³, 150 ppm	
TLV	Long-term value: 375 mg/m³, 100 ppm 75 mg/m³, 20 ppm NIC-BEI	
106-97-8 n-butane		
REL TLV	1900 mg/m³, 800 ppm Varies mg/m³, 1000 ppm	
108-65-6 PM acetate		
WEEL	50 ppm	

112926-00-8 Silicon Dioxide  $\mathsf{TLV}$ 

Short-term value: 6 mg/m³ Long-term value: 10 mg/m³

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas. In cases

where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you

suspect overexposure conditions exist, please consult an authority on chemical hygeine.

Protective gloves. The glove material has to be impermeable and resistant to the substance. No glove

recommendation can be given.

Eye protection: Tightly sealed goggles

## 9 Physical and chemical properties:

**General Information:** 

Hand protection:

Odor: Aromatic -44°C (-47°F) **Boiling point:** Flash point: -19°C (-2°F)

Auto igniting: Product is not self-igniting.

Danger of explosion: Stable at normal temperatures. Can may burst when exposed to temperatures exceeding 120

degrees fahrenheit.

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.5 Vol % 10.9 Vol % Upper Explosion Limit: Vapor Pressure: 40 PSI, 2750 hPa

Density at 20°C (68°F): 0.75 g/cm<sup>3</sup>

Specific Gravity: Between 0.77 and 0.85 (Water equals 1.00)

563.5 g/l / 4.70 lb/gl VOC content:

VOC content (less exempt solvents): 58.4 % MIR Value: 1.18 Solids content: 18.5 %

## 10 Stability and reactivity:

Conditions to avoid: Do not allow the can to exceed 120 degrees Fahrenheit. Stable at normal temperatures.

Materials to be avoided:

**Hazardous Reactions:** No dangerous reactions known.

# 11 Toxicological information:

Skin effects: No irritant effect. Eye effects: Irritating effect.

(Contd. on page 3)

## Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/06/2010 Revised On 10/06/2010

Trade name: PIROGUE GREEN

(Contd. of page 2)

Sensitization: No sensitizing effects known.

## 12 Ecological information

Other information: This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's),

perfluorocarbons (PFC's), or chlorinated solvents. Hazardous for water, do not empty into drains. Aquatic toxicity:

# 13 Disposal considerations

DISPOSAL METHOD: Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty can's should be recycled.

## 14 Transport information:

**Hazard class:** 2.1 Identification number: N/A Label 2.1

ADR/RID/TDG class: 5F Gases

**UN-Number:** 1950 IMDG Class: 2.1 Packaging group: Ш EMS Number: F-D,S-U No Marine pollutant: ICAO/IATA Class: 2.1

Aerosols, Flammable Proper shipping name:

Consumer Commodity ORM-D

## 15 Regulations

# SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

# SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

TSCA: All ingredients are listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

1333-86-4 Carbon black 100-41-4 ethyl benzene California Proposition 65

chemicals known to cause

108-88-3 Toluene developmental toxicity: CANADIAN

**ENVIRONMENTAL** PROTECTION ACT:

WHMIS Symbols for

Canada:

 Compressed gas D2A - Very toxic material causing other toxic effects



EPA: A= Known human carcinogen B= Probable human carcinogen

C= Possible human carcinogen

D= Not classifiable as to human carcinogenicity: Inadequate human and animal evidence of carcinogenicity (or no data is available).

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

'Data are inadequate for an assessment of human carcinogeni potential.'

'Inadequate information to assess carcinogenic potential.'

67-64-1	Acetone	Ι
108-88-3	Toluene	Ш

IARC: Group 2A: The ingredient is probably carcinogenic to humans.

Group 2B: The ingredient is possibly carcinogenic to humans. There is limited evidence of carcinogenicity

Group 3: The ingredient is unclassifiable as to its carcinogenicity to humans.

108-88-3 Toluene 3

ACGIH: A1-designates a confirmed human carcinogen.

A2-designates a suspected human carcinogen.

A3-designates an animal carcinogen.

A4-designates "not classifiable as a human carcinogen".

67-64-1 Acetone A4 108-88-3 Toluene A4

(Contd. on page 4) USA

# Material Safety Data Sheet acc. to ISO/DIS 11014

Printing date 10/06/2010 Revised On 10/06/2010

Trade name: PIROGUE GREEN

(Contd. of page 3)

NIOSH:

13463-67-7 titanium dioxide 1333-86-4 Carbon black

Risk phrases: Extremely flammable.

Irritating to eyes.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Safety phrases: Keep out of the reach of children.

Keep away from sources of ignition - No smoking.

Do not breathe gas/fumes/vapour/spray.

Do not empty into drains, dispose of this material and its container at hazardous or special waste

collection point

Wear suitable protective clothing and gloves.

If swallowed, seek medical advice immediately and show this container or label. Use only in well-ventilated areas.

### 16 Other information

This product was manufactured in the U.S.A.

The information on this sheet is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Contact: Regulatory Affairs

Abbreviations and

acronyms:

IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
PP: Severe Marine Pollutant
P: Marine Pollutant
P: Marine Pollutant
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
ISO: International Organization for Standardization
EPA: Environmental Protection Agency
IARC: International Agency for the Research of Cancer
NIOSH: National Institute for Occupational Safety and Health
TSCA: Toxic Substances Control Act
CPSC: Consumer Product Safety Commission

USA