



Revision Number: 004.2

Issue date: 12/09/2011

## 1. PRODUCT AND COMPANY IDENTIFICATION

<b>Product name:</b>	<b>Loctite® Super Glue Gel</b>	<b>IDH number:</b>	1399965
<b>Product type:</b>	Super glue	<b>Region:</b>	United States
<b>Company address:</b>		<b>Contact information:</b>	
Henkel Corporation		Telephone: 800.624.7767	
One Henkel Way		MEDICAL EMERGENCY Phone: Poison Control Center	
Rocky Hill, Connecticut 06067		1-877-671-4608 (toll free) or 1-303-592-1711	
		TRANSPORT EMERGENCY Phone: CHEMTREC	
		1-800-424-9300 (toll free) or 1-703-527-3887	
		Internet: www.henkelna.com	

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

<b>Physical state:</b>	liquid	<b>HMIS:</b>	
<b>Color:</b>	colourless	<b>HEALTH:</b>	2
<b>Odor:</b>	irritating	<b>FLAMMABILITY:</b>	2
		<b>PHYSICAL HAZARD:</b>	1
		<b>Personal Protection:</b>	See MSDS Section 8

**WARNING:** BONDS SKIN IN SECONDS.  
MAY CAUSE EYE AND RESPIRATORY TRACT IRRITATION.  
COMBUSTIBLE LIQUID AND VAPOR.

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects

**Inhalation:** Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.

**Skin contact:** Bonds skin in seconds. May cause skin irritation. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.

**Eye contact:** Irritating to eyes. Causes excessive tearing. Eyelids may bond.

**Ingestion:** Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

**Existing conditions aggravated by exposure:** Eye, skin, and respiratory disorders.

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100

## 4. FIRST AID MEASURES

**Inhalation:** Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.

**Eye contact:**

Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.

**Ingestion:**

Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.

**Notes to physician:**

Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.

## 5. FIRE FIGHTING MEASURES

**Flash point:**

80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup

**Autoignition temperature:**

Not available.

**Flammable/Explosive limits - lower:**

Not available.

**Flammable/Explosive limits - upper:**

Not available.

**Extinguishing media:**

Dry powder. foam Carbon dioxide.

**Special firefighting procedures:**

Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).

**Unusual fire or explosion hazards:**

Not available.

**Hazardous combustion products:**

Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**

Do not allow product to enter sewer or waterways.

**Clean-up methods:**

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

## 7. HANDLING AND STORAGE

**Handling:**

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists of this product. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

**Storage:**

Keep in a cool, well ventilated area away from heat, sparks and open flame.  
Keep container tightly closed until ready for use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None

**Engineering controls:**

Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	liquid
Color:	colourless
Odor:	irritating
Odor threshold:	Not available.
pH:	Not available.
Vapor pressure:	Not available.
Boiling point/range:	Not available.
Melting point/ range:	Not available.
Vapor density:	Not available.
Flash point:	80 - 93.4 °C (176°F - 200.12 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not available.
Evaporation rate:	Not available.
Solubility in water:	Polymerises in presence of water.
Partition coefficient (n-octanol/water):	Not available.
VOC content:	Not available.

## 10. STABILITY AND REACTIVITY

**Stability:**

Stable under recommended storage conditions.

**Hazardous reactions:**

Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

**Hazardous decomposition products:**

None

**Incompatible materials:**

Water, Amines, Alkalis, Alcohols.

**Conditions to avoid:**

None if used for intended purpose.

## 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	No	No

Hazardous components	Health Effects/Target Organs
Ethyl 2-cyanoacrylate	Irritant, Allergen, Respiratory

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

**Hazardous waste number:** It is the responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching Procedure (TCLP) 40 CFR 261.20-24.

## 14. TRANSPORT INFORMATION

The shipping classification in this section are for bulk packaging only. Shipping classification may be different for non-bulk packaging as exceptions may apply. Refer to shipping documents for package specific transportation classification.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Combustible liquid, n.o.s. (Cyanoacrylate ester)  
**Hazard class or division:** Combustible Liquid  
**Identification number:** NA 1993  
**Packing group:** III  
**Exceptions:** (Not more than 450 Liters), Unrestricted

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)  
**Hazard class or division:** 9  
**Identification number:** UN 3334  
**Packing group:** None  
**Exceptions:** Not more than 500 ml (each inner package) - Unrestricted

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.  
**TSCA 12(b) Export Notification:** None above reporting de minimus  
**CERCLA/SARA Section 302 EHS:** None above reporting de minimus  
**CERCLA/SARA Section 311/312:** Immediate Health, Delayed Health, Fire, Reactive  
**CERCLA/SARA 313:** None above reporting de minimus  
**California Proposition 65:** No California Proposition 65 listed chemicals are known to be present.

### Canada Regulatory Information

**CEPA DSL/NDL Status:** One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

WHMIS hazard class:

B.3, D.2.B

## 16. OTHER INFORMATION

**This material safety data sheet contains changes from the previous version in sections:** New Material Safety Data Sheet format.

**Prepared by:** Karim Nasr, Regulatory Affairs Specialist

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.