



Exterior

Waterproofer

11020

Product Description:

Storm System Waterproofer is a transparent sealer that penetrates the surface of dry, porous wood surfaces to help prevent moisture penetration and water damage. This product dries clear and allows the wood surface to age naturally. This product will protect against salt water. For new construction, prevent weathering and water damage by applying this product immediately after installation.

Recommended Use:

Shingles, Shakes, Siding, Fencing, Decks and Rails, Timbers, Architectural Millwork, Sills, Outdoor Furniture, Log Homes, Storage Sheds, Kennels, Plywood Lumber, Paneling

Application:

WARNING! If you scrape, sand or remove old paint from any surface, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Carefully clean up with a wet mop or HEPA vacuum. Before you start, find out how to protect yourself and your family by contacting the U.S. EPA/Lead Information Hotline at 1-800-424-LEAD (5323) or log on to www.epa.gov/lead.

To allow for penetration, surfaces must be thoroughly dry, clean, and free from other coatings that may prevent penetration. Always test a small area before application for desired results before coating the entire surface.

Apply at temperatures above 50° F using a suitable brush, roller, pad applicator or flooding spray. Use sufficient material to saturate the surface. Do not apply a second coat over a dry first coat. It is acceptable to apply a second coat via a wet on wet method.

Architectural Specifications:

Wood: one or two coats (wet on wet) Storm System Waterproofer No. 11020

Precautions:

Do not re-coat with paint or other coatings.

Safety Information:

Keep out of reach of children. Do not take internally.

*14-19 sec. #2 Zahn

**48 hrs to reach full water repellency

Product Specifications:

Type: Acrylic Emulsion
Exposure: Exterior
Specular Gloss: @ 60° ±
Volume Solids: 11.9 % ±2
Solids by Weight: 12.5 % ±2
Vehicle: 98 % ±2
Pigment: 0 % ±2
Dry Film Thickness: <1 mils
Viscosity @ 77 °F: * KU ±5
Maximum VOC: <50 g/liter
Flash Pt °F: Non-combustible
Thinner: Water
Clean Up: Soap & Water

Available Colors and Bases:

Clear

Available Package Sizes:

Gallon 5 Gallon

(Weight Per Gallon: 8.4 lbs. ± .5 lb)

Drying Times:

To Touch: N/A** hrs.

To Handle: N/A** hrs.

To Recoat: 1/2 hr -6 hrs.

(@ 70-77 °F, 50% R.H.)

Surface Spread Rate:

Smooth: 240 s.f./gal.

Porous: 90 s.f./gal.

(Spray Application is 50% of above)

Tools and Equipment:

Brush -
Synthetic, Nylon or Polyester Pad Application

Roller -
3/8" Nap Synthetic Fiber

Airless Spray-
Flooding spray