



Medallion® Exterior Oil Primer



Product Description

Medallion Exterior Oil Primer is the perfect base coat for all oil and latex house paints, adding long-lasting protection to your home as it resists weather-related problems such as peeling and blistering. Gives mildew resistant coating that helps promote topcoat adhesion as it seals and primes exterior surfaces.

Features

- Resists peeling and blistering
- Mildew resistant

Recommended Uses

- Hardboard siding and trim
- Bare wood
- Previously painted, unprimed wood siding and trim
- Bare redwood, cedar, cypress, fir or gummy pines

Colors and Base Information

White	oz./gal. 128
-------	-----------------

Shipping and Packaging

Freight Classification: Paint or Paint Related Material. Protect from freezing.

Packaging: Quart & Gallon – 4 per carton
5-gallon pail

Typical Properties (185 White)

Vehicle Type:

Sheen: N/A

Solids by Volume: 75%

Solids by Weight: 87%

Weight per Gallon: 13.7 lbs./gal.

VOC: Less than 200 g/L

Viscosity: 85–90 Krebs Units

Dry Time: 77°F @ 50% Relative Humidity

To the touch: 8 hours

Recoat: 24 hours

Washing: Allow at least 7 days before washing. Use mild detergent and sponge.

Surface Coverage:

400 sq. ft. Depending on Surface Porosity

At: 4.0 mil Wet, 2.2 mil Dry

Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

Surface Preparation

Read the Lead Warning in Cautions section. **General:** Clean and dry surface thoroughly, removing all dirt, dust, rust and grease. **Bare Wood:** Prime the entire surface with this product. **Previously Painted Surfaces:** Scrape, sand, then prime. Wire brush badly chalking areas and wash with TSP and water. Dull glossy surfaces with gloss remover or sandpaper. Countersink nails, fill with putty. Apply a rust inhibitive metal primer on exposed nails. Caulk all cracks and joints. **Metal:** Remove rust and apply a rust inhibitive metal primer. **Hardboard Siding:** Remove any wax from bleed-through areas by wiping with a mineral spirits soaked cloth, turning the cloth often.

Application and Clean-up

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Stir thoroughly before and during use. Apply with a premium quality “one coat” roller, natural or polyester bristle brush or airless sprayer. If applying by spray, back-roll or back-brush to work primer into surface. Apply a liberal coat of primer evenly, working well into the surface. Clean up with mineral spirits.

Cautions (185 White)

WARNING: CONTAINS PETROLEUM DISTILLATE AND CRYSTALLINE SILICA. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. USE ONLY WITH ADEQUATE VENTILATION. Keep away from heat, sparks and flame. Avoid breathing vapors, spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, or if air monitoring demonstrates vapor/mist levels above applicable limits, wear an appropriate, properly-fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer’s directions for respirator use. AVOID CONTACT WITH THE EYES OR SKIN. Wash thoroughly after use. Close container after each use.

Warning: This product contains chemicals known to the State of California to cause cancer.

FIRST AID: EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

Delayed effect from long term exposure: Reports from commercial painters have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.

Cancer Hazard. Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

DO NOT TAKE INTERNALLY.

KEEP OUT OF REACH OF CHILDREN.

For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:
1-888-345-5732**

This product contains less than 200 g/L VOC

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.

valspar

1191 Wheeling Rd, Wheeling, IL 60090 888-313-5569
www.valsparpaint.com

09/10

PDS 185