MATERIAL SAFETY DATA SHEET

PRODUCT NAME: WALL PATCH & REPAIR KIT HMIS CODES: H F R P

0 0 0 PRODUCT CODE: 2030

MANUFACTURER'S NAME: Custom Building Products, Inc.

ADDRESS: 6511 SALT LAKE AVE., BELL, CA. 90201

EMERGENCY PHONE: (323) 582-0846 INFORMATION PHONE: (323) 582-0846

DATE REVISED : 12-13-99 NAME OF PREPARER: S. TAYLOR

====== SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION =======

OCCUPATION EXPOSURE

VAPOR

PRESSURE

LIMITS CAS NUMBER OSHA PEL ACGIH TLV mm Hg @ TEMP % COMPONENTS

NONE REPORTABLE

* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS ==========

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 0.5 VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: SLOWER THAN ETHER

SOLUBILITY IN WATER: DILUTABLE

APPEARANCE AND ODOR: WHITE MASTIC; SLIGHT AMMONICAL ODOR

======== SECTION IV - FIRE AND EXPLOSION HAZARD DATA ============

FLASH POINT: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/A UPPER: N/A

VOC = 0 q/1

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIREFIGHTING PROCEDURES

NONE

UNUSUAL FIRE AND EXPLOSION HAZARDS

MATERIAL CAN SPLATTER ABOVE 100 DEG.C/212F. DRIED POLYMER FILM CAN BURN.

STABILITY: STABLE

CONDITIONS TO AVOID

INCOMPATIBILITY (MATERIALS TO AVOID)

NONE

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

NONE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

NONE

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE SLIGHTLY IRRITATING TO EYES.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE NONE

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

HEALTH HAZARDS (ACUTE AND CHRONIC)

ACUTE: N/A CHRONIC: N/A

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

NONE

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

NONE

EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: FLUSH EYES WITH A LARGE AMOUNT OF WATER FOR AT LEAST 15 MINUTES.

SKIN CONTACT: FLUSH SKIN WITH LARGE AMOUNTS OF WATER

INHALATION: MOVE SUBJECT TO FRESH AIR

======= SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE =========

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED CONTAIN SPILL WITH INERT MATERIALS (e.g.SAND, EARTH). KEEP SPILLS AND RUN OFF OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

WASTE DISPOSAL METHOD
DISPOSE OF SPILLED PRODUCT ACCORDING TO LOCAL, STATE, AND FEDERAL
REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING NONE

OTHER PRECAUTIONS NONE

RESPIRATORY PROTECTION NONE REQUIRED.

VENTILATION LOCAL EXHAUST.

PROTECTIVE GLOVES LATEX GLOVES.

EYE PROTECTION SAFTEY GLASSES.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT NONE REQUIRED.

WORK/HYGIENIC PRACTICES
KEEP SPILLED MATERIALS CLEANED UP.

DISCLAIMER

THE INFORMATION PRESENTED HERE IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED T BE, WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED, THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.