



## Medallion® Interior Latex Semi-Gloss Series



### Product Description

This durable wall enamel protects with a 100% acrylic coating for long lasting interior beauty. The tough semi-gloss offers a scrubbable, stain resistant coating perfect for high traffic areas. The decorative sheen is ideal for walls and trim. Dries quickly and cleans up easily with soap and water.

### Features

- 100% Acrylic Durability
- Stain Resistant
- Washable
- Paint and Primer in One Product
- Mildew Resistant Finish
- Dries Quickly
- Soap and Water Cleanup
- Low odor, Low VOC

### Recommended Uses

- Plaster
- Wood
- Brick
- Drywall
- Cement
- Metal

### Colors and Base Information

	oz./gal.
White	128
Pastel Base	126
Tint Base	124
Clear Base	116

Reference store database for available colors.

### Shipping and Packaging

**Freight Classification:** Paint or Paint Related Material. Protect from freezing.

**Packaging:** Quart & Gallon – 4 per carton  
5-gallon pail

### Typical Properties (2400 White)

**Vehicle Type:** Acrylic Resin

**Sheen:** 30–40 Units @ 60° angle

**Solids by Volume:** 34%

**Solids by Weight:** 45%

**Weight per Gallon:** 10.1 lbs./gal.

**VOC:** Less than 50 g/L

**Viscosity:** 96–102 Krebs Units

**Dry Time:** 77°F @ 50% Relative Humidity

**To the touch:** 30–60 minutes

**Recoat:** 2–4 hours

**Washing:** Allow at least 7 days before washing.  
Use mild detergent and sponge.

### Surface Coverage:

400 sq. ft. (37.2 m<sup>2</sup>) per gallon  
**At:** 4.0 mil Wet, 1.4 mil Dry

### Storage and Disposal

- Keep container closed when not in use.
- Do not transfer contents to other containers for storage or disposal.
- In case of spillage, absorb with inert material such as sand or kitty litter.
- Dispose of contaminated absorbent, container and/or unused contents in accordance with local, state and federal regulations.

## Surface Preparation

Read the Lead Warning in Cautions section. Thoroughly clean the surface and allow to dry. Remove wallpaper and loose, peeling paint. Patch cracks and spot prime. Dull glossy surfaces. Prime new wallboard with latex wall primer. Prime new wood with enamel undercoater or latex wall primer.

## Application and Cleanup

Paint only when surface and air temperatures are 50–90 °F (10–32 °C). Stir paint thoroughly. Intermix all containers to ensure uniform color. Apply with a premium quality roller, polyester brush or airless sprayer. Thin only for spraying with up to 8 oz. of water per gallon of paint. Paint the ceiling first, then the walls. If applying by roller, roll from dry area into wet area using firm, crisscross strokes. Finish with long, even strokes in one direction. Clean tools and hands with warm, soapy water.

## Cautions (2400 White)

**WARNING: CONTAINS CRYSTALLINE SILICA.** May cause eye and skin irritation. Avoid breathing spray mist or dust. If painting indoors, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness, or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. **AVOID CONTACT WITH THE EYES AND SKIN.** Wash thoroughly after use. Close container after each use.

**Warning:** This product contains chemicals known to the State of California to cause cancer.

**FIRST AID:** EYE CONTACT: Flush thoroughly with water for at least 15 minutes. If irritation persists, **get medical attention.** IF INHALED: If affected by vapor or spray mist, move to fresh air. If breathing difficulty continues, **get medical attention.** IF SWALLOWED: Drink 2 glasses of water. **Get medical attention immediately.**

**Delayed effect from long term exposure:** Cancer Hazard. Crystalline silica may cause lung damage and cancer. Risk depends upon duration and level of exposure to dust generated from sanding surfaces or spray mist.

**DO NOT TAKE INTERNALLY.  
KEEP OUT OF REACH OF CHILDREN.**  
For additional safety and chronic health hazard information, refer to the Material Safety Data Sheet for this product.

**EMERGENCY MEDICAL TELEPHONE:  
1-888-345-5732**

**This product contains less than 50 g/L VOC**

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean-up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

The data on this sheet represents typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. **UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.** Your only remedy for any defect in this product, is the replacement of the defective product, or a refund of its purchase price, at our option.