## Material Safety Data Sheet for Product ID No: 33635

Starco Chemical, LLC · 4230 Charter St. · Vernon, CA 90058
Phone: (323) 973-1036 · FAX: (323) 277-9157
24- Hour Emergency Telephone: (800) 255-3924

DATE PREPARED: 10/05/08

This Material Safety Data Sheet contains environmental, health and toxicology information for your employees. Please make sure this information is given to them. It also contains information to help you meet community Right To Know emergency response reporting requirements under SARA TITLE III and many other laws. If you resell this product, this MSDS must be given to the buyer or the information incorporated in your MSDS.

This MSDS complies with 29 CFR 1910.1200 (The Hazard Communication Standard)

PRODUCT DESCRIPTION: STARCO PRIVATE LABEL CUSTOMER 70395 GRILLPRO STAINLESS CLN D.O.T. PROPER SHIPPING NAME: ORM-D CONSUMER COMMODITY NFPA CODES: HEALTH - 1 FLAMMABILITY - 2 CORROSIVE - 0 REACTIVITY - 0 ALIPHATIC DISTILLATES 20.0-35.0 % PEL: 100 PPM CAS #: 64742-88-7 TLV: 100 PPM PETROLEUM HYDROCARBON BASE STOCK 2.0-5.0 % PEL: NO LIMIT CAS #: 64742-54-7 TLV: NO LIMIT POLYDIMETHYLSILOXANE FLUID 0.5-6.5 % PEL: NOT ESTABLISHED CAS #: 63148-62-9 TLV: NOT ESTABLISHED INERT MATERIAL 45.0-60.0 % PEL: NOT ESTABLISHED TLV: NOT ESTABLISHED CAS #: 7732-18-5 HYDROCARBON PROPELLANT 10.0-20.0 % PEL: 800 PPM CAS #: 68-476-86-8 TLV: 800 PPM "\*" If present, IARL, NTP and OSHA carcinogens and chemical subject to this reporting requirements of SARA TITLE III, SECTION 313 are identified in this section. BOILING POINT FOR PRODUCT: NOT DETERMINED

VAPOR PRESSURE FOR PRODUCT: < 70 psi @ 60 deg F. VAPOR DENSITY FOR PRODUCT: NOT DETERMINED SPECIFIC GRAVITY: LIQUID: 0.92

## Material Safety Data Sheet for Product ID No: 33635

Starco Chemical, LLC · 4230 Charter St. · Vernon, CA 90058 Phone: (323) 973-1036 · FAX: (323) 277-9157 24- Hour Emergency Telephone: (800) 255-3924

70395 GRILLPRO STAINLESS CLN PAGE: 2 PRODUCT ID NO.: 33635 V.O.C. (GRAMS PER LITER): NOT DETERMINED WATER SOLUBILITY: LIQUID: 100% APPEARANCE: CLEAR LIQUID FLASH BACK DATE: EXTREMELY FLAMMABLE FLASH POINT(TOC): LEVEL 2 AEROSOL EXPLOSIVE LIMIT (PRODUCT): LOWER - N/A UPPER - N/A FIRE & EXPLOSIONS HAZARDS: Keep containers cool. Use equipment or shielding required to protect personnel against bursting, rupturing, venting containers. FIRE FIGHTING EQUIPMENT: At elevated temperatures (above 120 F) containers may vent, rupture, or burst. EXTINGUISHING MEDIA: Foam Dry Chemical, Carbon Dioxide. SEC05.10 THRESHOLD LIMIT VALUE: See Section II EFFECTS OF OVER EXPOSURE: Irritation to skin and eyes. EMERGENCY FIRST AID PROCEDURES: SKIN: Wash with soap and water. EYE: Flush with water for at least 15 minutes. INHALATION: Remove to fresh air. See a physician if irritation persist. ORAL: Call a physician. Do not induce vomiting. ADDITIONAL: Contact with eyes will be painful and irritating. Prolonged or repeated contact with skin may cause irritation. Mist caused by manufacturing operations may irritate the nasal passages. 06.20 STABILITY: Stable CONDITIONS TO AVOID: Temperatures above 130 degree F. HAZARDOUS POLYMERIZATION: Will not occur MATERIALS AND CONDITIONS TO AVOID INCOMPATIBILITY: Strong oxidizing agents HAZARDOUS DECOMPOSITION PRODUCTS: None SEC07.45 STEPS TO BE TAKEN IN CASE CONTAINER IS PUCTURED AND MATERIAL IS RELEASED: Clean up area by mopping or with absorbant materials and place in closed container for disposal. Consult Federal, State, and local disposal authorities.

## Material Safety Data Sheet for Product ID No: 33635

Starco Chemical, LLC · 4230 Charter St. · Vernon, CA 90058 Phone: (323) 973-1036 · FAX: (323) 277-9157 24- Hour Emergency Telephone: (800) 255-3924

## 70395 GRILLPRO STAINLESS CLN

WASTE DISPOSAL METHOD: Consult local authorities for proper waste disposal procedures. Empty de-pressurized containers can not be reused. Cans which are pressurized or contain liquid must be disposed of in a permitted waste management facility. Consult Federal, State, and local disposal authorities for approved procedures.

VENTILATION PROCEDURE: Use adequate ventilation

GLOVES PROTECTION: Neoprene or nitrile rubber gloves recommended.

RESPIRATORY PROTECTION: When applicable, wear a NIOSH approved respirator appropriate for the vapor or mist concentration at the point of use.

- EYE PROTECTION: Safety glasses.
- OTHER PROTECTION: None

====== SECTION IX - SPECIAL PRECAUTIONS OR OTHER COMMENTS ======= SEC09.45

- HANDLING STORAGE AND DECONTAMINATION PROCEDURES: When utilizing pressurized containers follow standard safety practices for handling aerosols.
- GENERAL COMMENTS: Do not store at temperatures above 120 degree F. Odor is not an adequate warning of potentially hazardous concentrations in air. Releases of these gases may cause a flammable atmosphere with explosion potential.
- PRECAUTIONARY STATEMENTS: Please read and follow the directions on the product label. They are your best guide to using this product in the most effective way, and give the necessary safety precautions to protect your health.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modification of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.