========	Section 1	PRODUCT AND COMPANY I	======================================	=======
PRODUCT N 63025/			HMIS C Health Flammabil	ity 0
MANUFACTU MINWAX 10 Mou Upper DATE OF E 01-APE	X* Water Based JRER'S NAME Company Intainview Roa Saddle River, PREPARATION 2-07		EMERGENCY TELEPHO (216) 566-2917 INFORMATION TELEP (800) 523-9299	NE NO. HONE NO.
	Section 2	COMPOSITION/INFORMATI INGREDIENT	ON ON INGREDIENTS	
		2-Methoxymethylethoxy ACGIH TLV 100 ACGIH TLV 150 OSHA PEL 100 OSHA PEL 150	ppm (Skin) ppm (Skin) STEL ppm (Skin) ppm (Skin) STEL	0.4 mm
1 5		Dimethylethanol Amine ACGIH TLV Not A OSHA PEL Not A 1-Methyl-2-Pyrrolidon	vailable vailable	4.4 mm
		ACGIH TLV Not A OSHA PEL Not A	vailable vailable	1 mm
	Section 3	HAZARDS IDENTIFICATIO		
INHALA EYE or EFFECTS O INHALA In a or SIGNS AND Rednes skin expo MEDICAL O None o CANCER IN	SKIN contact OF OVEREXPOSUR EYES: Irrita SKIN: Prolon ATION: Irrita confined area dizziness. SYMPTOMS OF s and itching osure. CONDITIONS AGG generally reco UFORMATION	tion. ged or repeated exposu tion of the upper resp vapors in high concent OVEREXPOSURE or burning sensation RAVATED BY EXPOSURE	re may cause irrita iratory system. ration may cause he may indicate eye or	adache, excessive

Continued on page 2

63025/7103	33	page 2		
Sect	ion 4 –– FIRST AID MEASURES			
EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention. SKIN: Wash affected area thoroughly with soap and water. Remove contaminated clothing and launder before re-use. INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet. INGESTION: Do not induce vomiting. Get medical attention immediately.				
Sect	ion 5 FIRE FIGHTING MEASURES			
UNUSUAL FIRE AN Closed conta exposed to extr During emerge cause a health medical attents SPECIAL FIRE FI Full protect should be used Water spray preferable. Wa	LASSIFICATION ole MEDIA ide, Dry Chemical, Alcohol Foam ND EXPLOSION HAZARDS ainers may explode (due to the build-up of pres reme heat. gency conditions overexposure to decomposition ; hazard. Symptoms may not be immediately appar ion. IGHTING PROCEDURES tive equipment including self-contained breathis	products may ent. Obtain ng apparatus zles are revent		
sect:	ion 6 ACCIDENTAL RELEASE MEASURES			
Remove all s	KEN IN CASE MATERIAL IS RELEASED OR SPILLED sources of ignition. Ventilate the area. inert absorbent.			
	ion 7 HANDLING AND STORAGE			
Keep contain containers with		pproved ke internally.		

heep oue of one reach of onitate

Continued on page 3

63025/71033

page 3

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

\_\_\_\_\_

PRECAUTIONS TO BE TAKEN IN USE

Use only with adequate ventilation.

Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using.

wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction). Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority. VENTILATION

Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108. RESPIRATORY PROTECTION

If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2.

When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive. PROTECTIVE GLOVES

Wear gloves which are recommended by glove supplier for protection against materials in Section 2. EYE PROTECTION

Wear safety spectacles with unperforated sideshields.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT 8.79 lb/gal 1053 g/l SPECIFIC GRAVITY 1.06 BOILING POINT 212 - 396 F 100 - 202 C MELTING POINT Not Available VOLATILE VOLUME 74 % EVAPORATION RATE Slower than ether VAPOR DENSITY Heavier than air SOLUBILITY IN WATER N.A. pH 8.0 VOLATILE ORGANIC COMPOUNDS 2.25 lb/gal 269 g/l 0.78 lb/gal 94 g/l ENTRY ENTRY ENTRY SOLVENTS

Continued on page 4

63025/71033		page 4				
Section	n 10 STABILITY AND REACTIVITY					
HAZARDOUS POLYMEN Will not occur	OID OSITION PRODUCTS on Dioxide, Carbon Monoxide RIZATION					
Section	n 11 TOXICOLOGICAL INFORMATION					
CHRONIC HEALTH HA No ingredient	AZARDS in this product is an IARC, NTP or OSHA listed c	arcinogen.				
TOXICOLOGY DATA CAS No.	Ingredient Name					
34590-94-8 108-01-0	2-Methoxymethylethoxypropanol LC50 RAT 4HR Not Available LD50 RAT 5135 mg/kg Dimethylethanol Amine					
872-50-4	LC50 RAT 4HR Not Available LD50 RAT 2340. mg/kg 1-Methyl-2-Pyrrolidone LC50 RAT 4HR Not Available LD50 RAT 4200 mg/kg					
Section 12 ECOLOGICAL INFORMATION						
ECOTOXICOLOGICAL INFORMATION No data available.						
Section 13 DISPOSAL CONSIDERATIONS						
WASTE DISPOSAL METHOD Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.						

63025/71033		page 5		
Section 14 TRANSPORT INFORMATION				
US Ground (DOT) Not Regulated for Transportation.				
Canada (TDG) Not Regulated for Transportation.				
IMO Not Regulated for Transportation.				
Section 15 REGULATORY INFORMATION	======	======		
SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION				
CAS No. CHEMICAL/COMPOUND	% by WT	% Element		
872-50-4 1-Methyl-2-Pyrrolidone	5			
CALIFORNIA PROPOSITION 65 WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. TSCA CERTIFICATION All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.				
Section 16 OTHER INFORMATION				
This product has been classified in accordance with the hazard criteria				

of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.