Material Safety Data Sheet May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements. U.S. Department of Labor Occupational Safety and Health Administration (Non-Mandatory Form) Form Approved OMB No. 1218-0072

## IDENTITY (As Used on Label and List) Bonide Japanese Beetle Killer RTU

I.D. NO. 4309 Date: October 3, 1998

### Section I

Bonide Products, Inc. (800) 424-9300 2 Wurz Ave. (315) 736-8231 Yorkville, NY 13495

## Section II - Hazardous Ingredients/Identity

Hazardous Components (Specific Chemical Identity: Common Name(s)	OSHA PEL	ACGIH	TLV	Other Limits	% (Optional)
Pyrethrins					0.02
Piperonyl Butoxide 51-03-06					0.20

## Section III - Fire/Explosion Hazard Data

FLASH POINT: N/A FLAMMABILITY: Puts out flame.
FIRE FIGHTING COMMENTS: Avoid use of water to reduce contamination hazard.
UNUSUAL FIRE/EXPLOSION HAZARD: None

## Section IV - Spill or Leak Procedures

PRECAUTIONS: Avoid prolonged contact with spilled material.

DISPOSAL: Soak up with absorbent. Small spills may be placed in original container, wrapped in paper and placed in trash. For large spills, consult State and Local authorities for disposal directives.

## Section V - Storage and Handling

STORAGE: Keep in a cool, dry place, and in an area inaccessible to children or pets. Avoid temperature extremes. HANDLING PRECAUTIONS: Avoid contact with eyes, skin or clothing. Wash thoroughly after handling. CONTAINER DISPOSAL: Wrap empty container and place in trash collection.

#### **Section VI - Health Hazard Data**

PRECAUTIONS: May be harmful if swallowed or absorbed through skin.

FIRST AID: IF IN EYES OR ON SKIN: Flush with plenty of water. Get medical attention if irritation persists. NOTE TO PHYSICIAN: May cause allergic reactions in susceptible individuals.

### Section VII - Additional Information/Hazards

This product is toxic to fish and other aquatic organisms. Do not contaminate water with this product.

# KEEP OUT OF REACH OF CHILDREN

## ABBREVIATION KEY

N/A: NOT AVAILABLE OR APPLICABLE
TLV: THRESHOLD LIMIT VALUE
STEL: SHORT TERM EXPOSURE LIMIT
TWA: TIME WEIGHTED AVG./8 HOUR WORKDAY
D.O.T.: DEPARTMENT OF TRANSPORTATION

## DISCLAIMER OF EXPRESSED AND IMPLIED WARRANTIES

Buyer assumes all risks of use, storage and handling of this material not in strict accordance with directions given herewith.