

U-MARK, Inc.

PRODUCT NAME: A 10 PAINT MARKER – A20 PAINT MARKER – A30 MEGAMARK™

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product Identifier: A 10 Paint Marker – A20 Paint Marker – A30 MEGAMARK™
 General Use: Marking on Most Surfaces
 Product Color: Black, Blue, Brown, Gray, Green, Lt.Blue, Lt.Green, Orange, Pink, Red, Violet, White, Yellow.

U-Mark, Inc., 102 Iowa Avenue, Belleville, IL 62220 USA tel. 618-235-7500
24-hour Emergency Phone: Infotrac 1-800-535-5053 (within USA & Canada),
1-352-323-3500 (International)

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS No.	% by Wt.	Exposure Limits (ppm)	
			OSHA TWA	ACGIH TWA
Propan-1-ol	71-23-8	<40	400	400

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Flammable liquid. Harmful. Keep liquid and vapors away from igniting sources, heat and static discharge. Avoid contact with eyes and skin. Avoid inhalation of mist or vapor.

POTENTIAL HEALTH EFFECTS:

INHALATION: Can cause nasal or respiratory tract irritation. Can cause Central Nervous system effects including fatigue, dizziness, headache, nausea and vomiting.
EYE CONTACT: Avoid contact with eyes. May cause severe irritation.
SKIN CONTACT: Wash thoroughly after handling.
EFFECTS OF OVEREXPOSURE: Intentional misuse of this product may be harmful or fatal. Reports have associated repeated overexposure to solvents with brain and nervous system damage.
CHRONIC: Does not contain materials listed as cancer causative agents by NTP, IARC, or OSHA.

4. FIRST AID MEASURES

INHALATION: Remove to fresh air. Call a physician in case of complaints.
EYE CONTACT: Flush opened eye with plenty of running water for fifteen minutes. Call a physician if irritation persists.
INGESTION: Do not induce vomiting. Call a physician. Wash out mouth with water if person is conscious.

5. FIRE FIGHTING MEASURES

FLAMMABLE PROPERTIES:
 Flash Point: 73°F (23° C) Method: TCC Flammable Limits: LEL 2.1% UEL 13.5 %
EXTINGUISHING MEDIA: CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam and ABC powder.
SPECIAL FIRE FIGHTING INSTRUCTIONS: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin or eyes.

6. ACCIDENTAL RELEASE MEASURES

SPILL: Eliminate all sources of ignition. Spills should be contained absorbed with liquid-binding material, and placed in a leak proof container. Liquid should be disposed of following all Federal, State and local regulations.

7. HANDLING AND STORAGE

HANDLING: Keep containers closed.

STORAGE: Store in a cool, well-ventilated area away from heat, sparks, or flames.

8. EXPOSURE CONTROL/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local and general exhaust should minimize any exposure.

RESPIRATORY PROTECTION: Use a suitable NIOSH/MSHA respiratory device in case of insufficient ventilation or if exposure limits are exceeded

SKIN PROTECTION: Not required for minor contact. Wash hands before breaks and at end of work. .

EYE PROTECTION: Wear chemical splash goggles if splashing is anticipated.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Alcohol.

BOILING POINT 96 °C (205° F)

APPEARANCE: Colored, opaque liquid.

SPECIFIC GRAVITY 0.931

IGNITION TEMPERATURE: 360° C (680° F)

10. STABILITY AND REACTIVITY

THERMAL DECOMPOSITION/CONDITIONS TO BE AVOIDED: No decomposition if used according to specifications.

DANGEROUS REACTIONS: Reacts with acids, alkalis and oxidizing agents.

DANGEROUS PRODUCTS OF DECOMPOSITION: Nitrogen Oxides, Carbon Monoxide and carbon dioxide.

11. TOXICOLOGICAL INFORMATION

71-238 propan-1-ol: LD/LC50 values Oral 1870 mg/kg (Rat); Dermal 5040 mg/kg. (Rabbit). Primary irritant effects: none known.

12. ECOLOGICAL INFORMATION

Slightly hazardous for water (self-assessment).

13. DISPOSAL CONSIDERATIONS

Disposal must be made according to Federal, State and Local laws.

14. TRANSPORT INFORMATION

IATA, IMDG, DOT: Printing Ink, 3, UN1210, PG III, Ltd. Qty.

USA GROUND Shipments: Consumer Commodity, ORM-D.

15. REGULATORY INFORMATION

EPCRA (SARA) Sec. 313 Reportable Materials: None. TSCA: All components are exempt. This product does not contain a chemical known to the State of California to cause cancer.

16. OTHER INFORMATION

HMIS and NFPA Ratings: Health 1, Flammability 3, Reactivity 0

(4= extreme, 3 high, 2 moderate, 1 slight, 0 least)

Caution!

Information presented herein has been compiled from sources considered to be dependable and is accurate and reliable to the best of our knowledge and belief but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment. This MSDS is supplied under the condition that all persons receiving it will make their own evaluation as to its suitability for their purposes before using it. Responsibility for compliance with all applicable Federal, State or local regulations concerning the use and dissemination of this MSDS and sale and use of the material described herein rests solely upon the purchaser.