

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)

24 hour Chemtrec telephone number: * (800) 424-9300

Page 1 of 3

*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 04/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1103 Gloss Red Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
VM&P Naphtha	64742-89-8	10-15	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	35-40	500 ppm.*	100 ppm.*
Monoazo Pigment	7023-61-2	1-5	Not Estab.	Not Estab.
Dianisidine Orange Pigment	6505-28-8	1-5	Not Estab.	Not Estab.

* Stoddard Solvent as Guide

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 246 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .903
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.52	VAPOR PRESSURE: 5.6 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 59.8	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 74 deg.F

OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IC

FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0

EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).

UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 04/17/2002

Product Identity: #1103 Gloss Red Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 04/17/2002

Product Identity: #1103 Gloss Red Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: * (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 4/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1111 Gloss Dark Blue Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
VM&P Naphtha	64742-89-8	10-15	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	30-35	500 ppm.*	100 ppm.*
Anti Flooding Agent	1317-65-3	1-5	15 mg/cu.m.	15 mg/cu.m.
Titanium Dioxide Pigment	13463-67-7	1-5	15 mg/cu.m.**	10 mg/cu.m.**
Copper Phthalocyanine Pigment	147-14-8	5-10	Not Estab.	Not Estab.
* Stoddard Solvent as Guide		** Total Dust		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 246 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .936
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.80	VAPOR PRESSURE: 5.6 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 56.7	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 74 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IC
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 4/17/2002

Product Identity: #1111 Gloss Dark Blue Brushing Enamel

SECTION V - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

SECTION VI - HEALTH HAZARD DATA

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

SECTION VII EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrac telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 4/17/2002

Product Identity: #1111 Gloss Dark Blue Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 4/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1114 Gloss Yellow Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
VM&P Naphtha	64742-89-8	20-25	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	25-30	500 ppm.*	100 ppm.*
Titanium Dioxide Pigment	13463-67-7	5-10	15 mg/cu.m.**	10 mg/cu.m.**
Diarylide Yellow Pigment	6358-37-8	1-5	Not Estab.	Not Estab.
* Stoddard Solvent as Guide		** Total Dust		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 246 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .934
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.78	VAPOR PRESSURE: 7.9 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 60.8	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 66 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 4/17/2002

Product Identity: #1114 Gloss Yellow Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 4/17/2002

Product Identity: #1114 Gloss Yellow Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 4/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1145 Gloss White Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
VM&P Naphtha	64742-89-8	15-20	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	20-25	500 ppm.*	100 ppm.*
Titanium Dioxide Pigment	13463-67-7	20-25	15 mg/cu.m.**	10 mg/cu.m.**
* Stoddard Solvent as Guide		** Total Dust		

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 246 to 370 deg.F	SPECIFIC GRAVITY (Water=1): 1.052
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 8.76	VAPOR PRESSURE: 8.1 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 58.6	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 65 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution! Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 4/17/2002

Product Identity: #1145 Gloss White Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? NO OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 4/17/2002

Product Identity: #1145 Gloss White Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 3/21/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

----- **SECTION I - PRODUCT IDENTIFICATION** -----

PRODUCT IDENTITY (TRADE NAME): #1146 Gloss Silver Oil Base Brushing Enamel

----- **SECTION II - HAZARDOUS INGREDIENTS** -----

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WI</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
Xylol (Xylene)	1330-20-7	5-10	100 ppm.	100 ppm.
Ethyl Benzene	100-41-4	1-5	100 ppm.	100 ppm.
Mineral Spirits	64742-88-7	40-45	500 ppm.*	100 ppm.*
Aluminum Pigment	7429-90-5	5-10	15 mg/cu.m.**	10 mg/cu.m.**
* Stoddard Solvent as Guide		** Total Dust		

----- **SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS** -----

BOILING RANGE: 272 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .928
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.73	VAPOR PRESSURE: 2.3 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 60.9	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

----- **SECTION IV - FIRE & EXPLOSION HAZARD DATA** -----

FLASH POINT (SFCC): 93 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IC
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 3/21/2002

Product Identity: #1146 Gloss Silver Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

*Ethyl Benzene component is an IARC Group 2B-possible carcinogen.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 3/21/2002

Product Identity: #1146 Gloss Silver Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number:* (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 4/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1147, #61147
Gloss Black Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
VM&P Naphtha	64742-89-8	20-25	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	30-35	500 ppm.*	100 ppm.*
Carbon Black Pigment	1333-86-4	1-5	3.5 mg/cu.m.	3.5 mg/cu.m.

* Stoddard Solvent as Guide

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 246 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .893
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.44	VAPOR PRESSURE: 7.5 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 59.9	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 67 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Flammable Liquid - CLASS IB
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 7.0
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 952-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 4/17/2002

Product Identity: #1147, #61147 Gloss Black Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Flammable.
Contain spilled product by diking. Eliminate all possible ignition sources.
Provide adequate ventilation. Equip emergency responders with appropriate
personal protection equipment. Take up spill with an absorbent material and
place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local,
state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Short term liquid or vapor contact may result in slight eye
irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Prolonged and repeated liquid contact can cause defatting and
drying of the skin which may result in skin irritation and dermatitis.

BREATHING: Vapors or mist may cause irritation to the throat, mucous membranes
and upper respiratory tract. Inhalation overexposure can lead to central
nervous system depression producing effects such as headaches, nausea,
dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into
lungs must be avoided as even small quantities in the lungs may result in
chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and
repeated inhalation exposures to light hydrocarbon vapors have shown possible
effects to the liver, kidney, and lungs. The relevance of these effects to
man is unknown.

*Carbon Black component is an IARC Group 2B-Possible carcinogen.

WARNING: This product contains a chemical known to the State of California
to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding
eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap
and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is
difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting
occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 952-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 4/17/2002

Product Identity: #1147, #61147 Gloss Black Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as flammable liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrac telephone number:* (800) 424-9300 Page 1 of 3
*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.

Date prepared: 4/17/2002

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)

SECTION I - PRODUCT IDENTIFICATION

PRODUCT IDENTITY (TRADE NAME): #1148 Thinner For Oil Base Brushing Enamel

SECTION II - HAZARDOUS INGREDIENTS

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
Xylol (Xylene)	1330-20-7	1-5	100 ppm.	100 ppm.
Ethyl Benzene	100-41-4	1	100 ppm.	100 ppm.
n-Propoxy Propanol	1569-01-3	90-95	Not Estab.	Not Estab.
Aromatic Hydrocarbon Solvent (High Boiling)	64742-94-5	1-5	100 ppm.* * Industry Recommendation	100 ppm.*

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 272 to 395 deg.F	SPECIFIC GRAVITY (Water=1): .880
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 7.33	VAPOR PRESSURE: 2 mm Hg @ 20 deg.C (calc.)
PERCENT VOLATILES (By Volume): 100	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Slower than Ethyl Ether.

SECTION IV - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (SFCC): 108 deg.F
OSHA FLAMMABILITY CLASSIFICATION: Combustible Liquid - CLASS II
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 16.9
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Combustible. Dilution with water will reduce burning rate. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).
UNUSUAL FIRE AND EXPLOSION HAZARDS: Cool fire exposed containers with water spray (fog). Vapors may travel to ignition source and flash back. This material may produce a floating fire hazard in extreme fire conditions. Overexposure to decomposition products may cause a health hazard.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 952-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 2 of 3

Date prepared: 4/17/2002

Product Identity: #1148 Thinner For Brushing Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution: Combustible. Contain spilled product by diking. Eliminate all possible ignition sources. Provide adequate ventilation. Equip emergency responders with appropriate personal protection equipment. Take up spill with an absorbent material and place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD:

Do not incinerate closed containers. Dispose of in accordance with local, state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? YES* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Vapor will cause stinging sensation, tear production and slight redness of conjunctiva. Liquid contact will produce pain and moderate conjunctivitis. Minor cornea injury expected to last a day or so may occur.

SKIN CONTACT: Contact for a few hours may result in the development of mild to moderate local redness and swelling. Sustained contact of many hours may cause more severe redness and swelling and possibly the development of local ulceration and necrosis. Can be absorbed due to prolonged contact.

BREATHING: Vapor may be irritating, causing discomfort or stinging sensations in the nose, throat and chest with nasal discharge, coughing and difficulty with breathing. Prolonged exposure to moderately high concentrations may cause dizziness, headache, faintness, weakness, incoordination of movements, speech difficulties, and loss of consciousness.

SWALLOWING: Moderately Toxic. Effects may include stinging or burning sensation in the mouth and throat and possibly swelling and irritation of the digestive tract. There may be nausea, vomiting, diarrhea, dizziness, unconsciousness and possibly liver and kidney injury.

CHRONIC OVEREXPOSURE: Repeated skin contact may cause drying of the skin and with heavy repeated skin contact there may be progressive dermatitis.

*Ethyl Benzene component is an IRAC Group 2B-possible carcinogen.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap and water thoroughly. If irritation persists, get medical attention.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET
THE TESTOR CORPORATION
440 BLACKHAWK PARK AVENUE
ROCKFORD, ILLINDIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)
24 hour Chemtrec telephone number: *(800) 424-9300

Page 3 of 3

Date prepared: 4/17/2002

Product Identity: #1148 Thinner For Brushing Enamel

----- **SECTION VIII- REACTIVITY DATA** -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- **SECTION IX SPECIAL PROTECTION INFORMATION** -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,
mists and/or dusts. If exposure may or does exceed occupational
exposure limits (Section II) use a NIOSH-approved respirator to
prevent overexposure. In accord with 29 CFR 1910.134 use either an
atmosphere-supplying respirator or an air purifying respirator with
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient
mechanical (general and/or local exhaust) ventilation to
maintain exposure below TLV(s). Heavy solvent vapors should be
removed from the lower levels of area, and all ignition sources
(non-explosion proof equipment) should be eliminated if
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.
Chemical Safety Shoes. Protective Clothing.

----- **SECTION X SPECIAL PRECAUTIONS** -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.
Store away from ignition sources in a cool well ventilated area. Handle
as combustible liquid. Do not drop container.

This product is packaged and sold as a consumer good. This information is
believed to be reliable and accurate, as of the date indicated. It is supplied
on the condition that recipients will make their own determination as to its
suitability and completeness for their purposes. The Testor Corporation assumes
no responsibility for any damages resulting from reliance on this information.