

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)  
24 hour Chemtrec telephone number:\* (800) 424-9300 Page 1 of 3  
24 hour Chemtrec International number:\* (703) 527-3887 (collect calls accepted.)  
\*TO BE USED ONLY IN THE EVENT OF CHEMICAL EMERGENCIES INVOLVING  
A SPILL, LEAK, FIRE, EXPOSURE, OR ACCIDENT INVOLVING CHEMICALS.  
Date prepared: 3/28/2012

This MSDS complies with OSHA 29 CFR 1910.1200 (The Hazard Communication Standard)  
\*\*\*\*\*

----- SECTION I - PRODUCT IDENTIFICATION -----

PRODUCT IDENTITY (TRADE NAME): #1214 (T. WM. CA) Gloss Yellow Spray Enamel  
3 oz. Aerosol Can.

----- SECTION II - HAZARDOUS INGREDIENTS -----

<u>SPECIFIC CHEMICAL NAME</u>	<u>CAS #</u>	<u>% WT</u>	<u>OSHA PEL/TWA</u>	<u>ACGIH TLV/TWA</u>
Tert-Butyl Acetate	540-88-5	1-5	200 ppm.	200 ppm.
VM&P Naphtha	64742-89-8	20-25	300 ppm.	300 ppm.
Lacquer Diluent	64742-89-8	5-10	300 ppm.	300 ppm.
Mineral Spirits	64742-88-7	10-15	500 ppm.*	100 ppm.*
Acetone	67-64-1	1-5	1000 ppm.	500 ppm.
Isopropyl Alcohol	67-63-0	1-5	400 ppm.	400 ppm.
Diacetone Alcohol	123-42-2	1-5	50 ppm.	50 ppm.
Diarylide Yellow Pigment	6358-37-8	1-5	Not Estab.	Not Estab.
Titanium Dioxide Pigment	13463-67-7	1-5	15 mg/cu.m.**	10 mg/cu.m.**
Hydrocarbon Propellant	68476-86-8	20-25	1000 ppm.	1000 ppm.
* Stoddard Solvent as Guide		** Total Dust		

----- SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS -----

BOILING RANGE: -44 to 370 deg.F	SPECIFIC GRAVITY (Water=1): .742
GALLON WEIGHT OF PRODUCT (Lbs/Gal): 6.18	VAPOR PRESSURE (Typ.): 55 PSIG @ 70 deg.F
PERCENT VOLATILES (By Volume): 87.5	VAPOR DENSITY: Heavier than air.
	EVAPORATION RATE: Faster than Ethyl Ether.

----- SECTION IV - FIRE & EXPLOSION HAZARD DATA -----

FLASH POINT (SFCC):<-44 deg.F (calc.)  
OSHA FLAMMABILITY CLASSIFICATION : Flammable Liquid - CLASS IA  
FLAMMABLE LIMITS (calc.) IN AIR: LEL 1.0 ,UEL 12.8  
EXTINGUISHING MEDIA: Alcohol resistant foam, carbon dioxide, or dry chemical.  
SPECIAL FIRE FIGHTING PROCEDURES: Caution: Extremely Flammable. A stream of water could spread fire. Avoid breathing vapors. Keep personnel removed from and upwind of fire. Wear full protective equipment: Eye/Face Shield, Body (Full Bunker Gear), Respiratory (SCBA).  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat. Cool fire exposed containers with water spray (fog). Vapors may travel considerable distance to ignition source and flash back. Product may float and be reignited at water's surface. Overexposure to decomposition products may cause a health hazard.  
Store in accordance with NFPA 30 B For Level 3 Aerosols.

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)

24 hour Chemtrec telephone number: \*(800) 424-9300

Page 2 of 3

24 hour Chemtrec International number: \*(703) 527-3887 (collect calls accepted.)

Date prepared: 3/28/2012

\*\*\*\*\*

Product Identity: #1214 Gloss Yellow Spray Enamel

----- SECTION V - SPILL OR LEAK PROCEDURES -----

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Caution:Extremely Flammable. Contain spilled product by diking. Eliminate all possible ignition sources. Provide adequate ventilation. Equip emergency responders with appropriate personal protection equipment. Take up spill with an absorbent material and place in non-leaking container. Seal container for proper disposal.

WASTE DISPOSAL METHOD: Do not incinerate closed containers.

Dispose of in accordance with local, state, and federal regulations.

----- SECTION VI - HEALTH HAZARD DATA -----

PRIMARY ROUTES OF ENTRY: Inhalation and skin contact.

CARCINOGENICITY: NTP? NO IARC? Yes\* OSHA REGULATED? NO

EFFECTS OF OVEREXPOSURE:

EYE CONTACT: Contact with liquefied gas, or gas under pressure may cause burning due to freezing effect. Short term liquid or vapor contact after propellant is expelled may result in slight eye irritation. Prolonged and repeated contact may be more irritating.

SKIN CONTACT: Contact with liquefied gas or gas under pressure may cause burning due to freezing effect. Prolonged and repeated liquid contact after propellant is expelled can cause defatting and drying of skin which may result in skin irritation and dermatitis.

BREATHING: Propellant is a simple asphyxiant and may exhibit anesthetic properties at very high concentrations. Hydrocarbon vapors or mist may cause irritation to throat, mucous membranes, and upper respiratory tract. Overexposure can lead to central nervous system depression producing effects such as headaches, nausea, dizziness and loss of consciousness.

SWALLOWING: May result in vomiting. Aspiration (breathing) of vomitus into lungs must be avoided as even small quantities in the lungs may result in chemical pneumonitis and pulmonary edema/hemorrhage.

CHRONIC OVEREXPOSURE: Reports of animal test studies involving prolonged and repeated inhalation exposures to light hydrocarbon vapors have shown possible effects to the liver, kidney, and lungs. The relevance of these effects to man is unknown. Overexposure to propellant may cause unconsciousness, coma, and death due to suffocation.

\*Titanium Dioxide component is an IARC Group 2B-Possible carcinogen.

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

----- SECTION VII EMERGENCY AND FIRST AID PROCEDURES -----

EYE CONTACT: Wash immediately with plenty of water for 15 minutes while holding eye lids open. Call a physician.

SKIN CONTACT: Remove any contaminated clothing and wash skin with soap and water thoroughly. Treat burned or frost bitten skin by immersing in lukewarm water. If skin is not burned, keep warm and stimulate with massage. Call a physician.

BREATHING: Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing. Get medical attention.

SWALLOWING: Do not induce vomiting. Call a physician at once. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs.

MATERIAL SAFETY DATA SHEET  
THE TESTOR CORPORATION  
440 BLACKHAWK PARK AVENUE  
ROCKFORD, ILLINOIS 61104

Telephone number: (815) 962-6654 (M-F 8:00 AM - 4:30 PM CDT)

24 hour Chemtrec telephone number: \*(800) 424-9300

Page 3 of 3

24 hour Chemtrec International number: \*(703) 527-3887 (collect calls accepted.)

Date prepared: 3/28/2012

\*\*\*\*\*

Product Identity: #1214 Gloss Yellow Spray Enamel

----- SECTION VIII- REACTIVITY DATA -----

STABILITY: Stable.

CONDITIONS TO AVOID: Avoid contact with heat, sparks, hot surfaces,  
open flames, and other ignition sources.

INCOMPATIBILITY (Materials to Avoid): Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and unidentified organic  
compounds may be formed during combustion.

HAZARDOUS POLYMERIZATION: Will not occur.

----- SECTION IX SPECIAL PROTECTION INFORMATION -----

RESPIRATORY PROTECTION: Avoid prolonged or repeated breathing of vapors,  
mists and/or dusts. If exposure may or does exceed occupational  
exposure limits (Section II) use a NIOSH-approved respirator to  
prevent overexposure. In accord with 29 CFR 1910.134 use either an  
atmosphere-supplying respirator or an air purifying respirator with  
appropriate chemical/mechanical filters.

VENTILATION: If the product is used in a confined area, provide sufficient  
mechanical (general and/or local exhaust) ventilation to  
maintain exposure below TLV(s). Heavy solvent vapors should be  
removed from the lower levels of area, and all ignition sources  
(non-explosion proof equipment) should be eliminated if  
flammable mixtures will be encountered.

PROTECTIVE GLOVES: Solvent resistant are recommended for prolonged contact.

EYE PROTECTION: Chemical safety splash goggles.

OTHER PROTECTIVE EQUIPMENT: Eye-Wash Station. Safety Shower. Rubber Apron.  
Chemical Safety Shoes. Protective Clothing.

----- SECTION X SPECIAL PRECAUTIONS -----

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Read all label cautions.  
Store away from ignition sources in a cool well ventilated area. Handle  
as extremely flammable liquid and gas. Do not drop container.

This product is packaged and sold as a consumer good. This information is  
believed to be reliable and accurate, as of the date indicated. It is supplied  
on the condition that recipients will make their own determination as to its  
suitability and completeness for their purposes. The Testor Corporation assumes  
no responsibility for any damages resulting from reliance on this information.