



# MATERIAL SAFETY DATA SHEET

Page 1 of 6

## PR300 - PLASTIC ROOF CEMENT

|  |  |   |                         |
|--|--|---|-------------------------|
| 1. Product And Company Identification  |  |   |                         |
| <b>Supplier</b><br>HENRY COMPANY<br>999 N. Sepulveda Blvd., Suite 800<br>El Segundo, CA 90245-2716<br><br><b>Company Contact:</b> Technical Services<br><b>Telephone Number:</b> (800) 486-1278<br><b>Web Site:</b> www.henry.com www.bakor.com            |  | <b>Manufacturer</b><br>HENRY COMPANY<br>999 N. Sepulveda Blvd., Suite 800<br>El Segundo, CA 90245-2716<br><br><b>Company Contact:</b> Technical Services<br><b>Telephone Number:</b> (800) 486-1278<br><b>Web Site:</b> www.henry.com www.bakor.com |                         |
| <b>Supplier Emergency Contacts &amp; Phone Number</b><br>CHEMTREC: (800) 424-9300<br>CHEMTREC: (703) 527-3887<br>CANUTEC: (613) 996-6666   |  | <b>Manufacturer Emergency Contacts &amp; Phone Number</b><br>CHEMTREC: (800) 424-9300<br>CHEMTREC: (703) 527-3887<br>CANUTEC: (613) 996-6666  |                         |
| <b>Issue Date:</b> 10/24/2011<br><br><b>Product Name:</b> PR300 - PLASTIC ROOF CEMENT<br><b>Product Code:</b> PR300  |  |   |                         |
| 2. Composition/Information On Ingredients  |  |   |                         |
| Ingredient Name  |  | CAS Number  | Percent Of Total Weight |
| petroleum asphalt  |  | 8052-42-4   | 30 - 50                 |
| attapulgite  |  | 12174-11-7  | 1 - 5                   |
| bentonite  |  | 1302-78-9   | 1 - 5                   |
| cellulose fiber  |  | 9004-34-6   | 5 - 10                  |
| stoddard solvent   |  | 8052-41-3   | 5 - 15                  |
| water  |  | 7732-18-5   | 20 - 40                 |
| Substances in this product have been pre-registered in accordance with the REACH Regulation - (EC) No. 1907/2006. See Section 15 for additional information. Stoddard Solvent (general CAS# 8052-41-3) is more specifically identified by CAS# 64742-88-7. |  |   |                         |
| EMERGENCY OVERVIEW   |  |   |                         |
| <b>CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.</b>  |  |   |                         |
| <b>Appearance/Odor: Black liquid, strong petroleum solvent odor</b>  |  |   |                         |
| 3. Hazards Identification  |  |   |                         |
| <b>Primary Routes(s) Of Entry</b><br>Inhalation  |  |   |                         |
| <b>Eye Hazards</b><br>May cause eye irritation (burning, tearing, redness or swelling).  |  |   |                         |
| <b>Skin Hazards</b><br>May cause skin irritation and contact dermatitis upon prolonged contact.  |  |   |                         |



PR300 - PLASTIC ROOF CEMENT

3. Hazards Identification - Continued

**Ingestion Hazards**

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

**Inhalation Hazards**

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

**Chronic/Carcinogenicity Effects**

None of the ingredients of this product comprising over 0.1% are classified as carcinogenic according to OSHA, National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) or the American Conference of Governmental Industrial Hygienists (ACGIH).

4. First Aid Measures

**Eye**

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

**Skin**

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

**Ingestion**

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

**Inhalation**

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

**Note To Physician**

Aspiration of liquid into the lungs during swallowing or vomiting can cause lung inflammation, serious lung damage and even death from chemical pneumonitis.

5. Fire Fighting Measures

**Flash Point:** 105 °F

**Flash Point Method:** Setaflash

**Lower Explosive Limit:** 0.9

**Upper Explosive Limit:** 6.0

**Fire And Explosion Hazards**

Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

**Extinguishing Media**

Chemical foam, carbon dioxide (CO2), water fog or dry chemical.

**Fire Fighting Instructions**

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations.

7. Handling And Storage

**Handling And Storage Precautions**

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near strong oxidants or strong acids. Use only with adequate ventilation.



PR300 - PLASTIC ROOF CEMENT

8. Exposure Controls/Personal Protection

**Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

**Eye/Face Protection**

Safety glasses with side shields or goggles recommended.

**Skin Protection**

Use with chemical-protective gloves to prevent skin contact.

**Respiratory Protection**

This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

**Ingredient(s) - Exposure Limits**

petroleum asphalt

ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)

bentonite

ACGIH TLV-TWA 10 mg/m3 (total dust)

ACGIH TLV-TWA 3 mg/m3 (respirable dust)

OSHA PEL-TWA 15 mg/m3 (total dust)

OSHA PEL-TWA 5 mg/m3 (respirable dust)

cellulose fiber

ACGIH TLV-TWA 10 mg/m3

stoddard solvent

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 500 ppm

9. Physical And Chemical Properties

**Appearance**

Black Liquid

**Odor**

Strong Petroleum Solvent Odor

**Chemical Type:** Mixture

**Physical State:** Liquid

**Boiling Point:** 310-400 °F

**Specific Gravity:** 1.01

**Vapor Pressure:** 2@68°F

**Vapor Density:** >1

**pH Factor:** not applicable

**Solubility:** insoluble in water

**Evaporation Rate:** <1



PR300 - PLASTIC ROOF CEMENT

10. Stability And Reactivity

**Stability:** Stable

**Hazardous Polymerization:** Will not occur

**Incompatible Materials**

Avoid contact with strong oxidizing agents and acids.

**Hazardous Decomposition Products**

Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO2).

11. Toxicological Information

**Chronic/Carcinogenicity**

None of the ingredients present in this product, at concentrations equal to or greater than 0.1%, have been determined to be carcinogenic by IARC, NTP, OSHA, or ACGIH.

**Miscellaneous Toxicological Information**

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

**Ingredient(s) - Toxicological Data**

cellulose fiber

LD50 (oral, rat): >2000 mg/kg

LC50 (rat): >5800 mg/m3 (4-hour exposure)

stoddard solvent

oral-rat LD50: >5000 mg/kg

dermal-rabbit LD50: >3000 mg/kg

inhal-rat LC50: >5500 mg/m3 (880 ppm)

inhal-rat LC50: >1300 ppm

12. Ecological Information

No specific information available.

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground or Water Domestic Voyage

Not restricted if shipped in containers <450L (119 gallons)

Restricted if shipped in containers >450L (119 gallons)

US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III

Canada UN1999, Tars liquid, 3, III

Unless departs >flash point:

Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III

IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages

IATA UN1999, Tars liquid, 3, III

**PR300 - PLASTIC ROOF CEMENT**

**DOT (Pictograms)**



15. Regulatory Information

**U.S. Regulatory Information**

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

**Ingredient(s) - State Regulations**

- petroleum asphalt
  - New Jersey - Workplace Hazard
  - Pennsylvania - Workplace Hazard
  - Massachusetts - Hazardous Substance
  - New York City - Hazardous Substance
- attapulgitite
  - California - Proposition 65
- cellulose fiber
  - Pennsylvania - Workplace Hazard
- stoddard solvent
  - New Jersey - Workplace Hazard
  - Pennsylvania - Workplace Hazard
  - Massachusetts - Hazardous Substance
  - New York City - Hazardous Substance

**Canadian Regulatory Information**

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic

**Ingredient(s) - Canadian Regulatory Information**

- stoddard solvent
  - WHMIS - Ingredient Disclosure List


**European Union (EU) Regulatory Information**

REACH Pre-registration Information:

| Substance (CAS#)              | Reference Number                 |
|-------------------------------|----------------------------------|
| Asphalt (8052-42-4)           | 05-2114366982-36-0000            |
| Stoddard Solvent (64742-88-7) | 05-2114367025-53-0000            |
| Bentonite (1302-78-9)         | 05-2114501887-43-0000            |
| Cellulose (9004-34-6)         | 05-2114366989-22-0000            |
| Attapulgitite (12174-11-7)    | NA-Naturally Occurring Substance |
| Water (7732-18-5)             | NA-Naturally Occurring Substance |

### PR300 - PLASTIC ROOF CEMENT

**WHMIS - Canada (Pictograms)**



| NFPA                | HMIS  |        |   |              |   |            |   |                     |  |
|---------------------|---|--------|---|--------------|---|------------|---|---------------------|--|
|                     | <table border="1"> <tr> <td>HEALTH</td> <td>1</td> </tr> <tr> <td>FLAMMABILITY</td> <td>2</td> </tr> <tr> <td>REACTIVITY</td> <td>0</td> </tr> <tr> <td>PERSONAL PROTECTION</td> <td></td> </tr> </table> | HEALTH | 1 | FLAMMABILITY | 2 | REACTIVITY | 0 | PERSONAL PROTECTION |  |
| HEALTH              | 1   |        |   |              |   |            |   |                     |  |
| FLAMMABILITY        | 2   |        |   |              |   |            |   |                     |  |
| REACTIVITY          | 0   |        |   |              |   |            |   |                     |  |
| PERSONAL PROTECTION |   |        |   |              |   |            |   |                     |  |

16. Other Information

**Revision/Preparer Information**

This MSDS Supersedes A Previous MSDS Dated: 11/24/2008

**Disclaimer**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).