



MATERIAL SAFETY DATA SHEET

Page 1 of 7

HE208 - WET PATCH ROOF CEMENT

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 07/01/2008 Product Name: HE208 - WET PATCH ROOF CEMENT Product Code: HE208	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
1,2,4-trimethylbenzene	95-63-6		0.5 - 5
1,3,5-trimethylbenzene	108-67-8		0.5 - 5
aromatic petroleum distillates	64742-95-6		0 - 5
petroleum asphalt	8052-42-4		30 - 60
attapulgite	12174-11-7		7 - 13
calcium carbonate	1317-65-3		15 - 40
cellulose fiber	9004-34-6		3 - 10
amine salt	28701-67-9		0.5 - 5
silica, quartz	14808-60-7		1 - 5
stoddard solvent	8052-41-3		10 - 30
xylene	1330-20-7		0.1 - 1

EMERGENCY OVERVIEW	
CAUTION! Combustible Liquid. Central nervous system depressant. Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.	
Appearance/Odor: Black paste, strong petroleum solvent odor	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).



HE208 - WET PATCH ROOF CEMENT

3. Hazards Identification - Continued

Skin Hazards

May cause skin irritation and contact dermatitis upon prolonged contact. Dermal sensitization may occur from repeated and prolonged exposures.

Ingestion Hazards

May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.

Inhalation Hazards

Exposure to vapors may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.

Chronic/Carcinogenicity Effects

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

4. First Aid Measures

Eye

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

Skin

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

Ingestion

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.

Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.

5. Fire Fighting Measures

Flash Point: 120 °F

Flash Point Method: Setaflash

Lower Explosive Limit: 0.9

Upper Explosive Limit: 6.0

Fire And Explosion Hazards

Combustible Liquid. Vapors are heavier than air and may spread long distances and ignite. Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.

Extinguishing Media

Chemical foam, carbon dioxide (CO2), or dry chemical. Do not use direct stream of water.

Fire Fighting Instructions

Firefighters should wear self-contained breathing apparatus and full protective gear.

6. Accidental Release Measures

Collect and dispose in accordance with applicable regulations.

7. Handling And Storage

Handling And Storage Precautions

Keep away from ignition sources. Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near heat, sparks, flame, strong oxidants or strong acids. Use only with adequate ventilation. Ground all




HE208 - WET PATCH ROOF CEMENT

7. Handling And Storage - Continued
Handling And Storage Precautions - Continued containers.
8. Exposure Controls/Personal Protection
Engineering Controls Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.
Eye/Face Protection Safety glasses with side shields or goggles recommended.
Skin Protection Use with chemical-protective gloves to prevent skin contact.
Respiratory Protection The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.
Occupational Exposure Limits for individual ingredients (if available) are listed below.
Ingredient(s) - Exposure Limits
1,2,4-trimethylbenzene ACGIH TLV-TWA 25 ppm
1,3,5-trimethylbenzene ACGIH TLV-TWA 25 ppm
aromatic petroleum distillates OSHA PEL-TWA 500 ppm
petroleum asphalt ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol)
calcium carbonate OSHA PEL-TWA 15 mg/m3 (total dust) OSHA PEL-TWA 5 mg/m3 (respirable dust)
cellulose fiber ACGIH TLV-TWA 10 mg/m3
silica, quartz ACGIH TLV-TWA 0.025 mg/m3 OSHA PEL-TWA 30mg/m3 / (%SiO2+2) (total dust) OSHA PEL-TWA 10 mg/m3/ (%SiO2+2) (respirable dust)
stoddard solvent ACGIH TLV-TWA 100 ppm OSHA PEL-TWA 500 ppm
xylene ACGIH TLV-STEL 150 ppm ACGIH TLV-TWA 100 ppm OSHA PEL-TWA 100 ppm
9. Physical And Chemical Properties
Appearance Black Paste

HE208 - WET PATCH ROOF CEMENT

<p>9. Physical And Chemical Properties - Continued</p> <p>Odor Strong Petroleum Solvent Odor</p> <p>Chemical Type: Mixture Physical State: Solid Boiling Point: 310-400 °F Specific Gravity: 1.14 Percent Volatiles: 22 Vapor Pressure: 2@68°F Vapor Density: >1 pH Factor: not applicable Solubility: insoluble in water Evaporation Rate: <1</p>
<p>10. Stability And Reactivity</p> <p>Stability: Stable Hazardous Polymerization: Will not occur</p> <p>Incompatible Materials Avoid contact with strong oxidizing agents and acids.</p> <p>Hazardous Decomposition Products Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO2).</p>
<p>11. Toxicological Information</p> <p>Chronic/Carcinogenicity IARC has concluded that the following chemicals in this product are carcinogenic to humans (Group 1): silica, quartz ACGIH has designated the following chemicals in this product as suspected human carcinogens (A2): silica, quartz NTP has listed the following chemicals in this product as known human carcinogens: silica, quartz</p> <p>Risk of cancer depends on duration and level of exposure to this product as a dust.</p> <p>Miscellaneous Toxicological Information Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.</p> <p>Ingredient(s) - Toxicological Data 1,2,4-trimethylbenzene LD50 (oral, rat): 5000 mg/kg LC50 (rat): 18 g/m3 (4-hour exposure) 1,3,5-trimethylbenzene Lethal dose (oral, rat): 23 g/kg lethal to 7 of 10 test animals LC50 (rat): 24 g/m3 (4-hour exposure) aromatic petroleum distillates LD50 (oral, rat): 2900 mg/kg calcium carbonate oral-rat LD50: 6450 mg/kg cellulose fiber LD50 (oral, rat): >2000 mg/kg LC50 (rat): >5800 mg/m3 (4-hour exposure) silica, quartz iv-rat LD50: 500 mg/kg bw/Quartz (10-200 um)</p>

HE208 - WET PATCH ROOF CEMENT

11. Toxicological Information - Continued
<p><u>Ingredient(s) - Toxicological Data - Continued</u> stoddard solvent oral-rat LD50: >5000 mg/kg dermal-rabbit LD50: >3000 mg/kg inhal-rat LC50: >5500 mg/m3 (880 ppm) inhal-rat LC50: >1300 ppm xylene LD50 (oral, rat): 5400 mg/kg LD50 (dermal, rabbit): 12180 mg/kg LC50 (rat): 6350 ppm (4-hour exposure)</p>
12. Ecological Information
No specific information available.
13. Disposal Considerations
Dispose in accordance with applicable federal, state and local government regulations.
14. Transport Information
<p>Ground or Water Domestic Voyage</p> <p>Not restricted if shipped in containers <450L (119 gallons) Restricted if shipped in containers >450L (119 gallons)</p> <p>US NA1993, Combustible liquid, n.o.s., (Petroleum Distillates mixture), Combustible liquid, III</p> <p>Canada UN1999, Tars liquid, 3, III</p> <p>Unless departs >flash point:</p> <p>Both UN3256, Elevated Temperature liquid, flammable, n.o.s., (Petroleum Distillates mixture), 3, III</p> <p>IMDG IMDG Code 2.3.2.5 - exempted from marking, labeling & testing of packages</p> <p>IATA UN1999, Tars liquid, 3, III</p>
<u>DOT (Pictograms)</u>

15. Regulatory Information
<p><u>U.S. Regulatory Information</u> Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.</p> <p><u>Ingredient(s) - U.S. Regulatory Information</u> 1,2,4-trimethylbenzene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical xylene SARA Title III - Section 313 Form "R"/TRI Reportable Chemical</p>



HE208 - WET PATCH ROOF CEMENT

15. Regulatory Information - Continued

Ingredient(s) - State Regulations

1,2,4-trimethylbenzene

- New Jersey - Workplace Hazard
- New Jersey - Environmental Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

1,3,5-trimethylbenzene

- New Jersey - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

aromatic petroleum distillates

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard

petroleum asphalt

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

attapulgit

- California - Proposition 65

calcium carbonate

- Pennsylvania - Workplace Hazard

cellulose fiber

- Pennsylvania - Workplace Hazard

silica, quartz

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- California - Proposition 65
- Massachusetts - Hazardous Substance

stoddard solvent

- New Jersey - Workplace Hazard
- Pennsylvania - Workplace Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

xylene

- New Jersey - Workplace Hazard
- New Jersey - Environmental Hazard
- New Jersey - Special Hazard
- Pennsylvania - Workplace Hazard
- Pennsylvania - Environmental Hazard
- Massachusetts - Hazardous Substance
- New York City - Hazardous Substance

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: B3 - Combustible Liquid, D2A - Very Toxic

Ingredient(s) - Canadian Regulatory Information

1,2,4-trimethylbenzene

- WHMIS - Ingredient Disclosure List

1,3,5-trimethylbenzene

HE208 - WET PATCH ROOF CEMENT

15. Regulatory Information - Continued


Ingredient(s) - Canadian Regulatory Information - Continued

WHMIS - Ingredient Disclosure List
 silica, quartz
 WHMIS - Ingredient Disclosure List
 stoddard solvent
 WHMIS - Ingredient Disclosure List

WHMIS - Canada (Pictograms)



NFPA



HMIS

HEALTH	2
FLAMMABILITY	2
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 03/04/2008

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).