

M A T E R I A L   S A F E T Y   D A T A   S H E E T

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : DIAMOND HARD SANDY BEIGE  
 IDENTIFICATION NUMBER: 8-1503 DATE PRINTED: 03/10/09  
 PRODUCT USE/CLASS : Non-Flat Hi Gloss Arch.Coating

SUPPLIER: Yenkin-Majestic Paint Corporation  
 1920 Leonard Avenue  
 Columbus, OH 43219 USA  
 MANUFACTURER: Yenkin-Majestic Paint Corporation  
 1920 Leonard Avenue  
 Columbus, OH 43219 USA

CHEMTREC 18004249300/ 17035273887  
 24 Hr. Emergency Hotline  
 CHEMTREC 18004249300/ 17035273887  
 24 Hr. Emergency Hotline

PREPARER: Tony L. Montjoy, PHONE: 614-253-8511, PREPARE DATE: 03/10/09

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER	WT/WT % LESS THAN
01	TITANIUM DIOXIDE	13463-67-7	20.0 %
02	DIETHYLENE GLYCOL MONOBUTYL ETHER (HAP)	112-34-5	5.0 %

ITEM	EXPOSURE LIMITS				COMPANY TLV-TWA	SKIN
	ACGIH		OSHA			
TLV-TWA	TLV-STEL	PEL-TWA	PEL-CEILING	TLV-TWA		
01	5 mg/m3	N.E.	5 mg/m3	N.E.	N.E.	NO
02	N.E.	N.E.	N.E.	N.E.	35 ppm	YES

(See Section 16 for abbreviation legend)

SECTION 3 - HAZARDS IDENTIFICATION

\*\*\* EMERGENCY OVERVIEW \*\*\*: Harmful if swallowed. Vapors irritating to eyes and respiratory tract.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Severely irritating. If not removed promptly, will injure eye tissue, which may result in permanent damage.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin irritation. Allergic reactions are possible.

(Continued on Page 2)

SECTION 3 - HAZARDS IDENTIFICATION
------------------------------------

EFFECTS OF OVEREXPOSURE - INHALATION: No hazard in normal residential usage. When incorporated in the liquid paint, pigments or extenders pose a minimal risk of exposure. Sanding or abrading the dried paint film increases the risk of exposure. Proper respiratory protection MUST be worn when sanding or abrading surfaces painted with this product.

EFFECTS OF OVEREXPOSURE - INGESTION: This material may be irritating to the mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information.

PRIMARY ROUTE(S) OF ENTRY: SKIN ABSORPTION INHALATION

SECTION 4 - FIRST AID MEASURES
--------------------------------

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

FIRST AID - SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: No Information.

FIRST AID - INGESTION: If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5 - FIRE FIGHTING MEASURES
------------------------------------

FLASH POINT: 200 F  
(SETAFLASH CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 0.8 %  
UPPER EXPLOSIVE LIMIT: 24.6 %

AUTOIGNITION TEMPERATURE: N.A.

EXTINGUISHING MEDIA: ALCOHOL FOAM CO2 DRY CHEMICAL FOAM WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information.

SPECIAL FIREFIGHTING PROCEDURES: Containers can build up pressure if exposed to heat (fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Water runoff can cause environmental damage. Dike and collect water used to fight fire.

(Continued on Page 3)

SECTION 6 - ACCIDENTAL RELEASE MEASURES
---

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE
----------------------------------

HANDLING: Wash thoroughly after handling.

STORAGE: Keep from freezing. Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION
---

ENGINEERING CONTROLS: Good general ventilation should be sufficient to control airborne levels. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

RESPIRATORY PROTECTION: No Information.

SKIN PROTECTION: No Information.

EYE PROTECTION: No Information.

OTHER PROTECTIVE EQUIPMENT: No Information.

HYGIENIC PRACTICES: Wash hands before eating. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES
--

BOILING RANGE	: 212 - 475 F	VAPOR DENSITY	: Is heavier than air
ODOR	: Ammonia Like	ODOR THRESHOLD	: N.D.
APPEARANCE	: Brown Liquid	EVAPORATION RATE	: Is slower than Ether
SOLUBILITY IN H2O	: Soluble		
FREEZE POINT	: 10° F	SPECIFIC GRAVITY	: 1.1704
VAPOR PRESSURE	: N.D.	pH @ 100.0 %	: 9.15
PHYSICAL STATE	: LIQUID	VISCOSITY	: 88-94 KU
COEFFICIENT OF WATER/OIL DISTRIBUTION: N.D.			

(See Section 16 for abbreviation legend)

(Continued on Page 4)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: High temperatures or High humidity.

INCOMPATIBILITY: Strong acids and/or Strong bases.

HAZARDOUS DECOMPOSITION PRODUCTS: May produce fumes when heated to decomposition, as in welding or fire. Fumes may contain: Carbon Monoxide, Carbon Dioxide and various other hydrocarbons.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

PRODUCT/COMPONENT TOXICOLOGICAL INFORMATION: No Information.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dried material may be disposed of in landfill. If liquid is present, add absorbent (such as Cat Litter) and stir until there is no free liquid remaining and dispose of properly.

SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME:

DOT TECHNICAL NAME:

DOT HAZARD CLASS: NOT REGULATED

HAZARD SUBCLASS:

DOT UN/NA NUMBER:

PACKING GROUP:

RESP. GUIDE PAGE:

EXCEPTIONS: No Information.

(Continued on Page 5)

## SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT % IS LESS THAN
DIETHYLENE GLYCOL MONOBUTYL ETHER (HAP)	112-34-5	5.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
No information is available.	

U.S. STATE REGULATIONS: AS FOLLOWS -

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product:

----- CHEMICAL NAME -----	CAS NUMBER
H2O	7732-18-5

MODIFIED ACRYLIC COPOLYMER	MIXTURE
----------------------------	---------

SUNFLOWER/CORN OIL ESTER W/PROPYLENE GLYCOL	Mixture
---	---------

(Continued on Page 6)

## SECTION 15 - REGULATORY INFORMATION

## PENNSYLVANIA RIGHT-TO-KNOW:

The following non-hazardous ingredients are present in the product at greater than 3%:

----- CHEMICAL NAME -----	CAS NUMBER
H2O	7732-18-5

MODIFIED ACRYLIC COPOLYMER	MIXTURE
----------------------------	---------

## CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer:

----- CHEMICAL NAME -----	CAS NUMBER
No chemicals containing Proposition 65-listed carcinogens exist in this product.	

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
No chemicals containing Proposition 65-listed reproductive toxins exist in this product.	

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
DIBUTYL PHTHALATE (HAP)	84-74-2
DIBUTYL PHTHALATE (HAP)	

CARBON BLACK	1333-86-4
CARBON BLACK	

## INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

(Continued on Page 7)

SECTION 16 - OTHER INFORMATION
--------------------------------

HMIS RATINGS - HEALTH: 1      FLAMMABILITY: 1      REACTIVITY: 0

PREVIOUS MSDS REVISION DATE: 03/10/09

VOLATILE ORGANIC COMPOUNDS (VOCS): 1.16 lbs/gal,    138 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

---

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.

---

<END OF MSDS>