```
DATE: MARCH, 2007
                          MATERIAL SAFETY DATA SHEETS
              FOR COATINGS, RESINS AND RELATED MATERIALS
**************************
                          SECTION I
**************************
Manufacturers Name SHEFFIELD BRONZE PAINT CORP Emergency Phone No.
Street Address 17814 S.WATERLOO RD. (216) 481-8330
City, State, Zip CLEVELAND, OHIO 44119 TRANSPORTATION EMERGENCIES: CHEMTREC
                                 (800) 424-9300 CONTINENTAL U.S.
PRODUCT NUMBER: 11-965
                                  (202) 483-7616 (COLLECT) FROM
PRODUCT NAME: LAMP BLACK - 11 TINTSALL
                                             ALASKA & HAWAII
PRODUCT CLASS: UNIVERSAL TINTING COLOR
*****************************
                SECTION II - HAZARDOUS INGREDIENTS
****************************
INGREDIENT
                * CAS NUMBER*PERCENT* TLV
                                              VAPOR PRESSURE
                       ******************************
           : 13333-86-4 : 5.4 :
: LAMP BLACK
: CALCIUM CARBONATE : 471-34-1 : 54.3 :
NON-IONIC BIODEGRADABLE
               68154-97-2 : 19.9 :
                                   :
**DIACETONE ALCOHOL 123-42-2 : 19.9 : 50 : 240 : 1.8 : .9
: ADDITIVES : LESS THAN : 1.0 :
*ALL INGREDIENTS ARE LISTED ON THE EPA/TSCA INVENTORY
*SARA TITLE 111 SECTION 313 REPORTING FOR SUPERFUND AMENDMENTS
*****************************
                SECTION III - PHYSICAL DATA
****************************
                        Vapor Density: HEAVIER THAN AIR
Boiling Range: 337dgr F
Evaporation Rate: SLOWER than Butyl Acetate V.O.C.: 2.57#/GALLON; 310 GRAMS/LI
Percent Volatile by VOLUME: 31.6
                          Weight per GALLON: 12.9 LBS.
Percent Volatile by WEIGHT: 20.1
*****************************
                SECTION IV - FIRE and EXPLOSION DATA
*****************************
DOT CATEGORY: COMBUSTIBLE
                             FLASH POINT (SETA) - 138 Degrees F.
EXTINGUISHING MEDIA: CO-2, DRY CHEMICAL, FOAM, FOG
UNUSUAL FIRE AND EXPLOSION HAZARDS: HANDLE AS A COMBUSTIBLE LIQUID
SPECIAL FIRE FIGHTING PROCEDURES: NONE
****************************
                SECTION V - HEALTH HAZARD DATA
*****************************
THRESHOLD LIMIT VALUE: 50ppm OR 240MG/M3 TWA (8 hr. Workday)
EFFECTS OF OVEREXPOSURE: BREATHING VAPOR IS IRRITATING TO EYES, NOSE AND
THROAT. CONTACT WITH EYES AND SKIN CAN CAUSE DRYNESS & IRRITATION
```

THRESHOLD LIMIT VALUE: 50ppm OR 240MG/M3 TWA (8 hr. Workday)
EFFECTS OF OVEREXPOSURE: BREATHING VAPOR IS IRRITATING TO EYES, NOSE AND
THROAT. CONTACT WITH EYES AND SKIN CAN CAUSE DRYNESS & IRRITATION
EMERGENCY AND FIRST AID PROCEDURES: Flush eyes immediately with large amounts of water. Wash skin areas with water. Remove to fresh air. IF INGESTED: If patient is conscious can swallow, give two glasses of water (16 oz.), induce vomiting as directed by medical personnel. Do not induce vomiting or give anything by mouth to an unconscious or convulsing person.
Get medical attention immediately.

```
SECTION VI - REACTIVITY DATA
****************************
CONDITIONS AND MATERIALS TO AVOID: HIGH HEAT, FLAME, STRONG OXIDIZING AGENTS,
  NITRIC ACID AND STRONG BASES.
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON MONOXIDE AND/OR CARBON DIOXIDE AND
  UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.
HAZARDOUS POLYMERIZATION: WILL NOT OCCUR
******************************
                  SECTION VII - SPILL OR LEAK PROCEDURES
**************************
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:
Remove all sources of ignition, ventilate, avoid breathing vapors.
Remove with INERT ABSORBENT(sand, earth, sawdust etc.) WEAR SUITABLE PROTECTIVE
  EQUIPMENT.
WASTE DISPOSAL METHOD:
DISPOSE IN ACCORDANCE WITH FEDERAL, STATE, and LOCAL REGULATIONS. AT VERY LOW
  CONCENTRATIONS IN WATER, THIS PRODUCT IS BIODEGRADABLE IN A BIOLOGICAL WASTE
  WATER TREATMENT PLANT.
******************************
                  SECTION VIII - SPECIAL PROTECTION INFORMATION
   RESPIRATORY PROTECTION: NIOSH APPROVED AIR-PURIFYING RESPIRATOR FOR ORGANIC
VAPORS. IN AREAS OF HIGH VAPOR CONCENTRATION, USE AN ATMOSPHERE SUPPLYING
BREATHING APPARATUS.
            VENTILATION: MECHANICAL VENTILATION EQUAL TO OUTDOORS
       PROTECTIVE GLOVES: RECOMMENDED FOR PROLONGED OR REPEATED CONTACT
         EYE PROTECTION: SAFETY GLASSES WITH UNPERFORATED SIDESHIELDS
OTHER PROTECTIVE EQUIPMENT: SAFETY SHOWERS, CHEMICAL RESISTANT CLOTHING
*******************************
                  SECTION IX - SPECIAL PRECAUTIONS
******************************
PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: HANDLE AS A COMBUSTIBLE
LIQUID. STORE IN A COOL DRY PLACE. USE ADEQUATE VENTILATION EQUIVALENT TO THE
OUTDOORS
OTHER PRECAUTIONS:
                KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME. SMOKING SHOULD
BE PROHIBITED WHERE USED. KEEP OUT OF REACH OF CHILDREN.
*****************************
                  SECTION X - HAZARDOUS MATERIAL IDENTIFICATION
********************************
LISTED IN THIS SECTION IS NPCA-HMIS CLASSIFICATION FOR THIS PRODUCT
                   2 :
                :
                    2
Flammability
                :
                     0
Reactivity
Personal Protection: B
***********************************
Information above pertains to this product as currently formulated. Addition of
other additives may alter the Composition and Hazards. WE MAKE NO WARRANTIES,
EXPRESS OR IMPLIED AND ASSUME NO LIABILITY WITH USE OF THIS INFORMATION.
```

: PAGE TWO - LAMP BLACK - 11 TINTSALL #11-965