

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: 65AR FLOWABLE SILICONE WINDSHIELD & GLASS SEALER 1.5 FO
Item No: 81730
Product Type: Silicone elastomer

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	>60	Not listed	Not listed
POLYDIMETHYLSILOXANE 63148-62-9	<20	Not listed	Not listed
VINYL OXIMINOSILANE 2224-33-1	<10	Not listed	Not listed
2-BUTANONE OXIME 96-29-7	0.5-2.0	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. May irritate respiratory system upon frequent or prolonged use. May irritate lips, gums, tongue, mouth, nose and throat. When this product is exposed to moisture, butanone oxime may be formed.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Butanone oxime produced during curing is toxic and irritates eyes, nose and throat. Overexposure to the silane may cause coma and respiratory failure.
Aggravated Medical Condition: None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. Obtain medical attention.
Skin Contact: Wipe off material with paper towel or cloth. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. If skin irritation persists, call a physician.
Eye Contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde
Unusual Fire/Explosion Hazards: None.
Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Wipe or scrape up spill material. Maintain good ventilation for large spills. Place scrap material in a well-ventilated area and allow to cure to rubber. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store away from water or moisture.
Handling: Avoid contact with skin and eyes. Do not wear contact lenses. Use in a well ventilated area. Do not take internally. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.
Comments: When heated to temperatures above 300 degrees F. in the presence of air, this product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Safe handling conditions may be maintained by keeping vapor concentrations below the OSHA permissible limit for formaldehyde

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Clear viscous liquid
Odor: Mild
Boiling Point: Not applicable, polymeric material
pH: Does not apply
Solubility in Water: Polymerized
Specific Gravity: 1.03
VOC(Wt.%): <3%
Vapor Pressure: <5 mm Hg @ 80°F
Vapor Density (Air=1): 3.0
Evaporation Rate: n/d

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Polymerized by contact with moisture, Strong oxidizers, Acids, Iron
Conditions to Avoid: Exposure to moisture
Hazardous Products of Combustion: Oxides of carbon, Oxides of nitrogen, Methyl ethyl ketone, possibly methyl ethyl ketoxime, Silica fume, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Not regulated
Hazard Class: None
UN/ID Number: None

IATA (Air)

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG (Vessel)

Proper Shipping Name: Not regulated
Hazard Class: None

Product Name: 65AR FLOWABLE SILICONE WINDSHIELD &
GLASS SEALER 1.5 FO

Item No. 81730

UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: March 12, 2013

Revision Number: 10