



## Material Safety Data Sheet

### 1. PRODUCT AND COMPANY IDENTIFICATION

#### Product Identification

**Product ID:** 044.0021833  
Product Name: VAL AR EN GL BRN  
Product Use: Paint product.  
Print date: 02/Aug/2009  
Revision Date: 02/Aug/2009

#### Company Identification

The Valspar Corporation - Architectural Coatings Division  
1191 Wheeling Road  
Wheeling, IL 60090

**Manufacturer's Phone:** 1-847-520-8580

**24-Hour Medical Emergency Phone:** 1-888-345-5732

### 2. HAZARDS IDENTIFICATION

#### Primary Routes of Exposure:

Inhalation  
Ingestion  
Skin absorption

#### Eye Contact:

- Moderate eye irritation

#### Skin Contact:

- Causes skin irritation.
- May cause defatting of the skin.
- Dermatitis
- Can be absorbed through skin.
- May cause sensitization by skin contact.

#### Ingestion:

- Irritation of the mouth, throat, and stomach.
- Aspiration hazard if swallowed - can enter lungs and cause damage.

#### Inhalation:

- Causes respiratory tract irritation.
- Harmful by inhalation.
- May cause sensitization by inhalation.

**Target Organ and Other Health Effects:**

- Kidney injury may occur.
- Liver injury may occur.
- Causes headache, drowsiness or other effects to the central nervous system.

**This product contains ingredients that may contribute to the following potential chronic health effects:**

- Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.
- Prolonged exposure over TLV may produce pneumoconiosis.
- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).
- Chronic exposure may cause permanent damage of health.
- Possible sensitization.

**Carcinogens:**

- Possible cancer hazard. Contains material which may cause cancer based on animal data.
- Cancer hazard. Contains material which can cause cancer.

**3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS**

Ingredient Name CAS-No.	Approx. Weight %	Chemical Name
MINERAL SPIRITS 64742-47-8	25 - 30	Petroleum distillates, hydrotreated light
PROPRIETARY INERT	10 - 15	PROPRIETARY INERT
MINERAL SPIRITS 64742-47-8	5 - 10	Petroleum distillates, hydrotreated light
PROPRIETARY INERT	1 - 5	PROPRIETARY INERT
XYLENE 1330-20-7	1 - 5	Xylenes (o-, m-, p- isomers)
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	Carbon black
ETHYLBENZENE 100-41-4	.1 - 1	Ethyl benzene
COBALT OCTOATE 136-52-7	.1 - 1	Hexanoic acid, 2-ethyl-, cobalt(2+) salt
SILICA 14808-60-7	.1 - 1	QUARTZ (SiO <sub>2</sub> )

If this section is blank there are no hazardous components per OSHA guidelines.

**4. FIRST AID MEASURES****Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water. Remove any contact lenses and open eyes wide apart.

**Skin Contact:**

Remove contaminated clothing and shoes. Wash off immediately with plenty of water for at least 15 minutes. Get medical attention, if symptoms develop or persist.

**Ingestion:**

Rinse mouth with water. Give one or two glasses of water. Only induce vomiting at the instruction of medical personnel. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs, keep head lower than hips to prevent aspiration. Get medical attention immediately.

**Inhalation:**

Move injured person into fresh air and keep person calm under observation. Get medical attention immediately. For breathing difficulties, oxygen may be necessary. If breathing stops, provide artificial respiration.

**Medical conditions aggravated by exposure:**

Any respiratory or skin condition.

**5. FIRE FIGHTING MEASURES**

Flash point (Fahrenheit):	101°F (38°C)
Lower explosive limit:	1 %
Upper explosive limit:	6 %
Autoignition temperature:	not determined -°F (°C)
Sensitivity to impact:	no
Sensitivity to static discharge:	Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.
Hazardous combustion products:	See Section 10.

**Unusual fire and explosion hazards:**

Contaminated rags, wipes, saw dust, etc., may catch fire spontaneously. Store waste under water in closed metal containers or in approved self-closing containers designed to prevent spontaneous combustion until disposed of in compliance with applicable regulations. Oxidizing Material

**Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

**Fire fighting procedures:**

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

**6. ACCIDENTAL RELEASE MEASURES****Action to be taken if material is released or spilled:**

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Remove all sources of ignition. Soak up with inert absorbent material. Use only non-sparking tools. Avoid contact with eyes.

**7. HANDLING AND STORAGE****Precautions to be taken in handling and storage:**

Keep away from heat, sparks and open flame. - No smoking. Keep container closed when not in use. Do not store above 120 degrees F. (49 degrees C). Based on flash point and vapor pressure, suitable storage should be provided in accordance with OSHA regulation 1910.106, Ontario OH&S regulation 851 section 22. Empty containers may contain product residue, including flammable or explosive vapors. Do not cut, puncture or weld on or near container. All label warnings must be observed until the container has been commercially cleaned or reconditioned. If the product is used near or above the flashpoint, an ignition hazard may be present. Activities, uses, or operations which liberate vapor (such as mixing or free fall of liquids) may also present an ignition hazard. Please ensure containers and other interconnected equipment are properly bonded and grounded at all times.

**8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS****Personal Protective Equipment****Eye and face protection:**

Chemical goggles, also wear a face shield if splashing hazard exists.

**Skin protection:**

Appropriate chemical resistant gloves should be worn.

**Other Personal Protection Data:**

To prevent skin contact wear protective clothing covering all exposed areas.

**Respiratory protection:**

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

**Ventilation**

Use only in well-ventilated areas. Ensure adequate ventilation, especially in confined areas. Ovens used for curing should contain a fresh air purge to prevent vapours from accumulating and creating a possible explosive mixture. Where the product is used in a hazardous classified area, use explosion-proof electrical/ventilating/lighting/equipment.

**Exposure Guidelines**

**OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
PROPRIETARY INERT	10 - 15	5 mg/m <sup>3</sup> Respirable fraction. 15 mg/m <sup>3</sup> Total dust.		
PROPRIETARY INERT	1 - 5	5 mg/m <sup>3</sup> Respirable fraction. 15 mg/m <sup>3</sup> Total dust. Respirable fraction. Listed. Total dust. Listed.		
XYLENE 1330-20-7	1 - 5	435 mg/m <sup>3</sup> 100 ppm		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup>		
ETHYLBENZENE 100-41-4	.1 - 1	435 mg/m <sup>3</sup> 100 ppm		
SILICA 14808-60-7	.1 - 1	Respirable. Listed. Total dust. Listed.		

**ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
PROPRIETARY INERT	10 - 15	10 mg/m <sup>3</sup> Inhalable particles. 3 mg/m <sup>3</sup> Respirable particles.			
PROPRIETARY INERT	1 - 5	2 mg/m <sup>3</sup> Respirable fraction. The value is for particulate matter containing no asbestos and <1% crystalline silica.			
XYLENE 1330-20-7	1 - 5	100 ppm	150 ppm		
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	3.5 mg/m <sup>3</sup>			

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
ETHYLBENZENE 100-41-4	.1 - 1	100 ppm	125 ppm		
COBALT OCTOATE 136-52-7	.1 - 1	0.02 mg/m <sup>3</sup> Co			
SILICA 14808-60-7	.1 - 1	0.05 mg/m <sup>3</sup> Respirable fraction.			

## 9. PHYSICAL PROPERTIES

Odor:	Normal for this product type.
Physical State:	liquid
pH:	not determined
Vapor pressure:	90.2255639 mmHg @ 77°F (25°C)
Vapor density (air = 1.0):	5.1
Boiling point:	not determined
Solubility in water:	not determined
Coefficient of water/oil distribution:	not determined
Density (lbs per US gallon):	8.81
Specific Gravity:	1.06
Evaporation rate (butyl acetate = 1.0):	0.6
Flash point (Fahrenheit):	101°F (38°C)
Lower explosive limit:	1 %
Upper explosive limit:	6 %
Autoignition temperature:	not determined -°F (°C)

## 10. STABILITY AND REACTIVITY

Stability:	Stable under normal conditions.
Conditions to Avoid:	Heat.
Incompatibility:	Strong oxidizing agents
Hazardous Polymerization:	None anticipated.
Hazardous Decomposition Products:	Carbon monoxide and carbon dioxide. Metal oxide fumes. Nitrogen compounds.

**Sensitivity to static discharge:** Can be sensitive to static discharge hazards. Please see bonding and grounding information in Section 7.

## 11. TOXICOLOGICAL INFORMATION

Ingredient Name CAS-No.	Approx. Weight %	NIOSH - Selected LD50s and LC50s
XYLENE 1330-20-7	1 - 5	Inhalation LC50 Rat : 5000 ppm/4H Oral LD50 Rat : 4300 mg/kg Dermal LD50 Rabbit : >1700 mg/kg
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1	ORAL LD50 (RAT): >10,000 MG/KG, INTRAVAVENOUS LD50 (RAT): 120 MG/KG
ETHYLBENZENE 100-41-4	.1 - 1	Oral LD50 Rat : 3500 mg/kg Dermal LD50 Rabbit : 17800 uL/kg

**Mutagens/Teratogens/Carcinogens:**

Possible cancer hazard. Contains material which may cause cancer based on animal data. Cancer hazard. Contains material which can cause cancer.

Contains ethylbenzene, which has been determined by NTP to be an animal carcinogen with no known relevance to humans. IARC has classified ethylbenzene as possibly carcinogenic to humans (2b) on the basis of sufficient evidence of carcinogenicity in laboratory animals but inadequate evidence of cancer in humans. IARC has classified carbon black as possibly carcinogenic to humans (Group 2B). Contains crystalline silica. The IARC has determined that crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystalline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dust or respirable particles in spray mist. The International Agency For Research On Cancer (IARC) has determined that Cobalt and Cobalt Compounds are substances that are possibly carcinogenic to humans (IARC group 2B).

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
ETHYLBENZENE 100-41-4	.1 - 1		Listed: June 11, 2004 Carcinogenic.
SILICA 14808-60-7	.1 - 1		Listed: October 1, 1988 Carcinogenic.

Ingredient Name CAS-No.	Approx. Weight %	IARC Group 1 - Human Evidence	IARC Group 2A - Limited Human Data	IARC Group 2B - Sufficient Animal Data
C.I. PIGMENT BLACK 7 1333-86-4	.1 - 1			Monograph 65, 1996
ETHYLBENZENE 100-41-4	.1 - 1			Monograph 77, 2000
COBALT OCTOATE 136-52-7	.1 - 1			YES
SILICA 14808-60-7	.1 - 1	Monograph 68, 1997; (inhaled in the form of quartz or cristobalite from occupational sources)		

Ingredient Name CAS-No.	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens	NTP Evidence of Carcinogenicity
ETHYLBENZENE 100-41-4	.1 - 1			male rat-clear evidence; female rat-some evidence; male mice- some evidence; female mice-some evidence
SILICA 14808-60-7	.1 - 1	Known carcinogen.		

Ingredient Name CAS-No.	Approx. Weight %	OSHA Select Carcinogens	OSHA Possible Select Carcinogens	ACGIH Carcinogens
ETHYLBENZENE 100-41-4	.1 - 1			Group A3 Confirmed animal carcinogen with unknown relevance to humans.
COBALT OCTOATE 136-52-7	.1 - 1			Group A3 Confirmed animal carcinogen with unknown relevance to humans.
SILICA 14808-60-7	.1 - 1			Group A2 Suspected human carcinogen.

## 12. ECOLOGICAL DATA

No information on ecology is available.

## 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

## 14. TRANSPORTATION INFORMATION

### U.S. Department of Transportation

Proper Shipping Name: PAINT  
Hazard Class: COMBUSTIBLE LIQUID  
UN ID Number: UN1263  
Packing Group: III

### U.S. Highway & Rail Shipments

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

### Reportable Quantity Description:

### International Air Transport Association (IATA):

Proper Shipping Name: Paint  
Hazard Class: 3  
UN ID Number: UN1263  
Packing Group: III

### International Maritime Organization (IMO):

Proper Shipping Name: PAINT  
Hazard Class: 3  
IMO UN/ID Number: UN1263  
Packing Group: III

## 15. REGULATORY INFORMATION

### U.S. FEDERAL REGULATIONS:

Ingredient Name CAS-No.	Approx. Weight %	SARA 302	SARA 313	CERCLA RQ in lbs.
XYLENE 1330-20-7	1 - 5		form R reporting required for 1.0% de minimis concentration	100
ETHYLBENZENE 100-41-4	.1 - 1		form R reporting required for 1.0% de minimis concentration	1000
COBALT OCTOATE 136-52-7	.1 - 1		YES	1

### SARA 311/312 Hazard Class:

Acute: yes  
Chronic: yes  
Flammability: yes  
Reactivity: no  
Sudden Pressure: no

## U.S. STATE REGULATIONS:

### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

### Pennsylvania Right To Know:

MINERAL SPIRITS	64742-47-8
PROPRIETARY INERT	Trade Secret
PROPRIETARY INERT	Trade Secret
MINERAL SPIRITS	64742-47-8
XYLENE	1330-20-7

### Additional Non-Hazardous Materials

C.I. PIGMENT RED 101	1332-37-2
PROPRIETARY RESIN	Trade Secret
PROPRIETARY RESIN	Trade Secret
PROPRIETARY RESIN	Trade Secret

### California Proposition 65:

WARNING: This product contains chemicals known to the State of California to cause cancer.

### Rule 66 status of product

Not photochemically reactive.

## INTERNATIONAL REGULATIONS - Chemical Inventories

### US TSCA Inventory:

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

### Canada Domestic Substances List:

All components of this product are listed on the Domestic Substances List.

## 16. OTHER INFORMATION

### HMIS Codes

Health:	2*
Flammability:	2
Reactivity:	1
PPE:	X - See Section 8 for Personal Protective Equipment (PPE).

### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.



**Disclaimer:**

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

**Preparation Information:**

Prepared By: Regulatory Affairs Department  
Print date: 02/Aug/2009  
Revision Date: 02/Aug/2009