

ITW Permatex
 10 Columbus Blvd.
 Hartford, CT 06106 USA
 Telephone: 1-87-Permatex
 (877) 376-2839
 Emergency: 800-255-3924 (ChemTel)
 International Emergency: 00+ 1+ 813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: GASKET REMOVER 4 OZ.
Item No: 80645
Product Type: Cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	Weight%	ACGIH; TLV-TWA	OSHA PEL
WATER 7732-18-5	50-70	Not listed	Not listed
DIMETHYL GLUTARATE 1119-40-0	10-30	Not listed	Not listed
DIMETHYL ADIPATE 627-93-0	<5	Not listed	Not listed
MINERAL OIL 8042-47-5	<5	5 mg/m ³	Not listed
DIMETHYL SUCCINATE 106-65-0	<5	Not listed	Not listed
NITROGEN 7727-37-9	<5	Not listed	Not listed

3. HAZARDS IDENTIFICATION

Toxicity: May irritate respiratory system upon frequent or prolonged use. May irritate the eyes.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: May cause redness to eyes and irritation to nasal passages.
Aggravated Medical Condition: None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, do not induce vomiting - seek medical advice. Never give anything by mouth to an unconscious person.
Inhalation: Move to fresh air in case of accidental inhalation of vapours. If symptoms persist, call a physician.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F PMCC
Recommended Extinguishing Media: Carbon dioxide, Dry chemical, Foam
Special Fire-Fighting Procedures: ***Warning: This container is pressurized with nitrogen. Do not remove rubber plug. Use water spray to cool exposed containers. Oxides of carbon
Hazardous Products of Combustion: Oxides of carbon
Unusual Fire/Explosion Hazards: Contents under pressure. Heated cans may burst. Do not puncture or incinerate container.
Lower Explosive Limit: n/d
Upper Explosive Limit: n/d

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage: Store away from heat, sparks or open flame. Do not store at temperatures above 100°F (38°C).
Handling: Do not puncture or incinerate container. Avoid contact with skin and eyes. Wash hands before eating and smoking.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.
Ventilation: Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.
Respiratory Protection: An approved organic vapor respirator should be worn when exposures are expected to exceed the applicable limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White viscous lotion
Odor: Ester
Boiling Point: n/d
pH: 5.9-7.1
Solubility in Water: Soluble
Specific Gravity: 1.07
VOC(Wt.%): 6%
Vapor Pressure: n/d
Vapor Density (Air=1): >1
Evaporation Rate: <1 (butyl acetate = 1)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur
Incompatibilities: Strong oxidizers, acids, alkalines
Conditions to Avoid: Keep away from heat, sparks and open flame. - No smoking, Freezing
Hazardous Products of Combustion: Oxides of carbon

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

U.S. Department of Transportation - DOT - 49 CFR (Ground)

DOT Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN/ID Number: UN 1950

IATA (Air)

Proper Shipping Name: Consumer Commodity
Class or Division: Class 9
UN/ID Number: ID 8000

IMDG (Vessel)

Proper Shipping Name: Aerosols, Limited Quantity
Hazard Class: Class 2.2
UN Number: UN 1950

Marine Pollutant: None

Product Name: GASKET REMOVER 4 OZ.

Item No. 80645

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

(NFPA is a registered trademark of the National Fire Protection Association)

(HMIS is a registered trademark of the National Paint and Coatings Association)

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: ITW Permatex 10 Columbus Blvd. Hartford, CT USA 06106
Telephone No.: 1-87-Permatex (877) 376-2839

Revision Date: August 02, 2013

Revision Number: 6