

May be used to comply with  
OSHA's Hazard Communication Standard  
29 CFR 1910.1200. Standard must be  
consulted for specific requirements.

**U.S. Department of Labor**  
Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form-Approved  
OMB No. 1218.0072

IDENTITY (As Used on Label and List)		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
PASTE WAX #3206					
<b>Section I</b>					
Manufacturer's Name : <b>Lundmark Wax Company, Inc.</b>		Emergency Telephone Number : <b>(630) 628-1199</b>			
Address (Number, Street, City, and Zip Code): <b>350 S. LaLonde Ave.</b>		Telephone Number for Information: <b>(630) 628-1199</b>			
<b>Addison, IL 60101</b>		Date Prepared: <b>April 15, 2001</b>			
		Signature of preparer (optional) :			
<b>Section II-Hazardous Ingredients/Identity Information</b>					
Hazardous Components (specific Chemical Identity; Common Name(s))		OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (optional)
Petroleum Distillate	Cas. No.	8030-30-6	500ppm		< 85%
Turpentine	Cas. No.	8006-64-2	100ppm		< 25%
<b>Section III-Physical/Chemical Characteristics</b>					
Boiling Point: <b>Over</b>		<b>300° F</b>	Specific Gravity (H <sub>2</sub> O =1):		<b>.75 - .80</b>
Vapor Pressure (mm Hg.):		<b>Unknown</b>	Melting Point:		<b>N.A.</b>
Vapor Density (AIR =1):		<b>Unknown</b>	Evaporation Rate (Butyl Acetate = 1)		<b>Unknown</b>
Solubility in Water: <b>Nil</b>					
Appearance and Odor: <b>White, firm paste, solvent odor.</b>					
<b>Section IV--Fire and Explosion Hazard Data</b>					
Flash Point (Method Used): <b>104° F</b>		Flammable Limits: <b>N.A.</b>		<b>LEL: N.A.</b>	<b>UEL: N.A.</b>
Extinguishing Media: <b>Water fog, dry chemical, CO<sub>2</sub>.</b>					
Special Fire Fighting Procedures: <b>None</b>					
Unusual Fire and Explosion Hazards: <b>None</b>					
(Reproduce locally)					
OSHA 174, Sept 1985					

<b>Section V--Reactivity Data</b>			<b>PASTE WAX #3206</b>		
Stability:	Unstable		Conditions to Avoid:		
	Stable	X			
Incompatibility (Materials to Avoid): <b>None</b>					
Hazardous Decomposition or By-products: <b>On burning, carbon monoxide and dioxide</b>					
Hazardous Polymerization	May Occur		Conditions to Avoid:		
	Will Not Occur	X			
<b>Section VI--Health Hazard Data</b>					
Route(s) of Entry:	Inhalation?	X	Skin?	X	Ingestion?
					X
Health Hazards (Acute and Chronic): <b>May cause burns to eyes. Harmful if swallowed. Vapors harmful.</b>					
Carcinogenicity: <b>None</b>	NIP?	IARC Monographs?		OSHA Regulated?	
Signs and Symptoms of Exposure: <b>Eyes and skin: burning. Vapors: Headache, nausea and dizziness.</b>					
<b>Ingestion: Gastro intestinal irritation.</b>					
Medical Conditions Generally Aggravated by Exposure:		<b>Unknown</b>			
Emergency and First Aid Procedures: <b>Eyes and skin - Flush with water for 10 minutes. Vapors: Remove to fresh air.</b>					
<b>Ingestion: Do not induce vomiting. CALL PHYSICIAN.</b>					
<b>Section VII--Precautions for Safe Handling and Use</b>					
Steps to be Taken in Case Material is Released or Spilled: <b>Absorb on clay or rags.</b>					
Waste Disposal Method: <b>Sanitary land fill. Check with Federal, Local and State regulations.</b>					
Precautions to be Taken in Handling and Storing: <b>Keep away from spark or flame.</b>					
Other Precautions: <b>Keep out of the reach of children.</b>					
<b>Section VIII--Control Measures</b>					
Respiratory Protection (Specific Type): <b>None</b>					
Ventilation:	Local Exhaust: <b>Optional</b>		Special: <b>N.A.</b>		
N.A.	Mechanical (General): <b>N.A.</b>		Other: <b>N.A.</b>		
Protective Gloves: <b>Required</b>			Eye Protection: <b>Required</b>		
Other Protective Clothing or Equipment: <b>None</b>					
Work/Hygienic Practices: <b>Observe personal hygiene.</b>					
<div style="display: flex; justify-content: space-between;"> <span><b>Page 2</b></span> <span><small>*U.S.G.P.O. 1986-491529/15775</small></span> </div>					