

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC
MSDS Number: P73184115
Version Number
Revision Date: OCT-13-2005
Page Number: 1

SECTION I - PRODUCT AND COMPANY INFORMATION

Product Name: PL (R) MIRROR MASTIC Adhesive low VOC
HMIS Hazard Rating: Health: 1 Fire: 3 Reactivity: 0 PPE: B

Company Identification: HENKEL CONSUMER ADHESIVES
7405 PRODUCTION DRIVE
MENTOR OH 44060

Contact (24 hour): Customer Affairs (800)321-0253
Information phone/Fax: (440) 255-8900 / (440) 974-8358
CHEMTREC Emergency (24 hour): (703) 527-3887 (International)
(800) 424-9300
in Canada CANUTEC 613-996-6666

Product Class ADHESIVE
Trade Name PL BRAND
Product Code See above

SECTION II - INGREDIENT AND HAZARD INFORMATION

Table with 4 columns: Hazardous Ingredient Name, CAS Number, Percent, TSCA. Rows include ACETONE, Light Aliphatic Naphtha, Methyl Acetate, Toluene, and n-Hexane.

Ingredient Notes:
Remaining ingredients are not considered OSHA hazardous.

SECTION III - PHYSICAL AND CHEMICAL PROPERTIES

Form: Non-sag mastic
Appearance/Color: Tan
Odor: Sharp
Solubility (in water): insol. in water
pH Value, +/- .3: Not Applicable
Boiling Range: 150.°F - 250.°F (65.56°C - 121.11°C)

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC
MSDS Number: P73184115
Version Number
Revision Date: OCT-13-2005
Page Number: 2

Vapor Pressure (mmHg): 155.@ 68.F (20.C)
Evaporation Rate: 5.5 times Faster than n-Butyl Acetate
Vapor Density: Heavier than air
% Volatile, Weight 28.%
% Volatile, Volume 40.%
Specific Gravity: 1.16537
VOC (less H2O or exempt) < 195 gr/L, 13%

NOTE:

\*BOIL RANGE, EVAP RATE, VAPOR DENSITY AND PRESSURE FOR SOLVENT ONLY!

SECTION IV - FIRE FIGHTING MEASURES (Flash,UEL,LEL for solvent only)

Flammability Class I B
Flash Range: 0.F - 45.F (-17.78C - 7.22C)
Tag Closed Cup
Explosive Range (LEL/UEL): 1.%
6.5%

EXTINGUISHING MEDIA:

Carbon Dioxide---Dry Chemical---Foam
Use water fog to cool material in vicinity of fire.

SPECIAL FIRE-FIGHTING PROCEDURES:

Use self-contained breathing apparatus with full facepiece
operated in pressure demand with full protective equipment.

UNUSUAL FIRE AND EXPLOSION HAZARDS:

Any closed container may rupture when exposed to extreme heat.
Solvent vapors are heavier than air and travel along the ground.
Vapors given off are flammable and may be ignited in air explosively.

SECTION V - HEALTH HAZARD DATA

ROUTES OF ENTRY:

ENTRY THROUGH... Inhalation and skin most likely

CARCINOGENICITY...

NTP? N/E | IARC Monographs? N/E | OSHA? NO

EFFECTS OF OVEREXPOSURE

Eyes: Can cause irritation, redness, tearing and blurred vision.
Skin: Prolonged or repeated contact can cause moderate
irritation, defatting, and dermatitis.
Inhalation: May cause nose or throat irritation. High concen-
trations may cause acute central nervous system depression
characterized by headaches, dizziness, nausea and confusion.
Ingestion: Can cause gastrointestinal irritation, nausea,

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC  
MSDS Number: P73184115  
Version Number  
Revision Date: OCT-13-2005  
Page Number: 3

-----  
vomiting and diarrhea.

**FIRST AID MEASURES**

Eyes: Flush eyes gently with water for at least 15 minutes  
lifting eyelids occasionally; get prompt medical attention  
Skin: Wash thoroughly with soap and water; apply a mild skin cream.  
Remove contaminated clothing.  
Inhalation: Move affected person to fresh air; if breathing is  
difficult, administer oxygen; if breathing has stopped,  
give artificial respiration. Get medical attention.  
Ingestion: DO NOT INDUCE VOMITING! Get immediate medical attention.

**CHRONIC HAZARDS**

NOTICE: Reports have associated repeated and prolonged  
occupational overexposure to solvents with permanent brain,  
nervous system, liver or kidney damage or may cause cardiac  
arrhythmia. INTENTIONAL misuse of this product by  
deliberately inhaling its vapors may be harmful or fatal.  
N-HEXANE can cause peripheral neuropathy (arm and leg damage) and  
central nervous system damage. Prolonged and repeated exposure has  
been suggested as a cause of the following effects in lab animals:  
liver and reproductive abnormalities, kidney, spleen, lung or eye damage  
May aggravate pre-existing disorders of these organs in humans.  
May be harmful if absorbed through skin.  
Repeated overexposure to TOLUENE may cause liver damage.  
Toluene has been found to cause Kidney, Lung and Spleen damage  
in laboratory animals.

-----  
**SECTION VI - STABILITY AND REACTIVITY**

Stability: This product is stable  
Hazardous Polymerization: Hazardous polymerization will not occur

**INCOMPATIBILITY:**

Keep away from strong oxidizing agents.

**CONDITIONS TO AVOID:**

Keep away from heat, spark, open flames and any ignition source.

**HAZARDOUS DECOMPOSITION PRODUCTS:**

Will produce fumes and smoke containing carbon monoxide and  
dioxide under fire conditions.

-----  
**SECTION VII - ACCIDENTAL RELEASE AND DISPOSAL MEASURES:**

**STEPS TO BE TAKEN IN CASE OF SPILL:**

Eliminate all ignition sources. Ventilate confined areas.  
(Open windows and doors). Wear appropriate protective clothing.  
Cover with absorbent. Scoop into sealable safety container.

**WASTE DISPOSAL METHOD:**

Dispose of following local, state, and federal regulations.  
-----

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC  
MSDS Number: P73184115  
Version Number  
Revision Date: OCT-13-2005  
Page Number: 4

SECTION VIII - EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

|                         | ACGIH TLV  | ACGIH TLV-C | ACGIH STEL  | OSHA STEL   | OSHA PEL   |
|-------------------------|------------|-------------|-------------|-------------|------------|
| ACETONE                 | 750.00 PPM | N/est       | 1000.00 PPM | 1000.00 PPM | 750.00 PPM |
| Light Aliphatic Naphtha | 300.00 PPM | N/est       | N/est       | 500.00 PPM  | 300.00 PPM |
| Methyl Acetate          | 200.00 PPM | N/est       | 250.00 PPM  | 250.00 PPM  | 200.00 PPM |
| Toluene                 | 50.00 PPM  | N/est       | 150.00 PPM  | 150.00 PPM  | 100.00 PPM |
| n-Hexane                | 50.00 PPM  | N/est       | N/est       | N/est       | 50.00 PPM  |

RESPIRATORY PROTECTION:

If TLV of the product is exceeded, a NIOSH/MSHA jointly approved air supply respirator is advised in the absence of proper ventilation. OSHA regulations also permit the use of other types of NIOSH/MSHA respirators under specified conditions. (See your safety equipment supplier for more information)

VENTILATION:

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV. Ventilate during application and curing of this product.

PROTECTIVE CLOTHING:

Rubber gloves should be worn where skin contact is likely. Wear impervious clothing and shoes.

EYE PROTECTION:

Chemical goggles or safety glasses should be worn.

HANDLING AND STORAGE PRECAUTIONS:

Keep away from heat, spark and flame.  
Keep out of reach of children.  
Keep container closed while not in use.  
Do not cut or burn recepticals that have contained a solvent based product. Do not reuse this container.  
Use only in a well ventilated area.

N/A=NOT APPLICABLE N/AV=NOT AVAILABLE N/E, N/est=NOT ESTABLISHED

**MATERIAL SAFETY DATA SHEET**

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC  
MSDS Number: P73184115  
Version Number  
Revision Date: OCT-13-2005  
Page Number: 5

---

**SECTION IX - TRANSPORT INFORMATION: (not all sizes available)**

**GROUND TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e.10oz, 28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D  
Shipping Document: CONSUMER COMMODITY, ORM-D  
ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE  
Classification: CLASS 3  
DOT Label Required: Flammable Liquid, UN1133, Class 3  
Shipping Document: ADHESIVE,3,UN1133, PGIII,  
for 50 gal. drum use PG II  
ERG Code: 128

**AIR TRANSPORT (DOT) - DOMESTIC**

Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: ORM-D  
DOT Label Required: ORM-D-AIR  
Shipping Document: Consumer Commodity, ORM-D  
ERG Code: 171

Units GREATER than 5L i.e. 5 gal. pail

Proper Shipping Name: ADHESIVE  
Classification: Class 3  
DOT Label Required: Flammable Liquid, UN 1133, Class 3  
Shipping Document: ADHESIVE, 3, UN1133, PG III,  
for 50 gal. drum use PG II  
ERG Code: 128

**AIR TRANSPORT ( IATA ) - INTERNATIONAL**

Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1 gal.

Proper Shipping Name: CONSUMER COMMODITY  
Classification: class 9  
Label Required: ID8000  
Shipping Document: Consumer Commodity,9, ID8000  
ERG Code: 9L

Units GREATER than 5L i.e. 5 Gal. pail, 50 gal.drums

Proper Shipping Name: ADHESIVE  
Classification: Class 3

---

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC
MSDS Number: P73184115
Version Number
Revision Date: OCT-13-2005
Page Number: 6

Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII, for 50 gal. drum use PG II
ERG Code: 3L
MARINE - OCEAN TRANSPORT ( IMDG )
Units less than 5L (1.3 gallons liquid) i.e.10oz,28oz, 1 gal.

Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN1133, Class 3, Ltd. Qty. (on Ocean container only, not required on cartons)
Shipping Document: ADHESIVE,3, UN1133, PG III, LTD.QTY.
EMS Code: F-E, S-D

Units GREATER than 5L i.e. 5 gal. pail, 50 gal drum
Proper Shipping Name: ADHESIVE
Classification: Class 3
Label Required: Flammable Liquid, UN 1133, Class 3
Shipping Document: ADHESIVE, 3, UN1133, PGIII, for 50 gal. drum use PG II
EMS Code: F-E, S-D

SECTION X - REGULATORY INFORMATION:

SARA TITLE III SECTION 313:

This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR 372:

Table with 3 columns: Ingredient Name, CAS Number, Percent. Rows include Toluene (108-88-3, < 5.0) and n-Hexane (110-54-3, < 5.0).

-PROP 65 (TERATOGEN)

WARNING: This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

Table with 3 columns: Ingredient Name, CAS Number, Percent. Row includes Toluene (108-88-3, < 5.0).

The following ingredients are registered for TSCA 12B

Table with 3 columns: Ingredient Name, CAS Number, Percent. Rows include ACETONE (67-64-1, 5 - 10) and n-Hexane (110-54-3, < 5.0).

MATERIAL SAFETY DATA SHEET

MSDS Name: PL (R) MIRROR MASTIC Adhesive low VOC

MSDS Number: P73184115

Version Number

Revision Date: OCT-13-2005

Page Number: 7

---

SARA Section 311/312 Hazard Categories met: Fire Hazard,  
Immediate (Acute) and Delayed (Chronic) Health Hazards.

Chemical ingredients are listed on the TSCA inventory.

**DISCLAIMER:**

The information contained herein is based on data available as of the date of preparation of this MSDS and which we believe to be reliable. However, no warranty is expressed or implied regarding the accuracy of the data. We shall not be responsible for the use of this information, or of any product, method, apparatus mentioned, and user must make his own investigation to determine the suitability of the information or products for his particular purpose, for the protection of the environment, and the health & safety of the users of this material.