Material Safety Data Sheet

Section 1 General Information

Manufacturer:

Zinsser Company, Inc. 173 Belmont Drive Somerset, NJ 08875 (732) 469-8100

Emergency Telephone: Chemtrec (800) 424-9300 Date: June 12, 2007

Product Name: Bulls Eye Oil Base

Codes: 03540 03541 03544

Section 2 Hazardous Ingredients

Hazardous Component	CAS#	OSHA <u>PEL</u>	ACGIH <u>TLV</u>
Petroleum Distillate	64742-95-6	500 ppm	N/E
Limestone	1317-65-3	$15 \text{ mg/m}^3 * (5 \text{ mg/m}^3 **)$	$10 \text{ mg/m}^{3 \text{ t}} (3 \text{ mg/m}^{3 **})$
Kaolin	1332-58-7	$15 \text{ mg/m}^3 * (5 \text{ mg/m}^3 **)$	2 mg/m^3
Magnesite	546-93-0	$15 \text{ mg/m}^3 * (5 \text{ mg/m}^3 **)$	N/E
Mineral Spirits	8052-41-3	500 ppm	100 ppm
Quartz	14808-60-7	$0.1 \text{ mg/m}^3 **$	$0.1 \text{ mg/m}^3 **$
Talc	14807-96-6	20 mppcf	$2 \text{ mg/m}^3 *$
Titanium dioxide	13463-67-7	$15 \text{ Mg/m}^3 *$	10 Mg/m^3

Section 3 Hazard Identification

Emergency Overview: This material is a solvent-based primer-sealer used to coat wood and other surfaces before painting. This material is a white flowable liquid with a flash point of 104° F.

Primary Potential Routes of Exposure:

Inhalation Skin Contact Eye Contact

Potential Acute Health Effects:

Eye: May cause eye irritation.

Skin: May cause skin irritation.

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: Bullseye Oil Base MSDS (6-12-07)

Ingestion: Although not considered a significant route of exposure, ingestion may cause gastrointestinal irritation if ingested.

Inhalation: Inhalation of vapors may cause respiratory tract irritation.

(See also Sections 4, 8, and 11for related information)

Section 4 First Aid Measures

Eye contact: Flush eyes with water for at least 15 minutes. Get medical attention.

Skin contact: Wash with soap and water. If irritation persists, get medical attention.

Ingestion: If swallowed, Do Not induce vomiting. Contact a physician, poison control center, or hospital emergency room immediately.

Inhalation: If exposed to excessive levels of vapor, remove person to fresh air. Seek medical attention if cough or other symptoms develop.

Section 5 Fire Fighting Measures

Flash Point [method]: 104° F (40° C)

Extinguishing Media: Water, Dry Chemical, CO₂, Foam.

Protection of Firefighters: As in any fire, wear self-contained breathing apparatus in pressure demand mode and full protective gear.

Section 6 Accidental Release Measures

Clean Up Methods: Eliminate all ignition sources. Keep unnecessary people away. Dike and contain spill with inert material (sand, earth, etc.). Transfer liquid to containers for recovery or disposal, or absorb with absorbent materials and place into containers for disposal. Keep spill out of sewer and open bodies of water. Floors may be slippery; care should be exercised to avoid falls during clean up operations.

(See also Section 8 for information on Exposure Controls and Personal Protective Equipment)

Section 7 Handling and Storage

Handling: Avoid contact with eyes, skin, and clothing.

Storage: Store in a cool, dry place away from excessive heat or open flame. Do not store near oxidizers. Keep from freezing.

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

Section 8 Exposure Controls / Personal Protection

Engineering Controls: Use in well-ventilated areas. If necessary, use mechanical local exhaust ventilation or general room dilution ventilation to reduce vapor concentrations.

Personal Protective Equipment (PPE):

Eye Protection: Prevent eye contact. Wear chemical splash goggles or similar eye protection if the potential exists for eye contact.

Skin Protection: Avoid unnecessary skin contact. It is recommended that rubber gloves be worn to prevent skin contact. Depending on conditions of use additional protective equipment may be necessary such as face-shield, apron or coveralls.

Respiratory Protection: None required for normally expected use conditions. If exposure limits are exceeded or if irritation is experienced, appropriate NIOSH approved respiratory protection with organic vapor cartridges should be worn.

General Hygiene Practices: Wash after handling material. Prevent Eye contact. Avoid prolonged skin and inhalation contact. Wash thoroughly before handling food, cosmetics, or before smoking.

Section 9 Physical Data

Appearance: White, flowable liquid **Odor**: Petroleum hydrocarbon odor

Physical State: Liquid **pH**: N/A (non-aqueous system)

Boiling Point: > 212° F **Melting Point**: N/A

Vapor Pressure: N/D Vapor Density (Air =1): N/D

Odor Threshold: N/D Viscosity: 85 KU

Solubility in Water: Not soluble **Specific Gravity** (water = 1): 1.5

VOC Content: $\leq 350 \text{ g/l}$

Section 10 Stability and Reactivity

Stability: This material is stable.

Hazardous Polymerization: Not expected or known to occur.

Hazardous Decomposition Products: None known.

Conditions to Avoid: Keep away from heat and open flames.

Incompatibility: None Known.

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: Bullseye Oil Base MSDS (6-12-07)

Section 11 Toxicological Information

Carcinogenicity: The following ingredients are present at greater than 0.1% and are classified by IARC, NTP, or OSHA as carcinogenic:

Ingredient
quartzCAS #
14808-60-7IARTC
YesNTP
YesOSHA
No

Section 12 Ecological Information

Chemical Fate and Effects: No data available.

Section 13 Disposal Considerations

RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of ignitability (D001). The transportation, storage, treatment, and disposal of this waste must be conducted in compliance with 40 CFR 262, 263, 264, 268, and 270. Disposal can only occur in properly permitted facilities. Check state and local regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this MSDS incomplete, inaccurate, or otherwise inappropriate.

Section 14 Transportation Information

Regulated by DOT: No (Combustible liquid)

Section 15 Regulatory Information

CERCLA:

The Comprehensive Environmental Response Compensation and Liability Act of 1980 (CERCLA) requires notification to the National Response Center for releases of quantities of Hazardous Substances equal to or greater than the reportable quantities (RQs) in 40 CFR 302.4 (for CERCLA 102).

Components present in this product at a level which could require reporting under the statute are:

<u>Chemical Name</u> <u>CAS#</u> <u>Maximum Concentration (Wt. %)</u>

None N/A N/A

SARA Title III, section 311/312:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires emergency planning based on Threshold Planning Quantities (TPQs) and release reporting based on Reportable Quantities (RQs) in 40 CFR 355 (used for SARA 302, 304, 311 and 312).

Components present in this product at a level which could require reporting under the statute are:

Chemical Name CAS# Maximum Concentration (Wt. %)

None N/A N/A

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: Bullseye Oil Base MSDS (6-12-07)

Page 4 of 6 pages.

SARA Title III, section 313:

The Superfund Amendments and Reauthorization Act of 1986 (SARA) Title III requires submission of annual reports of release of toxic chemicals that appear in 40 CFR 372 (for SARA 313).

Components present in this product at a level which could require reporting under the statute are:

Chemical Name CAS# Maximum Concentration (Wt. %)

None N/A N/A

TSCA:

The components of this mixture are listed in the Toxic Substance Control Act Inventory of Chemical Substances.

This product contains the following chemicals which require export notification under section 12(b) of the TSCA regulation:

<u>Chemical Name</u> <u>CAS#</u> <u>TSCA Section</u>

Methyl ethyl ketoxime 96-29-7 Sec. 4

Section 16 Other Information

Legend: N/A: Not Applicable N/D: Not Determined

PPM: Parts Per MillionPEL: Permissible Exposure LimitPPB: Parts Per BillionTLV: Threshold Limit Value

TWA: Time Weighted Average mg/m³: Milligrams per cubic Meter

mppcf: Million particles per cubic foot of air.

ACGIH: American Conference of Governmental Industrial Hygienists

DOT: United States Department of Transportation

OSHA: Occupational Safety and Health Administration (US Dept. of Labor)

RCRA: Resource Conservation and recovery Act

SARA: Superfund Amendment and Reauthorization Act

TSCA: Toxic Substance Control Act FHSA: Federal Hazardous Substance Act

Prepared By: Zinsser Health and Safety Manager, Regulatory Compliance Dept.

173 Belmont Drive Somerset, NJ 08875 (732) 469-8100

Disclaimer: Zinsser Company, Inc. believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials and make no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used

N/A: Not Applicable N/D: Not Determined N/E: Not Established N/R: Not Required Est.: Estimated

MSDS Code: Bullseye Oil Base MSDS (6-12-07)



MSDS Code: Bullseye Oil Base MSDS (6-12-07)

Page 6 of 6 pages.