

# **Material Safety Data Sheet**

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identification** 

Product ID: 157.0057033

Product Name: OPT INT LTX SGL NEUBS

Product Use: Paint product.
Print date: 30/May/2013
Revision Date: 22/May/2013

**Company Identification** 

The Valspar Corporation - Architectural Coatings Division 1191 Wheeling Road Wheeling, IL 60090

**Manufacturer's Phone:** 1-847-520-8580

**24-Hour Medical Emergency** 1-888-345-5732

Phone:

## 2. HAZARDS IDENTIFICATION

# **Primary Routes of Exposure:**

Inhalation Ingestion Skin absorption

# **Eye Contact:**

None known.

#### **Skin Contact:**

None known.

# Ingestion:

None known.

## Inhalation:

None known.

# **Target Organ and Other Health Effects:**

Kidney injury may occur.

## This product contains ingredients that may contribute to the following potential chronic health effects:

- Chronic exposure may cause permanent damage of health.
- Prolonged exposure to respirable crystalline quartz silica may cause delayed chronic injury (silicosis).

# Carcinogens:

· Cancer hazard. Contains material which can cause cancer.

# 3. COMPOSITION / INFORMATION ON HAZARDOUS INGREDIENTS

9	Approx. Weight %	Chemical Name
SILICA	.1 - 1	QUARTZ (Si02)
14808-60-7		

If this section is blank there are no hazardous components per OSHA guidelines.

# 4. FIRST AID MEASURES

# **Eye Contact:**

Get medical attention, if symptoms develop or persist. Immediately flush eye(s) with plenty of water.

#### **Skin Contact:**

Wash off with plenty of water.

#### Ingestion:

Get medical attention if symptoms occur

#### Inhalation:

Get medical attention, if symptoms develop or persist. Move to fresh air.

#### Medical conditions aggravated by exposure:

Any respiratory or skin condition.

# 5. FIRE FIGHTING MEASURES

Flash point (Fahrenheit): 205 Flash point (Celsius): 96

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

Sensitivity to impact:

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

Hazardous combustion products: See Section 10.

#### Unusual fire and explosion hazards:

None known.

# **Extinguishing media:**

Carbon dioxide, dry chemical, foam and/or water fog.

# Fire fighting procedures:

Firefighters should be equipped with self-contained breathing apparatus and turn out gear. Keep containers and surroundings cool with water spray.

## 6. ACCIDENTAL RELEASE MEASURES

# 6. ACCIDENTAL RELEASE MEASURES

## Action to be taken if material is released or spilled:

Ventilate the area. Avoid breathing dust or vapor. Use self-containing breathing apparatus or airmask for large spills in a confined area. Wipe, scrape or soak up in an inert material and put in a container for disposal. See section 7, "Handling and Storage", for proper container and storage procedures. Avoid contact with eyes.

# 7. HANDLING AND STORAGE

## Precautions to be taken in handling and storage:

Keep container closed when not in use. Do not freeze. Since emptied containers may contain product residue, follow all label warnings, even after container is emptied. Do not cut, drill, grind, or weld on or near this container.

# 8. PERSONAL PROTECTIVE EQUIPMENT AND EXPOSURE CONTROLS

# **Personal Protective Equipment**

# Eye and face protection:

Avoid contact with eyes. Wear chemical goggles if there is the possibility of contact or splashing in the eye.

## Skin protection:

Appropriate chemical resistant gloves should be worn.

## Respiratory protection:

If exposure cannot be controlled below applicable limits, use the appropriate NIOSH approved respirator such as an air purifying respirator with organic vapor cartridge and dust/mist filter. Consult the respirator manufacturer's literature to ensure that the respirator will provide adequate protection. Read and follow all respirator manufacturer's instructions.

#### Ventilation

Ensure adequate ventilation, especially in confined areas.

#### **Exposure Guidelines**

# **OSHA Permissible Exposure Limits (PEL's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA (final)	Ceilings limits (final)	Skin designations
SILICA	.1 - 1	$(30)/(\%SiO2 + 2) mg/m^3$		
14808-60-7		TWA, total dust		
		(250)/(%SiO2 + 5) mppcf		
		TWA, respirable fraction		
		(10)/(%SiO2 + 2) mg/m <sup>3</sup>		
		TWA, respirable fraction		

#### **ACGIH Threshold Limit Value (TLV's)**

Ingredient Name CAS-No.	Approx. Weight %	TWA	STEL	Ceiling limits	Skin designations
SILICA	.1 - 1	0.025 mg/m <sup>3</sup> TWA			
14808-60-7		respirable fraction			

# 9. PHYSICAL PROPERTIES

Odor: Normal for this product type.

Physical State: liquid

pH: not determined

# 9. PHYSICAL PROPERTIES

Vapor pressure: 24 mmHg @ 77°F (25°C)

Vapor density (air = 1.0): 0.6

Boiling point: 212°F (100°C)
Solubility in water: not determined
Coefficient of water/oil distribution: not determined

Density (lbs per US gallon):

Evaporation rate (butyl acetate = 1.0):

Flash point (Fahrenheit):

Flash point (Celsius):

96

Lower explosive limit (%):

Upper explosive limit (%):

Autoignition temperature:

not determined
not determined

# 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: None known.

Incompatibility: Strong oxidizing agents Hazardous Polymerization: None anticipated.

Hazardous Decomposition Products: Carbon monoxide and carbon dioxide.

Sensitivity to static discharge: Sensitivity to static discharge is not expected.

# 11. TOXICOLOGICAL INFORMATION

9	Approx. Weight %	NIOSH - Selected LD50s and LC50s
SILICA 14808-60-7	.1 - 1	= 500 mg/kg Oral LD50 Rat

# Mutagens/Teratogens/Carcinogens:

Cancer hazard. Contains material which can cause cancer.

Contains crystaline silica. The IARC has determined that crystaline silica inhaled in the form of quartz or cristobablite from occupational sources is carcinogenic to humans (group 1). Refer to IARC monograph 68 in conjunction with the use of these materials. Risk of cancer depends on the duration and level of exposure. In coatings products, risk is due primarily to inhalation of sanding dusts or respirable particles in spray mists. The NTP has also determined that crystaline silica is a known human carcinogen in the form of fine, breathable particles. Risk of cancer depends on duration and level of exposure in coatings products, risk is due primarily to inhalation of sanding dust or respirable particles in spray mist.

Ingredient Name CAS-No.	Approx. Weight %	California Prop 65 - Reproductive (Female)	California Prop 65 - Carcinogen
SILICA	.1 - 1		Listed. initial date 10/1/88 -
14808-60-7			carcinogen

Ingredient Name	Approx.	IARC Group 1 - Human	IARC Group 2A - Limited	IARC Group 2B -
CAS-No.	Weight %	Evidence	Human Data	Sufficient Animal Data
SILICA	.1 - 1	Monograph 68 [1997]		
14808-60-7				

•	Approx. Weight %	NTP Known Carcinogens	NTP Suspect Carcinogens
SILICA 14808-60-7	.1 - 1	Known Human Carcinogen	

Ingredient Name CAS-No.	Approx. Weight %	OSHA - Hazard Communication Carcinogens	OSHA - Specifically Regulated Carcinogens	ACGIH Carcinogens
SILICA	.1 - 1	Present		A2 Suspected Human
14808-60-7				Carcinogen

## 12. ECOLOGICAL DATA

No information on ecology is available.

# 13. DISPOSAL CONSIDERATIONS

Disposal should be made in accordance with federal, state and local regulations.

# 14. TRANSPORTATION INFORMATION

## **U.S. Department of Transportation**

UN ID Number (msds): NRPAIN

Proper Shipping Name: PAINT, NOT REGULATED

# U.S Hazmat and/or International DG shipment exceptions

The supplier may apply one of the following exceptions: Combustible Liquid, Consumer Commodity, Limited Quantity, Viscous Liquid, Does Not Sustain Combustion, or others, as allowed under 49CFR Hazmat Regulations. Please consult 49CFR Subchapter C to ensure that subsequent shipments comply with these exceptions.

# **Reportable Quantity Description:**

## International Air Transport Association (IATA):

Proper shipping name: NOT REGULATED

# **International Maritime Organization (IMO):**

Proper shipping name: NOT REGULATED

Marine Pollutant No

# 15. REGULATORY INFORMATION

# U.S. FEDERAL REGULATIONS: SARA 311/312 Hazard Class:

Acute: no
Chronic: yes
Flammability: no
Reactivity: no
Sudden Pressure: no

#### **U.S. STATE REGULATIONS:**

#### Right to Know:

The specific chemical identity of a component may be withheld as a trade secret under 34 Pennsylvania Code, Chapter 317.

## Pennsylvania Right To Know:

#### **Additional Non-Hazardous Materials**

PROPRIETARY INGREDIENT Trade Secret
PROPRIETARY RESIN Trade Secret
PROPRIETARY RESIN Trade Secret

#### **California Proposition 65:**

WARNING! This product contains a chemical known in the State of California to cause cancer.

Rule 66 status of product

Not photochemically reactive.

#### **INTERNATIONAL REGULATIONS - Chemical Inventories**

# **US TSCA Inventory:**

All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

### **Canada Domestic Substances List:**

All components of this product are listed on the Domestic Substances List.

#### 16. OTHER INFORMATION

## **HMIS Codes**

Health: 0\*
Flammability: 0
Reactivity: 1

PPE: X - See Section 8 for Personal Protective Equipment (PPE).

#### Abbreviations:

OSHA - Occupational Safety and Health Administration, IARC - International Agency for Research on Cancer, NIOSH - National Institute of Occupational Safety and Health, NTP - National Toxicology Program, ACGIH - American Conference of Governmental Industrial Hygienists, SCAQMD - South Coast Air Quality Management District, TSCA - Toxic Substances Control Act, IATA - International Air Transport Association, IMO - International Maritime Organization, DOT - Department of Transportation, NA - Not applicable, NOT ESTAB - Not established, N.A.V. - Not available, RQ - Reportable quantity, WT - Weight, MG/CU M - Milligrams per cubic meter, G/L - Grams per liter, MM - Millimeters, MPPCF - Millions of particles per cubic foot, PPM - parts per million, PPT - parts per thousand, TCC/PM - Tag closed cup / Pensky-Martens, PB - Lead, PEL - Permissible exposure level, TWA - Time Weighted Average, STEL - Short term exposure limit, C - Celsius, F - Fahrenheit.

#### Disclaimer:

The data on this sheet represent typical values. Since application variables are a major factor in product performance, this information should serve only as a general guide. Valspar assumes no obligation or liability for use of this information. UNLESS VALSPAR AGREES OTHERWISE IN WRITING, VALSPAR MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. VALSPAR WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Your only remedy for any defect in this product is the replacement of the defective product, or a refund of its purchase price, at our option. This MSDS contains additional information required by the state of Pennsylvania.

## **Preparation Information:**

Prepared By: Regulatory Affairs Department

Print date: 30/May/2013 Revision Date: 22/May/2013