

**Material Safety Data Sheet**

May be used to comply with  
 OSHA's Hazard Communication Standard  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**

Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form-Approved  
 OMB No. 1218.0072

IDENTITY (As Used on Label and List) <b>AMBER PASTE WAX #3353</b>		Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.			
<b>Section I</b>					
Manufacturer's Name: <b>Lundmark Wax Company, Inc.</b>		Emergency Telephone Number: <b>(630) 628-1199</b>			
Address (Number, Street, City, and Zip Code): <b>350 S. LaLonde Ave.</b>		Telephone Number for Information: <b>(630) 628-1199</b>			
<b>Addison, IL 60101</b>		Date Prepared: <b>JULY 1, 2008</b>			
		Signature of preparer (optional):			
<b>Section II-Hazardous Ingredients/Identity Information</b>					
Hazardous Components (specific Chemical Identity; Common Name(s))		OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	% (optional)
Petroleum Distillate		Cas. No. 8030-30-6	500ppm		< 85%
Turpentine		Cas. No. 8006-64-2	100ppm		< 25%
<b>Section III-Physical/Chemical Characteristics</b>					
Boiling Point: <b>Over</b>		<b>300° F</b>	Specific Gravity (H <sub>2</sub> O = 1):		<b>.75 - .80</b>
Vapor Pressure (mm Hg.):		<b>Unknown</b>	Melting Point:		<b>N.A.</b>
Vapor Density (AIR = 1):		<b>Unknown</b>	Evaporation Rate (Butyl Acetate = 1)		<b>Unknown</b>
Solubility in Water: <b>Nil</b>					
Appearance and Odor: <b>White, firm paste, solvent odor.</b>					
<b>Section IV--Fire and Explosion Hazard Data</b>					
Flash Point (Method Used): <b>104° F</b>		Flammable Limits: <b>N.A.</b>		LEL: <b>N.A.</b>	UEL: <b>N.A.</b>
Extinguishing Media: <b>Water fog, dry chemical, CO<sub>2</sub>.</b>					
Special Fire Fighting Procedures: <b>None</b>					
Unusual Fire and Explosion Hazards: <b>None</b>					
(Reproduce locally)					
OSHA 174, Sept 1985					

**Section V--Reactivity Data****AMBER PASTE WAX #3353**

Stability:	Unstable		Conditions to Avoid:
	Stable	X	
Incompatibility (Materials to Avoid): <b>None</b>			
Hazardous Decomposition or By-products: <b>On burning, carbon monoxide and dioxide</b>			
Hazardous Polymerization	May Occur		Conditions to Avoid:
	Will Not Occur	X	

**Section VI--Health Hazard Data**

Route(s) of Entry:	Inhalation?	X	Skin?	X	Ingestion?	X
Health Hazards (Acute and Chronic): <b>May cause burns to eyes. Harmful if swallowed. Vapors harmful.</b>						
Carcinogenicity: <b>None</b>	NIP?		IARC Monographs?		OSHA Regulated?	
Signs and Symptoms of Exposure: <b>Eyes and skin: burning. Vapors: Headache, nausea and dizziness.</b>						
Ingestion: <b>Gastro intestinal irritation.</b>						
Medical Conditions Generally Aggravated by Exposure: <b>Unknown</b>						
Emergency and First Aid Procedures: <b>Eyes and skin - Flush with water for 10 minutes. Vapors: Remove to fresh air.</b>						
Ingestion: <b>Do not induce vomiting. CALL PHYSICIAN.</b>						

**Section VII--Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled: <b>Absorb on clay or rags.</b>	
Waste Disposal Method: <b>Sanitary land fill. Check with Federal, Local and State regulations.</b>	
Precautions to be Taken in Handling and Storing: <b>Keep away from spark or flame.</b>	
Other Precautions: <b>Keep out of the reach of children.</b>	

**Section VIII--Control Measures**

Respiratory Protection (Specific Type): <b>None</b>			
Ventilation:	Local Exhaust:	Optional	Special: <b>N.A.</b>
	Mechanical (General):	<b>N.A.</b>	Other: <b>N.A.</b>
Protective Gloves:	<b>Required</b>		Eye Protection: <b>Required</b>
Other Protective Clothing or Equipment: <b>None</b>			
Work/Hygienic Practices: <b>Observe personal hygiene.</b>			