Material Safety Data Sheet

Famowood Liquid Filler & Adhesive Resin

H2 F1 R1 PH

Eclectic Products, Inc. 1075 Arrowsmith Eugene OR 97402 Information: 800-767-4667 Emergency: 800-535-5053

Section I - Product Identification

Product Name: Famowood Liquid Filler & Adhesive Resin

Product Code: 371085200

Section II - Hazardous Ingredients

Composition Epoxy Resin

Cresyl Glycidyl Ether

CAS No. 26447-14-3

Percent 76

24

Section III - Physical Data

Specific Gravity: 1.13

Boiling Point: N/A

Solubility: N/A

Vapor Pressure: N/A

Vapor Density: Non-volatile

Appearance and Odor: Clear, < light amber> liquid of low viscosity.

Section IV - Fire and Explosion Hazards

Flash Point: 350 ° F (PMCC)

LEL: N/A

UEL: N/A

Extinguishing Media: Use foam, dry chemicals, or carbon dioxide.

Special Fire Fighting Procedures: Wear positive pressure self-contained breathing apparatus

during fire fighting.

Unusual Fire and Explosion Hazards: N/A

Material Safety Data Sheet

Section V - Reactivity

Stability: Stable

Incompatibility: Strong oxidizers, acids, bases, and epoxy

hardeners under uncontrolled conditions.

Hazardous polymerization will not occur.

Conditions to avoid: Masses of more than one pound of product plus an aliphatic amine will cause irreversible polymerization with heat build up. Excessive heating over long periods of time degrades the resin. Freezing may cause a temporary haziness. Fire conditions increase viscosity.

Hazardous Decomposition Products: Under conditions of imperfect combustion and/or pyrolysis various phenolic compounds CO and/or CO2 may be evolved.

Section VI - Employee Protection

Engineering Controls: Good room ventilation is usually adequate for most operations.

Respiratory Protection: NIOSH approved respirator in the absence of proper environmental control.

Skin Protection: Rubber Gloves.

Eye Protection: Chemical Safety Goggles.

Other Protection: Rubber apron, shoes, or boots.

Section VII - Health Information

May cause eye irritation.

Prolonged or repeated exposure may cause skin irritation or sensitization.

Section VIII - Emergency and First Aid Procedures

Eye Contact: Immediately flush with plenty of water for at least 15 minutes. Get prompt medical attention. (Contact lenses should not be worn while working with this material).

Skin Contact: Wash exposed skin with soap and water. Get medial attention if irritation develops. Remove contaminated clothing, shoes, and thoroughly clean before reuse.

Famowood Liquid Filler & Adhesive Resin

Material Safety Data Sheet

Inhalation: Move exposed person(s) to fresh air. Get medical attention.

Ingestion: Induce vomiting if large amounts ingested. Call physician immediately.

Section IX - Spill Procedures

Steps to be taken in case material is released or spilled: Soak up in non-reactive absorbent material or scrape up. The residue can be removed with hot soapy water.

Avoid: Use of Methylene Chloride, Acetone, or aromatic solvents in clean up.

Waste Disposal Method: Materials and container Disposal must be carried out in accordance with local, state, and federal regulations.

Section X - Special Precautions

This material may cause sensitization. Do not get in eyes, on skin, or on clothing.

Section VI - Disclaimer

The information contained herein is based on the data available to us and is believed to be correct. However, Eclectic Products, Inc. makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Eclectic Products, Inc. assumes no responsibility for injury from the use of this product described herein.