

Page 1 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

1. Product And Company Identification

Supplier HENRY COMPANY

909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724

**Company Contact:** Technical Services **Telephone Number:** (800) 486-1278

Web Site: www.henry.com www.bakor.com

**Supplier Emergency Contacts & Phone Number** 

CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666 Manufacturer

**HENRY COMPANY** 

909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724

Company Contact: Technical Services Telephone Number: (800) 486-1278

Web Site: www.henry.com www.bakor.com

Manufacturer Emergency Contacts & Phone Number

CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666

Issue Date: 06/10/2010

Product Name: HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H

Product/Material Uses

Sealant

#### 2. Composition/Information On Ingredients

	Ingredient Name	CAS Number		Percent Of Total Weight	
ethyl benzene		100-41-4		3 - 9	
polymer		9003-55-8		20 - 40	
silica, amorphous		112926-00-8		1 - 5	
xylene		1330-20-7		30 - 50	

Substances in this product have been pre-registered in accordance with the REACH Regulation - (EC) No. 1907/2006. See Section 15 for additional information.

#### **EMERGENCY OVERVIEW**

CAUTION! Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Direct skin and eye contact may cause irritation. Ingestion may cause gastric distress.

Appearance/Odor: liquid, solvent odor.

# 3. Hazards Identification

## Primary Routes(s) Of Entry

Inhalation, skin absorption

## **Eye Hazards**

May cause eye irritation (burning, tearing, redness or swelling).

# **Skin Hazards**

Causes skin irritation, possible defatting and dermatitis to skin.



Page 2 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

#### 3. Hazards Identification - Continued

## **Ingestion Hazards**

May be harmful if swallowed. May cause central nervous system depression, kidney damage, and liver damage. Symptoms may include: headache, excitement, fatigue, nausea, vomiting, stupor, and coma. Causes gastrointestinal irritation with nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which may be fatal. May cause gastric distress, vomiting and diarrhea. May cause irritation to the mouth, throat, and digestive tract.

## **Inhalation Hazards**

Inhalation of vapors or mists may cause irritation of the nose and throat, headaches, nausea, dizziness, disorientaion, and numbness in fingers and toes.

# **Chronic/Carcinogenicity Effects**

This product or one of its ingredients present at 0.1% or more is listed as a carcinogen by NTP, IARC or OSHA. See Section 11 (Toxicological Information) for more details.

Chronic exposure can lead to permanent brain and central nervous sytem damage.

#### 4. First Aid Measures

#### Eve

In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.

#### <u>Skin</u>

Remove contaminated clothing and shoes. Wash affected areas with soap and water.

# **Ingestion**

Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim.

#### Inhalation

Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Contact a physician if symptoms develop.

# 5. Fire Fighting Measures

Flash Point: 75 °F 24 °C Flash Point Method: TCC

Lower Explosive Limit: not available Upper Explosive Limit: not available

## **Fire And Explosion Hazards**

Flammable liquid. During a fire, toxic and irritating gases may be generated, including carbon dioxide, and carbon monoxide.

# **Extinguishing Media**

Carbon dioxide, water, water fog, dry chemical, chemical foam.

## **Fire Fighting Instructions**

Keep containers cool with water spray to prevent pressure build up and container rupture which could exacerbate existing fire. Fire fighters should wear self-contained breathing apparatus and full protective gear.

#### 6. Accidental Release Measures

Avoid runoff to waterways and sewers. Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations.



Page 3 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

# 7. Handling And Storage

# **Handling And Storage Precautions**

Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Protect from physical damage. Protect from extreme temperatures. Keep out of reach of children.

## 8. Exposure Controls/Personal Protection

## **Engineering Controls**

Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.

# **Eye/Face Protection**

If there is a potential for splashing, faceshield over safety glasses or goggles.

# **Skin Protection**

Use with chemical-protective gloves to prevent skin contact.

# **Respiratory Protection**

The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator. Respirator use may be required due to secondary operations such as mixing, spraying, sanding, buffing, etc.

Occupational Exposure Limits for individual ingredients (if available) are listed below.

# Ingredient(s) - Exposure Limits

ethyl benzene

ACGIH TLV-STEL 125 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

silica, amorphous

OSHA PEL-TWA 80 mg/m3 / (%SiO2)

xylene

ACGIH TLV-STEL 150 ppm

ACGIH TLV-TWA 100 ppm

OSHA PEL-TWA 100 ppm

#### 9. Physical And Chemical Properties

## **Appearance**

liquid

## <u>Odor</u>

solvent odor

Chemical Type: Mixture Physical State: Liquid

Boiling Point: not applicable °F not applicable °C

Specific Gravity: 1 approx.

Percent Volatiles: approximately 50 Vapor Pressure: not available

Vapor Density: >1 pH Factor: not applicable Solubility: not soluble

Evaporation Rate: not available

# Henry

# MATERIAL SAFETY DATA SHEET

Page 4 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

## 10. Stability And Reactivity

Stability: stable

Hazardous Polymerization: not expected to occur

# **Conditions To Avoid (Stability)**

Keep away from ignition sources, heat, sparks and flames.

## **Hazardous Decomposition Products**

Decomposition not likely to occur if handled and stored properly.

## 11. Toxicological Information

## **Chronic/Carcinogenicity**

IARC has concluded that the following chemicals in this product are possibly carcinogenic to humans (Group 2B): ethyl benzene.

Mixed xylenes are considered fetotoxic, based on observations of reduced fetal weight, delayed ossification and persistent behavioral effects in the absence of maternal toxicity. Other developmental effects have been observed in the presence of maternal toxicity.

Risk of cancer depends on duration and level of exposure to this product as a dust or aerosol mist.

## Miscellaneous Toxicological Information

Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.

# Ingredient(s) - Toxicological Data

ethyl benzene

LC50 (rat) approximately 4000 ppm (4 hour)

LD50 (oral rat) 3500 mg/kg

LD50 (dermal rabbit) 15380 mg/kg (17.8 mL/kg)

xylene

LD50 (oral, rat): 5400 mg/kg

LD50 (dermal, rabbit): 12180 mg/kg LC50 (rat): 6350 ppm (4-hour exposure)

## 12. Ecological Information

## 13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

## 14. Transport Information

300 ml and 10.1 oz. Cartridges/Tubes:

Ground (US): Consumer Commodity, ORM-D

Ground (Canada): UN1133, Adhesives, 3, III, Ltd. Qty.

IMDG: UN1133, Adhesives, 3, III, Ltd. Qty.

IATA: UN1133, Adhesives, 3, III, Ltd. Qty.

Pails and Combination Packaging Containing more than 10 L:

# Henry

# MATERIAL SAFETY DATA SHEET

Page 5 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

14. Transport Information - Continued

Ground: UN1133, Adhesives, 3, III

IMDG: UN1133, Adhesives, 3, III

IATA: UN1133, Adhesives, 3, III

## **DOT (Pictograms)**



# 15. Regulatory Information

## **SARA Hazard Classes**

Acute Health Hazard

# Ingredient(s) - U.S. Regulatory Information

ethyl benzene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

xylene

SARA Title III - Section 313 Form "R"/TRI Reportable Chemical

# Ingredient(s) - State Regulations

ethyl benzene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

New Jersey - Special Hazard

Pennsylvania - Workplace Hazard

Pennsylvania - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

silica, amorphous

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

xylene

New Jersey - Workplace Hazard

New Jersey - Environmental Hazard

New Jersey - Special Hazard

Pennsylvania - Workplace Hazard

Pennsylvania - Environmental Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance

# Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: D2A - Very Toxic, B2 - Flammable Liquid.

# Ingredient(s) - Canadian Regulatory Information

ethyl benzene

WHMIS - Ingredient Disclosure List

## **European Union (EU) Regulatory Information**

**REACH Pre-registration Information:** 



Page 6 of 6

# **HE212 - CRYSTAL CLEAR ALL PURPOSE PATC H**

## 15. Regulatory Information - Continued

# **European Union (EU) Regulatory Information - Continued**

Substance (CAS#) Reference Number

Silica, amorphous (112926-00-8)

Xylene (1330-20-7)

Styrene Butadiene Polymer

-Styrene (100-42-5)

-Buta-1,3-diene (106-99-0)

05-2114501829-45-0000 05-2114367081-55-0000

NA - Polymer (the monomers below have been pre-registered)


05-2114367032-58-0000 05-2114367037-48-0000

# WHMIS - Canada (Pictograms)





#### **NFPA**



<u>HMIS</u>	
HEALTH	1
FLAMMABILITY	3
REACTIVITY	0
PERSONAL PROTECTION	

## 16. Other Information

## **Revision/Preparer Information**

This MSDS Supersedes A Previous MSDS Dated: 11/12/2008

#### Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).

#### **HENRY COMPANY**

Printed Using MSDS Generator™ 2000