

Material Safety Data Sheet

Section 1: Product & Company Identification

Product Name: Duster[™] Moisture-Free Dust & Lint Remover

Product Number (s): 05185, 05185-6

Manufactured By:

CRC Industries, Inc.

885 Louis Drive

Warminster, PA 18974

www.crcindustries.com

General Information
Technical Assistance
(800) 521-3168
Customer Service
(800) 272-8963
24-Hr Emergency (CHEMTREC)
(800) 424-9300

Section 2: Hazards Identification

Emergency Overview

Appearance & Odor:

Expelled product is a clear gas with a faint ethereal odor. Pressurized product is a liquefied gas.

CAUTION

Contents Under Pressure.

As defined by OSHA's Hazard Communication Standard, this product is hazardous.

Potential Health Effects:

EYE: Contact with dispersed gas is not expected to cause negative effects. Contact with liquid

product can cause severe irritation, redness, tearing, blurred vision, and possible freeze

burns.

SKIN: Contact with dispersed gas is not expected to cause negative effects. Contact with liquid

product or concentrated expelled gas can cause frostbite.

INHALATION: Inhalation of dispersed gas is not expected to cause negative effects. Inhalation of

concentrated vapor may product anesthetic effects and feeling of euphoria. Prolonged

exposure can cause rapid breathing, headache, dizziness, narcosis, and

unconsciousness. Deliberately inhaling this product can lead to death from asphyxiation

depending on concentration and duration of exposure.

INGESTION: Ingestion of liquid product may cause frostbite to mouth and throat. Liquid product may

pose aspiration hazard. This product contains a bittering agent. Direct ingestion of

expelled gas or liquid will create an extreme bitter taste in the mouth.

CHRONIC EFFECTS: Unknown

TARGET ORGANS: None known

Medical Conditions Aggravated by Exposure: None known

See Section 11 for toxicology and carcinogenicity information on product ingredients.

Product Number (s): 05185, 05185-6

Section 3: Composition/Information on Ingredients

COMPONENT	CAS NUMBER	% by Wt.	
1,1-Difluoroethane (HFC-152a)	75-37-6	> 99	

Section 4: First Aid Measures

Eye Contact: For liquid contact, immediately flush with plenty of water for 15 minutes. Call a physician if

frostbite occurs.

Skin Contact: For liquid contact, warm area gradually and get medical attention if there is evidence of tissue

damage. Flush area with plenty of water. Treat as frostbite.

Inhalation: Remove person to fresh air. Keep person calm. If not breathing, give artificial respiration. If

breathing is difficult give oxygen. Call a physician.

Ingestion: Do not induce vomiting. Contact a physician immediately.

Note to Physicians: None

Section 5: Fire-Fighting Measures

<u>Flammable Properties</u>: In accordance with aerosol flammability definitions, this product is non-flammable.

However, the pressurized liquefied gas is extremely flammable. Using this product in

an upside-down position, or shaking while using, can cause liquid product to be

expelled. The below information applies to the liquefied gas.

Flash Point: - 58 F (COC) Upper Explosive Limit: 16.9% Autoignition Temperature: ND Lower Explosive Limit: 3.9%

Suitable Extinguishing Media: Dry chemical extinguisher (B-C), water

Products of Combustion: oxides of carbon, hydrogen fluoride

Protection of Fire-Fighters: Firefighters should wear self-contained, NIOSH-approved breathing apparatus for

protection against suffocation and possible toxic decomposition products. Proper eye and skin protection should be provided. Stop the release of material if possible. Use water spray to keep fire-exposed containers cool and to knock down vapors which

may result from product decomposition.

Section 6: Accidental Release Measures

Personal Precautions: Use personal protection recommended in Section 8.

Environmental Precautions: Take precautions to prevent contamination of ground and surface waters. Do not flush

into sewers or storm drains.

Methods for Containment & Clean-up: Eliminate sources of ignition. Ventilate the area with plenty of fresh air. If in

confined space or limited air circulation area, clean-up workers should wear

Product Number (s): 05185, 05185-6

appropriate respiratory protection. If liquid is present, recover or absorb spilled material using an absorbent designed for chemical spills. Place used absorbents into proper waste containers.

Section 7: Handling and Storage

Handling Procedures: Vapors are heavier than air and may travel along the ground. Certain vapor concentrations

may be ignited by sources of ignition. Deliberately concentrating and inhaling the vapors of

this product may result in death.

Storage Procedures: Store in a cool dry area out of direct sunlight. Aerosol cans must be maintained below 120 F

to prevent cans from rupturing. Keep out of reach of children.

Aerosol Storage Level:

Section 8: Exposure Controls/Personal Protection

Exposure Guidelines:

	OSHA		ACGIH		OTHER		
COMPONENT	TWA	STEL	TWA	STEL	TWA	SOURCE	UNIT
1,1-Difluoroethane (HFC-152a)	NE	NE	NE	NE	1000	AIHA	ppm
N.E. – Not Established (c) – ceiling (s) – skin (v) – vacated							

Engineering Controls: Area should have ventilation to provide fresh air. Use local exhaust to prevent accumulation

of vapors. Use mechanical means if necessary to maintain vapor levels below the exposure

guidelines. If working in a confined space, follow applicable OSHA regulations

Respiratory Protection: None required for normal work where adequate ventilation is provided. Use a NIOSH-

approved cartridge respirator with organic vapor cartridge if vapors exceed exposure limits.

Use a self-contained breathing apparatus in confined spaces and for emergencies.

Eye/face Protection: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid

contact, wear splash-proof goggles.

Skin Protection: Use protective gloves such as insulated rubber. Also, use impervious clothing if there is

potential for contact of liquid with skin.

Section 9: Physical and Chemical Properties

Physical State: dispensed product is a gas; pressurized product is a liquefied gas

Color: colorless Odor: ethereal

Specific Gravity: 0.909 Initial Boiling Point: - 13 F

Freezing Point: ND

Vapor Pressure: 62.5 psig @ 70 F Vapor Density: 2.4 (air = 1) Evaporation Rate: > 1 (ether = 1)

Solubility: 0.28% (in water) at 70 F

Product Number (s): 05185, 05185-6

pH: NA

Volatile Organic Compounds: wt %: 0 (exempt) g/L: 0 lbs./gal: 0

Section 10: Stability and Reactivity

Stability: Stable

Conditions to Avoid: High heat, spark and open flame.

Incompatible Materials: Alkali or alkaline earth metals (Al, Zn)

Hazardous Decomposition Products: Hydrofluoric acid and carbonyl halides

Possibility of Hazardous Reactions: No

Section 11: Toxicological Information

Long-term toxicological studies have not been conducted for this product. The following information is available for components of this product.

ACUTE EFFECTS

Component	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
1,1-difluoroethane	LC50	977 g/m³/2H	Inhalation	Mouse

CHRONIC EFFECTS

Carcinogenicity:

<u>Component</u> Result

OSHA: None listed IARC: None listed NTP: None listed

Mutagenicity: No information available

Other: None

Section 12: Ecological Information

Ecological studies have not been conducted for this product. The following information is available for components of this product.

Ecotoxicity: No information available
Persistence / Degradability: No information available
Bioaccumulation / Accumulation: No information available
Mobility in Environment: No information available

Section 13: Disposal Considerations

Disposal: This product, as packaged, is a RCRA hazardous waste for flammability and reactivity. Waste codes

Product Number (s): 05185, 05185-6

would include D001 & D003. (See 40 CFR Part 261.20 - 261.33)

Dispensed product is not a hazardous waste. Empty containers may be recycled.

All disposal activities must comply with federal, state and local regulations. Local regulations may be more stringent than state or national requirements.

Section 14: Transport Information

Proper shipping description:

US DOT (ground): 1,1-Difluoroethane, R152A, 2.1, UN1030

Special Provisions: DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling

requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-

SP 11516'.

Section 15: Regulatory Information

U.S. Federal

Toxic Substances Control Act (TSCA):

All ingredients are either listed on the TSCA inventory or are exempt.

Comprehensive Environmental Response, Compensation and Liability Act (CERCLA):

Reportable Quantities (RQ's) exist for the following ingredients: None

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

Superfund Amendments Reauthorization Act (SARA) Title III:

Section 302 Extremely Hazardous Substances (EHS): None

Section 311/312 Hazard Categories: Fire Hazard Yes

Reactive Hazard No
Release of Pressure Yes
Acute Health Hazard Yes
Chronic Health Hazard No

Section 313 Toxic Chemicals: This product contains the following substances subject to the reporting

requirements of Section 313 of Title III of the Superfund Amendments and

Reauthorization Act of 1986 and 40 CFR Part 372:

None

Clean Air Act:

Section 112 Hazardous Air Pollutants (HAPs): None

Consumer Product Safety Act General Conformity Certification: This product was evaluated by CRC Industries, Inc., and is certified to be in compliance with the provisions of the Consumer Product Safety Act, the Federal Hazardous Substances Act and the Poison Prevention Packaging Act, as applicable. This product was manufactured at the location listed in Section 1 of this MSDS. The date of manufacture is stamped on the

Product Number (s): 05185, 05185-6

product container. No testing is required to certify compliance with the above

State Regulations

California Safe Drinking Water and Toxic Enforcement Act (Prop 65):

This product may contain the following chemicals known to the state of California to cause cancer, birth defects or other reproductive harm:

None

State Right to Know:

New Jersey: 75-37-6 Pennsylvania: 75-37-6 Massachusetts: 75-37-6 Rhode Island: 75-37-6

Additional Regulatory Information: This product contains a bittering agent to help to prevent inhalant abuse.

Section 16: Other Information

NFPA: Health: 1 Flammability: 4 Reactivity: 1

HMIS: Health: 1 Flammability: 4 Reactivity: 1 PPE: B

Prepared By: Michelle Rudnick

CRC #: 917A Revision Date: 11/10/2008

Changes since last revision: Formula number revised

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label.

CAS: **Chemical Abstract Service** NA: Not Applicable Not Determined ppm: Parts per Million ND: Tag Closed Cup Not Established TCC: NE: Pensky-Martens Closed Cup PMCC: grams per Liter g/L: PPE: Personal Protection Equipment lbs./gal: pounds per gallon

TWA: Time Weighted Average STEL: Short Term Exposure Limit

OSHA: Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists

NIOSH National Institute of Occupational Safety & Health

AIHA: American Industrial Hygiene Association