

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: **AQUA ZAR GLOSS**
PRODUCT CODE: **17**

HMIS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: **UNITED GILSONITE LABORATORIES**
ADDRESS: **1396 JEFFERSON AVENUE
SCRANTON, PA 18509**

EMERGENCY PHONE: **(800) 424-9300**
INFORMATION PHONE: **(570) 344-1202**
NAME OF PREPARER: **R. BARAKO**

DATE REVISED: OCTOBER 2007
SUPERSEDES: MARCH 2005

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mmHg@TEMP | WEIGHT PERCENT |
|-------------------------|------------|------------------------------|-----------|-----------|-----------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| WATER | 7732-18-5 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 1.0 (68F) | 55-60 |
| ACRYLIC COPOLYMER | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15-20 |
| POLYURETHANE RESIN | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15 |
| PROPYLENE GLYCOL | 57-55-6 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.2 (68F) | <5 |
| *N-METHYL-2-PYRROLIDONE | 872-50-4 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.3 (77F) | 8 |

*Indicates chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.
This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 (F)
VAPOR DENSITY: HEAVIER THAN AIR
COATING VOC: 236 g/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: CLEAR TO MILKY, TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H20 =1) 1.0
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: 2.2% **UPPER:** 12.5%

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH. PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH DUST PARTICLE AND ORGANIC VAPOR CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: **AQUA ZAR SEMI GLOSS**
PRODUCT CODE: 9

HMS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: **UNITED GILSONITE LABORATORIES**
ADDRESS: **1396 JEFFERSON AVENUE
SCRANTON, PA 18509**

EMERGENCY PHONE: **(800) 424-9300**
INFORMATION PHONE: **(570) 344-1202**
NAME OF PREPARER: **R. BARAKO**

DATE REVISED: OCTOBER 2007
SUPERCEDES: JULY 2004

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mmHg@TEMP | WEIGHT PERCENT |
|------------------------|-------------|------------------------------|-----------|-----------|-----------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| WATER | 7732-18-5 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 1.0 (68F) | 55-60 |
| ACRYLIC COPOLYMER | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15-20 |
| POLYURETHANE RESIN | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15 |
| AMORPHOUS FUMED SILICA | 112945-52-5 | 20 MPPCF | 10 MG/M3 | NOT ESTAB | N/A | <5 |
| *N-METHYL-2-PYROLIDONE | 872-50-4 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.3 (77F) | 8 |
| PROPYLENE GLYCOL | 57-55-6 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.2 (68F) | <5 |

*Indicates chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.
This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 (F)
VAPOR DENSITY: HEAVIER THAN AIR
COATING VOC: 238 g/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: CLEAR TO MILKY, TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H20 =1) 1.0
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: 2.2% **UPPER:** 12.5%

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH DUST PARTICLE AND ORGANIC VAPOR CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: **AQUA ZAR SATIN**
PRODUCT CODE: **27**

HMS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: **UNITED GILSONITE LABORATORIES**
ADDRESS: **1396 JEFFERSON AVENUE
SCRANTON, PA 18509**

EMERGENCY PHONE: **(800) 424-9300**
INFORMATION PHONE: **(570) 344-1202**
NAME OF PREPARER: **R. BARAKO**

DATE REVISED: OCTOBER 2007
SUPERSEDES: MARCH 2005

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mmHg@TEMP | WEIGHT PERCENT |
|------------------------|-------------|------------------------------|----------------------|-----------|-----------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| WATER | 7732-18-5 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 1.0 (68F) | 55-60 |
| ACRYLIC COPOLYMER | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15-20 |
| POLYURETHANE RESIN | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15 |
| AMORPHOUS FUMED SILICA | 112945-52-5 | 20 MPPCF | 10 MG/M ³ | NOT ESTAB | N/A | <5 |
| *N-METHYL-2-PYROLIDONE | 872-50-4 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.3 (77F) | 8 |
| PROPYLENE GLYCOL | 57-55-6 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.2 (68F) | <5 |

*Indicates chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.
This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 (F)
VAPOR DENSITY: HEAVIER THAN AIR
COATING VOC: 237 g/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: CLEAR TO MILKY, TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O =1) 1.0
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: 2.2% **UPPER:** 12.5%

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH DUST PARTICLE AND ORGANIC VAPOR CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: AQUA ZAR ANTIQUE
PRODUCT CODE: 8

HMS CODES: H F R P
1 0 0

SECTION I – MANUFACTURER IDENTIFICATION

MANUFACTURE'S NAME: UNITED GILSONITE LABORATORIES
ADDRESS: 1396 JEFFERSON AVENUE
SCRANTON, PA 18509

EMERGENCY PHONE: (800) 424-9300
INFORMATION PHONE: (570) 344-1202
NAME OF PREPARER: R. BARAKO

DATE REVISED: OCTOBER 2007
SUPERCEDES: JULY 2004

SECTION II – HAZARDOUS INGREDIENTS/SARA III INFORMATION

| HAZARDOUS COMPONENTS | CAS NUMBER | OCCUPATIONAL EXPOSURE LIMITS | | | VAPOR PRESSURE mmHg@TEMP | WEIGHT PERCENT |
|------------------------|-------------|------------------------------|-----------|-----------|-----------------------------|-------------------|
| | | OSHA PEL | ACGIH TLV | OTHER | | |
| WATER | 7732-18-5 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 1.0 (68F) | 55-60 |
| ACRYLIC COPOLYMER | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15-20 |
| POLYURETHANE RESIN | NOT ESTAB | NOT ESTAB | NOT ESTAB | NOT ESTAB | N/A | 15 |
| AMORPHOUS FUMED SILICA | 112945-52-5 | 20 MPPCF | 10 MG/M3 | NOT ESTAB | N/A | <5 |
| *N-METHYL-2-PYROLIDONE | 872-50-4 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.3 (77F) | 8 |
| PROPYLENE GLYCOL | 57-55-6 | NOT ESTAB | NOT ESTAB | NOT ESTAB | 0.2 (68F) | <5 |

*Indicates chemical(s) subject to the reporting requirements of Section 313 of Title III and of 40 CFR 372.
This product contains a chemical known to the state of California to cause birth defects or other reproductive harm.

SECTION III – PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: 212 (F)
VAPOR DENSITY: HEAVIER THAN AIR
COATING VOC: 234 g/l
SOLUBILITY IN WATER: SOLUBLE
APPEARANCE AND ODOR: CLEAR TO MILKY, TYPICAL AMINE ODOR

SPECIFIC GRAVITY (H₂O =1) 1.0
EVAPORATION RATE: SLOWER THAN ETHER

SECTION IV – FIRE AND EXPLOSION HAZARD DATA

FLASHPOINT: N/A

METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME:

LOWER: 2.2% UPPER: 12.5%

EXTINGUISHING MEDIA: NONE KNOWN

SPECIAL FIRE FIGHTING PROCEDURES: CONTAINER MAY SWELL AND BURST DURING A FIRE DUE TO INTERNAL PRESSURE CAUSED BY HEAT. THIS MAY CAUSE A SLIPPERY CONDITION ON FLOORS

UNUSUAL FIRE AND EXPLOSION HAZARDS: N/A

SECTION V – REACTIVITY DATA

STABILITY: PRODUCT IS STABLE

CONDITIONS TO AVOID: TEMPERATURES BELOW 32 (F) FOR STORAGE. TEMPERATURES BELOW 50 (F) FOR APPLICATION

INCOMPATIBILITY (MATERIALS TO AVOID): N/A

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: N/A

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

SECTION VI – HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: IN IT'S WET STATE, THIS PRODUCT SHOULD NOT POSE ANY THREAT TO HEALTH DUE TO OVEREXPOSURE

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: DIRECT CONTACT MAY CAUSE BURNING, TEARING, REDNESS AND SWELLING

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: CAN CAUSE SLIGHT IRRITATION

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: MAY PRODUCE SIGNS OF INTOXICATION CHARACTERIZED BY INCOORDINATION, DIZZINESS, DROWSINESS, HEADACHE, NAUSEA, MENTAL CONFUSION DEPENDING ON THE QUANTITY OF MATERIAL INGESTED

HEALTH HAZARDS (ACUTE AND CHRONIC): NONE KNOWN

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: INHALATION OF THE SPRAYED MATERIAL OR THE DUST FROM SANDING THE DRY FILM CAN AGGRAVATE RESPIRATORY CONDITIONS

EMERGENCY AND FIRST AID PROCEDURES:

EYES: FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. CONSULT A PHYSICIAN IF IRRITATION PERSISTS

INGESTION: SEEK MEDICAL ATTENTION. IF INDIVIDUAL IS DROWSY OR UNCONSCIOUS, DO NOT GIVE ANYTHING BY MOUTH; PLACE INDIVIDUAL ON THE LEFT SIDE WITH HEAD DOWN. CONTACT A PHYSICIAN, MEDICAL FACILITY OR POISON CONTROL CENTER FOR ADVICE ABOUT WHETHER TO INDUCE VOMITING

INHALATION: REMOVE VICTIM TO FRESH AIR

SECTION VII – PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: DIKE AREA AROUND SPILL. APPLY ABSORBENT MATERIAL, THEN SWEEP UP AND PLACE IN PROPER CONTAINERS

WASTE DISPOSAL METHOD: DISPOSE OF IN APPROVED SITES ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: AVOID BREATHING SANDING DUST. KEEP FROM FREEZING. STORE MATERIAL IN AREAS WHERE TEMPERATURES RANGE FROM 50 (F) TO 90 (F)

OTHER PRECAUTIONS: N/A

SECTIONS VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: WHEN SPRAYING OR SANDING DRY FILM, USE NIOSH APPROVED RESPIRATOR WITH DUST PARTICLE AND ORGANIC VAPOR CARTRIDGES

VENTILATION: USE ADEQUATE VENTILATION IN VOLUME AND PATTERN TO MAINTAIN EXPOSURE LEVELS BELOW THAT LISTED IN SECTION II

PROTECTIVE GLOVES: USE NEOPRENE RUBBER GLOVES TO PREVENT SKIN CONTACT

EYE PROTECTION: USE SAFETY EYEWEAR WITH SPLASH GUARDS

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE

WORK / HYGIENIC PRACTICES: WASH HANDS BEFORE EATING, SMOKING OR USING WASH ROOM

SECTION IX – DISCLAIMER

This information is furnished without warranty, representation, inducement or license of any kind, except that it is accurate to the best of UGL's knowledge, or obtained from sources believed by UGL to be accurate, and UGL does not assume any legal responsibility for use or reliance upon same. Before using any product, read the label.