# **Material Safety Data Sheet**



Revision Number: 000.0 Issue date: 11/24/2010

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: OSI GreenSeries Flameseal Sealant II

Product type: Sealant

**IDH number:** 1390035

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 800.624.7767

One Henkel Way

Rocky Hill, Connecticut 06067

MEDICAL EMERGENCY Phone: Poison Control Center
1-877-671-4608 (toll free) or 1-303-592-1711
TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

#### 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

HMIS:

Physical state:pastyHEALTH:1Color:RedFLAMMABILITY:0Odor:Mild, aromaticPHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

CAUTION: MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Inhalation, Skin contact, Eyes

**Potential Health Effects** 

Inhalation: May cause irritation to nose and throat. Skin contact: May cause slight irritation to skin.

Eye contact: May cause slight irritation to eyes on contact.

Ingestion: Not expected to be harmful by ingestion. Ingestion of large amounts may produce

gastrointestinal disturbances including irritation, nausea, and diarrhea.

Existing conditions aggravated by

exposure:

None known

This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).

See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Vinyl Acetate Polymer	Unknown	10 - 30

# 4. FIRST AID MEASURES

Inhalation: Move to fresh air in case of accidental inhalation of vapours.

Skin contact: Wash affected area immediately with soap and water.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. If

symptoms develop and persist, get medical attention.

**Ingestion:** Consult a physician if necessary.

IDH number: 1390035 Product name: OSI GreenSeries Flameseal Sealant

### 5. FIRE FIGHTING MEASURES

Flash point: not applicable

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

**Extinguishing media:** All standard firefighting procedures.

Special firefighting procedures: Do not breathe combustion gases. Wear protective equipment.

Unusual fire or explosion hazards: None known

**Hazardous combustion products:** Carbon dioxide. Carbon monoxide. Hydrocarbons.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Do not empty into drains.

Clean-up methods: Scrape up spilled material and place in a closed container for disposal. Wear

appropriate protective equipment and clothing during clean-up.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Keep out of the reach of children.

Storage: For safe storage, store between 4 °C (39.2 °F) and 32 °C (89.6 °F)

Keep from freezing. Store in a cool, dry area. Keep containers closed when

not in use.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Vinyl Acetate Polymer	None	None	None	None

Engineering controls: Use general ventilation and use local exhaust, where possible, in confined or

enclosed spaces.

Respiratory protection: Not normally required. Use NIOSH approved respirator if there is potential to

exceed exposure limit(s).

**Eye/face protection:** Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves. Neoprene, Butyl-rubber, or nitrile-

rubber gloves.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: pasty Color: Red

Odor:Mild, aromaticOdor threshold:Not availablepH:8.0 - 9.0

IDH number: 1390035 Product name: OSI GreenSeries Flameseal Sealant

Vapor pressure: 18.51880 mm hg Boiling point/range: > 100 °C (> 212°F)

Melting point/ range: Not available

Specific gravity: 1.40 - 1.50 at 25 °C (77°F) Vapor density: Heavier than air, (Air = 1)

Flash point: not applicable Flammable/Explosive limits - lower: Not available Flammable/Explosive limits - upper: Not available Autoignition temperature: Not available **Evaporation rate:** < 1

Solubility in water: Not available Partition coefficient (n-octanol/water): Not determined **VOC** content: 32.5 g/l (calculated)

## 10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Not available

Hazardous decomposition products: Carbon dioxide. Carbon monoxide.

Incompatible materials: Alkalis. Mineral acids.

Conditions to avoid: Do not freeze.

#### 11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen	
nazar adad dempending	itti Gardinogon	nate caromogen	(Specifically Regulated)	
Vinyl Acetate Polymer	No	No	No	

Hazardous components	Health Effects/Target Organs
Vinvl Acetate Polymer	No Data

### 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available

#### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: It is the responsibility of the user to determine if an item is hazardous as

defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics

Leaching Procedure (TCLP) 40 CFR 261.20-24.

### 14. TRANSPORT INFORMATION

### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

IDH number: 1390035 Product name: OSI GreenSeries Flameseal Sealant International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division: None Identification number: None Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated

Hazard class or division:

Identification number:

None
Packing group:

None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: No California Proposition 65 listed chemicals are known to be present. No California

Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

WHMIS hazard class:

IDH number: 1390035

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List. Not controlled

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Mary Ellen Roddy, Sr. Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.